

SAFETY DATA SHEET

040

DETECTAGAS REFILLABLE (276PS106) Product Name

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113

131 262, (02) 8874 4400 **Telephone** 132 427 (24 hours) Fax

1800 653 572 (24/7) (Australia only) **Emergency**

Web Site http://www.boc.com.au/

040 - SDS NUMBER • PORTA-SPEC ZERO AIR (FORMERLY) • PRODUCT CODE: 276PS106 Synonym(s)

CALIBRATION • INDUSTRIAL APPLICATIONS Use(s)

SDS Date 26 Mar 2010

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No. 1002 **DG Class** 2.2 Subsidiary Risk(s) None Allocated

EPG Packing Group None Allocated Hazchem Code 2T 2C1

3. COMPOSITION/ INFORMATION ON INGREDIENTS

| Ingredient | Formula | CAS No. | Content |
|------------|---------|-----------|---------|
| OXYGEN | O2 | 7782-44-7 | 20.5% |
| NITROGEN | N2 | 7727-37-9 | 79.5% |

4. FIRST AID MEASURES

Eye None required.

Inhalation If inhaled, remove from contaminated area. If other than minor symptoms are displayed, seek immediate medical

attention. An inhalation hazard is not anticipated under normal conditions of use. For advice, contact a Poisons

Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin None required.

Ingestion Due to product form and application, ingestion is considered unlikely.

Advice to Doctor Treat symptomatically

5. FIRE FIGHTING MEASURES

Flammability Non flammable.

Fire and Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying

Explosion water from a protected location. Do not approach cylinders or containers suspected of being hot.

Extinguishing Use water fog to cool containers from protected area.

Hazchem Code 2T

ChemAlert.

Reviewed: 26 Mar 2010 Printed: 26 Mar 2010

DETECTAGAS REFILLABLE (276PS106)

6. ACCIDENTAL RELEASE MEASURES

Spillage

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices.

7. STORAGE AND HANDLING

Storage Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling.

Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm

level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

Handling Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The

uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder

movement.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds

| Ingredient | Reference | TWA | | STEL | | |
|------------|------------|------------|-------|------|-------|--|
| | | ppm | mg/m3 | ppm | mg/m3 | |
| Nitrogen | ASCC (AUS) | Asphyxiant | | | | |

Biological Limits

No biological limit allocated.

Engineering Controls

No special precautions are normally required when handling this product.

PPE

Wear safety boots, leather gloves and safety glasses.







9. PHYSICAL AND CHEMICAL PROPERTIES

COLOURLESS GAS Appearance Solubility (Water) 0.018 cm3/cm3 Odour **ODOURLESS Specific Gravity** NOT APPLICABLE

NOT APPLICABLE pН % Volatiles 100 %

Vapour Pressure **NOT AVAILABLE Flammability** NON FLAMMABLE Vapour Density 1 (Air = 1)Flash Point NOT RELEVANT -194°C **NOT RELEVANT Boiling Point Upper Explosion Limit Melting Point NOT AVAILABLE** NOT RELEVANT **Lower Explosion Limit**

Evaporation Rate NOT APPLICABLE

Critical Pressure 3.774 kPa **Critical Temperature** -140°C

Cylinder Pressure 13,700 kPa @ 15°C

10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended conditions of storage.

Conditions to Avoid Avoid heat, sparks, open flames and other ignition sources.

Material to Avoid Compatible with most commonly used materials. Decomposition May evolve toxic gases if heated to decomposition.

Hazardous Reactions Polymerization will not occur.



RMT

Reviewed: 26 Mar 2010 Printed: 26 Mar 2010

Product Name DETECTAGAS REFILLABLE (276PS106)

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary

Non toxic gas. As the amount of oxygen inhaled is increased, chest tightness, burning pains and coughing spasms may occur. Other symptoms of hyperoxia include cramps, nausea, dizziness, hypothermia, amblyopia (loss of vision), bradycardia, fainting spells and convulsions capable of causing death. Over exposure at normal or elevated pressure may result in severe thickening and scarring of lung tissues. Not carcinogenic or mutagenic.

Eye Non irritant.

Inhalation Non irritant. Adverse health effects are not anticipated under normal conditions of use.

Skin Non irritant.

Ingestion Ingestion is considered unlikely due to product form.

Toxicity Data No LD50 data available for this product.

12. ECOLOGICAL INFORMATION

Environment No known ecological damage is caused by this product.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

Transport Ensure cylinder is separated from driver and that outlet of relief device is not obstructed.



CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name AIR, COMPRESSED

UN No. 1002 DG Class 2.2 Subsidiary Risk(s) None Allocated

Packing Group None Allocated Hazchem Code 2T EPG 2C

15. REGULATORY INFORMATION

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform

Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European Inventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m3 - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).



Page 3 of 4

RMT Reviewed: 26 Mar 2010

Printed: 26 Mar 2010

Product Name DETECTAGAS REFILLABLE (276PS106)

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances. TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au

Web: www.rmt.com.au

SDS Date: 26 Mar 2010 End of Report

