MATERIAL SAFETY DATA SHEET _____

| | | | | | | | | | | | | | | - |
|------|------------|---------|--------|-------|------|------|-------|-------|-----|-------|--------|--------|-----|-------|
| j | SECT | ION 1 - | - CHEN | MICAL | PROD | UCT | AND | COMPA | ANY | IDENT | TIFICA | ATION | | j |
| | | | | | | | | | | | | | | - |
| THIS | MATERIAL S | SAFETY | בדבת | SHEET | TS | Δ1/Δ | T.ART | E TN | SPA | NISH | IIDOM | BEOIIE | .ST | |

THIS MATERIAL SAFETY DATA SHEET IS AVAILABLE IN SPANISH UPON REQUEST.

LOS DATOS DE SEGURIDAD DEL PRODUCTO PUEDEN OBTENERSE EN ESPANOL SI LO REQUIERE.

: LE 3000 Sheet Goods Adhesive PRODUCT NAME

UPC NUMBER : 60758, 60760, 60761, 60762, 25176, 26178

PRODUCT USE/CLASS : Resilent Sheet Goods Adhesive

24 HOUR EMERGENCY: MANUFACTURER:

DAP INC. TRANSPORTATION: 1-800-535-5053 (352-323-3500) MEDICAL : 1-800-327-3874 (513-558-5111) 2400 BOSTON STREET

BALTIMORE, MD 21224

PREPARE DATE : 01/17/1996 GENERAL INFORMATION:

REVISION NO. : 3 DAP INC. : 1-888-DAP-TIPS (1-888-327-8477)

REVISION DATE: 01/05/2000

|-----SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

WT/WT %

----- CHEMICAL NAME ----- CAS NUMBER RANGE ______

NO HAZARDOUS MATERIALS ARE CONTAINED IN THIS PRODUCT.

----- EXPOSURE LIMITS ------ACGIH OSHA COMPANY

ITEM TLV-TWA TLV-STEL PEL-TWA PEL-CEILING TLV-TWA SKIN ______

(See Section 16 for abbreviation legend)

Ingredients are not considered hazardous per the OSHA Hazard Communication Standard.

Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); limits may vary between states.

|-----| SECTION 3 - HAZARDS IDENTIFICATION |-----

EMERGENCY OVERVIEW: CAUTION! In an emergency situation, this product should not pose a significant immediate concern for emergency response personnel.

POTENTIAL HEALTH EFFECTS:

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation.

| Product Name: LE 3000 Sheet Goods Adhesive Revision Date: 01/05/2000 Page 2 |
|--|
| SECTION 3 - HAZARDS IDENTIFICATION |
| EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact with skin may cause irritation. |
| EFFECTS OF OVEREXPOSURE - INHALATION: Vapor may irritate nose and upper respiratory tract. |
| EFFECTS OF OVEREXPOSURE - INGESTION: No Information. |
| EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Prolonged or repeated contact with skin may cause irritation. |
| MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY CONTACT: None known. |
| PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INGESTION |
| SECTION 4 - FIRST AID MEASURES |
| EYE CONTACT: Flush with large quantities of water until irritation subsides. Contact a physician. |
| SKIN CONTACT: Wash with soap and water. |
| INHALATION: Remove to fresh air. Contact a physician immediately. |
| INGESTION: DO NOT INDUCE VOMITING. Contact a physician or Regional Poison Control Center immediately. |
| COMMENTS: None. |
| SECTION 5 - FIRE FIGHTING MEASURES |
| FLASH POINT: >200 F (SETAFLASH CLOSED CUP) LOWER EXPLOSIVE LIMIT: N.A. UPPER EXPLOSIVE LIMIT: N.A. |
| AUTOIGNITION TEMPERATURE: N.E. |
| EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM |
| UNUSUAL FIRE AND EXPLOSION HAZARDS: None known. |
| SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces. |
| SECTION 6 - ACCIDENTAL RELEASE MEASURES |

SPILL OR LEAK PROCEDURES: Use absorbent material or scrape up dried material and place into containers.

Product Name: LE 3000 Sheet Goods Adhesive

Revision Date: 01/05/2000 Page 3

_____ SECTION 7 - HANDLING AND STORAGE

HANDLING INFORMATION: KEEP OUT OF REACH OF CHILDREN. Avoid prolonged or repeated contact with skin. Avoid contact with eyes.

STORAGE INFORMATION: Store away from caustics and oxidizers. Keep containers tightly closed when not in use. Keep containers from excessive heat and freezing. Do not store at temperatures above 120 degrees F.

OTHER PRECAUTIONS: Use in a well ventilated area. Provide fresh air such that chemical odors cannot be detected during use and while drying.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Good mechanical ventilation and local exhaust.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Not required under normal usage and adequate ventilation.

EYE PROTECTION: Safety glasses with side shields recommended.

SKIN PROTECTION: Gloves recommended for repeated or prolonged contact with skin.

OTHER PROTECTIVE EQUIPMENT: None.

HYGIENIC PRACTICES: Although this product is not considered an eye irritant, inhalation hazard, or a skin contact hazard under normal conditions, it is advisable that personnel minimize skin contact, inhalation of vapors, and eye contact. Remove contaminated clothing and wash before reuse.

_____ SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES _____

BOILING RANGE : 210 - 220 F VAPOR DENSITY : Is heavier than air

ODOR : Sweet Odor

APPEARANCE : Off-White EVAPORATION RATE: Is slower than Butyl

SOLUBILITY IN H2O: N.E. Acetate

SPECIFIC GRAVITY : 1.2798

VAPOR PRESSURE : 17.5 mm Hg @ 68F.

PHYSICAL STATE : Paste

(See Section 16 for abbreviation legend)

| Product Name: LE 3000 Sheet Goods Adhesive Revision Date: 01/05/2000 | Page | |
|---|-------------------------------|------------|
| | | j |
| CONDITIONS TO AVOID: Excessive heat and freezing. | | |
| INCOMPATIBILITY: Strong oxidizers and caustics. | | |
| HAZARDOUS DECOMPOSITION PRODUCTS: Normal decompositon products, NOx | i.e. CO | Ͻx, |
| HAZARDOUS POLYMERIZATION: Will not occur under normal conditions. | | |
| STABILITY: This product is stable under normal storage conditions | | |
| SECTION 11 - TOXICOLOGICAL PROPERTIES | | |
| The toxicological properties of this material are unknown, however cased on the toxicity of its constituents, it is expected to have relatively low toxicity. | | |
| SECTION 12 - ECOLOGICAL INFORMATION | | İ |
| No Information. | | ' |
| SECTION 13 - DISPOSAL CONSIDERATIONS | | |
| WASTE MANAGEMENT/DISPOSAL: Dispose of according to Federal, State Local Standards. This product does not meet the definition of a local standards to U.S. EPA Hazardous Waste Management Regulations Section 261. State and Local regulations/restrictions are completed if for from Federal regulations. Responsiblity for proper waste downth the owner of the waste. | hazardo s, 40 (x and r | CFR nay |
| EPA WASTE CODE - If discarded (40 CFR 261): None. | | |
| SECTION 14 - TRANSPORTATION INFORMATION | | |
| DOT PROPER SHIPPING NAME: Not Regulated by D.O.T. | | |
| DOT HAZARD CLASS: NONE | | |

DOT UN/NA NUMBER: NONE PACKING GROUP: NONE

______ Product Name: LE 3000 Sheet Goods Adhesive Revision Date: 01/05/2000 Page 5 |-----| SECTION 15 - REGULATORY INFORMATION |-----| U.S. FEDERAL REGULATIONS: AS FOLLOWS -OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200) SARA SECTION 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: ----- CHEMICAL NAME ----- CAS NUMBER WT/WT % RANGE No SARA Section 313 components exist in this product. TOXIC SUBSTANCES CONTROL ACT: This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States: ----- CHEMICAL NAME ----- CAS NUMBER No information is available NEW JERSEY RIGHT-TO-KNOW: The following materials are non-hazardous, but are among the top five components in this product: ----- CHEMICAL NAME ----- CAS NUMBER Water 7732-18-5 Hydrocarbon resin TSRN-801000805128P Hydrous Aluminum Silicate 1332-58-7 Hydrocarbon Oil TSRN-618608-5025P Calcium Carbonate 1317-65-3 PENNSYLVANIA RIGHT-TO-KNOW: The following non-hazardous ingredients are present in the product at greater than 3%: ----- CHEMICAL NAME ----- CAS NUMBER 7732-18-5 Hydrocarbon resin proprietary Carboxylated styrene butadiene proprietary Hydrous Aluminum Silicate 1332-58-7 Calcium Carbonate 1317-65-3 CALIFORNIA PROPOSITION 65: WARNING: The chemical(s) noted below and contained in this product, are

known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME ----- CAS NUMBER No Proposition 65 chemicals are known to exist in this product.

| Product Name: LE 3000 Sheet Goods Adhesive Revision Date: 01/05/2000 Pa | ge | 6 |
|---|------|----|
| SECTION 15 - REGULATORY INFORMATION | | |
| INTERNATIONAL REGULATIONS: AS FOLLOWS - | | |
| CANADIAN WHMIS: This MSDS has been prepared in compliance with Contr Product Regulations except for use of the 16 headings. | olle | ed |
| CANADIAN WHMIS CLASS: No information available. | | |
| SECTION 16 - OTHER INFORMATION | | |
| HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0 PREVIOUS MSDS REVISION DATE: 02/01/1997 | | |
| REASON FOR REVISION: SECTION 1: Address change and new emergency contact phone numbers. | | |
| VOC LESS WATER, LESS EXEMPT SOLVENTS: 0 grams/ltr VOC MATERIAL : 0 grams/ltr | | |
| LEGEND: ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGI N.A NOT APPLICABLE N.E NOT ESTABLISHED PEL - PERMISSIBLE EXPOSURE LIMIT NTP - NATIONAL TOXICOLOGY PROGRAM SARA - SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 198 STEL - SHORT TERM EXPOSURE LIMIT TLV - THRESHOLD LIMIT VALUE(8 HR. TIME WEIGHTED AVERAGE O VOC - VOLATILE ORGANIC COMPOUND | 6 | |
| NJRTK - NEW JERSEY RIGHT TO KNOW LAW N.D NOT DETERMINED | | |

MSDS# 77140

This data is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.
