

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: 005-W0136 BRITISH PAINTS EXTERIOR VARNISH

**GLOSS SPRAYPACK** 

Recommended use of the chemical

and restrictions on use:

Paint packed under pressure in an aerosol can.

Supplier: Cabot's Australia, a division of DuluxGroup (Australia) Pty Ltd

**ABN**: 67 000 049 427

Street Address: 1956 Dandenong Road

Clayton, Victoria

Australia

**Telephone Number:** +61 3 9263 5678

1800 011 006 (toll free) +61 3 9543 4346

1800 657 977 (toll free)

Emergency Telephone: 1 800 033 111 (ALL HOURS)

## 2. HAZARDS IDENTIFICATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS SUBSTANCE.

#### Risk Phrase(s):

Facsimile:

R12 Extremely Flammable.

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Poisons Schedule (SUSMP): None allocated.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Acetone	67-64-1	30-60%	R11 R36 R66 R67
Propellant (propane/butane)	-	10-<30%	R12
Mineral turpentine	-	10-<30%	R10, R38, R65
Kerosine	8008-20-6	1-<10%	R10, R38, R65
Ingredients determined not to be hazardous	-	to 100%	-

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Product Name: 005-W0136 BRITISH PAINTS EXTERIOR

VARNISH GLOSS SPRAYPACK Substance No: 000000052492 Issued: 05/09/2013

Version: 1



#### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

#### **Skin Contact:**

If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

#### **Eye Contact:**

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

#### Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

#### Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

### Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Hazchem or Emergency Action Code: 2YE

#### Specific hazards arising from the substance or mixture:

Flammable gas. On burning will emit toxic fumes, including those of oxides of carbon.

#### Special protective equipment and precautions for fire-fighters:

Keep containers cool with water spray. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Shut off all possible sources of ignition. In the event of an aerosol can developing a leak, allow to fully discharge in the open air before disposal.

### 7. HANDLING AND STORAGE

#### Precautions for safe handling:

Ensure spray nozzle is always directed away from the user. May form flammable vapour mixtures with air. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke. Avoid skin and eye contact and breathing in vapour. Keep out of reach of children. Vapour may travel a considerable distance to source of ignition and flash back.

#### Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

Product Name: 005-W0136 BRITISH PAINTS EXTERIOR

VARNISH GLOSS SPRAYPACK Substance No: 000000052492

Version: 1



## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control Parameters:** No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Acetone: 8hr TWA = 1185 mg/m<sup>3</sup> (500 ppm), 15 min STEL = 2375 mg/m<sup>3</sup> (1000 ppm)

Butane: 8hr TWA = 1900 mg/m³ (800 ppm) Mineral turpentine: 8hr TWA = 480 mg/m³

Propane: Asphyxiant

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

No Exposure Standards assigned to other constituents.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

Asphyxiant - gases which can lead to reduction of oxygen concentration by displacement or dilution. The minimum oxygen content in air should be 18% by volume under normal atmospheric pressure.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

#### Appropriate engineering controls:

Use in well ventilated areas. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

#### Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Personal Protection: G - OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.









Always wash hands before smoking, eating, drinking or using the toilet.

FOR CONSUMER USE: No special personal protective equipment required. Use with adequate ventilation. MANUFACTURE, PACKAGING AND TRANSPORT: Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS1716.

Product Name: 005-W0136 BRITISH PAINTS EXTERIOR

VARNISH GLOSS SPRAYPACK Substance No: 000000052492

Version: 1



## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Aerosol

**Solubility:** Insoluble in water. Soluble in organic solvents.

Specific Gravity: 0.8 @ 20°C

Relative Vapour Density (air=1): >1

Vapour Pressure (20 °C): Not available Flash Point (°C): -104°C (propane) Flammability Limits (%): 2.4-9.5 (propane) Not available **Autoignition Temperature (°C):** % Volatile by Volume: Not available Solubility in water (g/L): Insoluble Melting Point/Range (°C): Not applicable Boiling Point/Range (°C): Not available **Decomposition Point (°C):** Not available Not available Viscosity: **Evaporation Rate:** Not available

## 10. STABILITY AND REACTIVITY

**Reactivity:** No information available.

**Chemical stability:** Stable under normal conditions of use.

Possibility of hazardous reactions: Hazardous polymerisation will not occur.

Conditions to avoid: Avoid exposure to heat, sources of ignition, and open flame. Avoid exposure to direct

sunlight.

**Incompatible materials:** Incompatible with oxidising agents.

Hazardous decomposition

products:

Oxides of carbon.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

**Ingestion:** Swallowing can result in nausea, vomiting and central nervous system depression. If

the victim is showing signs of central system depression (like those of drunkeness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs. Breathing in vomit may lead to aspiration pneumonia (inflammation of the lung).

**Eye contact:** An eye irritant.

**Skin contact:** Contact with skin may result in irritation. Will have a degreasing action on the skin.

Repeated or prolonged skin contact may lead to irritant contact dermatitis.

Product Name: 005-W0136 BRITISH PAINTS EXTERIOR

VARNISH GLOSS SPRAYPACK Substance No: 000000052492 Issued: 05/09/2013

Version: 1



**Inhalation:** Intentional misuse by deliberately concentrating and breathing the contents can be

harmful or fatal. Material may be irritant to the mucous membranes of the respiratory tract (airways). Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if

exposure is prolonged, unconsciousness.

**Acute toxicity:** No LD50 data available for the product.

**Chronic effects:** No information available for the product.

### 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Avoid contaminating waterways.

### 13. DISPOSAL CONSIDERATIONS

#### Disposal methods:

Do not puncture or burn can when empty; contents are under pressure. If aerosol can develops a leak, allow to fully discharge before disposal. Normally suitable for disposal at approved land waste site.

## 14. TRANSPORT INFORMATION

#### Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail: DANGEROUS GOODS.



**UN No:** 1950

Transport Hazard Class: 2.1 Flammable Gas
Proper Shipping Name or AEROSOLS

**Technical Name:** 

Hazchem or Emergency Action 2YE

Code:

#### **Marine Transport**

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

**UN No:** 1950

Transport Hazard Class: 2.1 Flammable Gas

Proper Shipping Name or

**Technical Name:** 

AEROSOLS

Product Name: 005-W0136 BRITISH PAINTS EXTERIOR

VARNISH GLOSS SPRAYPACK Substance No: 000000052492

Version: 1



#### Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

**UN No:** 1950

Transport Hazard Class: 2.1 Flammable Gas
Proper Shipping Name or AEROSOLS, FLAMMABLE

**Technical Name:** 

## 15. REGULATORY INFORMATION

#### Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS SUBSTANCE.

#### Risk Phrase(s):

R12 Extremely Flammable.

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Poisons Schedule (SUSMP): None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION

#### Reason(s) for Issue:

First Issue Primary SDS

This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

DuluxGroup owns the Dulux trade mark in Australia, New Zealand, PNG and Fiji. It is not associated with and has no connection to the owners of the Dulux trade mark in other countries, nor does it sell Dulux products in other countries.

Product Name: 005-W0136 BRITISH PAINTS EXTERIOR

VARNISH GLOSS SPRAYPACK Substance No: 000000052492 Version: 1