



SAFETY DATA SHEET

SDS ID NO.: 0107MAR019 **Revision Date:** 05/14/2015

1. IDENTIFICATION

Product Name: Marathon Petroleum Iso-Butane

Synonym: Isobutane

Chemical Family: Hydrocarbon Gas

Recommended Use: Chemical intermediate.

Use Restrictions: All others.

Supplier Name and Address:

MARATHON PETROLEUM COMPANY LP 539 South Main Street Findlay, OH 45840

SDS information: 1-419-421-3070 **Emergency Telephone:** 1-877-627-5463

2. HAZARD IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous according to the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable gases	Category 1
Gases under pressure	Liquefied Gas
Simple Asphyxiant	-
Reproductive toxicity	Category 2
Acute aquatic toxicity	Category 3
Chronic aquatic toxicity	Category 3

Hazards Not Otherwise Classified (HNOC)

Static accumulating flammable liquid Liquid product may cause freeze burn

Label elements

EMERGENCY OVERVIEW

Danger

Extremely flammable gas

Contains gas under pressure; may explode if heated May accumulate electrostatic charge and ignite or explode

SDS ID NO.: 0107MAR019 Product name: Marathon Petroleum Iso-Butane Page 1 of 14

May displace oxygen and cause rapid suffocation Contact with liquid product may cause freeze burn Suspected of damaging fertility or the unborn child Harmful to aquatic life with long lasting effects



Appearance Colorless Liquefied Gas

Physical State Liquefied Gas

Odor Slight Hydrocarbon

Revision Date: 05/14/2015

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood Keep away from heat/sparks/open flames/hot surfaces. — No smoking Wear protective gloves/protective clothing/eye protection/face protection Avoid release to the environment

Precautionary Statements - Response

IF exposed or concerned: Get medical attention Leaking gas fire: Do not extinguish, unless leak can be stopped safely Eliminate all ignition sources if safe to do so

Precautionary Statements - Storage

Store in a well-ventilated place Protect from sunlight Store locked up

Precautionary Statements - Disposal

Dispose of contents/container at an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Iso-Butane is a mixture of aliphatic petroleum hydrocarbons.

Composition Information:

Name	CAS Number	Weight %
Isobutane	75-28-5	30-100
n-Butane	106-97-8	0-65
Butenes	25167-67-3	0-12
Propane	74-98-6	0-10
Isopentane	78-78-4	0-9
Isobutylene	115-11-7	0-4
n-Pentane	109-66-0	0-2.5
2,2-dimethylpropane	463-82-1	0-2
Propylene	115-07-1	0-2
n-Hexane	110-54-3	0-0.8

4. FIRST AID MEASURES

First Aid Measures

General advice

In case of accident or if you feel unwell, seek medical advice immediately (show directions for use or safety data sheet if possible).

SDS ID NO.: 0107MAR019 Product name: Marathon Petroleum Iso-Butane Page 2 of 14

0107MAR019 Marathon Petroleum Iso-Butane

Inhalation: Remove to fresh air. If not breathing, institute rescue breathing. If breathing is difficult,

ensure airway is clear, give oxygen and continue to monitor. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). GET IMMEDIATE MEDICAL

Revision Date: 05/14/2015

ATTENTION.

Skin Contact: If liquefied product has caused frostbite, remove contaminated clothing. Thaw frost bitten

areas slowly with lukewarm water or by wrapping affected areas with blankets. Do not rub affected areas. Let circulation reestablish itself naturally, exercising area if possible. GET

IMMEDIATE MEDICAL ATTENTION.

Eye Contact: Liquid: Flush with large amounts of tepid water for at least 15 minutes. If frostbite is

suspected (cloudy lens or greyish white tissue around the eye), GET IMMEDIATE

MEDICAL ATTENTION.

Gas: Call a physician if signs or symptoms of contact occur, including irritation.

Ingestion: Ingestion not likely. If swallowed, immediately call a physician.

Most important signs and symptoms, both short-term and delayed with overexposure

Adverse Effects: Asphyxiant gas. High concentrations in the immediate area can displace oxygen causing

the feeling of suffocation and can cause headache, drowsiness, dizziness, loss of

coordination, disorientation and fatigue from oxygen deprivation.

Indication of any immediate medical attention and special treatment needed

NOTES TO PHYSICIAN: Treat symptomatically. Administer supplemental oxygen as needed. Epinephrine and other

sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this

material. Administration of sympathomimetic drugs should be avoided.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

For small fires, Class B fire extinguishing media such as CO2 or dry chemical can be used. For large fires use water spray or fog. Firefighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.

Unsuitable extinguishing media

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the chemical

This product has been determined to be an extremely flammable gas per the OSHA Hazard Communication Standard and should be handled accordingly. May accumulate electrostatic charge and ignite or explode. Sealed containers may rupture when heated. A phenomena known as boiling liquid expanding vapor explosions (Bleve) can occur when a liquid in a pressurized container comes in close proximity to a fire and reaches a temperature well above its boiling point. A catastrophic failure of the vessel can occur, resulting in flying equipment fragments, a shock wave and a fireball causing serious damage and death. For additional fire related information see NFPA 30 or North American Emergency Response Guide 115.

Hazardous combustion products

Smoke, carbon monoxide, and other products of incomplete combustion.

Explosion data

Sensitivity to Mechanical Impact No. Sensitivity to Static Discharge Yes.

Special protective equipment and precautions for firefighters

Firefighters should wear full protective clothing and positive-pressure self-contained breathing apparatus (SCBA) with a full face-piece, as appropriate. Isolate hazard area. If safe to do so, stop the flow of gas and allow fire to burn out. Extinguishing the flame before shutting off the supply can cause the formation of explosive mixtures. In some cases it may be preferred to allow the flame to continue to burn. Use extreme caution when fighting liquefied petroleum gas fires. Keep surrounding area cool with water spray from a distance and prevent further ignition of combustible material. Avoid use of solid water streams. Contact with water and liquefied product can cause increased vaporization.

NFPA: Health 1 Flammability 4 Instability 1 Special Hazards -

SDS ID NO.: 0107MAR019 Product name: Marathon Petroleum Iso-Butane Page 3 of 14

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Keep people away from and upwind of spill/leak. Isolate and evacuate area. Shut off source

if safe to do so. Distant ignition and flashback are possible. Eliminate all ignition sources. Use grounded and bonded, explosion-proof equipment. Monitor area for flammable or explosive atmosphere. Before entry, especially into confined areas, check atmosphere with

Revision Date: 05/14/2015

an appropriate monitor.

Protective Equipment: Use personal protection measures as recommended in Section 8.

Emergency Procedures: Leaking containers should be moved outdoors or to well-ventilated area and contents

transferred to a suitable container. Product vapor is heavier than air and can collect in low areas that are without sufficient ventilation. Notify local health and pollution control

agencies, if appropriate.

Environmental precautions: If leaking, take appropriate steps to disperse gas.

Methods and materials for

containment:

Prevent further leakage or spillage if safe to do so.

Methods and materials for cleaning Shut off gas supply, if safe to do so. Isolate area until gas has dispersed. **up:**

7. HANDLING AND STORAGE

Safe Handling Precautions: Avoid breathing gas or mists. Use only with adequate ventilation. Gas may accumulate

along the ground, settle in low lying areas or be moved by ventilation and ignited by many sources such as pilot lights, sparks, electric motors, static discharge, or other ignition sources at locations distant from material handling. Flashback may occur along vapor trails. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. Use only non-sparking tools Use appropriate grounding and bonding practices. Bonding and grounding may be insufficient to eliminate the hazard from static electricity. Do not cut, drill, grind or weld on empty containers since explosive residues may remain. Comply with all

applicable EPA, OSHA, NFPA and consistent state and local requirements.

Storage Conditions: Product is stored as a liquid but used in the gaseous state. Store in properly closed

containers that are appropriately labeled and in a cool, well-ventilated area. Keep product and empty container away from heat and sources of ignition. Do not puncture or incinerate

container.

Incompatible materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	ACGIH TLV	OSHA PELS:	OSHA - Vacated PELs	NIOSH IDLH
Isobutane 75-28-5	1000 ppm STEL	-	-	-
n-Butane 106-97-8	1000 ppm STEL	-	800 ppm TWA 1900 mg/m³ TWA	-
Butenes 25167-67-3	250 ppm TWA	-	-	-
Propane 74-98-6	Simple asphyxiant	TWA: 1000 ppm TWA: 1800 mg/m ³	1000 ppm TWA 1800 mg/m³ TWA	2100 ppm
Isopentane 78-78-4	1000 ppm TWA	-	-	-
Isobutylene 115-11-7	250 ppm TWA	-	-	-

SDS ID NO.: 0107MAR019 Product name: Marathon Petroleum Iso-Butane Page 4 of 14

n-Pentane 109-66-0	1000 ppm TWA	TWA: 1000 ppm TWA: 2950 mg/m ³	600 ppm TWA 1800 mg/m³ TWA 750 ppm STEL 2250 mg/m³ STEL	1500 ppm
2,2-dimethylpropane 463-82-1	1000 ppm TWA	-	-	-
Propylene 115-07-1	500 ppm TWA	-	-	-
n-Hexane 110-54-3	50 ppm TWA Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 500 ppm TWA: 1800 mg/m³	50 ppm TWA 180 mg/m³ TWA	1100 ppm

Notes:

The manufacturer has voluntarily elected to provide exposure limits contained in OSHA's 1989 air contaminants standard in its SDSs, even though certain of those exposure limits were vacated in 1992.

Revision Date: 05/14/2015

Engineering measures:

Local or general exhaust required in an enclosed area or when there is inadequate ventilation. Use mechanical ventilation equipment that is explosion-proof. Monitor atmospheric oxygen levels.

Personal protective equipment

Eye protection: Goggles or faceshield may be needed when handling pressurized gases.

Skin and body protection: Wear insulated gloves to prevent skin contact and frostbite or freeze burn. Contact the

glove manufacturer for specific advice on glove selection and breakthrough times.

Respiratory protection: Use atmosphere supplying respirators in the event of oxygen deficiency, when material

produces vapors that exceed permissible limits, or when excessive vapors are generated. Observe respirator assigned protection factors (APFs) criteria cited in federal OSHA 29

CFR 1910.134.

Note: Air purifying respirators are not to be used in atmospheres that exceed the maximum use concentration (as directed by regulation or the manufacturers instructions), in oxygen deficient atmospheres, (less than 19.5% oxygen) or under conditions that are immediately

dangerous to life and health (IDLH).

Extremely flammable gas

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes and clothing. Do not smoke while handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquefied Gas

Appearance Colorless Liquefied Gas

Color Colorless

OdorSlight HydrocarbonOdor ThresholdNo available data.

Property
Melting Point / Freezing Point
Initial Boiling Point / Boiling Range
Flash Point
Evaporation Rate

Values (Method)
-159 °C / -255 °F
-11 °C / 11 °F
-87 °C / -124 °F
No available data.

Flammability (solid, gas)
Flammability Limit in Air (%)

Upper Flammability Limit: 8.4 Lower Flammability Limit: 1.8

Vapor Pressure 72.8 psi @ 100°F Vapor Density 2.1 (Air = 1) Specific Gravity / Relative Density 0.564

SDS ID NO.: 0107MAR019 Product name: Marathon Petroleum Iso-Butane Page 5 of 14

Water Solubility No available data. Solubility in other solvents No available data. **Partition Coefficient** No available data. **Decomposition temperature:** No available data. pH: Not applicable 462 °C / 863 °F **Autoignition Temperature Kinematic Viscosity** No available data. **Dynamic Viscosity** No available data. **Explosive Properties** No available data. **Softening Point** No available data. **VOC Content (%)** No available data. 35.20 lb/ft3 @ 60°F **Density Bulk Density** Not applicable

10. STABILITY AND REACTIVITY

Reactivity The product is non-reactive under normal conditions.

<u>Chemical stability</u> The material is stable at 70°F, 760 mmHg pressure.

<u>Possibility of hazardous reactions</u>

None under normal processing.

<u>Hazardous polymerization</u>

Does not polymerize except under special conditions (extreme

temperatures, pressure, oxidizers).

Revision Date: 05/14/2015

<u>Conditions to avoid</u> Sources of heat or ignition.

Incompatible materials Strong oxidizing agents.

<u>Hazardous decomposition products</u>

None known under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Potential short-term adverse effects from overexposures

Inhalation May cause central nervous system depression with nausea, headache, dizziness, vomiting,

and incoordination. In high concentration the gas may cause suffocation. Victim may not be

aware of asphyxiation.

Eye contact Vapor is generally non-irritating to eyes. Direct contact with liquefied product can cause

freeze burn or frostbite.

Skin contact Vapor is generally non-irritating to skin. Direct contact with liquefied product can cause

freeze burn or frostbite.

Ingestion Ingestion not likely.

Acute Toxicological data

Name	Oral LD50	Dermal LD50	Inhalation LC50
Isobutane 75-28-5	-	-	570,000 ppm (Rat) 15 min
n-Butane 106-97-8	-	-	658 mg/L (Rat) 4 h
Butenes 25167-67-3	-	-	658 mg/L (Rat) 4 h
Propane 74-98-6	-	-	> 1,464 mg/L (Rat) 15 min
Isopentane 78-78-4	-	-	450 mg/L (Mouse) 2 h

SDS ID NO.: 0107MAR019 Product name: Marathon Petroleum Iso-Butane Page 6 of 14

Isobutylene 115-11-7	620 mg/kg (Rat)	-	-
n-Pentane 109-66-0	-	-	364 mg/L (Rat) 4 h
2,2-dimethylpropane 463-82-1	-	-	-
Propylene 115-07-1	-	-	658 mg/L (Rat) 4 h
n-Hexane 110-54-3	15000 mg/kg (Rat)	3000 mg/kg (Rabbit)	48000 ppm (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

BUTANES: Studies in laboratory animals indicate exposure to extremely high levels of butanes (1-10 or higher vol.% in air) may cause cardiac arrhythmias (irregular heartbeats) which may be serious or fatal.

Revision Date: 05/14/2015

BUTENES: Exposure to 0, 500, 2000 or 8000 ppm isobutene for two years did not produce evidence of carcinogencity in male and female mice or female rats. Male rats exposed to 8000 ppm produced an increase in thyroid tumors compared to controls in the study but not compared to historical controls. Thyroid tumors observed in chronic rat studies have been regarded as of questionable relevance to humans at low concentrations since isobutene is not genotoxic and chronic respiratory irritation (stress) can cause disruption of thyroid metabolism. Male and female rats exposed to up to 5000 ppm, 8000 ppm or 8000 ppm 1-butene, 2-butane or isobutene for 4-6 weeks prior to and during mating resulted in no general systemic/neurotoxic effects. No effects on fertility or reproductive performance, pup survival and neonatal development were observed with any butene isomer tested. PROPANE: Studies in laboratory animals indicate exposure to extremely high levels of propane (1 to 10 vol.% in air) may cause cardiac arrhythmias (irregular heartbeats) which may be serious or fatal.

PENTANES: Studies of pentane isomers in laboratory animals indicate exposure to extremely high levels (roughly 10 vol.%) may induce cardiac arrhythmias (irregular heartbeats) which may be serious or fatal.

PROPYLENE: At extremely high levels propylene gas acts as a general anesthetic and central nervous system depressant. Studies in laboratory animals indicate evidence of mild, reversible hydrocarbon nephropathy in male rats exposed to levels of 1000-4,500 ppm propylene for 90-days. The International Agency for Research in Cancer (IARC) has determined that there is inadequate evidence in experimental animals for the carcinogenicity of propylene. Overall evaluation: Propylene is not classifiable as to its carcinogenicity to humans (Group 3).

N-HEXANE: Long-term or repeated exposure to n-hexane can cause peripheral nerve damage. Initial symptoms are numbness of the fingers and toes. Also, motor weakness can occur in the digits, but may also involve muscles of the arms, thighs and forearms. The onset of these symptoms may be delayed for several months to a year after the beginning of exposure. Testicular atrophy and partial to full loss of the germ cell line were observed in sub-chronic high-dose inhalation studies of laboratory rodents. These effects appeared irreversible. Rodent reproduction studies have shown evidence of reduced fetal weight but no frank malformations.

Adverse effects related to the physical, chemical and toxicological characteristics

Signs & Symptoms Headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue.

Sensitization Not expected to be a skin or respiratory sensitizer.

Mutagenic effects None known.

Carcinogenicity Cancer designations are listed in the table below.

Name	ACGIH	IARC	NTP	OSHA
	(Class)	(Class)		

SDS ID NO.: 0107MAR019 Product name: Marathon Petroleum Iso-Butane Page 7 of 14

Isobutane 75-28-5	Not Listed	Not Listed	Not Listed	Not Listed
n-Butane 106-97-8	Not Listed	Not Listed	Not Listed	Not Listed
Butenes 25167-67-3	Not Listed	Not Listed	Not Listed	Not Listed
Propane 74-98-6	Not Listed	Not Listed	Not Listed	Not Listed
Isopentane 78-78-4	Not Listed	Not Listed	Not Listed	Not Listed
Isobutylene 115-11-7	Not classifiable (A4)	Not Listed	Not Listed	Not Listed
n-Pentane 109-66-0	Not Listed	Not Listed	Not Listed	Not Listed
2,2-dimethylpropane 463-82-1	Not Listed	Not Listed	Not Listed	Not Listed
Propylene 115-07-1	Not Listed	Not Classifiable (3)	Not Listed	Not Listed
n-Hexane 110-54-3	Not Listed	Not Listed	Not Listed	Not Listed

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (STOT) - single exposure

Not classified.

Specific Target Organ Toxicity (STOT) - repeated exposure

Not classified.

Aspiration hazard Not applicable.

12. ECOLOGICAL INFORMATION

Ecotoxicity

This product should be considered harmful to aquatic organisms, with the potential to cause long lasting adverse effects in the aquatic environment.

Revision Date: 05/14/2015

Name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Isobutane 75-28-5	-	-	-	-
n-Butane 106-97-8	-	-	-	-
Butenes 25167-67-3	-	96-hr LC50 = 19 mg/L Fish	-	48-hr LC50 = 11 mg/l Daphnia
Propane 74-98-6	-	-	-	-
Isopentane 78-78-4	-	96-hr LC50 = 3.1 mg/L Rainbow trout	-	48-hr EC50 = >1 - <10 mg/L Daphnia magna
Isobutylene 115-11-7	-	96-hr LC50 = 22 mg/L Fish	-	-
n-Pentane 109-66-0	-	96-hr LC50 >1 - <10 mg/L Rainbow trout	-	48-hr EC50 = 9.7 mg/L Daphnia magna
2,2-dimethylpropane 463-82-1	-	-	-	-
Propylene 115-07-1	-	-	-	-
n-Hexane 110-54-3	-	96-hr LC50 = 2.5 mg/l Fathead minnow	<u>-</u>	-

<u>Persistence and degradability</u> Expected to be inherently biodegradable.

<u>Bioaccummulation</u> Not expected to bioaccumulate in aquatic organisms.

<u>Mobility in soil</u> Expected to rapidly partition to air.

SDS ID NO.: 0107MAR019 Product name: Marathon Petroleum Iso-Butane Page 8 of 14

Revision Date: 05/14/2015

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Description of Waste Residues

No information available.

Safe Handling of Wastes

Handle in accordance with applicable local, state, and federal regulations. Use personal protection measures as required. Use appropriate grounding and bonding practices. Use only non-sparking tools. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. No smoking.

Disposal of Wastes / Methods of Disposal

The user is responsible for determining if any discarded material is a hazardous waste (40 CFR 262.11). Dispose of in accordance with federal, state and local regulations.

Methods of Contaminated Packaging Disposal

Empty containers should be completely drained and then discarded or recycled, if possible. Do not cut, drill, grind or weld on empty containers since explosive residues may be present. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT (49 CFR 172.101):

UN Proper shipping name:
UN/Identification No:
UN 1969
Transport Hazard Class(es):
2.1

Packing group: Not applicable

TDG (Canada):

UN Proper shipping name: Isobutane UN/Identification No: UN 1969 Transport Hazard Class(es): 2.1

Packing group: Not applicable

15. REGULATORY INFORMATION

US Federal Regulatory Information:

US TSCA Chemical Inventory Section 8(b): This product and/or its components are listed on the TSCA

Chemical Inventory.

EPA Superfund Amendment & Reauthorization Act (SARA):

SARA Section 302: This product does not contain any component(s) included on EPA's Extremely Hazardous Substance (EHS) List.

Name	CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs
Isobutane	NA
n-Butane	NA
Butenes	NA
Propane	NA
Isopentane	NA
Isobutylene	NA
n-Pentane	NA
2,2-dimethylpropane	NA
Propylene	NA
n-Hexane	NA

SDS ID NO.: 0107MAR019 Product name: Marathon Petroleum Iso-Butane Page 9 of 14

SARA Section 304:

This product may contain component(s) identified either as an EHS or a CERCLA Hazardous substance which in case of a spill or release may be subject to SARA reporting

Revision Date: 05/14/2015

requirements:

Name	CERCLA/SARA - Hazardous Substances and the Reportable Quantities	
Isobutane	NA	
n-Butane	NA	
Butenes	NA	
Propane	NA	
Isopentane	NA	
Isobutylene	NA	
n-Pentane	NA	
2,2-dimethylpropane	NA	
Propylene	NA	
n-Hexane	5000 lb final RQ 2270 kg final RQ	

SARA: The following EPA hazard categories apply to this product:

Acute Health Hazard Chronic Health Hazard

Fire Hazard

Sudden Release Of Pressure

SARA Section 313:

This product may contain component(s), which if in exceedance of the de minimus threshold, may be subject to the reporting requirements of SARA Title III Section 313 Toxic Release Reporting (Form R).

Name	CERCLA/SARA 313 Emission reporting:
Isobutane	None
n-Butane	None
Butenes	None
Propane	None
Isopentane	None
Isobutylene	None
n-Pentane	None
2,2-dimethylpropane	None
Propylene	1.0 % de minimis concentration
n-Hexane	1.0 % de minimis concentration

State and Community Right-To-Know Regulations:

The following component(s) of this material are identified on the regulatory lists below:

Isobutane

Louisiana Right-To-Know: Not Listed. California Proposition 65: Not Listed. New Jersey Right-To-Know: SN 1040 Pennsylvania Right-To-Know: Present Massachusetts Right-To Know: Present Florida Substance List: Not Listed. Rhode Island Right-To-Know: Not Listed. Michigan Critical Materials Register List: Not Listed. Massachusetts Extraordinarily Hazardous Substances: Not Listed. California - Regulated Carcinogens: Not Listed. Pennsylvania RTK - Special Hazardous Not Listed.

Substances:

New Jersey - Special Hazardous Substances:

New Jersey - Environmental Hazardous

Flammable - fourth degree

SN 1040 TPQ: 500 lb

Substances List:

Illinois - Toxic Air Contaminants Not Listed.

SDS ID NO.: 0107MAR019 Product name: Marathon Petroleum Iso-Butane Page 10 of 14

Revision Date: 05/14/2015

New York - Reporting of Releases Part 597 - Not Listed.

List of Hazardous Substances:

n-Butane

Louisiana Right-To-Know:Not Listed.California Proposition 65:Not Listed.New Jersey Right-To-Know:SN 0273Pennsylvania Right-To-Know:PresentMassachusetts Right-To Know:PresentFlorida Substance List:Not Listed.

Rhode Island Right-To-Know: Toxic; Flammable

Michigan Critical Materials Register List:

Massachusetts Extraordinarily Hazardous Substances:

California - Regulated Carcinogens:

Pennsylvania RTK - Special Hazardous

Not Listed.

Not Listed.

Not Listed.

Substances:

New Jersey - Special Hazardous Substances: Flammable - fourth degree New Jersey - Environmental Hazardous SN 0273 TPQ: 500 lb

Substances List:

Illinois - Toxic Air Contaminants Not Listed.

New York - Reporting of Releases Part 597 - Not Listed.

List of Hazardous Substances:

Butenes

Louisiana Right-To-Know: Not Listed. California Proposition 65: Not Listed. New Jersey Right-To-Know: SN 0286 Pennsylvania Right-To-Know: Present Massachusetts Right-To Know: Not Listed. Florida Substance List: Not Listed. Rhode Island Right-To-Know: Flammable Michigan Critical Materials Register List: Not Listed. Massachusetts Extraordinarily Hazardous Substances: Not Listed. California - Regulated Carcinogens: Not Listed. Pennsylvania RTK - Special Hazardous Not Listed.

Substances:

New Jersey - Special Hazardous Substances: Flammable - fourth degree New Jersey - Environmental Hazardous SN 0286 TPQ: 500 lb

Substances List:

Illinois - Toxic Air Contaminants Not Listed.

New York - Reporting of Releases Part 597 - Not Listed.

List of Hazardous Substances:

Propane

Louisiana Right-To-Know:Not Listed.California Proposition 65:Not Listed.New Jersey Right-To-Know:SN 1594Pennsylvania Right-To-Know:PresentMassachusetts Right-To Know:PresentFlorida Substance List:Not Listed.

Rhode Island Right-To-Know: Toxic; Flammable Michigan Critical Materials Register List: Not Listed.

Massachusetts Extraordinarily Hazardous Substances:
California - Regulated Carcinogens:
Pennsylvania RTK - Special Hazardous
Not Listed.
Not Listed.
Not Listed.

Substances:

New Jersey - Special Hazardous Substances: Flammable - fourth degree New Jersey - Environmental Hazardous SN 1594 TPQ: 500 lb

Substances List:

Illinois - Toxic Air Contaminants Not Listed.

New York - Reporting of Releases Part 597 - Not Listed.

List of Hazardous Substances:

Isopentane

Louisiana Right-To-Know: Not Listed.
California Proposition 65: Not Listed.

SDS ID NO.: 0107MAR019 Product name: Marathon Petroleum Iso-Butane Page 11 of 14

Revision Date: 05/14/2015

New Jersey Right-To-Know: SN 1064 Pennsylvania Right-To-Know: Present Massachusetts Right-To Know: Present Florida Substance List: Not Listed. Rhode Island Right-To-Know: Not Listed. Michigan Critical Materials Register List: Not Listed. Massachusetts Extraordinarily Hazardous Substances: Not Listed. California - Regulated Carcinogens: Not Listed. Pennsylvania RTK - Special Hazardous Not Listed.

Substances:

New Jersey - Special Hazardous Substances: Flammable - fourth degree New Jersey - Environmental Hazardous SN 1064 TPQ: 500 lb

Substances List:

Illinois - Toxic Air Contaminants Not Listed.

New York - Reporting of Releases Part 597 - Not Listed.

List of Hazardous Substances:

Isobutylene

Louisiana Right-To-Know: Not Listed. California Proposition 65: Not Listed. New Jersey Right-To-Know: SN 1045 Pennsylvania Right-To-Know: Present Massachusetts Right-To Know: Present Florida Substance List: Not Listed. Rhode Island Right-To-Know: Flammable Michigan Critical Materials Register List: Not Listed. Massachusetts Extraordinarily Hazardous Substances: Not Listed. California - Regulated Carcinogens: Not Listed. Pennsylvania RTK - Special Hazardous Not Listed.

Substances:

New Jersey - Special Hazardous Substances: Flammable - fourth degree New Jersey - Environmental Hazardous SN 1045 TPQ: 500 lb

Substances List:

Illinois - Toxic Air Contaminants Not Listed.

New York - Reporting of Releases Part 597 - Not Listed.

List of Hazardous Substances:

n-Pentane

Louisiana Right-To-Know:Not Listed.California Proposition 65:Not Listed.New Jersey Right-To-Know:SN 1476Pennsylvania Right-To-Know:PresentMassachusetts Right-To Know:PresentFlorida Substance List:Not Listed.

Rhode Island Right-To-Know: Toxic; Flammable

Michigan Critical Materials Register List:

Massachusetts Extraordinarily Hazardous Substances:
California - Regulated Carcinogens:
Pennsylvania RTK - Special Hazardous

Not Listed.
Not Listed.
Not Listed.

Substances:

New Jersey - Special Hazardous Substances: Flammable - fourth degree New Jersey - Environmental Hazardous SN 1476 TPQ: 500 lb

Substances List:

Illinois - Toxic Air Contaminants Not Listed.

New York - Reporting of Releases Part 597 - Not Listed.

List of Hazardous Substances:

2,2-dimethylpropane

Louisiana Right-To-Know:

California Proposition 65:

New Jersey Right-To-Know:

Pennsylvania Right-To-Know:

Massachusetts Right-To Know:

Florida Substance List:

Rhode Island Right-To-Know:

Not Listed.

Not Listed.

Not Listed.

SDS ID NO.: 0107MAR019 Product name: Marathon Petroleum Iso-Butane Page 12 of 14

0107MAR019 Marathon Petroleum Iso-Butane

Revision Date: 05/14/2015

Michigan Critical Materials Register List:

Massachusetts Extraordinarily Hazardous Substances:

California - Regulated Carcinogens:

Pennsylvania RTK - Special Hazardous

Not Listed.

Not Listed.

Not Listed.

Substances:

New Jersey - Special Hazardous Substances: Flammable - fourth degree New Jersey - Environmental Hazardous SN 0766 TPQ: 500 lb

Substances List:

Illinois - Toxic Air Contaminants Not Listed.

New York - Reporting of Releases Part 597 - Not Listed.

List of Hazardous Substances:

Propylene

Louisiana Right-To-Know:

California Proposition 65:

New Jersey Right-To-Know:

Not Listed.

Not Listed.

Not Listed.

Not Listed.

SN 1609

Pennsylvania Right-To-Know: Environmental hazard

Massachusetts Right-To Know: Present
Florida Substance List: Not Listed.

Rhode Island Right-To-Know: Toxic; Flammable

Michigan Critical Materials Register List:

Massachusetts Extraordinarily Hazardous Substances:

California - Regulated Carcinogens:

Pennsylvania RTK - Special Hazardous

Not Listed.

Not Listed.

Not Listed.

Substances:

New Jersey - Special Hazardous Substances: Flammable - fourth degree New Jersey - Environmental Hazardous SN 1609 TPQ: 500 lb

Substances List:

Illinois - Toxic Air Contaminants Not Listed.

New York - Reporting of Releases Part 597 - Not Listed.

List of Hazardous Substances:

n-Hexane

Louisiana Right-To-Know:Not Listed.California Proposition 65:Not Listed.New Jersey Right-To-Know:SN 1340Pennsylvania Right-To-Know:PresentMassachusetts Right-To Know:PresentFlorida Substance List:Not Listed.

Rhode Island Right-To-Know: Toxic; Flammable

Michigan Critical Materials Register List:

Massachusetts Extraordinarily Hazardous Substances:
California - Regulated Carcinogens:
Pennsylvania RTK - Special Hazardous

Not Listed.
Not Listed.
Not Listed.

Substances:

New Jersey - Special Hazardous Substances: Flammable - third degree New Jersey - Environmental Hazardous SN 1340 TPQ: 500 lb

Substances List:

Illinois - Toxic Air Contaminants Present

New York - Reporting of Releases Part 597 - 1 lb RQ (air); 1 lb RQ (land/water)

List of Hazardous Substances:

Canada DSL/NDSL Inventory: This product and/or its components are listed either on the Domestic Substances List (DSL)

or are exempt.

Canadian Regulatory Information: "This product has been classified in accordance with the hazard criteria of the Controlled

Products Regulations and the (M)SDS contains all the information required by the

Controlled Products Regulations."

Name	Canada - WHMIS: Classifications of Substances:	Canada - WHMIS: Ingredient Disclosure:
Isobutane	A,B1	1%
n-Butane	A,B1	1%
Butenes	A,B1	1%

SDS ID NO.: 0107MAR019 Product name: Marathon Petroleum Iso-Butane Page 13 of 14

0107MAR019 Marathon Petroleum Iso-Butane

Revision Date: 05/14/2015

Propane	A,B1	1%
Isopentane	B2	1%
Isobutylene	A,B1	1%
n-Pentane	B2	1%
2,2-dimethylpropane	A,B1	1%
Propylene	A,B1,D2B	1%
n-Hexane	B2,D2A,D2B	1%



NOTE: Not Applicable.

16. OTHER INFORMATION

Prepared By Toxicology and Product Safety

Revision Date: 05/14/2015

Revision Note: Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is intended as guidance for safe handling, use, processing, storage, transportation, accidental release, clean-up and disposal and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SDS ID NO.: 0107MAR019 Product name: Marathon Petroleum Iso-Butane Page 14 of 14