

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version 8.0	Revision Date: 11/29/2017	SDS Number: 380769-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	---

SECTION 1. IDENTIFICATION

Product name : Industrial Enamel Paint, Gloss, Safety Yellow, 425 g

Product code : 892.177

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : CANUTEC (24/7): +1 (613) 996-6666 or/ou *666 (cellular/cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Paint
Coatings

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1

Gases under pressure : Liquefied gas

Eye irritation : Category 2A

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ systemic toxicity - single exposure : Category 3

Specific target organ systemic toxicity - repeated exposure : Category 2 (Central nervous system, Liver, Kidney)

Simple Asphyxiant : Category 1

GHS label elements

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version 8.0	Revision Date: 11/29/2017	SDS Number: 380769-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	---

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs (Central nervous system, Liver, Kidney) through prolonged or repeated exposure.
May displace oxygen and cause rapid suffocation.

Precautionary Statements

:

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Other hazards

Repeated exposure may cause skin dryness or cracking.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Acetone	67-64-1	$\geq 20 - < 30$
Propane	74-98-6	$\geq 10 - < 20$
Butane	106-97-8	$\geq 5 - < 10$
Isobutyl methyl ketone	108-10-1	$\geq 1 - < 5$
Titanium dioxide	13463-67-7	$\geq 1 - < 5$
2-(Propyloxy)ethanol	2807-30-9	$\geq 1 - < 5$
n-Butyl acetate	123-86-4	$\geq 1 - < 5$
Xylene	1330-20-7	$\geq 1 - < 5$
Pentan-2-one	107-87-9	$\geq 1 - < 5$
Ethylethoxypropionate	763-69-9	$\geq 1 - < 5$
Isobutyl acetate	110-19-0	$\geq 1 - < 5$
Ethylbenzene	100-41-4	$\geq 0.1 - < 1$
Zirconium octoate	22464-99-9	$\geq 0.1 - < 1$

SECTION 4. FIRST AID MEASURES

General advice	: In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	: If inhaled, remove to fresh air. Get medical attention.
In case of skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention.
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	: Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version 8.0	Revision Date: 11/29/2017	SDS Number: 380769-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	---

Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.
Prolonged or repeated contact may dry skin and cause irritation.

Protection of first-aiders	:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
Notes to physician	:	Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides
Metal oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures	: See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	: Use with local exhaust ventilation. Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential
Advice on safe handling	: Do not spray on an open flame or other ignition source. Do not get on skin or clothing. Do not breathe vapors or spray mist. Do not swallow. Do not get in eyes. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.
Conditions for safe storage	: Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.
Materials to avoid	: Do not store with the following product types:

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version 8.0 Revision Date: 11/29/2017 SDS Number: 380769-00008 Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives

Recommended storage temperature : 49 °C

Further information on storage stability : Protect from frost, heat and sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m ³	CA AB OEL
		STEL	750 ppm 1,800 mg/m ³	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	500 ppm 1,190 mg/m ³	CA QC OEL
		STEV	1,000 ppm 2,380 mg/m ³	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
		TWA	1,000 ppm	CA ON OEL
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm 1,900 mg/m ³	CA QC OEL
		TWA	800 ppm	CA ON OEL
		STEL	1,000 ppm	ACGIH
Isobutyl methyl ketone	108-10-1	TWA	50 ppm 205 mg/m ³	CA AB OEL
		STEL	75 ppm 307 mg/m ³	CA AB OEL

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**
Version
8.0Revision Date:
11/29/2017SDS Number:
380769-00008Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

		TWA	20 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWAEV	50 ppm 205 mg/m ³	CA QC OEL
		STEV	75 ppm 307 mg/m ³	CA QC OEL
		TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
Titanium dioxide	13463-67-7	TWA	10 mg/m ³	CA AB OEL
		TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m ³	CA BC OEL
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH
2-(Propyloxy)ethanol	2807-30-9	TWA	25 ppm 110 mg/m ³	CA ON OEL
n-Butyl acetate	123-86-4	STEL	200 ppm 950 mg/m ³	CA AB OEL
		TWA	150 ppm 713 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	150 ppm 713 mg/m ³	CA QC OEL
		STEV	200 ppm 950 mg/m ³	CA QC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Xylene	1330-20-7	STEL	150 ppm 651 mg/m ³	CA AB OEL
		TWA	100 ppm 434 mg/m ³	CA AB OEL
		TWAEV	100 ppm 434 mg/m ³	CA QC OEL
		STEV	150 ppm 651 mg/m ³	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
Pentan-2-one	107-87-9	STEL	250 ppm 881 mg/m ³	CA AB OEL
		TWA	200 ppm 705 mg/m ³	CA AB OEL
		TWA	150 ppm	CA BC OEL
		STEL	250 ppm	CA BC OEL
		TWAEV	150 ppm 530 mg/m ³	CA QC OEL
		STEL	150 ppm	ACGIH

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

 Version
8.0

 Revision Date:
11/29/2017

 SDS Number:
380769-00008

 Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

Ethylethoxypropionate	763-69-9	TWA	50 ppm 300 mg/m ³	CA ON OEL
Isobutyl acetate	110-19-0	TWA	150 ppm 713 mg/m ³	CA AB OEL
		TWA	150 ppm	CA BC OEL
		TWAEV	150 ppm 713 mg/m ³	CA QC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m ³	CA AB OEL
		STEL	125 ppm 543 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	100 ppm 434 mg/m ³	CA QC OEL
		STEV	125 ppm 543 mg/m ³	CA QC OEL
		TWA	20 ppm	ACGIH
Zirconium octoate	22464-99-9	TWA	5 mg/m ³ (Zirconium)	CA AB OEL
		STEL	10 mg/m ³ (Zirconium)	CA AB OEL
		TWAEV	5 mg/m ³ (Zirconium)	CA QC OEL
		STEV	10 mg/m ³ (Zirconium)	CA QC OEL
		TWA	5 mg/m ³ (Zirconium)	CA BC OEL
		STEL	10 mg/m ³ (Zirconium)	CA BC OEL
		TWA	5 mg/m ³ (Zirconium)	ACGIH
		STEL	10 mg/m ³ (Zirconium)	ACGIH

Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly-	Urine	End of shift (As soon as possible)	0.15 g/g creatinine	ACGIH BEI

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version 8.0 Revision Date: 11/29/2017 SDS Number: 380769-00008 Date of last issue: 06/27/2017
Date of first issue: 12/30/2009

		oxylic acid		after exposure ceases)		
Isobutyl methyl ketone	108-10-1	methyl isobutyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI
Xylene	1330-20-7	Methyl-hippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential
Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection
Material : Protective gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
Flame retardant antistatic protective clothing, unless assessment demonstrates that the risk of explosive atmospheres or flash fires is low
Skin contact must be avoided by using impervious protective

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version 8.0	Revision Date: 11/29/2017	SDS Number: 380769-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	---



clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Color	: yellow
Odor	: solvent
Odor Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: -42 °C
Flash point	: -35 °C Active ingredient
Evaporation rate	: 5.6
Flammability (solid, gas)	: Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	: 16 %(V)
Lower explosion limit / Lower flammability limit	: 1 %(V)
Vapor pressure	: Not applicable
Relative vapor density	: 5
Relative density	: No data available
Density	: 0.8 g/cm ³
Solubility(ies) Water solubility	: No data available
Partition coefficient: n-octanol/water	: Not applicable
Autoignition temperature	: No data available

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version 8.0	Revision Date: 11/29/2017	SDS Number: 380769-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	---

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.
Vapors may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 40 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Ingredients:**Acetone:**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 40 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg

Propane:

Acute inhalation toxicity	: LC50 (Rat): > 800000 ppm Exposure time: 15 min Test atmosphere: gas
---------------------------	---

Butane:

Acute inhalation toxicity	: LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: vapor
---------------------------	--

Isobutyl methyl ketone:

Acute oral toxicity	: LD50 (Rat): 2,080 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 11.6 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

Titanium dioxide:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 6.82 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity

2-(Propyloxy)ethanol:

Acute oral toxicity	: LD50 (Mouse): 3,089 mg/kg
Acute dermal toxicity	: LD50 (Rabbit): 1,337 mg/kg

n-Butyl acetate:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
---------------------	-----------------------------

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Xylene:

Acute oral toxicity : LD50 (Rat): 4,300 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): 27.5 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg
Method: Expert judgment
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Pentan-2-one:

Acute oral toxicity : LD50 (Rat): 1,600 - 3,200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25.5 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 436
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Ethylethoxypropionate:

Acute oral toxicity : LD50 (Rat): 4,309 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): 4,080 mg/kg

Isobutyl acetate:

Acute oral toxicity : LD50 (Rat): 13,413 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 30 mg/l
Exposure time: 6 h

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version 8.0	Revision Date: 11/29/2017	SDS Number: 380769-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	---

Test atmosphere: vapor
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 17,400 mg/kg

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17.2 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Zirconium octoate:

Acute oral toxicity : LD50 (Rat): 2,043 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Ingredients:**Acetone:**

Assessment: Repeated exposure may cause skin dryness or cracking.

Isobutyl methyl ketone:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Assessment: Repeated exposure may cause skin dryness or cracking.

Titanium dioxide:

Species: Rabbit
Result: No skin irritation

2-(Propyloxy)ethanol:

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Species: Rabbit
Result: No skin irritation

n-Butyl acetate:

Species: Rabbit
Result: No skin irritation

Assessment: Repeated exposure may cause skin dryness or cracking.

Xylene:

Species: Rabbit
Result: Skin irritation

Pentan-2-one:

Species: Guinea pig
Method: OECD Test Guideline 404
Result: No skin irritation

Ethylethoxypropionate:

Assessment: Repeated exposure may cause skin dryness or cracking.

Isobutyl acetate:

Assessment: Repeated exposure may cause skin dryness or cracking.

Zirconium octoate:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Ingredients:**Acetone:**

Species: Rabbit
Result: Irritation to eyes, reversing within 21 days
Method: OECD Test Guideline 405

Isobutyl methyl ketone:

Result: Irritation to eyes, reversing within 21 days
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Titanium dioxide:

Species: Rabbit
Result: No eye irritation

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

2-(Propyloxy)ethanol:

Species: Rabbit
Result: Irritation to eyes, reversing within 21 days

n-Butyl acetate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Xylene:

Species: Rabbit
Result: Irritation to eyes, reversing within 7 days

Pentan-2-one:

Species: Rabbit
Result: Irritation to eyes, reversing within 7 days

Ethylethoxypropionate:

Species: Rabbit
Result: No eye irritation

Isobutyl acetate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
Remarks: Based on data from similar materials

Ethylbenzene:

Species: Rabbit
Result: No eye irritation

Zirconium octoate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:**Acetone:**

Test Type: Maximization Test

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Routes of exposure: Skin contact
Species: Guinea pig
Result: negative

Isobutyl methyl ketone:

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Titanium dioxide:

Test Type: Local lymph node assay (LLNA)
Routes of exposure: Skin contact
Species: Mouse
Result: negative

2-(Propyloxy)ethanol:

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

n-Butyl acetate:

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative

Xylene:

Test Type: Local lymph node assay (LLNA)
Routes of exposure: Skin contact
Species: Mouse
Method: OECD Test Guideline 429
Result: negative

Ethylethoxypropionate:

Test Type: Freund's complete adjuvant test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative

Isobutyl acetate:

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Result: negative

Ethylbenzene:

Test Type: Human repeat insult patch test (HRIPT)
Routes of exposure: Skin contact
Result: negative

Zirconium octoate:

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative
Remarks: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Ingredients:**Acetone:**

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
Genotoxicity in vivo	: Test Type: In vivo micronucleus test Species: Hamster Application Route: Intraperitoneal injection Result: negative

Propane:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 474 Result: negative

Butane:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 474 Result: negative

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version 8.0	Revision Date: 11/29/2017	SDS Number: 380769-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	---

Remarks: Based on data from similar materials

Isobutyl methyl ketone:

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Result: negative Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative

Titanium dioxide:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: In vivo micronucleus test Species: Mouse Result: negative

2-(Propyloxy)ethanol:

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
-----------------------	--

n-Butyl acetate:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
-----------------------	--

Xylene:

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Result: negative Test Type: In vitro sister chromatid exchange assay in mammalian cells Result: negative
Genotoxicity in vivo	: Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Mouse

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version 8.0	Revision Date: 11/29/2017	SDS Number: 380769-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	---

Application Route: Skin contact
Result: negative

Pentan-2-one:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Ethylethoxypropionate:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Isobutyl acetate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Ethylbenzene:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with mammalian liver cells in vivo
Species: Mouse
Application Route: Inhalation
Method: OECD Test Guideline 486
Result: negative

Zirconium octoate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Suspected of causing cancer.

Ingredients:**Acetone:**

Species: Mouse
Application Route: Skin contact
Exposure time: 1 Years
Result: negative

Isobutyl methyl ketone:

Species: Rat
Application Route: inhalation (vapor)
Exposure time: 2 Years
Method: OECD Test Guideline 451
Result: positive
Remarks: The mechanism or mode of action may not be relevant in humans.

Species: Mouse
Application Route: inhalation (vapor)
Exposure time: 2 Years
Method: OECD Test Guideline 451
Result: positive
Remarks: The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Titanium dioxide:

Species: Rat
Application Route: inhalation (dust/mist/fume)
Exposure time: 2 Years
Method: OECD Test Guideline 453
Result: positive
Remarks: The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

Xylene:

Species: Rat

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Application Route: Ingestion
Exposure time: 103 weeks
Result: negative

Ethylbenzene:

Species: Rat
Application Route: Inhalation
Exposure time: 104 weeks
Result: positive
Remarks: The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Suspected of damaging the unborn child.

Ingredients:**Acetone:**

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Result: negative

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Butane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Isobutyl methyl ketone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: inhalation (vapor)
Result: negative

2-(Propyloxy)ethanol:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: inhalation (vapor)
Result: negative

n-Butyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Pentan-2-one:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version 8.0	Revision Date: 11/29/2017	SDS Number: 380769-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	---

test
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 421
Result: negative

Ethylethoxypropionate:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Isobutyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OPPTS 870.3800
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Inhalation
Result: negative
Remarks: Based on data from similar materials

Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 415
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

Zirconium octoate:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

STOT-single exposure

May cause drowsiness or dizziness.

Ingredients:**Acetone:**

Assessment: May cause drowsiness or dizziness.

Propane:

Assessment: May cause drowsiness or dizziness.

Butane:

Assessment: May cause drowsiness or dizziness.

Isobutyl methyl ketone:

Assessment: May cause respiratory irritation.

n-Butyl acetate:

Assessment: May cause drowsiness or dizziness.

Xylene:

Assessment: May cause respiratory irritation.

Isobutyl acetate:

Assessment: May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Central nervous system, Liver, Kidney) through prolonged or repeated exposure.

Ingredients:**Xylene:**

Routes of exposure: inhalation (vapor)

Target Organs: Central nervous system, Liver, Kidney

Assessment: Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Ethylbenzene:

Routes of exposure: inhalation (vapor)

Target Organs: Auditory system

Assessment: Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Repeated dose toxicity**Ingredients:****Acetone:**

Species: Rat
LOAEL: 1,700 mg/kg
Application Route: Ingestion
Exposure time: 90 Days

Propane:

Species: Rat
NOAEL: 7.214 mg/l
Application Route: inhalation (gas)
Exposure time: 6 Weeks
Method: OECD Test Guideline 422

Butane:

Species: Rat
NOAEL: 9000 ppm
Application Route: inhalation (gas)
Exposure time: 6 Weeks
Method: OECD Test Guideline 422

Isobutyl methyl ketone:

Species: Rat
NOAEL: 1,840 mg/m³
Application Route: inhalation (vapor)
Exposure time: 13 Weeks

Titanium dioxide:

Species: Rat
NOAEL: 24,000 mg/kg
Application Route: Ingestion
Exposure time: 28 Days

Species: Rat
NOAEL: 10 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 2 y

2-(Propyloxy)ethanol:

Species: Rat
LOAEL: 195 mg/kg
Application Route: Ingestion
Exposure time: 6 Weeks

n-Butyl acetate:

Species: Rat

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

NOAEL: 2.4 mg/l
Application Route: inhalation (vapor)
Exposure time: 90 Days

Xylene:

Species: Rat
NOAEL: 4.35 mg/l
Application Route: inhalation (vapor)
Exposure time: 90 Days

Ethylethoxypropionate:

Species: Rat
NOAEL: 1,000 mg/kg
Application Route: Ingestion
Exposure time: 29 Days
Method: OECD Test Guideline 407

Isobutyl acetate:

Species: Rat
NOAEL: 316 mg/kg
Application Route: Ingestion
Exposure time: 92 Days
Remarks: Based on data from similar materials

Ethylbenzene:

Species: Rat, female
LOAEL: 75 ppm
Application Route: inhalation (vapor)
Exposure time: 104 Weeks

Zirconium octoate:

Species: Rat
NOAEL: 300 mg/kg
Application Route: Ingestion
Exposure time: 91 - 93 Days
Remarks: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Ingredients:**Xylene:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

II**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****Acetone:**

- | | | |
|--|---|---|
| Toxicity to fish | : | LC50 (Pimephales promelas (fathead minnow)): 6,210 - 8,120 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia pulex (Water flea)): 8,800 mg/l
Exposure time: 48 h |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC (Daphnia magna (Water flea)): 1,106 - 2,212 mg/l
Exposure time: 28 d |

Isobutyl methyl ketone:

- | | | |
|--|---|---|
| Toxicity to fish | : | LC50 (Danio rerio (zebra fish)): > 179 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 200 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC (Daphnia magna (Water flea)): 30 mg/l
Exposure time: 21 d |
| Toxicity to microorganisms | : | EC10 (Pseudomonas putida): 275 mg/l
Exposure time: 16 h |

Titanium dioxide:

- | | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h |
| Toxicity to algae | : | EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l
Exposure time: 72 h |
| Toxicity to microorganisms | : | EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209 |

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

2-(Propyloxy)ethanol:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 5,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 5,000 mg/l Exposure time: 48 h
Toxicity to algae	: NOEC (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to microorganisms	: IC50: > 1,000 mg/l Exposure time: 16 h

n-Butyl acetate:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 18 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia sp. (Water flea)): 44 mg/l Exposure time: 48 h
Toxicity to algae	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 23.2 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
Toxicity to microorganisms	: IC50 (Tetrahymena pyriformis): 356 mg/l Exposure time: 40 h

Xylene:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 2.6 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
------------------	---

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Toxicity to daphnia and other aquatic invertebrates	:	IC50 (Daphnia magna (Water flea)): 1 mg/l Exposure time: 24 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae	:	EC10 (Pseudokirchneriella subcapitata (green algae)): 1.9 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials ErC50 (Pseudokirchneriella subcapitata (green algae)): 4.36 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to fish (Chronic toxicity)	:	NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l Exposure time: 56 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	EC10 (Daphnia magna (Water flea)): 1.91 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
Toxicity to microorganisms	:	EC50: > 157 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Based on data from similar materials

Pentan-2-one:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 1,240 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 110 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	:	EC50 (Pseudokirchneriella subcapitata (green algae)): > 150 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 NOEC (Pseudokirchneriella subcapitata (green algae)): 73.77 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

Ethylethoxypropionate:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 55.3 mg/l Exposure time: 96 h
------------------	---	---

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

	Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (<i>Daphnia magna</i> (Water flea)): > 479.7 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	: EC50 (<i>Pseudokirchneriella subcapitata</i> (green algae)): > 114.86 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
	NOEC (<i>Pseudokirchneriella subcapitata</i> (green algae)): 114.86 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to microorganisms	: NOEC: 500 mg/l Exposure time: 16 h

Isobutyl acetate:

Toxicity to fish	: LC50 (<i>Oryzias latipes</i> (Japanese medaka)): 17 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (<i>Daphnia magna</i> (Water flea)): 25 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	: ErC50 (<i>Pseudokirchneriella subcapitata</i> (green algae)): 370 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
	NOEC (<i>Pseudokirchneriella subcapitata</i> (green algae)): 95 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (<i>Daphnia magna</i> (Water flea)): 23 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	: EC10 (<i>Pseudomonas putida</i>): 200 mg/l Exposure time: 16 h

Ethylbenzene:

Toxicity to fish	: LC50 (<i>Oncorhynchus mykiss</i> (rainbow trout)): 4.2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (<i>Daphnia magna</i> (Water flea)): 1.8 - 2.4 mg/l Exposure time: 48 h

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Toxicity to algae	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 5.4 mg/l Exposure time: 72 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Ceriodaphnia dubia (water flea)): 0.96 mg/l Exposure time: 7 d
Toxicity to microorganisms	:	EC50 (Nitrosomonas sp.): 96 mg/l Exposure time: 24 h Method: OECD Test Guideline 209

Zirconium octoate:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 180 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 0.17 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: No toxicity at the limit of solubility.
Toxicity to algae	:	EC50 (Desmodesmus subspicatus (green algae)): 49.3 mg/l Exposure time: 96 h Remarks: Based on data from similar materials EC10 (Desmodesmus subspicatus (green algae)): 32 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 25 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
Toxicity to microorganisms	:	EC50 (Pseudomonas putida): 112.1 mg/l Exposure time: 17 h Method: DIN 38 412 Part 8 Remarks: Based on data from similar materials

Persistence and degradability**Ingredients:****Acetone:**

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 91 % Exposure time: 28 d
------------------	---	---

Propane:

Biodegradability	:	Result: Readily biodegradable.
------------------	---	--------------------------------

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version 8.0	Revision Date: 11/29/2017	SDS Number: 380769-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	---

Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Butane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Isobutyl methyl ketone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

2-(Propyloxy)ethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 20 d

n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 87.8 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Pentan-2-one:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Ethylethoxypropionate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 18 d
Method: OECD Test Guideline 301B

Isobutyl acetate:

Biodegradability : Result: Readily biodegradable.

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version 8.0	Revision Date: 11/29/2017	SDS Number: 380769-00008	Date of last issue: 06/27/2017 Date of first issue: 12/30/2009
----------------	------------------------------	-----------------------------	---

Biodegradation: 81 %
Exposure time: 20 d

Ethylbenzene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d

Zirconium octoate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 99 %
Exposure time: 28 d
Method: OECD Test Guideline 301E
Remarks: Based on data from similar materials

Bioaccumulative potential**Ingredients:****Acetone:**

Partition coefficient: n-octanol/water : log Pow: -0.24

Butane:

Partition coefficient: n-octanol/water : log Pow: 2.31

Isobutyl methyl ketone:

Partition coefficient: n-octanol/water : log Pow: 1.9

2-(Propyloxy)ethanol:

Partition coefficient: n-octanol/water : log Pow: 0.673

n-Butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3

Xylene:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 5.4 - 25.9

Partition coefficient: n-octanol/water : log Pow: 3.12 - 3.2

Pentan-2-one:

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Partition coefficient: n-octanol/water : log Pow: 0.857

Ethylethoxypropionate:

Partition coefficient: n-octanol/water : log Pow: 1.47

Isobutyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3

Ethylbenzene:

Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): < 100
Remarks: Based on data from similar materials

Partition coefficient: n-octanol/water : log Pow: 3.6

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 1950

Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Labels : 2.1**IATA-DGR**

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable

Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
ERG Code : 126
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**Volatile organic compounds
(VOC) content**

VOC content: 72.36 % / 574.49 g/l

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWA	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
--	---	---

**Industrial Enamel Paint, Gloss, Safety Yellow,
425 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/27/2017
8.0	11/29/2017	380769-00008	Date of first issue: 12/30/2009

Revision Date : 11/29/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8