

Product name DUR-O-SET® E-200
MSDS number 85403
Revision Number 4

Revision Date NAGH/EN
Issuing date May.26.2015
May.26.2015

1. Product and company identification

Trade Name

DUR-O-SET® E-200

Celanese Ltd.

222 W. Las Colinas Blvd., Suite 900N
Irving, TX 75039
United States
Phone: 972 443 4000
Internet: www.celanese.com

Transportation emergency phone numbers:

For Chemical Emergency: Spill Leak Fire Exposure or Accident
Call CHEMTREC Day or Night
DOMESTIC NORTH AMERICA: 800-424-9300
INTERNATIONAL, CALL +1 703-527-3887 (collect calls accepted)

2. Hazard Identification

Hazard Statements

This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard (29CFR 1910.1200)

3. Composition/information on ingredients

Chemical characterization Water-borne polymer emulsion.

Components	CAS-No	Percent %
Vinyl Acetate - Ethylene Copolymer		54.5 - 56.5
Water	7732-18-5	43.5 - 45.5

4. First aid measures

General Information

Wash contaminated clothing before re-use.

Skin

Wash off with soap and water. If symptoms persist, call a physician.

Eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.

Product name	DUR-O-SET® E-200		NAGH/EN
MSDS number	85403	Revision Date	May.26.2015
Revision Number	4	Issuing date	May.26.2015

Inhalation

Move to fresh air. If symptoms persist, call a physician.

Ingestion

If swallowed, seek medical advice immediately and show this container or label.

5. Fire-fighting measures

Suitable extinguishing media

The product in solution form does not burn. The product will burn only after the water it contains is driven off. For dry polymer, use alcohol resistant foam, carbon dioxide (CO₂) or dry chemical.

Special protective equipment for fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

Other Information

This is a water-based product and presents no particular fire or explosion hazard

6. Accidental release measures

Personal precautions

Contaminated surfaces will be extremely slippery. Avoid contact with the skin and the eyes.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Contaminated equipment (brushes, rags) must be cleaned immediately with water. Dispose of in accordance with local regulations.

7. Handling and storage

Advice on safe handling

Product may contain hazardous volatile ingredients which could accumulate in the unvented headspace of drums or containers. Open containers in ventilated area. Do not breathe vapor. During longer storage small amounts of carbon monoxide may form. To the best of our knowledge, no OEL (occupational exposure limit) is exceeded during the intended use. Containers/tanks may only be entered after thoroughly executed ventilation while considering national regulations and international standards for inspection of containers/tanks. In any case of doubt a measurement of the CO concentration is necessary.

Protection - fire and explosion:

No special protective measures against fire required.

Technical measures/Storage conditions

Keep tightly closed in a dry and cool place. No special technical protective measures required.

Material storage

Protect from frost. Keep at temperatures between 5°C and 35°C (40°F and 95°F). Agitate before use. Keep tightly closed in a dry and cool place.

Product name DUR-O-SET® E-200
MSDS number 85403
Revision Number 4

Revision Date
Issuing date

NAGH/EN
 May.26.2015
 May.26.2015

Incompatible products
 Materials that react with water

8. Exposure controls / personal protection

OSHA Exposure Limits
 No exposure limits established.

ACGIH Exposure Limits
 No exposure limits established.

Mexico National Exposure Limits
 No exposure limits established

Exposure controls

Engineering measures
 Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Protective equipment
 A safety shower and eyebath should be readily available.

General advice
 Avoid contact with skin and eyes.

Skin protection:
 Wear impervious clothing and gloves when there is a reasonable chance for skin contact..

Eyel/face protection:
 safety glasses with side-shields.

9. Physical and chemical properties

Appearance

Form	liquid
Color	milky white
Odor	sweet
Freezing point	0°C
Boiling point/range	100°C (212°F)
pH	4.5
Viscosity	2300 cPs
Specific Gravity	1.00

Product name DUR-O-SET® E-200
MSDS number 85403
Revision Number 4

Revision Date NAGH/EN
Issuing date May.26.2015
 May.26.2015

10. Stability and reactivity

Chemical stability

Stable under recommended storage conditions

Conditions to avoid

Do not freeze

Incompatible Materials

Materials that react with water

Possibility of hazardous reactions

No hazards to be especially mentioned.

11. Toxicological information

Potential health effects

Routes of exposure Skin, eyes, ingestion

Immediate effects

Skin	Prolonged or repeated exposure may cause: skin irritation
Eyes	May cause eye irritation.
Ingestion	May cause gastrointestinal irritation.

Toxicological data are not available. Observe the usual hygienic measures for handling chemicals.

12. Ecological Information

Ecotoxicological data are not available. According to experience, the material has no harmful effect on the environment.

13. Disposal considerations

Disposal considerations

Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste.

Product name DUR-O-SET® E-200
MSDS number 85403
Revision Number 4

Revision Date NAGH/EN
Issuing date May.26.2015
May.26.2015

14. Transport information

US Department of Transportation Not regulated

TDG Not regulated

Mexico Transport Information Not regulated

ICAO/IATA Not restricted

IMDG Not regulated

15. Regulatory Information

US State Regulations

Chemicals associated with the product which are subject to the state right-to-know regulations are listed along with the applicable state(s):
none

U.S. FEDERAL REGULATIONS

TSCA Inventory:

This product complies with the U.S. Toxic Substances Control Act (TSCA).

Environmental Regulations:

SARA 313 Chemicals

Contains no substances at or above the reporting threshold under Section 313.

SARA 311:

INTERNATIONAL REGULATIONS

CANADIAN REGULATIONS

WHMIS Classification: Not a WHMIS controlled product.

16. Other information

HMIS: Health: 1 Flammability: 0 Physical Hazard: 0

Prepared By

Product Stewardship Department
Celanese

For more information, consult the Technical Data Sheet (www.celanese-emulsions.com)

Product name	DUR-O-SET® E-200		NAGH/EN
MSDS number	85403	Revision Date	May.26.2015
Revision Number	4	Issuing date	May.26.2015

Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on Celanese owned data and public sources deemed valid or acceptable.. The absence of data elements required by ANSI or 1907/2006/EC indicates that no data meeting these requirements is available..

Changes against the previous version are marked by ***

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. Celanese makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Material safety data sheets are provided on the Internet by Celanese as a service to its customers. Possession of an Internet MSDS does not indicate that the possessor of the MSDS was a purchaser or user of the subject product.