

Material Safety Data Sheets

1. Product and Company Identification

Product Name	: UV ink LF-200 Magenta
Product Code	: SPC-0558M,SPC-0591M,SPC-0660M
General Use	: Inkjet Ink
Product Description	: UV Inkjet Ink
MSDS Number	: 031-34U05MC
Manufacture	
Company Name	: MIMAKI ENGINEERING Co., Ltd
Address	: 2182-3 Otsu, Shigeno, Tomi-shi, Nagano 389-0512 Japan
Telephone No.	: +81-268-64-2413
Importer/Distributor Established in USA	
Company Name	: MIMAKI USA. INC.
Address	: 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A
Telephone No.	: 1-678-730-0100
Emergency Telephone No.	: +81-268-64-2413

2. Hazards Identification

Emergency Overview	: Closed containers exposed to heat from fire may build pressure and explode. Hazardous polymerization may occur. May cause severe eye irritation. May cause allergic skin reaction. May cause severe skin irritation. Contains a chemical or chemicals which can cause birth defects or other reproductive effects.
Potential Health Effects	
Inhalation	: Respiratory Tract Irritation Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.
Eye Contact	: Severe Eye Irritation Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.
Skin Contact	: Severe Skin Irritation Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Material Safety Data Sheets

: Allergic Skin Reaction (non-photo induced)

Signs/symptoms may include redness, swelling, blistering, and itching

Ingestion

: Gastrointestinal Irritation

Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Medical Conditions

: Contains a chemical or chemicals which can cause birth defects or other reproductive effects.

HMIS Rating (scale 0 – 4)

Not available

NFPA Rating (scale 0 – 4)

Health: 2

Flammability: 1

Instability: 2

Special: None



3. Composition / Information On Ingredients

No.	Chemical Name	Wt%	CAS No.	Chemical Formula
1	Isobornyl Acrylate	40-50	5888-33-5	C ₁₃ H ₂₀ O ₂
2	Tetrahydrofurfuryl Acrylate	10-20	2399-48-6	C ₈ H ₁₂ O ₃
3	2,4,6-Trimethylbenzoyldiphenylphosphine oxide	5.0-15	75980-60-8	C ₂₂ H ₂₁ O ₂ P
4	Diethylene Glycol Ethyl Ether Acrylate	5.0-15	7328-17-8	C ₉ H ₁₆ O ₄
5	Substituted Triazine	1.0-15	Trade Secret	Trade Secret
6	Amine Modified Acrylate Oligomer	1.0-15	Trade Secret	Trade Secret
7	9H-Thioxanthen-9-one,2,4-diethyl-	1.0-10	82799-44-8	C ₁₇ H ₁₆ OS
8	Polymeric Amide 510390490-8248P	1.0-10	Trade Secret	Trade Secret
9	2,9-Dichloroquinacridone	1.0-10	3089-17-6	C ₂₀ H ₁₀ O ₂ N ₂ Cl ₂
10	4-Methoxyphenol	<0.5	150-76-5	C ₇ H ₈ O ₂

4. First Aid Measures

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Inhalation

: Remove person to fresh air.

If signs/symptoms develop, get medical attention.

Material Safety Data Sheets

Eye Contact	: Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.
Skin Contact	: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.
Ingestion	: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

5. Fire Fighting Measures

Flammable Properties	Autoignition temperature	: No Data Available
	Flash Point	: >200 degree Fahrenheit [Test Method: Closed Cup]
	Flammable Limits – LEL	: No Data Available
	Flammable Limits – UEL	: No Data Available
Extinguishing Media	: Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).	
Protection of Fire Fighters		
Special Fire Fighting Procedures	: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).	
Unusual Fire and Explosion Hazards	: Closed containers exposed to heat from fire may build pressure and explode.	

Note: See Stability and Reactivity (SECTION 10) for hazardous combustion and thermal decomposition information.

Material Safety Data Sheets

6. Accidental Release Measures

Observe precautions from other sections.

Evacuate unprotected and untrained personnel from hazard area.

The spill should be cleaned up by qualified personnel.

Ventilate the area with fresh air.

For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

Contain spill.

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material.

Mix in sufficient absorbent until it appears dry.

Collect as much of the spilled material as possible.

Clean up residue with an appropriate solvent selected by a qualified and authorized person.

Ventilate the area with fresh air.

Read and follow safety precautions on the solvent label and MSDS.

Collect the resulting residue containing solution.

Place in a closed container approved for transportation by appropriate authorities.

Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state and federal regulations.

7. Handling And Storage

- | | |
|----------|---|
| Handling | : Do not eat, drink or smoke when using this product.
Wash exposed areas thoroughly with soap and water.
Avoid breathing of vapors, mists or spray.
Avoid skin contact.
Avoid eye contact with vapors, mists, or spray.
Avoid contact with oxidizing agents. |
| Storage | : Store away from heat.
Store out of direct sunlight. |

Material Safety Data Sheets

Store away from oxidizing agents.

8. Exposure Controls / Personal Protection

Exposure Limit Values

No.	Chemical Name		TWA	Additional Information
1	4-Methoxyphenol	ACGIH	5.0mg/m ³	Table Z-1A
		OSHA	5.0mg/m ³	

Source of exposure limit data:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

Exposure Controls

Occupational Exposure Controls

Engineering Controls : Provide local exhaust ventilation at transfer points.
 Provide Appropriate local exhaust when product is heated.
 Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

Personal Protection

Respiratory Protection : Avoid breathing of vapors, mists or spray.



Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations:

Half facepiece or fullface air-purifying respirator with organic vapor cartridges.

Eye/Face Protection : Avoid eye contact with vapors, mists, or spray. The following eye protection(s) are recommended:



Safety Glasses with side shields, Indirect Vented Goggles.(Goggles recommended when a splash potential exists.)

Material Safety Data Sheets

Skin Protection



: Wear appropriate gloves, such as Nomex, when handling this material to prevent thermal burns.

Avoid skin contact.

Avoid skin contact with hot material.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment.

Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Nitrile Rubber.

Prevention of Swallowing

: Do not eat, drink or smoke when using this product.

Wash exposed areas thoroughly with soap and water.

9. Physical And Chemical Properties

Appearance	- Physical state	: Liquid
	- Color	: Magenta
Odor		: Acrylate odor
pH		: Not Applicable
Boiling Point / Boiling Range		: >200 degree F
Melting Point / Melting Range		: Not Applicable
Flash Point		: >200 degree F [Test Method: Closed Cup]
Autoignition Temperature		: No data available
Flammable Limits		: No data available
Vapor Pressure		: <10 mmHg [20 degree C]
Specific Gravity		: 1.04 [Ref Std: WATER=1]
Water Solubility		: Negligible
Viscosity		: 7~11mPa·s (45 degree C)
Vapor Density		: >1 [ref Std: Air=1]

10. Stability And Reactivity

Stability	: Stable
Materials and Conditions to avoid	: Strong oxidizing agents: Heat

Material Safety Data Sheets

Hazardous	: Hazardous polymerization may occur.	
Polymerization	(Upon depletion of inhibitor or exposure to heat)	
Hazardous Decomposition or By-Products	Substance	Condition
	Carbon monoxide	During Combustion
	Carbon dioxide	During Combustion

11. Toxicological Information

Acute Toxicity	: Not available
Eye Irritation	: May cause severe eye irritation.
Skin Irritation	: May cause severe skin irritation.
Inhalation	: The irritation of the respiratory system.
Ingestion	: A gastrointestinal tract organization may be irritated.
Sensitization	: May cause allergic skin irritation.
Mutagenicity	: Not available
Reproductive and Developmental Toxicity	: Contains a chemical or chemicals which can cause birth defects or other reproductive effects

12. Ecological Information

Handling is noted because it might influence the environment when leaking and abandoning it. Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch.

Ecotoxicity	: Not available
Persistence and Degradability	: Not available
Bioaccumulative Potential	: Not available
Other Adverse Effects	: Not available

13. Disposal Considerations

Waste Disposal Method	: Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste. Since regulations vary, consult applicable regulations or authorities before disposal. <u>Do not dump this product into sewers, on the ground or into any body of water.</u>
-----------------------	--

Material Safety Data Sheets

EPA Hazardous Waste Number (RCRA): Not regulated


Since regulations vary, consult applicable regulations or authorities before.

14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

Land transport ADR/RID (cross-border)



ADR/RID class : 9 Miscellaneous dangerous substances and articles.

Danger code (Kemler) : 90


UN-Number : 3082

Packaging group : III

Hazard label : 9

Description of goods : 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.

Sea Transport (IMDG)



Class : 9

Packing Group (PG) : III


UN Number : 3082

Proper Shipping : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

Name : N.O.S.

Marine Pollutant : No

Air Transport (ICAO/IATA)



Class : 9

Material Safety Data Sheets

Packing Group(PG) : III
 UN Number : 3082
 Proper Shipping Name : Proper shipping name: ENVIRONMENTALLY HAZARDOUS
 Name : SUBSTANCE, LIQUID, N.O.S.
 UN "Model Regulation"
 : UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
 LIQUID, N.O.S.; 9; III
 Special precautions for user
 : Warning: Miscellaneous dangerous substances and articles
 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
 : Not applicable.

15. Regulatory Information

US Federal regulations

Section 311/312 : Fire Hazard-No Pressure Hazard-No Reactivity Hazard-No
 (40 CFR 370) Immediate Hazard – Yes Delayed Hazard – Yes
 Section 313 : Subject to the reporting requirements of this section and that.
 (40 CFR 372) EPCRA

Ingredient	Diethylene Glycol Ethyl Ether Acrylate
CAS No.	7328-17-8
Wt%	5.0-15

TSCA Status : The components of this product are in compliance with the chemical notification requirements of TSCA.

TSCA Section12[b] : Requirements of export notification

Ingredient	4-Methoxyphenol	9H-Thioxanthen-9-one,2,4-diethyl-
CAS No.	150-76-5	82799-44-8
Regulation	TSCA4 Test Rule Chemicals	TSCA5 SNUR or Consent Order Chemicals
States	Applicable	Applicable

TSCA Section 5 : EPA Significant New Use Rule Regulation

Ingredient	9H-Thioxanthen-9-one,2,4-diethyl-
CAS No.	82799-44-8
Reference	63FR3393

Please refer to any other USA, national and local measures.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard,29 CFR 1910.1200

Material Safety Data Sheets

16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation. It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process. Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.

Revision history

Version	Date	Content
1.0	2008/08/28	First issue
2.0	2009/07/24	Revised
3.0	2010/05/13	Revised
4.0	2011/10/11	Revised (14.Transport Information)