

Safety Data Sheets

1. Identification

Product Name : Latex ink LX100/LX101 White
Order No. : LX100-W-22
Ink Ver. : 3
General Use : Ink for ink jet printer
Product Description : Aqueous ink
SDS Number : 031-38W30WC
Manufacture
Company Name : Mimaki Engineering Co., Ltd.
Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN
Telephone No. : +81-268-64-2413
Importer / Distributor Established in USA
Company Name : MIMAKI USA, INC.
Address : 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A.
Telephone No. : +1-678-730-0100
Emergency Telephone No. : +81-268-64-2281

2. Hazards Identification

[GHS Classification]

Physical Hazards

Out of classification or No classification

Health Hazards

Skin Corrosion / Irritation : Category 3
Eye Damage / Irritation : Category 2A
Toxic to Reproduction : Category 2

Environmental Hazards

Out of classification or No classification

[GHS Label Elements]

Symbol



Safety Data Sheets

Signal Word

Warning

Hazard Statements

H316 Causes mild skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

Precautionary Statements

[Prevention]

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

[Response]

P308 + P313 If exposed or concerned: Get medical advice/attention.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

[Disposal]

P501 Dispose of contents / container in accordance with local / regional / national / international regulation.

3. Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.	Chemical Formula
1	Diethylene glycol derivative	10-30	Trade Secret	Trade Secret
2	Alcohol derivative	20-40	Trade Secret	Trade Secret
3	Pigment (Titanium dioxide)	1-10	13463-67-7	Trade Secret
4	Resin	1-10	Trade Secret	Trade Secret
5	Amine	0.1-1.5	Trade Secret	Trade Secret
6	Water	balance	7732-18-5	H ₂ O



Product Name: Latex ink LX100/LX101 White

MSDS No. 031-38W30WC

First issue: 2012/11/30

Revised: 2013/06/25

Safety Data Sheets

OSHA Hazardous : This material is considered hazardous.

Components

(29 CFR 1910.1200)

4. First Aid Measures

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, oxygen should be administered by qualified personnel. If breathing has stopped, start artificial respiration at once. Get immediate medical attention.

Eye Contact : Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get immediate medical attention.

Skin Contact : Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Ingestion : If swallowed, get medical attention. Do not give anything by mouth to an unconscious person.

5. Fire Fighting Measures

See Section 9 for Flammability Properties

NFPA Ratings : Health: 1 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate

3 = Serious 4 = Severe

Flammable Properties : This product is not a fire hazard, but may burn. Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition.

Extinguishing Media : regular dry chemical, carbon dioxide, water spray, foam

Fire Fighting : Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Instructions : Move container from fire area if it can be done without risk. Do not scatter spilled material with high-pressure water streams. Dike for



Product Name: Latex ink LX100/LX101 White

MSDS No. 031-38W30WC

First issue: 2012/11/30

Revised: 2013/06/25

Safety Data Sheets

later disposal. Use extinguishing agents appropriate for surrounding fire. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

6. Accidental Release Measures

Occupational spill/release : Wear personal protective clothing and equipment, see Section 8.
Collect spilled material in appropriate container for disposal. Keep unnecessary people away, isolate hazard area and deny entry. Avoid creation of vapor or mist.

7. Handling and Storage

Handling : Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Wash thoroughly after handling.
Storage : Store and handle in accordance with all current regulations and standards. Store in a tightly closed container. Keep away from incompatible materials.

8. Exposure Controls / Personal Protection

Exposure Limit Values

Titanium dioxide

ACGIH : 10 mg/m³ TLV-TWA

OSHA : 15 mg/m³ TWA

Exposure Controls

Occupational Exposure Controls

Engineering Controls : Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits

Personal Protection

Respiratory : Any chemical cartridge respirator with organic vapor cartridge(s).
Protection

Hand Protection : Wear appropriate chemical resistant gloves.

Eye Protection : Wear splash resistant safety goggles with a faceshield.



Product Name: Latex ink LX100/LX101 White

MSDS No. 031-38W30WC

First issue: 2012/11/30

Revised: 2013/06/25

Safety Data Sheets

Skin Protection : Wear appropriate chemical resistant clothing.

9. Physical and Chemical Properties

Appearance	- Physical State	: liquid
	- Color	: White
Odor		: faint
pH		: 9.3 ± 0.5
Boiling Point / Boiling Range		: Not available
Melting Point / Melting Range		: Not available
Flash Point		: None
Density		: 1.08 ± 0.01
Water Solubility		: soluble
Viscosity		: Not available
Vapor Density		: Not available
VOC		: Not available

10. Stability and Reactivity

Conditions to Avoid	: Avoid contact with incompatible materials.
Stability	: Stable at standard temperatures and pressure.
Materials to Avoid	: halogens, oxidizing materials
Hazardous Reactions / Decomposition Products	: No reactivity hazard is expected. Hazardous polymerization will not occur. Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition.

11. Toxicological Information

Acute Toxicity	:	Oral LD50(rat)	Dermal LD50(rabbit)
	Water	>90 mL/kg	
	Alcohol derivative	16 g/kg	
	Diethylene glycol derivative	4920 μ L/kg	3560 μ L/kg
	Titanium dioxide	>12000 mg/kg	>10000 mg/kg
Irritation	: eye irritation, skin irritation, respiratory tract irritation		
Carcinogenicity	: Titanium dioxide		
	ACGIH : A4 - Not Classifiable as a Human Carcinogen		



Product Name: Latex ink LX100/LX101 White

MSDS No. 031-38W30WC

First issue: 2012/11/30

Revised: 2013/06/25

Safety Data Sheets

NIOSH : potential occupational carcinogen

IARC : Monograph 93 [2010]; (Group 2B (possibly carcinogenic to humans))

Medical Conditions : respiratory disorders

Aggravated by Exposure

12. Ecological Information

: Handling is noted because it might influence the environment when leaking and abandoning it.

Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch.

Ecotoxicity : Components of this product are hazardous to aquatic life

13. Disposal Considerations

Disposal Methods : Dispose in accordance with all applicable regulations.

Do not dump this product into sewers, on the ground or into any body of water.

Component Waste Numbers : The U.S. EPA has not published waste numbers for this product's components.

14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

US DOT Information : Not regulated

TDG Information : Not regulated

UN Number : Not regulated

15. Regulatory Information

U.S. Federal Regulations

: None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR



Product Name: Latex ink LX100/LX101 White

MSDS No. 031-38W30WC

First issue: 2012/11/30

Revised: 2013/06/25

Safety Data Sheets

372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA 311/312 : Acute Health: Yes Chronic Health: Yes Fire: No Pressure: No
Reactive: No

HMIS Ratings : Health: 1* Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate

3 = Serious 4 = Severe * = Chronic hazard

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Titanium dioxide	13463-67-7	No	Yes	Yes	Yes	Yes

16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.