

Material Safety Data Sheet

MSDS ID NO.: 0324MAR019 **Revision date:** 12/07/2010

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product code: MR0261

Product name: Marathon American Spirit Synthetic SAE 5W-30 Motor Oil

Synonym: American Spirit Synthetic SAE 5W-30 Motor Oil, Motor Oil, SAE 5W30 American

Spirit Synthetic; 5W30 Motor Oil, Marathon American Spirit Synthetic

Chemical Family: Motor/Lube Oil

Formula: Mixture

Manufacturer:

Marathon Petroleum Company LP 539 South Main Street

Findlay OH 45840

Other information: 419-421-3070 Emergency telephone number: 877-627-5463

2. COMPOSITION/INFORMATION ON INGREDIENTS

Motor oil is a complex mixture of highly refined lubricating oil base stocks and additives. The base oil for this product can be a mixture of any of the following highly refined petroleum streams: 64741-88-4, 64742-54-7, and 64742-65-0.

Product information:

Name	CAS Number	Weight %	ACGIH Exposure Limits:	OSHA - Vacated PELs - Time Weighted Ave	Other:
Marathon American Spirit Synthetic SAE 5W-30 Motor Oil	Mixture	100			

Component Information:

MSDS ID NO.: 0324MAR019

Name	CAS Number	Weight %	ACGIH Exposure Limits:	OSHA - Vacated PELs - Time Weighted Ave	Other:
Petroleum Distillates, Hydrotreated Heavy Paraffinic	64742-54-7	>80			Mineral Oil Mist (MOM) =5 mg/m³ TWA = 10 mg/m³ STEL
Additives	Not specified	10-18			
Zinc Alkyl Dithiophosphate	68649-42-3	>1			

Notes: The manufacturer has voluntarily elected to reflect exposure limits contained in

OSHA's 1989 air contaminants standard in its MSDS's, even though certain of those

exposure limits were vacated in 1992.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

THIS PRODUCT IS A NON-VOLATILE AND NON-COMBUSTIBLE, AMBER COLORED LIQUID, BUT WILL IGNITE AND BURN AT ELEVATED TEMPERATURES.

Inhalation:

No acute effects expected from routine operations. Overheating of product may produce vapors which can cause respiratory irritation, dizziness and nausea.

Ingestion:

Product has a low order of acute toxicity. This is based on data from components or similar products.

Skin contact:

Prolonged or repeated liquid contact can cause dermatitis, folliculitis or oil acne.

Eye contact:

Liquid or vapor contact may result in slight eye irritation.

Carcinogenic Evaluation:

Product information:

Name	IARC Carcinogens:	NTP Carcinogens:	ACGIH - Carcinogens:	OSHA - Select Carcinogens:
Marathon American Spirit Synthetic SAE 5W-30 Motor Oil	NE			
Mixture				

Notes:

The International Agency for Research on Cancer (IARC) has determined that there is no evidence that severely solvent-refined oils are carcinogenic to experimental animals.

Component Information:

Name	IARC	NTP	ACGIH -	OSHA - Select
	Carcinogens:	Carcinogens:	Carcinogens:	Carcinogens:
Petroleum Distillates, Hydrotreated Heavy Paraffinic 64742-54-7	Supplement 7 [1987], Monograph 33 [1984]			Present

4. FIRST AID MEASURES

Eye Contact:

Flush eyes with large amounts of tepid water for at least 15 minutes. If symptoms or irritation occur, call a physician.

irritation occur, call a physician

Skin Contact:

Wash with soap and large amounts of water. Remove contaminated clothing. If

symptoms or irritation occur, call a physician.

If product is accidentally injected into or under the skin, regardless of wound size or initial absence of symptoms, the individual should be evaluated immediately by a

physician as a surgical emergency.

Ingestion:

Not expected to be acutely toxic. If large amounts are swallowed, immediately call a

physician.

Inhalation:

MSDS ID NO.: 0324MAR019 Product name: Marathon American Spirit Synthetic SAE 5W-30 Motor Oil

4. FIRST AID MEASURES

If affected, move person to fresh air. If breathing is difficult, administer oxygen. If not breathing or if no heartbeat, give artificial respiration or cardiopulmonary resuscitation (CPR). Immediately call a physician. If symptoms or irritation occur with any exposure, call a physician.

NOTES TO PHYSICIAN:

No data available.

Medical Conditions Aggravated By Exposure:

Skin contact could aggravate an existing skin disorder or dermatitis condition.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media:

For small fires, Class B fire extinguishing media such as CO2, dry chemical, foam (AFFF/ATC) or water spray can be used. For large fires, water spray, fog or foam (AFFF/ATC) can be used. Fire fighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.

•

Specific hazards:

This material is not combustible per the OSHA Hazard Communication Standard, but will ignite and burn at elevated temperatures.

Special protective equipment for firefighters:

Avoid using straight water streams. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible. Avoid excessive water spray application. Use water spray to cool exposed surfaces from as far a distance as possible. Keep run-off water out of sewers and water sources.

Flash point:

Autoignition temperature:

Flammable limits in air - lower (%): Flammable limits in air - upper (%):

>390 F, >198 C No data available. No data available. No data available.

NFPA rating: Health: 1

Flammability: 1 Instability: 0 Other: -

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Keep public away. Isolate and evacuate area. Shut off source if safe to do so. Advise authorities and National Response Center (800-424-8802) if the product has entered a water course or sewer. Advise local and state emergency services agencies, if appropriate. Contain liquid with sand or soil. Recover and return free product to proper containers. Use suitable absorbent materials such as vermiculite, sand, or clay to clean up residual liquids.

7. HANDLING AND STORAGE

Handling:

MSDS ID NO.: 0324MAR019 Product name: Marathon American Spirit Synthetic SAE 5W-30 Motor Oil

7. HANDLING AND STORAGE

Comply with all applicable EPA, OSHA, NFPA and consistent state and local requirements. Use appropriate grounding and bonding practices. Store in properly closed containers that are appropriately labeled and in a cool well-ventilated area. Do not cut, drill, grind or weld on empty containers since they may contain explosive residues. Do not pressurize or expose to heat, open flames, strong oxidizers or other sources of ignition.

Avoid repeated and prolonged skin contact. Exercise good personal hygiene including removal of soiled clothing and prompt washing with soap and water.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT

Engineering measures: Local or general exhaust required when using at elevated temperatures that

generate vapors or mists.

Respiratory protection: Not required under normal conditions and adequate ventilation. Approved organic

vapor chemical cartridge or supplied air respirators should be worn when significant vapors are generated. Observe respirator assigned protection factors (APFs) criteria cited in federal OSHA 1910.134. Self-contained breathing apparatus should

be used for fire fighting.

Skin and body protection: Use chemical resistant gloves such as neoprene, nitrile, or PVA to prevent prolonged

or repeated skin contact.

Eye protection: No special eye protection is normally required.

Hygiene measures: No data available.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance: Amber Liquid

Physical state (Solid/Liquid/Gas):

Substance type (Pure/Mixture):

Color:

Odor:

Molecular weight:

Liquid

Mixture

Amber

Hydrocarbon

Not determined.

pH: Neutral

Boiling point/range (5-95%):

Melting point/range:

Not determined.

Not applicable.

Specific gravity:

Not applicable.

0.86 @ 60 F

Density: 7.15 lbs/gal @ 60 F
Bulk density: No data available.
Vapor density: No data available.
Vapor pressure: <1 mm Hg @ 100 F
Evaporation rate: No data available.

Solubility: <19

Solubility in other solvents: No data available.

Partition coefficient (n-octanol/water): >4.9

MSDS ID NO.: 0324MAR019

VOC content(%):No data available.Viscosity:48.2 cSt @ 40 C8.5 cSt @ 100 C

10. STABILITY AND REACTIVITY

Product name: Marathon American Spirit Synthetic SAE 5W-30 Motor Oil

10. STABILITY AND REACTIVITY

Stability: The material is stable at 70 F, 760 mm pressure.

Polymerization: Will not occur.

Hazardous decomposition products: Carbon monoxide, carbon dioxide, hydrogen sulfide, oxides

of sulfur, oxides of nitrogen, oxides of zinc, aldehydes and hydrocarbons., Thermal decomposition may produce hydrogen sulfide and other sulfur-containing gases at

temperatures greater than 150 F.

Materials to avoid: Strong oxidizers such as nitrates, chlorates, peroxides.

Conditions to avoid: Heat and open flames.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:

Product information:

Name	CAS Number	Inhalation:	Dermal:	Oral:
Marathon American Spirit Synthetic SAE 5W-30 Motor Oil	Mixture	No data available	No data available	No data available

Toxicology Information:

Based on data from components this product is considered to have a low order of acute oral and dermal toxicity. Chronic skin painting studies with severely solvent refined neutral oils did not produce evidence of skin cancer in mice.

This product contains approximately 0-1.5% of a zinc alkyl dithiophosphate (ZDDP) additive. ZDDP has been found to have weak mutagenic activity in cultured cells. Repeated dermal exposures of ZDDP produced severe skin irritation, significant weight loss and testicular atrophy in male rabbits but not male rats at high concentrations. Subsequent research showed that the testicular effect was due to the severe stress and weight loss as seen with other caustic materials and not a direct effect of ZDDP. The concentration of ZDDP in this product is significantly lower than exposure levels that produced these effects in rabbits.

Used motor oil applied to the skin of rabbits at doses of 8 ml/kg/day, 5 days/wk, for two weeks, produced significant weight loss and skin irritation but no mortality. Used motor oil was found to produce skin tumors in mice in lifetime skin painting studies. Solvent extracts of used motor oils were found to be positive in the Ames mutagenicity test.

12. ECOTOXICOLOGICAL INFORMATION

Mobility:

No data available.

Ecotoxicity:

No data available.

Bioaccummulation:

No data available.

MSDS ID NO.: 0324MAR019 Product name: Marathon American Spirit Synthetic SAE 5W-30 Motor Oil

12. ECOTOXICOLOGICAL INFORMATION

Persistance/Biodegradation:

Water accomated fractions (WAF) of highly refined base oils did not produce acute toxicity in fish (100-1000 mg/l), fresh water algae (500 mg/l) or daphnia (10,000 mg/l) in 48-96 hour LC50 studies.

Used motor and/or lube oils can be toxic to birds and fish.

13. DISPOSAL CONSIDERATIONS

Cleanup Considerations:

This material as supplied and by itself, when discarded or disposed of, is not an EPA RCRA hazardous waste according to federal regulations. This material could become a hazardous waste if mixed or contaminated with a hazardous waste or other substance(s). It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations.

Don't pollute. Conserve resources. Send used product to recycling center. Dispose of cleanup materials in accordance with applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

49 CFR 172.101:

DOT:

Transport Information: This material when transported via US commerce is NOT REGULATED by DOT

regulations.

Packing group:

DOT reportable quantity (lbs):

Not applicable.

Not applicable.

15. REGULATORY INFORMATION

US Federal Regulatory Information:

US TSCA Chemical Inventory Section 8(b): This product and/or its components are listed on the TSCA

Chemical Inventory.

OSHA Hazard Communication Standard: This product has been evaluated and determined not to be

hazardous as defined in OSHA's Hazard Communication

Standard.

EPA Superfund Amendment & Reauthorization Act (SARA):

SARA Section 302: This product contains the following component(s) that have been listed on EPA's

Extremely Hazardous Substance (EHS) List:

MSDS ID NO.: 0324MAR019 Product name: Marathon American Spirit Page 6 of 9

Synthetic SAE 5W-30 Motor Oil

Name	CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs
Petroleum Distillates, Hydrotreated	NA
Heavy Paraffinic	
Additives	NA
Zinc Alkyl Dithiophosphate	NA

SARA Section 304:

This product contains the following component(s) identified either as an EHS or a CERCLA Hazardous substance which in case of a spill or release may be subject to SARA reporting requirements:

Name	CERCLA/SARA - Hazardous Substances and their Reportable Quantities
Petroleum Distillates, Hydrotreated	NA
Heavy Paraffinic	
Additives	NA
Zinc Alkyl Dithiophosphate	NA

SARA Section 311/312

The following EPA hazard categories apply to this product:

None

SARA Section 313:

This product contains the following component(s) that may be subject to reporting on the Toxic Release Inventory (TRI) From R:

Name	CERCLA/SARA 313 Emission reporting:
Petroleum Distillates, Hydrotreated Heavy Paraffinic	None
Additives	None
Zinc Alkyl Dithiophosphate	= 1.0 % de minimis concentration

State and Community Right-To-Know Regulations:

The following component(s) of this material are identified on the regulatory lists below:

Petroleum Distillates, Hydrotreated Heavy Paraffinic

Louisiana Right-To-Know: Not Listed California Proposition 65: Not Listed New Jersey Right-To-Know: Not Listed. Pennsylvania Right-To-Know: Not Listed. Massachusetts Right-To Know: Not Listed. Florida substance List: Not Listed. Rhode Island Right-To-Know: Not Listed Michigan critical materials register list: Not Listed. Massachusetts Extraordinarily Hazardous Not Listed Substances: California - Regulated Carcinogens: Not Listed Pennsylvania RTK - Special Hazardous Not Listed Substances: New Jersey - Special Hazardous Substances: carcinogen New Jersey - Environmental Hazardous Not Listed Substances List: Not Listed Illinois - Toxic Air Contaminants New York - Reporting of Releases Part 597 -Not Listed List of Hazardous Substances:

Additives

MSDS ID NO.: 0324MAR019

Louisiana Right-To-Know:

California Proposition 65:

New Jersey Right-To-Know:

Pennsylvania Right-To-Know:

Not Listed.

Not Listed.

Not Listed.

Petroleum Distillates, Hydrotreated Heavy Paraffinic

Massachusetts Right-To Know:

Florida substance List:

Rhode Island Right-To-Know:

Michigan critical materials register list:

Massachusetts Extraordinarily Hazardous

Not Listed.

Not Listed.

Not Listed.

Substances:

California - Regulated Carcinogens: Not Listed Pennsylvania RTK - Special Hazardous Not Listed

Substances:

New Jersey - Special Hazardous Substances: Not Listed New Jersey - Environmental Hazardous Not Listed

Substances List:

Illinois - Toxic Air Contaminants Not Listed
New York - Reporting of Releases Part 597 - Not Listed

List of Hazardous Substances:

Zinc Alkyl Dithiophosphate

Louisiana Right-To-Know:

California Proposition 65:

New Jersey Right-To-Know:

Not Listed

Not 2 Sin 3012

Pennsylvania Right-To-Know: Environmental hazard

Massachusetts Right-To Know:

Florida substance List:

Rhode Island Right-To-Know:

Not Listed.

Not Listed.

Michigan critical materials register list: = 100 lb Annual usage threshold

Massachusetts Extraordinarily Hazardous Not Listed

Substances:

California - Regulated Carcinogens: Not Listed Pennsylvania RTK - Special Hazardous Not Listed

Substances:

MSDS ID NO.: 0324MAR019

New Jersey - Special Hazardous Substances: Not Listed

New Jersey - Environmental Hazardous SN 3012 TPQ 500 lb (Category Code N982. Includes any unique chemical substance that contains the named metal

as part of that chemical structure)

Illinois - Toxic Air Contaminants Not Listed
New York - Reporting of Releases Part 597 - Not Listed

List of Hazardous Substances:

Canadian Regulatory Information:

Canada DSL/NDSL Inventory: This product and/or its components are listed either on the Domestic Substances List

(DSL) or are exempt.

NOTE: Not Applicable.

16. OTHER INFORMATION

Additional Information: No data available.

Prepared by: Mark S. Swanson, Manager, Toxicology and Product Safety

The information and recommendations contained herein are based upon tests believed to be reliable. However, Marathon Petroleum Company LP (MPC) does not guarantee their accuracy or completeness nor shall any of this information constitute a warranty, whether expressed or implied, as to the safety of the goods, the merchantability of the goods, or the fitness of the goods for a particular purpose. Adjustment to conform to actual conditions of usage maybe required. MPC assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

End of Safety Data Sheet

Product name: Marathon American Spirit Synthetic SAE 5W-30 Motor Oil

MSDS ID NO.: 0324MAR019