

0338E and 0339E

MATERIAL SAFETY DATA SHEET PAGE 1

ABBREVIATIONS: NA=NOT APPLICABLE
 ND=NOT DETERMINED
 NE=NOT ESTABLISHED

HEALTH= 1
 FLAMMABILITY= 0
 REACTIVITY= 0
 PERSONAL PROTECTION= +
 + SEE SECTION VII

WHMIS CLASSIFICATION: D2

SECTION I PRODUCT IDENTIFICATION AND USE

MATERIAL NAME/IDENTIFIER: Leak Stopper Clear Patch

MANUFACTURER/SUPPLIER: Gardner-Gibson Corporation
 4161 E 7th Ave.
 Tampa Fla. 33605

PHONE: 1-905-677-5522 (Canada)
 EMERGENCY: 1-613-996-6666 CANUTEC (24 hr. emergency information only)

CHEMICAL FAMILY: Mixture
 CHEMICAL FORMULA/MOLECULAR WT: NA
 TRADE NAME AND SYNONYMS:
 MATERIAL USE: Acrylic Latex Sealant

SECTION II HAZARDOUS INGREDIENTS

CHEMICAL NAME	OSHA-PEL	ACGIH-TLV	LD50/LC50	%WT/WT
2,2,4-Trimethyl-1,3-pentanediol Monoisobutyrate	NE	NE	NE	<2.0%
CAS# 25265-774-4				
2-Amino-2-methyl-1-propanol	NE	NE	Oral LD50(rat) 2900mg/kg	<2.0%
CAS#124-68-5			Dermal LD50 (rabbit)	
>2000mg/kg				

SECTION III PHYSICAL DATA

APPEARANCE, PHYSICAL STATE AND ODOR: Milky white paste, sweet odor.
 ODOR THRESHOLD (PPM): ND
 SPECIFIC GRAVITY/DENSITY (G/ML): 1.05
 VAPOR PRESSURE (MM): 25mm @ 20°C
 VAPOR DENSITY (AIR=1): >1
 EVAPORATION RATE (BUAC=1): <1
 BOILING POINT: 100°C
 MELTING/FREEZING POINT: 0°C
 PH: 8-10
 COEFFICIENT OF WATER/OIL DISTRIBUTION: ND

SOLUBILITY IN WATER: Miscible
% VOLATILE BY VOLUME: 30-50

SECTION IV FIRE OR EXPLOSION DATA

FLASH POINT: Water based
AUTO IGNITION TEMPERATURE: NA
SENSITIVITY TO MECHANICAL IMPACT: NA
EXPLOSIVE POWER: NA
UPPER EXPLOSION LIMIT: NA
LOWER EXPLOSION LIMIT: NA
RATE OF BURNING: NA
SENSITIVITY TO STATIC DISCHARGE: NA
EXTINGUISHING MEDIA: NA

SPECIAL FIRE FIGHTING PROCEDURES:
NA

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Product will not burn as supplied. Dried film may burn if subject to source of ignition.

FLAMMABILITY: NO

UNDER WHAT CONDITIONS: NA

SECTION V REACTIVITY DATA

STABILITY - MATERIAL IS: Stable

CONDITIONS TO AVOID:

NA

HAZARDOUS DECOMPOSITION/COMBUSTION PRODUCTS:

Carbon dioxide, carbon monoxide

INCOMPATIBILITY (MATERIALS TO AVOID):

Strong oxidizers

HAZARDOUS POLYMERIZATION:

Will not occur

SECTION VI TOXICOLOGICAL PROPERTIES

PRIMARY ROUTES OF ENTRY:

- Skin -

EFFECTS OF OVEREXPOSURE, CHRONIC:

Prolonged/repeated skin contact may cause dermatitis.

EFFECTS OF OVEREXPOSURE, ACUTE:

Skin: Prolonged/repeated contact may irritate sensitive skin.

Eyes: May irritate.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Pre-existing skin disorders

CARCINOGENICITY: NO

LD50 OF PRODUCT: ND

IRRITANT: In some cases

SYNERGISTIC MATERIALS: NA

REPRODUCTIVE EFFECTS: NO

WHMIS CLASSIFICATION: D2

LC50 OF PRODUCT: ND

SENSITIZER: NO

TERATOGENIC: NO

MUTAGENIC: NO

SECTION VII PREVENTIVE MEASURES, SAFE HANDLING AND USE,
INFORMATION

REGULATORY

LEAK AND SPILL PROCEDURES:

Dike spill area. Recover free liquid. Add absorbent to spill area.

WASTE DISPOSAL METHOD:

Dispose of according to Federal, State and Local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Store in cool, dry area. Protect from freezing.

OTHER:

Keep out of the reach of children!

VENTILATION:

NA

RESPIRATORY PROTECTION:

NA

PROTECTIVE GLOVES: Not normally required.

EYE PROTECTION: NA

OTHER PROTECTIVE EQUIPMENT: NA

WORK/HYGIENIC PRACTICES:

Remove contaminated clothing, launder before reuse.

RCRA HAZARDOUS WASTE NO: None

DOT PROPER SHIPPING NAME: Caulking and Glaziers Compound

DOT HAZARD CLASS: Not regulated

VOLATILE ORGANIC COMPOUNDS (VOC): <250 G/L

TDG CLASSIFICATION (CAN): Not regulated

SECTION VIII FIRST AID MEASURES

EMERGENCY AND FIRST AID PROCEDURES:

Skin: Wash with soap and water. Eyes: Flush with copious amounts of water. Ingestion: Contact a physician.

SECTION IX PREPARATION INFORMATION

Prepared by: Technical Services Dept.

Revised Date: Jan. 2015

The information accumulated herein is believed to be accurate but is not warranted to be, whether originating with the Company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

0338, 0339