MSDS - Material Safety Data Sheet

Product Name: Soil Seal

MSDS No.: 04	7010
---------------------	------

Part Numbers Covered:

047010 047011 047012 047013 047020 047060 047062 047070								
I. Basic Information:								
Manufacturer: WILLIAM H. HARVEY COMPANY			NF	PA Fire				
Address: 4334 SOUTH 67TH STREET		3						
City, ST Zip: OMAHA, NE 68117-1019	Health Reactivity							
Emergency Contact: CHEMTREC								
Emergency Telephone Number: (800)424-9300								
Contact: Ray Rael / Jason Hertz				Special				
Information Telephone Number: (800)228-9681								
Last Update: 07/08/2002 Expiration Date: 3 Flammability								
Chemical State: Liquid Gas X Solid Reactivity								
Chemical Type: X Pure Mixture	_			Pers. Pro	tection			
II. Ingredients:								
Trade Secret								
_	EH	S IAF						
CAS No. Chemical Name	% Range	NTP	313 SUB Z	OSHA PEL	ACGIH TLV	Other Limits		
141786 ETHYL ACETATE	NI			NI	400 PPM	NI		
67630 ISOPROPYL ALCOHOL	NI			400 PPM	500 PPM	NI		
III. Hazardous Identification:								
Hazard Category:								
Acute Chronic	Fire		Pre	ssure		Reactive		
Hazardous Identification Information: NDA								
IV. First Aid Measures:								
Route(s) of Entry:								

Health Hazards (Acute and Chronic):

SKIN, INGESTION, AND INHALATION

DAMAGE TO NERVOUS SYSTEM, KIDNEYS, DROWSINESS AND HEADACHE, LETHARGY, NAUSEA, DIFFICULTY WALKING; EXCESS MAY CAUSE DAMAGE TO NERVOUS SYSTEM, BLOOD AND KIDNEYS; VAPOR CAN BE IRRITATING TO EYES, NOSE, AND THROAT; LIQUID MAY IRRITATE EYES.

MSDS - Material Safety Data Sheet

Product Name: Soil Seal

MSDS No.: 047010 Signs and Symptoms:

SEE ABOVE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure:

DROWSINESS AND HEADACHE; DAMAGE TO NERVOUS SYSTEM, KIDNEYS AND BLOOD; DIFFICULTY WALKING

Emergency and First Aid Procedures:

EMERGENCY FIRST AID CALL: 1-303-623-5716 COLLECT

EYES: FLUSH WITH LARGE AMOUNTS OF WATER AND CONSULT A PHYSICIAN

SKIN: WASH WITH SOAP AND WATER INHALATION: REMOVE TO FRESH AIR

INGESTION: DO NOT INDUCE VOMITING; CALL A PHYSICIAN

Other Health Warnings:

NI

V. Fire Fighting Measures:

Flash Point: 24 F DEG T Lower Explosive Limit: 2.0 Upper Explosive Limit:

F.P. Method:

Fire Extinguishing Media: CARBON DIOXIDE, WATER STREAM (FOG), OR DRY CHEMICAL

Special Fire Fighting Procedures:

WHEN EXPOSED TO HEAT AND FLAME, THIS IS A FIRE AND EXPLOSION HAZARD

Unusual Fire and Explosion:

WHEN BURNING, THIS MATERIAL PRODUCES TOXIC DEGRADATION PRODUCTS INCLUDING CO2, AND OXIDES OF NITROGEN; SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED IN FIGHTING FIRE.

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

CONFINE SPILLED MATERIAL, ALLOW TO SET UP THEN SCRAPE OR SWEEP UP RESIDUE AND PLACE IN TRASH CONTAINER. DO NOT INCINRATE!

VII. Handling and Storage:

Precautions to be Taken:

ELIMINATE IGNITION SOURCES; KEEP COOL, KEEP CONTAINER CLOSED AFTER USE.

Other Precautions:

KEEP OUT OF REACH OF CHILDREN AND PETS!

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

HAVE LOCAL EXHAUST AND MECHANICAL (GENERAL) EXHAUST

Personal Protective Equipment:

ADVISED TO USE PROTECTIVE GLOVES AND EYE GOGGLES. WEAR SYNTHETIC APRON OR STANDARD LONG SLEEVED WORK APPAREL, AND A VAPOR RESPIRATOR. USE NORMAL GOOD SAFETY AND HEALTH PROCEDURES.

MSDS - Material Safety Data Sheet

Product Name: Soil Seal

MSDS No.: 047010

IX. Physical and Chemical Properties:

Boiling Point: 171 F D Melting Point: NI

Evaporation Rate (Butyl Acetate = 1): NI Vapor Pressure (mm Hg.): 76@20 C

Specific Gravity (H20 = 1): 0.00000 Vapor Density (AIR = 1): NI

Solubility In Water: INSOLUBLE Appearance and Odor: GRAY PASTE WITH ALCOHOL ODOR

Other Information:

X. Stability and Reactivity:

Stability:

STABLE

Incompatibility (Materials to Avoid):

AVOID STRONG OXIDIZING AGENTS, STRONG ACIDS, STRONG BASES AND AMINES

Decomposition/By Products:

COMBUSTION PRODUCES CARBON DIOXIDE AND CARBON MONOXIDE

Hazardous Polymerization:

WILL NOT OCCUR

XI. Toxicological Information:

NDA

XII. Ecological Information:

NDA

XIII. Disposal Considerations:

DISPOSE OF WASTE MATERIAL ACCORDING TO APPLICABLE FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.

XIV. Transport Information:

TRANSPORATION INFORMATION:

DOT PROPER SHIPPING NAME: FLAMMABLE LIQUID

DOT LABEL: ORM-D HAZARD CLASS-3.2

DOT NUMBER: N/A

UN NUMBER: 1263 FOR BULK

IMCO CLASS: N/A

DOT HAZARD CLASSIFICATION: N/A

XV. Regulatory Information:

NDA

Page 4 of 4 Thursday, April 20, 2006

MSDS - Material Safety Data Sheet

Product Name: Soil Seal

MSDS No.: 047010

XVI. Other Information:

ABBREVIATIONS:

DISCLAIMER:

THE INFORMATION HEREIN HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE, UP-TO-DATE, AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, WILLIAM H. HARVEY COMPANY CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE WARRANTIES, NOR ASSUMES ANY LIABILITY FOR ITS USES.