

ASHLAND		Page: 1
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL
™ Trademark, Valvoline or its subsidiaries, regisred in various countries

Relevant identified uses of the substance or mixture and uses advised against

Details of the supplier of the safety data sheet Ashland P.O. Box 2219 Columbus, OH 43216 United States of America EHS Customer Requests@ashland.com	Emergency telephone number 1-800-ASHLAND (1-800-274-5263) Regulatory Information Number 1-800-325-3751 Product Information 614-790-3333
--	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Eye irritation : Category 2A

GHS Label element

Hazard pictograms :



Signal Word : Warning

Hazard Statements : Causes serious eye irritation.

Precautionary Statements : **Prevention:**
Wash skin thoroughly after handling.
Wear eye protection/ face protection.
Response:
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/ attention.

Other hazards

ASHLAND		Page: 2
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	Asp. Tox. 1; H304	1.3394
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts	113706-15-3	Skin Irrit. 2; H315 Eye Dam. 1; H318	1.0795

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If breathed in, move person into fresh air. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Remove contaminated clothing. If irritation develops, get medical attention. If on skin, rinse well with water. Wash contaminated clothing before re-use.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye.
If swallowed	: Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum

ASHLAND		Page: 3
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Causes serious eye irritation.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO2)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
Nitrogen oxides (NOx)
Sulphur oxides
hydrogen sulfide
mercaptans
zinc oxide
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, : Use personal protective equipment.

ASHLAND		Page: 4
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	PEL	500 ppm 2,000 mg/m3	OSHA_TRA NS
		REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS
				NIOSH/GUID E
				OSHA_TRA NS
		TWA	5 mg/m3	Z1A

ASHLAND		Page: 5
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

			Mist.	
				Z1A
		TWA	400 ppm 1,600 mg/m3	Z1A
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PA	64741-89-5			ACGIH
				ACGIHLIS_P
				ACGIHLIS_P
		REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS
		TWA	5 mg/m3 Inhalable fraction.	ACGIH

Hazardous components without workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
------------	---------	-------------------------------------	---	-------

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : Respiratory protection is not required under normal conditions of use.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear resistant gloves (consult your safety equipment supplier).
Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.

ASHLAND		Page: 6
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Melting point/range	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 390 °F / > 199 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 1.33 hPaCalculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 114 - 124 mm ² /s (40 °C)

ASHLAND		Page: 7
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Acids
Strong oxidizing agents
water

Hazardous decomposition products : carbon dioxide and carbon monoxide
hydrogen sulfide
Nitrogen oxides (NO_x)
Sulphur oxides
zinc oxide
mercaptans

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Acute oral toxicity : LD50 (Rat): 2,900 mg/kg

Remarks: Information given is based on data obtained from similar substances.

ASHLAND®		Page: 8
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
 Assessment: Not classified as acutely toxic by dermal absorption under GHS.
 Remarks: Information given is based on data obtained from similar substances.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result: Mildly irritating to skin

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Result: Irritating to skin.

Remarks: Information given is based on data obtained from similar substances.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result: Mildly irritating to eyes

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Result: Corrosive

Remarks: Information given is based on data obtained from similar substances.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Genotoxicity in vitro : Remarks: In vitro tests showed mutagenic effects which were not observed with in vivo test.

Genotoxicity in vivo : Test Type: chromosome aberration assay
 Test species: Mouse
 Cell type: peripheral blood cells

ASHLAND		Page: 9
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Effects on fertility : Species: Rat
Application Route: Oral
Dose: 100 mg/kg bw/day
Symptoms: No effects on reproduction parameters

Effects on foetal development : Species: Rat
Application Route: Oral
Developmental Toxicity: No observed adverse effect level F1:
100 mg/kg body weight

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

ASHLAND		Page: 10
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from similar substances.

Persistence and degradability

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Biodegradability : Result: Not readily biodegradable.

Remarks: Information given is based on data obtained from similar substances.

No data available

Bioaccumulative potential

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Bioaccumulation : Bioconcentration factor (BCF): 3

Remarks: Information given is based on data obtained from similar substances.

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

ASHLAND		Page: 11
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

ASHLAND		Page: 12
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Acute Health Hazard

SARA 313 Component(s)

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts	113706-15-3	1.07 %
---	-------------	--------

Pennsylvania Right To Know

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
---	------------

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
---	------------

DISTILLATES (PETROLEUM), SOLVENT- DEWAXED HEAVY PARAFFINIC	64742-65-0
---	------------

New Jersey Right To Know

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
---	------------

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
---	------------

DISTILLATES (PETROLEUM), SOLVENT- DEWAXED HEAVY PARAFFINIC	64742-65-0
---	------------

DINONYL DIPHENYLAMINE	36878-20-3
-----------------------	------------

BENZENEPROPANOIC ACID, 3,5-bis(1,1-DIMETHYLETHYL)-4-HYDROXY-, C7-9-BRANCHED ALKYL ESTERS	125643-61-0
--	-------------

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts	113706-15-3
---	-------------

DISTILLATES (PETROLEUM), SOLVENT- REFINED LIGHT PA	64741-89-5
---	------------

ASHLAND		Page: 13
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

California Prop 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 01/08/2016

NFPA:	HMIS III:						
<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td>HEALTH</td><td>2</td></tr> <tr> <td>FLAMMABILITY</td><td>1</td></tr> <tr> <td>PHYSICAL HAZARD</td><td>0</td></tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.

ASHLAND		Page: 14
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

H318 Causes serious eye damage.

Sources of key data used to compile the Safety Data Sheet
 Ashland internal data including own and sponsored test reports
 The UNECE administers regional agreements implementing harmonised classification for
 labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether
 originating with the company or not. Recipients are advised to confirm in advance of need that the
 information is current, applicable, and suitable to their circumstances. This SDS has been
 prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data
 sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

ASHLAND®		Page: 15
SAFETY DATA SHEET		Revision Date: 01/08/2016
		Print Date: 5/1/2017
		SDS Number: 000000263269
Valvoline™ High Mileage HEAVY DUTY DIESEL MAX LIFE™ SAE 15W-40 Motor Oil ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 869035		Version: 1.1

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System