

# **SAFETY DATA SHEET**

# 1666

# 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name 1.0% TO 1.7% PHOSPHINE, BALANCE NITROGEN

Synonym(s) 1666 - SDS NUMBER • PRODUCT CODES: 285, 288 • SPECIAL GAS MIXTURE

1.2 Uses and uses advised against

Use(s) CALIBRATION • INDUSTRIAL APPLICATIONS

1.3 Details of the supplier of the product

Supplier name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA

Telephone 131 262, (02) 8874 4400

Fax 132 427 (24 hours)

Website http://www.boc.com.au

1.4 Emergency telephone number(s)

**Emergency** 1800 653 572 (24/7) (Australia only)

# 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

**GHS classification(s)** Skin Corrosion/Irritation: Category 2

Acute Toxicity: Inhalation: Category 3 Aquatic Toxicity (Acute): Category 1

Serious Eye Damage / Eye Irritation: Category 2A Gases Under Pressure: Compressed gas

### 2.2 Label elements

Signal word DANGER

Pictogram(s)









### Hazard statement(s)

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation. H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H400 Very toxic to aquatic life.

# Prevention statement(s)

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.



Page 1 of 7

SDS Date: 09 Mar 2015

#### Response statement(s)

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P311 Call a POISON CENTER or doctor/physician.

P321 Specific treatment is advised - see first aid instructions.
P332 + P337 + P313 If skin or eye irritation occurs: Get medical advice/ attention.
Take off contaminated clothing and wash before re-use.

P391 Collect spillage.

Storage statement(s)

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal statement(s)

P501 Dispose of contents/container in accordance with relevant regulations.

#### 2.3 Other hazards

Asphyxiant. Effects are proportional to oxygen displacement.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content (v/v)
PHOSPHINE	7803-51-2	232-260-8	1 to <1.7%
NITROGEN	7727-37-9	231-783-9	Remainder

# 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to

stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained

Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion Ingestion is not considered a potential route of exposure.

First aid facilities Eye wash facilities and safety shower should be available.

# 4.2 Most important symptoms and effects, both acute and delayed

Toxic - irritating. Primary hazard is phosphine which acts on the central nervous system, lungs, heart and may result in injury to kidneys and other organs. Sub-acute exposure may result in anaemia, bronchitis, gastro-intestinal disorder, speech and motor disturbances (double vision, tremor and gait difficulties. Symptoms usually appear rapidly but may be delayed 1 to 3 days. Symptoms at higher exposure include faintness, weakness, apathy, nausea, vomiting, diarrhoea, tremors, intense thirst, abdominal pain, oppressed feeling in chest, dyspnoea, cough with sputum, coughing of frothy liquid, convulsions, paralysis and coma.

### 4.3 Immediate medical attention and special treatment needed

There is no specific antidote to phosphine poisoning and treatment is therefore symptomatic and supportive. Usual methods for pulmonary oedema, renal failure, cerebral oedema and circulatory collapse. Treatment for cold burns or asphyxiation.

# 5. FIRE FIGHTING MEASURES

# 5.1 Extinguishing media

Use water fog to cool containers from protected area.

#### 5.2 Special hazards arising from the substance or mixture

Non flammable.



SDS Date: 09 Mar 2015

Page 2 of 7

#### 5.3 Advice for firefighters

Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Remove cool cylinders from the path of the fire. Evacuate the area if unable to keep cylinders cool. Do not approach cylinders or containers suspected of being hot.

#### 5.4 Hazchem code

2RE

- 2 Fine Water Spray.
- R Wear liquid-tight chemical protective clothing and breathing apparatus. Dilute spill and run-off.
- E Evacuation of people in and around the immediate vicinity of the incident should be considered.

### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use Personal Protective Equipment (PPE) as detailed in Section 8 of the SDS.

#### 6.2 Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

#### 6.3 Methods of cleaning up

Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.

# 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

# 7.2 Conditions for safe storage, including any incompatibilities

Do not store near incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits. Replace valve seal and protective cap when not in use.

# 7.3 Specific end use(s)

No information provided.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

# 8.1 Control parameters

# **Exposure standards**

Ingredient	Reference	TWA		STEL	
	Kelefelice	ppm	mg/m³	ppm	mg/m³
Nitrogen	SWA (AUS)	Asphyxiant			
Phosphine	SWA (AUS)	0.3	0.42	1	1.4

### **Biological limits**

No biological limit values have been entered for this product.

#### 8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction

ventilation is recommended.



SDS Date: 09 Mar 2015

Page 3 of 7

**PPE** 

**Eye / Face** Wear safety glasses.

Hands Wear cotton or leather gloves.Body Wear safety boots and coveralls.

**Respiratory** Wear Self Contained Breathing Apparatus (SCBA) or an Air-line respirator.













# 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

**COLOURLESS GAS Appearance** Odour **ROTTEN FISH ODOUR Flammability** NON FLAMMABLE **NOT RELEVANT** Flash point **Boiling point NOT AVAILABLE Melting point NOT AVAILABLE NOT APPLICABLE Evaporation rate NOT APPLICABLE** Hq Vapour density 1.18 (Posphine) **NOT APPLICABLE** Specific gravity Solubility (water) 0.0149 L/L (Nitrogen) Vapour pressure **NOT AVAILABLE** 

**Upper explosion limit** 1.2 % (Phosphine in nitrogen)

Lower explosion limit **NOT AVAILABLE** Partition coefficient **NOT AVAILABLE Autoignition temperature NOT AVAILABLE Decomposition temperature NOT AVAILABLE NOT AVAILABLE** Viscosity **Explosive properties NOT AVAILABLE Oxidising properties NOT AVAILABLE Odour threshold NOT AVAILABLE** 

9.2 Other information

% Volatiles 100 %

# 10. STABILITY AND REACTIVITY

# 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

# 10.2 Chemical stability

Stable under recommended conditions of storage.

# 10.3 Possibility of hazardous reactions

Polymerization will not occur.

# 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

# 10.5 Incompatible materials

Moist carbon dioxide is corrosive, hence acid resistant materials are required (e.g. stainless steel). Certain properties of some plastics and rubbers may be affected by carbon dioxide (i.e. embrittlement, leaching of plasticisers, etc).

# 10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.



SDS Date: 09 Mar 2015

# 11. TOXICOLOGICAL INFORMATION

# 11.1 Information on toxicological effects

Acute toxicity Toxic if inhaled. Exposure to phosphine may result in anaemia, bronchitis, gastro-intestinal disorder, speech

and motor disturbances (double vision, tremor and gait difficulties. Symptoms at higher exposure include faintness, weakness, apathy, nausea, vomiting, diarrhoea, tremors, intense thirst, abdominal pain, oppressed feeling in chest, dyspnoea, cough with sputum, coughing of frothy liquid, convulsions, paralysis and coma.

**PHOSPHINE** 

LC50 (Inhalation): 11 ppm / 4 hours (rat)

Skin Irritating to the skin. Contact may result in irritation, redness, rash and dermatitis.

Eye Irritating to the eyes. Contact may result in irritation, lacrimation, pain and redness.

**Sensitization** Not classified as causing skin or respiratory sensitisation.

MutagenicityNot classified as a mutagen.CarcinogenicityNot classified as a carcinogen.ReproductiveNot classified as a reproductive toxin.

STOT – single exposure

Asphyxiant. Effects are proportional to oxygen displacement. Over exposure may result in dizziness, drowsiness, weakness, fatigue, breathing difficulties and unconsciousness. Phosphine acts on the central

nervous system, lungs, heart and may result in injury to kidneys and other organs.

STOT – repeated

exposure

Not classified as causing organ effects from repeated exposure. However, it has been claimed that chronic

exposure to phosphine may effect the bones in a manner similar to white phosphorous.

**Aspiration** Not classified as causing aspiration.

### 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

Very toxic to aquatic organisms.

#### 12.2 Persistence and degradability

No information provided.

# 12.3 Bioaccumulative potential

No information provided.

### 12.4 Mobility in soil

No information provided.

### 12.5 Other adverse effects

When discharged to the atmosphere, carbon dioxide may contribute to the greenhouse effect.

# 13. DISPOSAL CONSIDERATIONS

# 13.1 Waste treatment methods

Waste disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

**Legislation** Dispose of in accordance with relevant local legislation.

# 14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE





SDS Date: 09 Mar 2015

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1955	1955	1955
14.2 Proper Shipping Name	COMPRESSED GAS, TOXIC, N.O.S. (Contains phosphine)	COMPRESSED GAS, TOXIC, N.O.S. (Contains phosphine)	COMPRESSED GAS, TOXIC, N.O.S. (Contains phosphine)
14.3 Transport hazard class	2.3	2.3	2.3
14.4 Packing Group	None Allocated	None Allocated	None Allocated

14.5 Environmental hazards No information provided

14.6 Special precautions for user

Hazchem code 2RE EMS F-C, S-U

Other information Ensure cylinder is separated from driver and foodstuffs. Refer to Commonwealth, State and Territory

Dangerous Goods Legislation which contain requirements which affect gas storage and transport.

# 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule Classified as a Schedule 7 (S7) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and

Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous

Substances [NOHSC: 1008(2004)].

Hazard codes N Dangerous for the environment

T Toxic Xi Irritant

**Risk phrases** R23 Toxic by inhalation.

R36/38 Irritating to eyes and skin. R50 Very toxic to aquatic organisms.

Safety phrases S23 Do not breathe gas.

S28 After contact with skin, wash immediately with plenty of water.

S36/37 Wear suitable protective clothing and gloves.

S45 In case of accident or if you feel unwell seek medical advice immediately (show the label

where possible).

Avoid release to the environment. Refer to special instructions/safety data sheets.

In case of accident by inhalation, remove casualty to fresh air and keep at rest.

Inventory listing(s) AUSTRALIA: AICS (Australian Inventory of Chemical Substances)

All components are listed on AICS, or are exempt.

# 16. OTHER INFORMATION

Additional information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Liquid withdrawal through specialised equipment and controlled gas distribution to produce or building.

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.



SDS Date: 09 Mar 2015

Page 6 of 7

# HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

#### **Abbreviations**

**ACGIH** American Conference of Governmental Industrial Hygienists

CAS# Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous **EMS** 

Goods)

**GHS** Globally Harmonized System

**GTEPG** Group Text Emergency Procedure Guide **IARC** International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m<sup>3</sup> Milligrams per Cubic Metre OEL Occupational Exposure Limit

relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly pΗ

alkaline).

Parts Per Million ppm

Short-Term Exposure Limit STEL

STOT-RE Specific target organ toxicity (repeated exposure) STOT-SE Specific target organ toxicity (single exposure)

**SUSMP** Standard for the Uniform Scheduling of Medicines and Poisons

**SWA** Safe Work Australia Threshold Limit Value TLV Time Weighted Average **TWA** 

### **Revision history**

Revision	Description
2.4	Standard SDS Review
2.3	Standard SDS Review
2.2	Standard SDS Review
2.1	Standard SDS Review
2.0	Standard SDS Review.
1.0	Initial SDS creation

# Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

# Prepared by

Risk Management Technologies 5 Ventnor Ave. West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794

Email: info@rmt.com.au Web: www.rmt.com.au.

Revision: 2.4

**SDS date:** 09 March 2015

[ End of SDS ]



Page 7 of 7 09 Mar 2015 SDS Date: