

**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2016-05-31

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : Toluene Reference, Fuel Grade
Material : 1016965, 1016964, 1016968, 1016967, 1016963, 1016966

EC-No.Registration number

Chemical name	CAS-No. EC-No. Index No.	Legal Entity Registration number
Toluene	108-88-3 203-625-9 601-021-00-3	Chevron Phillips Chemicals International NV Pre-Registered

Company : Chevron Phillips Chemical Company LP
Specialty Chemicals
10001 Six Pines Drive
The Woodlands, TX 77380

Local : Chevron Phillips Chemicals International N.V.
Airport Plaza (Stockholm Building)
Leonardo Da Vincilaan 19
1831 Diegem
Belgium

SDS Requests: (800) 852-5530
Technical Information: (832) 813-4862
Responsible Party: Product Safety Group
Email:sds@cpchem.com

Emergency telephone:**Health:**

866.442.9628 (North America)
1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)
Asia: +800 CHEMCALL (+800 2436 2255) China:+86-21-22157316
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

Responsible Department : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com

SECTION 2: Hazards identification
Classification of the substance or mixture
REGULATION (EC) No 1272/2008

Flammable liquids, Category 2	H225: Highly flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Reproductive toxicity, Category 2	H361: Suspected of damaging fertility or the unborn child.
Specific target organ systemic toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness.
Specific target organ systemic toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.

Label elements**Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal Word : Danger

Hazard Statements	H225	Highly flammable liquid and vapor.
	H304	May be fatal if swallowed and enters airways.
	H315	Causes skin irritation.
	H336	May cause drowsiness or dizziness.
	H361	Suspected of damaging fertility or the unborn child.
	H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements	Prevention:	
	P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
	P260	Do not breathe
		dust/fume/gas/mist/vapor/spray.
	P281	Use personal protective equipment as required.
	Response:	
	P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
	P331	Do NOT induce vomiting.
	P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

Hazardous ingredients which must be listed on the label:

- 108-88-3 Toluene

SECTION 3: Composition/information on ingredients

Synonyms : Toluol
Toluene (Reference Fuel)

Molecular formula : C₇H₈

Mixtures**Hazardous ingredients**

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]
Toluene	108-88-3 203-625-9 601-021-00-3	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	99,95
Benzene	71-43-2 200-753-7 601-020-00-8	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Muta. 1B; H340 Carc. 1A; H350 Aquatic Chronic 3; H412 STOT RE 1; H372 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	0,05

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Do NOT induce vomiting. Never

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5: Firefighting measures

Flash point	: 4,4 °C (39,9 °F) Method: closed cup
Autoignition temperature	: 529 °C (984 °F)
Suitable extinguishing media	: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.
Specific hazards during fire fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Special protective equipment for fire-fighters	: Wear self-contained breathing apparatus for firefighting if necessary.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Fire and explosion protection	: Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
Hazardous decomposition products	: Carbon oxides.

SECTION 6: Accidental release measures

Personal precautions	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

SECTION 7: Handling and storage**Handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****SK**

Zložka	Podstata	Hodnota	Kontrolné parametre	Poznámka
Toluene	SK OEL	NPEL priemerný	50 ppm, 192 mg/m3	K,
	SK OEL	NPEL krátkodobý	100 ppm, 384 mg/m3	K,

K Znamená, že faktor môže byť ľahko absorbovaný kožou. Niektoré faktory, ktoré ľahko prenikajú kožou, môžu spôsobovať až smrteľné otravy, často bez varovných príznakov (napr. anilín, nitrobenzén, nitroglykol, fenoly a pod.). Pri látkach s významným prienikom cez kožu, či už v podobe kvapalín alebo pár, je osobitne dôležité zabrániť kožnému kontaktu.

SI

Sestavine	Osnova	Vrednost	Parametri nadzora	Pripomba
Toluene	SI OEL	MV	50 ppm, 192 mg/m3	EU**, K, BAT,

BAT Biološka mejna vrednost - določena je biološka mejna vrednost, ki pomeni opozorilno raven nevarne kemične snovi in njenih metabolitov v tkivih, telesnih tekočinah ali izdihanem zraku, ne glede na to, ali je nevarna kemična snov vnesena v organizem z vdihavanjem, zaužitjem ali skozi kožo.

EU** Mejna vrednost, določena z Direktivo Komisije 2006/15/ES z dne 7. februarja 2006 o določitvi drugega seznama indikativnih mejnih vrednosti za poklicno izpostavljenost pri izvajanju Direktive Sveta 98/24/ES ter o spremembi Direktive 91/322/EGS in Direktive 2000/39/ES (UL L, št. 38, z dne 9. februarja 2006, str. 36).

K Lastnost lažjega prehajanja snovi v organizem skozi kožo

SE

Beståndsdelar	Grundval	Värde	Kontrollparametrar	Anmärkning
Toluene	SE AFS	NGV	50 ppm, 192 mg/m3	B, H,
	SE AFS	KTV	100 ppm, 384 mg/m3	B, H,

B Exponering för vissa kemiska ämnen nära befintligt yrkeshygieniskt gränsvärde och samtidig exponering för buller nära insatsvärdet 80 dB kan orsaka hörselskada.

H Ämnet kan lätt upptas genom huden.

RO

Componente	Bază	Valoare	Parametri de control	Notă
Toluene	RO OEL	TWA	50 ppm, 192 mg/m3	P,
	RO OEL	STEL	100 ppm, 384 mg/m3	P,

P Substanțele cu indicativul P (piele) pot pătrunde în organism prin pielea sau mucoasele intacte. Indicativul P nu se referă la substanțele care au numai o acțiune locală de tip iritativ.

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

PT

Componentes	Bases	Valor	Parâmetros de controlo	Nota
Toluene	PT OEL	VLE-MP	20 ppm,	(1), P, A4, IBE,
	PT DL 305/2007	oito horas	50 ppm, 192 mg/m3	Cutânea,
	PT DL 305/2007	curta duração	100 ppm, 384 mg/m3	Cutânea,

- (1) Abrangido por legislação nacional específica ou por legislação comunitária não transposta
- A4 Agente não classificável como carcinogénico no Homem.
- Cutânea Uma notação cutânea atribuída ao valor limite de exposição profissional assinala a possibilidade de absorção significativa através de pele.
- IBE Identifica substâncias para as quais existem índices de exposição biológicos. Estes podem ser de dois tipos: IBE A referentes a pesticidas inibidores da acetilcolinesterase e IBE M indutores de metahemoglobina.
- P Perigo de absorção cutânea

PL

Składniki	Podstawa	Wartość	Parametry dotyczące kontroli	Uwaga
Toluene	PL NDS	NDS	100 mg/m3	
	PL NDS	NDSch	200 mg/m3	

NO

Komponenter	Grunnlag	Verdi	Kontrollparametere	Nota
Toluene	FOR-2011-12-06-1358	TWA	25 ppm, 94 mg/m3	E, H,

- E EU har en veiledende grenseverdi for stoffet
- H En del av stoffene kan i stor grad trenge gjennom huden selv om denne er uskadet, og således tas opp i kroppen.

NL

Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
Toluene	NL WG	TGG-8 uur	150 mg/m3	
	NL WG	TGG-15 min	384 mg/m3	

MT

Ingredients	Basis	Value	Control parameters	Note
Toluene	MT OEL	TWA	50 ppm, 192 mg/m3	Skin,
	MT OEL	STEL	100 ppm, 384 mg/m3	Skin,

Skin A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.

LV

Sastāvdaļas	Bāze	Vērtība	Pārvaldības parametri	Piezīme
Toluene	LV OEL	AER 8 st	14 ppm, 50 mg/m3	Āda,
	LV OEL	AER īslaicīgā	40 ppm, 150 mg/m3	Āda,

Āda Āda

LU

Composants	Base	Valeur	Paramètres de contrôle	Note
Toluene	LU OEL	TWA	50 ppm, 192 mg/m3	Peau,
	LU OEL	STEL	100 ppm, 384 mg/m3	Peau,

Peau Une pénétration cutanée s'ajoutant à l'inhalation réglementée est possible

LT

Komponentai	Pagrindas, bazė	Vertė	Kontrolės parametrai	Pastaba
Toluene	LT OEL	IPRD	50 ppm, 192 mg/m3	O,
	LT OEL	TPRD	100 ppm, 384 mg/m3	O,

O Oksiduojanti

IT

Componenti	Base	Valore	Parametri di controllo	Nota
Toluene	IT OEL	TWA	50 ppm, 192 mg/m3	Pelle,

Pelle La notazione 'Pelle' attribuita ai valori limite di esposizione indica possibilità di assorbimento significativo attraverso la pelle.

IE

Ingredients	Basis	Value	Control parameters	Note
Toluene	IE OEL	OELV - 8 hrs (TWA)	50 ppm, 192 mg/m3	Sk, IOELV,
	IE OEL	OELV - 15 min (STEL)	100 ppm, 384 mg/m3	Sk, IOELV,

IOELV Indicative Occupational Exposure Limit Value

Sk Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body

HU

Komponensek	Bázis	Érték	Ellenőrzési paraméterek	Megjegyzés
Toluene	HU OEL	AK-érték	190 mg/m3	b, EU2, i,
	HU OEL	CK-érték	380 mg/m3	b, EU2, i,

- b Bőrön át is felszívódik. Az AK-értékek a veszélyes anyagoknak ezt a tulajdonságát, illetve az ebből származó expozíciót csak a levegőben megengedett koncentrációjuk mértékének megfelelően veszik figyelembe
- EU2 96/94/EK irányelvben közölt érték
- i Ingerlő anyag (izgatja a bőrt, nyálkahártyát, szemet vagy mindhármat)

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

GR

Συστατικά	Βάση	Τιμή	Παράμετροι ελέγχου	Σημείωση
Toluene	GR OEL	TWA	50 ppm, 192 mg/m3	Δ,
	GR OEL	STEL	100 ppm, 384 mg/m3	Δ,

Δ Η ένδειξη 'δέρμα' (Δ), η οποία επισημαίνει ορισμένους χημικούς παράγοντες του πίνακα της παρ. 1 του άρθρου 3, υπονοεί την πιθανή συμβολή στην συνολική έκθεση του εργαζόμενου και της ποσότητας αυτών των χημικών παραγόντων που απορροφάται διαμέσου του δέρματος κατά την άμεση επαφή μαζί τους.

GB

Ingredients	Basis	Value	Control parameters	Note
Toluene	GB EH40	TWA	50 ppm, 191 mg/m3	Sk,
	GB EH40	STEL	100 ppm, 384 mg/m3	Sk,

Sk Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

FR

Composants	Base	Valeur	Paramètres de contrôle	Note
Toluene	FR VLE	VME	20 ppm, 76,8 mg/m3	R2, *, noir,
	FR VLE	VLCT (VLE)	100 ppm, 384 mg/m3	R2, *, noir,

* Risque de pénétration percutanée
noir Valeurs limites réglementaires contraignantes
R2 Substances préoccupantes en raison d'effets toxiques pour la reproduction possibles

FI

Aineosat	Peruste	Arvo	Valvontaa koskevat muuttujat	Huomautus
Toluene	FI OEL	HTP-arvot 8h	25 ppm, 81 mg/m3	melu, iho,
	FI OEL	HTP-arvot 15 min	100 ppm, 380 mg/m3	melu, iho,

iho Ihon läpi imeytyvien aineiden elimistöön joutuvia määriä ja elimistöön joutuneesta aineesta aiheutuvaa vaaraa ei voida näin ollen arvioida pelkästään ilmapitoisuuksien avulla.Tämän vuoksi näiden aineiden HTP-arvojen yhteyteen on huomautussarakkeeseen otettu ihon läpi imeytymisen osoittamiseksi merkintä 'iho'. Monet aineet, varsinkin voimakkaat hapot tai emäkset, voivat aiheuttaa iholle jouduttuaan ihon ärsyntyntymistä tai syöpymistä.

melu Melu: aineille, joiden tiedetään voimistavan melun haitallisia kuulovaikutuksia.

ES

Componentes	Base	Valor	Parámetros de control	Nota
Toluene	ES VLA	VLA-ED	50 ppm, 192 mg/m3	vía dérmica, r, VLB®, VLI,
	ES VLA	VLA-EC	100 ppm, 384 mg/m3	vía dérmica, r, VLB®, VLI,

r Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el 'Reglamento CE 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos' (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido.

vía dérmica Vía dérmica
VLB® Agente químico que tiene Valor Límite Biológico específico en este documento.
VLI Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.

EE

Komponendid, osad	Alused	Väärtus	Kontrolliparameetrid	Märkused
Toluene	EE OEL	Piirnorm	50 ppm, 192 mg/m3	A,
	EE OEL	Lühiajalise kokkupuute piirnorm	100 ppm, 384 mg/m3	A,

A Naha kaudu kergesti absorbeeruvad ained

DK

Komponenter	Basis	Værdi	Kontrolparametre	Note
Toluene	DK OEL	GV	25 ppm, 94 mg/m3	H, E,

E At stoffet har en EF-grænseværdi
H Betyder, at stoffet kan optages gennem huden.

DE

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
Toluene	DE TRGS 900	AGW	50 ppm, 190 mg/m3	DFG, EU, H, Y,

DFG Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission)
EU Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich.)
H Hautresorptiv
Y Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden

CZ

Složky	Základ	Hodnota	Kontrolní parametry	Poznámka
Toluene	CZ OEL	PEL	200 mg/m3	I, D,

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

	CZ OEL	NPK-P	500 mg/m3	I, D,
--	--------	-------	-----------	-------

- D Při expozici se významně uplatňuje pronikání látky kůží
I dráždí sliznice (oči, dýchací cesty) resp. kůži

CY

Συστατικά	Βάση	Τιμή	Παράμετροι ελέγχου	Σημείωση
Toluene	CY OEL	TWA	50 ppm, 192 mg/m3	
	CY OEL	STEL	100 ppm, 384 mg/m3	

CH

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
Toluene	CH SUVA	MAK-Wert	50 ppm, 190 mg/m3	OL, H, RE3, RF3, NIOSH, DFG, INRS, HSE, SSC,
	CH SUVA	KZGW	200 ppm, 760 mg/m3	OL, H, RE3, RF3, NIOSH, DFG, INRS, HSE, SSC,

- DFG Deutsche Forschungsgemeinschaft
H Vergiftung durch Hautresorption möglich; Bei Stoffen, welche die Haut leicht zu durchdringen vermögen, kann durch die zusätzliche Hautresorption die innere Belastung wesentlich höher werden als bei alleiniger Aufnahme durch die Atemwege.
HSE Health and Safety Executive (Occupational Medicine and Hygiene Laboratory)
INRS Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles
NIOSH National Institute for Occupational Safety and Health
OL lärmverstärkende Ototoxizität
RE3 Umfasst Stoffe, die wegen möglicher fruchtschädigender (entwicklungsschädigender) Wirkungen beim Menschen zu Besorgnis Anlass geben.
RF3 Umfasst Stoffe, die wegen möglicher Beeinträchtigung der Fortpflanzungsfähigkeit (Fruchtbarkeit) des Menschen zur Besorgnis Anlass geben.
SSC Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.

BG

Съставки	Основа	Стойност	Параметри на контрол	Бележка
Toluene	BG OEL	TWA	50 ppm, 192 mg/m3	-,
	BG OEL	STEL	100 ppm, 384 mg/m3	-,

- Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност. Граничните стойности на тези химични агенти във въздуха на работната среда, определени с наредбата, са съобразени със съответните стойности, приети за Европейската общност, като могат да бъдат равни или по-ниски от тях.

BE

Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
Toluene	BE OEL	TGG 8 hr	20 ppm, 77 mg/m3	D,
	BE OEL	TGG 15 min	100 ppm, 384 mg/m3	D,

- D Opname van het agens via de huid, de slijmvliezen of de ogen vormt een belangrijk deel van de totale blootstelling. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.

AT

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
Toluene	AT OEL	TMW	50 ppm, 190 mg/m3	H,
	AT OEL	KZW	100 ppm, 380 mg/m3	H,

- H Besondere Gefahr der Hautresorption

Biological exposure indices

DE

Stoffname	CAS-Nr.	Zu überwachende Parameter	Probennahmezeit punkt	Stand
Toluene	108-88-3	Toluol: 600 µg/l (Blut)	Expositionsende, bzw. Schichtende	2013-04-04
		o-Kresol: 1,5 mg/l (Urin)	Expositionsende, bzw. Schichtende bei Langzeitexposition: nach mehreren vorangegangenen Schichten	2013-04-04

DMEL
Benzene

: End Use: Workers
Routes of exposure: Skin contact
Potential health effects: Chronic effects, Systemic effects

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

Value: 234 mg/kg

End Use: Workers

Routes of exposure: Inhalation

Potential health effects: Chronic effects, Systemic effects

Value: 3,25 mg/m³

End Use: Consumers

Routes of exposure: Skin contact

Potential health effects: Chronic effects, Systemic effects

Value: 0,234 mg/kg

End Use: Consumers

Routes of exposure: Inhalation

Potential health effects: Chronic effects, Systemic effects

Value: 0,00325 mg/m³

Derived minimal effect level

End Use: Consumer use

Routes of exposure: Ingestion

Potential health effects: Chronic effects, Systemic effects

Value: 0,00014 mg/kg

Derived minimal effect level

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

- Respiratory protection : Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Flame retardant

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

antistatic protective clothing. Workers should wear antistatic footwear.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

Form : Non-viscous
 Physical state : Liquid
 Color : Clear
 Odor : Strong gasoline

Safety data

Flash point : 4,4 °C (39,9 °F)
 Method: closed cup

Lower explosion limit : 1,2 %(V)

Upper explosion limit : 7,1 %(V)

Oxidizing properties : no

Autoignition temperature : 529 °C (984 °F)

Molecular formula : C₇H₈

Molecular weight : 92,15 g/mol

pH : Not applicable

Pour point : No data available

Freezing point : -94,5 °C (-138,1 °F)

Boiling point/boiling range : 110,6 °C (231,1 °F)

Vapor pressure : 1,10 PSI
 at 37,8 °C (100,0 °F)

Relative density : 0,87
 at 15,6 °C (60,1 °F)

Density : 0,9 g/cm³

Water solubility : Soluble in alcohol, benzene, and ether; insoluble in water.

Partition coefficient: n-octanol/water : No data available

Viscosity, kinematic : No data available

Relative vapor density : 2,8
 (Air = 1.0)

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

Evaporation rate : 4,5
Percent volatile : > 99 %

Other information

Conductivity : 8 pSm
at 20 °C
Method: ASTM D4308

SECTION 10: Stability and reactivity

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Possibility of hazardous reactions

Conditions to avoid : Heat, flames and sparks.
Materials to avoid : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Hazardous decomposition products : Carbon oxides
Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Toluene Reference, Fuel Grade**

Acute oral toxicity : LD50: > 5.000 mg/kg
Method: Acute toxicity estimate

Toluene Reference, Fuel Grade

Acute inhalation toxicity : LC50: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Acute toxicity estimate

Toluene Reference, Fuel Grade

Acute dermal toxicity : LD50: > 5.000 mg/kg
Method: Acute toxicity estimate

Toluene Reference, Fuel Grade

Skin irritation : Irritating to skin.
May cause skin irritation in susceptible persons.

Toluene Reference, Fuel Grade

Eye irritation : Eye irritation.
Vapors may cause irritation to the eyes, respiratory system

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

and the skin.

Sensitization

Toluene : Did not cause sensitization on laboratory animals.

Benzene Did not cause sensitization on laboratory animals.

Toluene Reference, Fuel Grade

Repeated dose toxicity : Method: Based on product or component testing, long term repeated exposure may cause damage to the following organs:
 Target Organs: Auditory organs
 Estimated based on individual component values.

Toluene Reference, Fuel Grade

Carcinogenicity : Method: Estimated based on individual component values.
 Remarks: Suspect cancer hazard

Reproductive toxicity

Toluene : Species: Rat
 Application Route: Inhalation
 Dose: 0, 100, 500, 2000 ppm
 Test period: 95 d
 NOAEL Parent: 2000 ppm

Developmental Toxicity

Toluene : Species: Rat
 Application Route: Inhalation
 Dose: 0, 100, 500, 2000 ppm
 Test period: 95 d
 NOAEL Teratogenicity: 400-750 ppm

Toluene Reference, Fuel Grade

Aspiration toxicity : May be fatal if swallowed and enters airways.
 Substances known to cause human aspiration toxicity hazards or to be regarded as if they cause human aspiration toxicity hazard.

CMR effects

Toluene : Carcinogenicity: Not classifiable as a human carcinogen.
 Mutagenicity: Animal testing did not show any mutagenic effects.
 Teratogenicity: Some evidence of adverse effects on development, based on animal experiments.
 Reproductive toxicity: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

Benzene Carcinogenicity: Human carcinogen.
 Mutagenicity: In vivo tests showed mutagenic effects
 Teratogenicity: Did not show teratogenic effects in animal experiments.
 Reproductive toxicity: Animal testing did not show any effects

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

on fertility.

Toluene Reference, Fuel Grade**Further information** : Solvents may degrease the skin.**SECTION 12: Ecological information****Toxicity to fish**

Toluene : LC50: 18 - 36 mg/l
 Exposure time: 96 h
 Species: Pimephales promelas (fathead minnow)

Benzene LC50: 5,3 mg/l
 Exposure time: 96 h
 Species: Oncorhynchus mykiss (rainbow trout)
 flow-through test Test substance: yes
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

Toluene : EC50: 3,78 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)

Benzene EC50: 10 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)
 static test Test substance: yes
 Method: OECD Test Guideline 202

Toxicity to algae

Toluene : EC50: 134 mg/l
 Exposure time: 72 h
 Species: Chlamydomonas angulosa (Green algae)

Benzene ErC50: 100 mg/l
 Exposure time: 72 h
 Species: Pseudokirchneriella subcapitata (green algae)
 Test substance: yes
 Method: OECD Test Guideline 201

Elimination information (persistence and degradability)

Biodegradability : Expected to be biodegradable

Ecotoxicology Assessment

Acute aquatic toxicity
 Toluene : Toxic to aquatic life.

Benzene : Toxic to aquatic life.

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

Chronic aquatic toxicity Toluene	: Harmful to aquatic life with long lasting effects.
Benzene	: Harmful to aquatic life with long lasting effects.
Results of PBT assessment Toluene	: Non-classified vPvB substance, Non-classified PBT substance
Benzene	: This substance is not considered to be persistent, bioaccumulating and toxic (PBT)., This substance is not considered to be very persistent and very bioaccumulating (vPvB).
Additional ecological information	: Toxic to aquatic life. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1294, TOLUENE, 3, II, RQ (TOLUENE)

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1294, TOLUENE, 3, II, (4,4 °C)

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1294, TOLUENE, 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1294, TOLUENE, 3, II, (D/E)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN1294, TOLUENE, 3, II

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1294, TOLUENE, 3, II

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**SECTION 15: Regulatory information****National legislation**

Major Accident Hazard Legislation : 96/82/EC Update: 2003
 Highly flammable
 7b
 Quantity 1: 5.000 t
 Quantity 2: 50.000 t

Water contaminating class (Germany) : WGK 2 water endangering
 List with water hazardous substances (Class 1 till 3) in
 VwVwS

Notification status

Europe REACH : This mixture contains only ingredients which have been
 subject to a pre-registration according to Regulation
 (EU) No. 1907/2006 (REACH).

United States of America TSCA : On TSCA Inventory

Canada DSL : All components of this product are on the Canadian
 DSL

Australia AICS : On the inventory, or in compliance with the inventory

New Zealand NZIoC : On the inventory, or in compliance with the inventory

Japan ENCS : On the inventory, or in compliance with the inventory

Korea KECI : On the inventory, or in compliance with the inventory

Philippines PICCS : On the inventory, or in compliance with the inventory

China IECSC : On the inventory, or in compliance with the inventory


Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

SECTION 16: Other information

NFPA Classification : Health Hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 3476

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical	TWA	Time Weighted Average

Toluene Reference, Fuel Grade

Version 1.7

Revision Date 2016-05-31

	Substances in China		
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.