

# SAFETY DATA SHEET



## DIACEL® LX200 Cement Fluid Loss Additive

Version 1.3

Revision Date 2016-08-16

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### Product information

Product Name : DIACEL® LX200 Cement Fluid Loss Additive  
Material : 1088906, 1084450

#### Company

: Chevron Phillips Chemical Company LP  
Specialty Chemicals  
10001 Six Pines Drive  
The Woodlands, TX 77380

#### Local

: Chevron Phillips Chemicals International N.V.  
Airport Plaza (Stockholm Building)  
Leonardo Da Vinci laan 19  
1831 Diegem  
Belgium

SDS Requests: (800) 852-5530  
Technical Information: (832) 813-4862  
Responsible Party: Product Safety Group  
Email:sds@cpchem.com

#### Emergency telephone:

##### Health:

866.442.9628 (North America)  
1.832.813.4984 (International)

##### Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)  
Asia: +800 CHEMCALL (+800 2436 2255) China:+86-21-22157316  
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group  
E-mail address : SDS@CPChem.com  
Website : www.CPChem.com

### SECTION 2: Hazards identification

#### Classification of the substance or mixture

REGULATION (EC) No 1272/2008

**DIACEL® LX200 Cement Fluid Loss Additive**

Version 1.3

Revision Date 2016-08-16

Eye irritation, Category 2

H319:  
Causes serious eye irritation.**Label elements****Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms



Signal Word : Warning

Hazard Statements : H319 Causes serious eye irritation.

Precautionary Statements : **Prevention:**  
 P264 Wash skin thoroughly after handling.  
 P280 Wear eye protection/ face protection.  
**Response:**  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.

**SECTION 3: Composition/information on ingredients**

Molecular formula : Mixture

**Mixtures****Hazardous ingredients**

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]
<b>Ethoxylated, C9-C11-Iso-, C10-Rich Alcohols</b>	<b>78330-20-8</b>	Acute Tox. 4; H302 Eye Dam. 1; H318	0 - 3
Isononylphenol, ethoxylated	37205-87-1	Skin Irrit. 2; H315 Eye Irrit. 2; H319	0 - 3

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures**

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance.

**DIACEL® LX200 Cement Fluid Loss Additive**

Version 1.3

Revision Date 2016-08-16

If inhaled : If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

**SECTION 5: Firefighting measures**

Flash point : Not applicable

Autoignition temperature : Not applicable

Unsuitable extinguishing media : High volume water jet.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Fire and explosion protection : Normal measures for preventive fire protection.

**SECTION 6: Accidental release measures**

Personal precautions : Use personal protective equipment.

Environmental precautions : Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

**SECTION 7: Handling and storage****Handling**

Advice on safe handling : Do not breathe vapors/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.

**DIACEL® LX200 Cement Fluid Loss Additive**

Version 1.3

Revision Date 2016-08-16

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

**Storage**

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8: Exposure controls/personal protection****Engineering measures**

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**Personal protective equipment**

Respiratory protection : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:.. Full-Face Air-Purifying Respirator for Organic Vapors, Dusts and Mists. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:.. Complete head face and neck protection. Rubber apron. Footwear protecting against chemicals.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**DIACEL® LX200 Cement Fluid Loss Additive**

Version 1.3

Revision Date 2016-08-16

**SECTION 9: Physical and chemical properties****Information on basic physical and chemical properties****Appearance**

Form : Suspension  
Physical state : Liquid  
Color : Milky white  
Odor : Slight

**Safety data**

Flash point : Not applicable  
  
Lower explosion limit : Not applicable  
  
Upper explosion limit : Not applicable  
  
Oxidizing properties : no  
  
Autoignition temperature : Not applicable  
  
Molecular formula : Mixture  
  
Molecular weight : Not applicable  
  
pH : 8  
  
Pour point : No data available  
  
Freezing point : 0 °C (32 °F)  
  
Boiling point/boiling range : 100 °C (212 °F)  
  
Vapor pressure : 17,50 MMHG  
at 20 °C (68 °F)  
  
Relative density : 0,98  
at 20 °C (68 °F)  
  
Density : 1,01 g/cm3  
  
Water solubility : Miscible  
  
Partition coefficient: n-octanol/water : No data available  
Viscosity, kinematic : No data available  
  
Relative vapor density : 0,62  
(Air = 1.0)  
  
Evaporation rate : No data available

**DIACEL® LX200 Cement Fluid Loss Additive**

Version 1.3

Revision Date 2016-08-16

**SECTION 10: Stability and reactivity**

**Chemical stability** : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**Possibility of hazardous reactions**

**Conditions to avoid** : No data available.

**Other data** : No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information****DIACEL® LX200 Cement Fluid Loss Additive**

**Acute oral toxicity** : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

**DIACEL® LX200 Cement Fluid Loss Additive**

**Skin irritation** : Mild skin irritation

**DIACEL® LX200 Cement Fluid Loss Additive**

**Eye irritation** : Eye irritation

**DIACEL® LX200 Cement Fluid Loss Additive**

**Further information** : No data available.

**SECTION 12: Ecological information****Toxicity to fish**

Ethoxylated, C9-C11-Iso-, C10-Rich Alcohols : LC50: > 100 mg/l  
Exposure time: 96 h  
Species: Fish  
Method: QSAR modeled data  
Aquatic toxicity is unlikely due to low solubility.

**Toxicity to daphnia and other aquatic invertebrates**

Ethoxylated, C9-C11-Iso-, C10-Rich Alcohols : EC50: > 100 mg/l  
Exposure time: 48 h  
Species: Daphnia  
Method: QSAR modeled data

**Toxicity to algae**

Ethoxylated, C9-C11-Iso-, C10-Rich Alcohols : EC50: 96,3 mg/l  
Exposure time: 96 h

**DIACEL® LX200 Cement Fluid Loss Additive**

Version 1.3

Revision Date 2016-08-16

Method: QSAR modeled data

Elimination information (persistence and degradability)

Biodegradability : This material is not expected to be readily biodegradable.

**Ecotoxicology Assessment**

Acute aquatic toxicity

Ethoxylated, C9-C11-Iso-, : Harmful to aquatic life.

C10-Rich Alcohols

Isononylphenol, ethoxylated : Harmful to aquatic life.

Results of PBT assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional ecological information

: No data available

**SECTION 13: Disposal considerations**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

**SECTION 14: Transport information**

**The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

SDS Number:100000013405

7/10

**DIACEL® LX200 Cement Fluid Loss Additive**

Version 1.3

Revision Date 2016-08-16

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

**SECTION 15: Regulatory information****National legislation**

**Major Accident Hazard Legislation** : 96/82/EC      Update:  
Not applicable

**Notification status**

Europe REACH	: On the inventory, or in compliance with the inventory
Switzerland CH INV	: Not in compliance with the inventory
United States of America TSCA	: On the inventory, or in compliance with the inventory
Canada DSL	: On the inventory, or in compliance with the inventory
Australia AICS	: On the inventory, or in compliance with the inventory
New Zealand NZIoC	: On the inventory, or in compliance with the inventory
Japan ENCS	: On the inventory, or in compliance with the inventory
Korea KECI	: On the inventory, or in compliance with the inventory
Philippines PICCS	: On the inventory, or in compliance with the inventory
China IECSC	: On the inventory, or in compliance with the inventory


**DIACEL® LX200 Cement Fluid Loss Additive**

Version 1.3

Revision Date 2016-08-16

**SECTION 16: Other information****NFPA Classification**

: Health Hazard: 2  
 Fire Hazard: 1  
 Reactivity Hazard: 0

**Further information**

Legacy SDS Number : CPC00288

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical	TWA	Time Weighted Average

# DIACEL® LX200 Cement Fluid Loss Additive

Version 1.3

Revision Date 2016-08-16

	Substances in China		
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

## **Full text of H-Statements referred to under sections 2 and 3.**

H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.