

**sec-Butyl Mercaptan**

Version 1.6

Revision Date 2016-06-03

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : sec-Butyl Mercaptan
Material : 1021484, 1021479, 1021493, 1021475, 1021476, 1021478, 1021480, 1021477

Company : Chevron Phillips Chemical Company LP
Specialty Chemicals
10001 Six Pines Drive
The Woodlands, TX 77380

Local : Chevron Phillips Chemicals International N.V.
Airport Plaza (Stockholm Building)
Leonardo Da Vincilaan 19
1831 Diegem
Belgium

SDS Requests: (800) 852-5530
Technical Information: (832) 813-4862
Responsible Party: Product Safety Group
Email:sds@cpchem.com

Emergency telephone:**Health:**

866.442.9628 (North America)
1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)
Asia: +800 CHEMCALL (+800 2436 2255) China:+86-21-22157316
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group
E-mail address : SDS@CPChem.com
Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture
REGULATION (EC) No 1272/2008**




sec-Butyl Mercaptan

Version 1.6

Revision Date 2016-06-03

Flammable liquids, Category 2	H225: Highly flammable liquid and vapor.
Skin sensitization, Sub-category 1B	H317: May cause an allergic skin reaction.
Acute aquatic toxicity, Category 1	H400: Very toxic to aquatic life.
Chronic aquatic toxicity, Category 1	H410: Very toxic to aquatic life with long lasting effects.

Label elements**Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms	:	  
Signal Word	:	Danger
Hazard Statements	:	H225 Highly flammable liquid and vapor. H317 May cause an allergic skin reaction. H410 Very toxic to aquatic life with long lasting effects.
Precautionary Statements	:	Prevention: P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P273 Avoid release to the environment. Response: P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Hazardous ingredients which must be listed on the label:

- 513-53-1 sec-butyl Mercaptan

SECTION 3: Composition/information on ingredients

Synonyms : secondary Butyl mercaptan
1-methyl-1-propanethiol
Gas Odorant

Molecular formula : C₄H₁₀S

Mixtures**Hazardous ingredients**

sec-Butyl Mercaptan

Version 1.6

Revision Date 2016-06-03

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]
sec-butyl Mercaptan	513-53-1 208-165-2	Flam. Liq. 2; H225 Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	99
n-Butyl Mercaptan	109-79-5 203-705-3	Flam. Liq. 2; H225 Acute Tox. 4; H302 Skin Sens. 1B; H317 Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	1

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
- If inhaled : Consult a physician after significant exposure. If unconscious place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5: Firefighting measures

- Flash point : -23 °C (-9 °F)
estimated
- Autoignition temperature : No data available
- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.
- Unsuitable extinguishing media : High volume water jet.
- Specific hazards during fire : Do not allow run-off from fire fighting to enter drains or water

sec-Butyl Mercaptan

Version 1.6

Revision Date 2016-06-03

fighting	courses.
Special protective equipment for fire-fighters	: Wear self-contained breathing apparatus for firefighting if necessary.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Fire and explosion protection	: Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
Hazardous decomposition products	: Carbon oxides. Sulfur oxides.

SECTION 6: Accidental release measures

Personal precautions	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

Advice on safe handling	: Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Advice on protection against fire and explosion	: Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

sec-Butyl Mercaptan

Version 1.6

Revision Date 2016-06-03

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****SK**

Zložka	Podstata	Hodnota	Kontrolné parametre	Poznámka
n-Butyl Mercaptan	SK OEL	NPEL priemerný	0,5 ppm, 1,9 mg/m ³	
	SK OEL	NPEL krátkodobý	1 ppm, 3,8 mg/m ³	

SI

Sestavine	Osnova	Vrednost	Parametri nadzora	Pripomba
n-Butyl Mercaptan	SI OEL	MV	0,5 ppm, 1,9 mg/m ³	Y,

Y Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in BAT vrednosti.

PT

Componentes	Bases	Valor	Parâmetros de controlo	Nota
n-Butyl Mercaptan	PT OEL	VLE-MP	0,5 ppm,	irritação do TRS,

irritação do trato respiratório superior
TRS

PL

Składniki	Podstawa	Wartość	Parametry dotyczące kontroli	Uwaga
n-Butyl Mercaptan	PL NDS	NDS	1 mg/m ³	
	PL NDS	NDSch	2 mg/m ³	

NO

Komponenter	Grunnlag	Verdi	Kontrollparametere	Nota
n-Butyl Mercaptan	FOR-2011-12-06-1358	TWA	0,5 ppm, 1,5 mg/m ³	

IE

Ingredients	Basis	Value	Control parameters	Note
n-Butyl Mercaptan	IE OEL	OELV - 8 hrs (TWA)	0,5 ppm, 1,8 mg/m ³	

GR

Συστατικά	Βάση	Τιμή	Παράμετροι ελέγχου	Σημείωση
n-Butyl Mercaptan	GR OEL	TWA	0,5 ppm, 1,8 mg/m ³	

FI

Aineosat	Peruste	Arvo	Valvontaa koskevat muuttujat	Huomautus
n-Butyl Mercaptan	FI OEL	HTP-arvot 8h	0,5 ppm, 1,9 mg/m ³	
	FI OEL	HTP-arvot 15 min	1,5 ppm, 5,6 mg/m ³	

ES

Componentes	Base	Valor	Parâmetros de control	Nota
n-Butyl Mercaptan	ES VLA	VLA-ED	0,5 ppm, 1,9 mg/m ³	

DK

Komponenter	Basis	Værdi	Kontrolparametre	Note
n-Butyl Mercaptan	DK OEL	GV	0,5 ppm, 1,5 mg/m ³	

DE

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
n-Butyl Mercaptan	DE TRGS 900	AGW	0,5 ppm, 1,9 mg/m ³	DFG, Y,

DFG Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission)

Y Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden

sec-Butyl Mercaptan

Version 1.6

Revision Date 2016-06-03

CZ

Složky	Základ	Hodnota	Kontrolní parametry	Poznámka
n-Butyl Mercaptan	CZ OEL	PEL	1,5 mg/m ³	
	CZ OEL	NPK-P	3 mg/m ³	

CH

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
n-Butyl Mercaptan	CH SUVA	MAK-Wert	0,5 ppm, 1,9 mg/m ³	NIOSH, SSc,
	CH SUVA	KZGW	1 ppm, 3,8 mg/m ³	NIOSH, SSc,

NIOSH National Institute for Occupational Safety and Health

SSc Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.

BE

Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
n-Butyl Mercaptan	BE OEL	TGG 8 hr	0,5 ppm, 1,8 mg/m ³	

AT

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
n-Butyl Mercaptan	AT OEL	TMW	0,5 ppm, 1,9 mg/m ³	
	AT OEL	KZW	0,5 ppm, 1,9 mg/m ³	

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

- Respiratory protection : Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate: Chemical resistant apron. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.

sec-Butyl Mercaptan

Version 1.6

Revision Date 2016-06-03

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

Form : Liquid
Physical state : Liquid
Color : Clear
Odor : Pungent

Safety data

Flash point : -23 °C (-9 °F)
estimated

Lower explosion limit : No data available

Upper explosion limit : No data available

Oxidizing properties : no

Autoignition temperature : No data available

Molecular formula : C₄H₁₀S

Molecular weight : 90,2 g/mol

pH : Not applicable

Pour point : No data available

Boiling point/boiling range : 84,98 °C (184,96 °F)

Vapor pressure : 2,75 PSI
at 38 °C (100 °F)

Relative density : 0,835
at 15,6 °C (60,1 °F)

Water solubility : Partly soluble

Partition coefficient: n-octanol/water : No data available

Viscosity, dynamic : 0,463 cP

Relative vapor density : 1
(Air = 1.0)

Evaporation rate : 1

Percent volatile : > 99 %

sec-Butyl Mercaptan

Version 1.6

Revision Date 2016-06-03

SECTION 10: Stability and reactivity

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Possibility of hazardous reactions

Conditions to avoid : Heat, flames and sparks.
Hazardous decomposition products : Carbon oxides
Sulfur oxides

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**sec-Butyl Mercaptan**

Acute oral toxicity : LD50: > 5.000 mg/kg
Species: Rat
Information refers to the main ingredient.

Acute inhalation toxicity

sec-butyl Mercaptan : LC50: 98,3 mg/l
Exposure time: 4 h
Species: Rat
Sex: male and female
Test atmosphere: vapor
Information given is based on data obtained from similar substances.

n-Butyl Mercaptan : LC50: 22,3 mg/l
Exposure time: 4 h
Species: Rat
Test atmosphere: dust/mist

Acute dermal toxicity

sec-butyl Mercaptan : LD50: >2000 milligram per kilogram
Species: Rat

Skin irritation

sec-butyl Mercaptan : No skin irritation
Information given is based on data obtained from similar substances.

n-Butyl Mercaptan : No skin irritation
Information given is based on data obtained from similar substances.

Eye irritation

sec-Butyl Mercaptan

Version 1.6

Revision Date 2016-06-03

n-Butyl Mercaptan : slight irritation. Information given is based on data obtained from similar substances.

Sensitization

sec-butyl Mercaptan : The product is a skin sensitizer, sub-category 1B. Information given is based on data obtained from similar substances.

n-Butyl Mercaptan The product is a skin sensitizer, sub-category 1B.

Repeated dose toxicity

sec-butyl Mercaptan : Species: Rat, male and female
Sex: male and female
Application Route: Inhalation
Exposure time: 13 wks
Number of exposures: 6 hrs/d, 5 d/wk
NOEL: 0,367 mg/l 99.6 ppm
Lowest observable effect level: 1,488 mg/l 403.4 ppm
Method: OECD Guideline 413
Target Organs: Blood, Liver, Kidney, Upper respiratory tract

n-Butyl Mercaptan Species: Rat
Application Route: Inhalation
Dose: 0, 9, 70, 150 ppm
Exposure time: 13 wk
Number of exposures: 6 h/d, 5 d/wk
NOEL: 9 ppm
Lowest observable effect level: 70 ppm

Reproductive toxicity

sec-butyl Mercaptan : Species: Rat
Sex: male and female
Application Route: oral gavage
Dose: 10, 50, 200 mg/kg bw/d
Number of exposures: Daily
Test period: 42-50 days
Method: OECD Guideline 422
NOAEL Parent: 200 mg/kg
NOAEL F1: 50 mg/kg
Information given is based on data obtained from similar substances.

Developmental Toxicity

sec-butyl Mercaptan : Species: Rat
Application Route: Inhalation
Dose: 11, 99, 195 ppm
Exposure time: GD 6-16
Number of exposures: 6 hrs/d
Method: OECD Guideline 414
NOAEL Teratogenicity: > = 195 ppm
NOAEL Maternal: > = 195 ppm
Information given is based on data obtained from similar substances.

sec-Butyl Mercaptan

Version 1.6

Revision Date 2016-06-03

	<p>Species: Mouse Application Route: Inhalation Dose: 11, 99, 195 ppm Exposure time: GD 6-16 Number of exposures: 6 hrs/d Method: OECD Guideline 414 NOAEL Teratogenicity: > = 195 ppm NOAEL Maternal: > = 195 ppm Information given is based on data obtained from similar substances.</p>
n-Butyl Mercaptan	<p>Species: Rat Application Route: Inhalation Dose: 0, 10, 68, 152 ppm Number of exposures: 6 h/d Test period: GD 6-19 NOAEL Teratogenicity: > 152 ppm NOAEL Maternal: > 152 ppm</p> <p>Species: Mouse Application Route: Inhalation Dose: 0, 10, 68, 152 ppm Number of exposures: 6 h/d Test period: GD 6-16 NOAEL Maternal: 10 ppm</p>
sec-Butyl Mercaptan Aspiration toxicity	: May be harmful if swallowed and enters airways.
sec-Butyl Mercaptan Further information	: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

SECTION 12: Ecological information**Toxicity to fish**

sec-butyl Mercaptan : LC50: 8,5 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)
static test Analytical monitoring: yes
Method: OECD Test Guideline 203

n-Butyl Mercaptan LC50: 2,4 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)
Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates

sec-butyl Mercaptan : 0,56 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
Immobilization Method: OECD Test Guideline 202

sec-Butyl Mercaptan

Version 1.6

Revision Date 2016-06-03

Information refers to the main ingredient.

n-Butyl Mercaptan

EC50: 0,38 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)
 Information given is based on data obtained from similar substances.

Toxicity to algae

sec-butyl Mercaptan

: EC50: 3,4 mg/l
 Exposure time: 72 h
 Species: Pseudokirchneriella subcapitata (green algae)
 Growth inhibition Method: OECD Test Guideline 201

n-Butyl Mercaptan

EC50: 3,0 mg/l
 Exposure time: 96 h
 Species: Selenastrum capricornutum (algae)
 Information given is based on data obtained from similar substances.

M-Factor
 butane-2-thiol

: 1

Biodegradability

sec-butyl Mercaptan

: aerobic
 Result: Not readily biodegradable.
 6 %
 Testing period: 63 d
 Method: OECD Test Guideline 301F
 Information given is based on data obtained from similar substances.

Ecotoxicology Assessment

Acute aquatic toxicity
 sec-butyl Mercaptan

: Very toxic to aquatic life.

n-Butyl Mercaptan

: Very toxic to aquatic life.

Chronic aquatic toxicity
 sec-butyl Mercaptan

: Very toxic to aquatic life with long lasting effects.

n-Butyl Mercaptan

: Very toxic to aquatic life with long lasting effects.

Toxicity Data on Soil

: No data available

Other organisms relevant to
 the environment

: No data available

Impact on Sewage

: No data available

Treatment

Additional ecological
 information

: Very toxic to aquatic life with long lasting effects.

sec-Butyl Mercaptan

Version 1.6

Revision Date 2016-06-03

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

- Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN2347, BUTYL MERCAPTANS, 3, II

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN2347, BUTYL MERCAPTANS, 3, II, (-23 °C), MARINE POLLUTANT, (SEC-BUTYL MERCAPTAN)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN2347, BUTYL MERCAPTAN, 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN2347, BUTYL MERCAPTAN, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (SEC-BUTYL MERCAPTAN)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN2347, BUTYL MERCAPTAN, 3, II, ENVIRONMENTALLY HAZARDOUS, (SEC-BUTYL MERCAPTAN)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN2347, BUTYL MERCAPTAN, 3, II, ENVIRONMENTALLY HAZARDOUS, (SEC-BUTYL

sec-Butyl Mercaptan

Version 1.6

Revision Date 2016-06-03

MERCAPTAN)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**National legislation**


Major Accident Hazard Legislation : 96/82/EC Update: 2003
 Highly flammable
 7b
 Quantity 1: 5.000 t
 Quantity 2: 50.000 t

Notification status

Europe REACH : On the inventory, or in compliance with the inventory
 United States of America TSCA : On the inventory, or in compliance with the inventory
 Canada NDSL : This product contains one or several components listed in the Canadian NDSL.
 Australia AICS : On the inventory, or in compliance with the inventory
 New Zealand NZIoC : On the inventory, or in compliance with the inventory
 Japan ENCS : On the inventory, or in compliance with the inventory
 Korea KECI : On the inventory, or in compliance with the inventory
 Philippines PICCS : Not in compliance with the inventory
 China IECSC : Not in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 2
 Fire Hazard: 3
 Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 427800

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

sec-Butyl Mercaptan

Version 1.6

Revision Date 2016-06-03

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapor.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.