

**Paraxylene**

Version 1.3

Revision Date 2014-08-22

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Trade name : Paraxylene
Material : 1059264, 1025305, 1015391

Company : Chevron Phillips Chemical Company LP
10001 Six Pines Drive
The Woodlands, TX 77380

Emergency telephone:**Health:**

866.442.9628 (North America)
1.832.813.4984 (International)

Transport:

North America: CHEMTREC 800.424.9300 or 703.527.3887
Asia: +800 CHEMCALL (+800 2436 2255)
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group
E-mail address : SDS@CPChem.com
Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Emergency Overview**Danger**

Form: Liquid **Physical state:** Liquid **Color:** Clear

OSHA Hazards : Flammable Liquid, Aspiration hazard, Carcinogen, Moderate skin irritant, Moderate eye irritant, Moderate respiratory irritant

Classification

: Flammable liquids , Category 3
Skin irritation , Category 2
Eye irritation , Category 2A
Specific target organ systemic toxicity - single exposure , Category 3 , Respiratory system
Specific target organ systemic toxicity - repeated exposure ,

Paraxylene

Version 1.3

Revision Date 2014-08-22

Category 2 , Inhalation , Auditory organs
Aspiration hazard , Category 1

Labeling

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H226: Flammable liquid and vapor.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H335: May cause respiratory irritation.
H373: May cause damage to organs (Auditory organs) through prolonged or repeated exposure if inhaled.

Precautionary Statements

: **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces.
- No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapor/spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
Disposal:

Paraxylene

Version 1.3

Revision Date 2014-08-22

P501 Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity:**IARC**

Group 2B: Possibly carcinogenic to humans

Ethylbenzene 100-41-4

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

ACGIH

Confirmed animal carcinogen with unknown relevance to humans

Ethylbenzene 100-41-4

SECTION 3: Composition/information on ingredients

Synonyms : Benzene, 1,4-Dimethyl
p-Xylene
1,4-Dimethyl-benzene
Xylene-p

Molecular formula : C8H10

Component	CAS-No.	Weight %
p-xylene	106-42-3	99
Ethylbenzene	100-41-4	0 - 1
o-xylene	95-47-6	0 - 1
m-xylene	108-38-3	0 - 1

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.

If inhaled : Move to fresh air. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.

Paraxylene

Version 1.3

Revision Date 2014-08-22

SECTION 5: Firefighting measures

Flash point	:	27 °C (81 °F) Method: closed cup
Autoignition temperature	:	528 °C (982 °F)
Suitable extinguishing media	:	Dry chemical. Carbon dioxide (CO ₂). Alcohol-resistant foam.
Specific hazards during fire fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Special protective equipment for fire-fighters	:	Wear self contained breathing apparatus for fire fighting if necessary.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Fire and explosion protection	:	Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
Hazardous decomposition products	:	Carbon oxides.

SECTION 6: Accidental release measures

Personal precautions	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid

Paraxylene

Version 1.3

Revision Date 2014-08-22

exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient. Review all operations, which have the potential to generating and accumulation of electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106 "Flammable and Combustible Liquids"; National Fire Protection Association (NFPA 77), "Recommended Practice on Static Electricity"; and/or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising Out of Static, Lightning, and stray Currents".

Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****US**

Ingredients	Basis	Value	Control parameters	Note
p-xylene	ACGIH	TWA	100 ppm,	BEI, A4,
	ACGIH	STEL	150 ppm,	BEI, A4,
Ethylbenzene	OSHA Z-1	TWA	100 ppm, 435 mg/m3	(b),
	OSHA Z-1	TWA	100 ppm, 435 mg/m3	(b),
	OSHA Z-1-A	TWA	100 ppm, 435 mg/m3	
	OSHA Z-1-A	STEL	125 ppm, 545 mg/m3	
m-xylene	ACGIH	TWA	20 ppm,	
	ACGIH	TWA	100 ppm,	BEI, A4,
	ACGIH	STEL	150 ppm,	BEI, A4,
o-xylene	OSHA Z-1	TWA	100 ppm, 435 mg/m3	(b),
	ACGIH	TWA	100 ppm,	BEI, A4,
	ACGIH	STEL	150 ppm,	BEI, A4,
	OSHA Z-1	TWA	100 ppm, 435 mg/m3	(b),

(b) The value in mg/m3 is approximate.

A4 Not classifiable as a human carcinogen

BEI Substances for which there is a Biological Exposure Index or Indices (see BEI® section)

Engineering measures

Paraxylene

Version 1.3

Revision Date 2014-08-22

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

- Respiratory protection : Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles. Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate: Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- Form : Liquid
Physical state : Liquid
Color : Clear

Safety data

- Flash point : 27 °C (81 °F)
Method: closed cup
Lower explosion limit : 1.1 %(V)
Upper explosion limit : 7 %(V)

Paraxylene

Version 1.3

Revision Date 2014-08-22

Oxidizing properties	: no
Autoignition temperature	: 528 °C (982 °F)
Molecular formula	: C ₈ H ₁₀
Molecular weight	: 106.17 g/mol
pH	: Not applicable
pour point	: No data available
Boiling point/boiling range	: 138.3 °C (280.9 °F)
Vapor pressure	: 0.16 PSI at 25 °C (77 °F)
Relative density	: 0.86, 25 °C(77 °F)
Water solubility	: Soluble in hydrocarbon solvents; insoluble in water.
Partition coefficient: n-octanol/water	: log Pow: 3.15
Viscosity, kinematic	: 0.70 cSt at 25 °C (77 °F)
Relative vapor density	: 3.7 (Air = 1.0)
Evaporation rate	: No data available
Percent volatile	: > 99 %

Other information

Conductivity	: < 50 pSm at 20 °C
--------------	------------------------

SECTION 10: Stability and reactivity

Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
--------------------	----------------------------------------------------------------------------------------------------------------------------------------

Possibility of hazardous reactions

Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Other data	: No decomposition if stored and applied as directed.

Paraxylene

Version 1.3

Revision Date 2014-08-22

SECTION 11: Toxicological information

- Paraxylene
Acute oral toxicity** : LD50 Oral: 3,426 mg/kg
Species: rat
Method: Acute toxicity estimate
- Paraxylene
Acute inhalation toxicity** : LC50: 26.44 mg/l
Exposure time: 4 h
Species: rat
Test atmosphere: vapor
Method: Acute toxicity estimate
- Paraxylene
Acute dermal toxicity** : LD50 Dermal: > 5,000 mg/kg
Method: Acute toxicity estimate
- Paraxylene
Skin irritation** : Irritating to skin.
- Paraxylene
Eye irritation** : Irritating to eyes.
- Paraxylene
Sensitization** : Classification: Contains no substance or substances classified as sensitizing.
Does not cause sensitization. largely based on human evidence. Information given is based on data obtained from similar substances.
- Paraxylene
Repeated dose toxicity** : Method: Based on product or component testing, long term repeated exposure may cause damage to the following organs:
Target Organs: Auditory organs
Estimated based on individual component values.
- Paraxylene
Carcinogenicity** : Method: Estimated based on individual component values.
Remarks: Suspect cancer hazard
- Paraxylene
Developmental Toxicity** : No adverse effects expected
- Paraxylene
Aspiration toxicity** : May be fatal if swallowed and enters airways.
Substances known to cause human aspiration toxicity hazards or to be regarded as if they cause human aspiration toxicity hazard.

CMR effects

Paraxylene

Version 1.3

Revision Date 2014-08-22

p-xylene	: Carcinogenicity: Animal testing did not show any carcinogenic effects. Mutagenicity: Did not show mutagenic effects in animal experiments. Teratogenicity: Did not show teratogenic effects in animal experiments. Reproductive toxicity: No toxicity to reproduction
Ethylbenzene	Mutagenicity: In vivo tests did not show mutagenic effects Teratogenicity: Did not show teratogenic effects in animal experiments. Reproductive toxicity: No toxicity to reproduction
o-xylene	Carcinogenicity: Animal testing did not show any carcinogenic effects. Mutagenicity: Did not show mutagenic effects in animal experiments. Teratogenicity: Did not show teratogenic effects in animal experiments. Reproductive toxicity: No toxicity to reproduction
m-xylene	Carcinogenicity: Animal testing did not show any carcinogenic effects. Mutagenicity: Did not show mutagenic effects in animal experiments. Teratogenicity: Did not show teratogenic effects in animal experiments. Reproductive toxicity: No toxicity to reproduction
Paraxylene Further information	: Solvents may degrease the skin. Concentrations substantially above the TLV value may cause narcotic effects. Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing.

SECTION 12: Ecological information**Toxicity to fish**

p-xylene	: LC50: 2.0 mg/l Exposure time: 96 h Species: Marone saxatilis (striped bass)
Ethylbenzene	LC50: 4.3 mg/l Exposure time: 96 h Species: Marone saxatilis (striped bass)
o-xylene	LC50: 7.6 mg/l Exposure time: 96 h Species: Salmo gairdneri (Rainbow trout)
m-xylene	LC50: 8.4 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) static test Test substance: yes Method: OECD Test Guideline 203

Paraxylene

Version 1.3

Revision Date 2014-08-22

Toxicity to daphnia and other aquatic invertebrates

p-xylene	: EC50: 3.6 mg/l Exposure time: 24 h Species: Daphnia static test Test substance: yes Method: OECD Test Guideline 202
Ethylbenzene	LC50: 2.6 mg/l Exposure time: 96 h Species: Mysidopsis bahia (mysid shrimp)
	EC50: 2.2 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea) Method: OECD Test Guideline 202
o-xylene	EC50: 1 mg/l Exposure time: 24 h Species: Daphnia magna (Water flea) Method: OECD Test Guideline 202
m-xylene	EC50: 4.7 mg/l Exposure time: 24 h Species: Daphnia magna (Water flea) Immobilization Test substance: yes Method: OECD Test Guideline 202

Toxicity to algae

p-xylene	: EL50: 3.2 mg/l Exposure time: 72 h Species: Selenastrum capricornutum (algae) static test Test substance: yes Method: OECD Test Guideline 201
Ethylbenzene	ErC50: 5.0 mg/l Exposure time: 96 h Species: Selenastrum capricornutum (algae)
	ErC50: 7.7 mg/l Exposure time: 72 h Species: Skeletonema costatum (Marine Algae)
o-xylene	EC50: 4.2 mg/l Exposure time: 8 Days Species: Selenastrum capricornutum (algae) static test Analytical monitoring: yes
m-xylene	EC50: 4.9 mg/l Exposure time: 72 h Species: Selenastrum capricornutum (algae) static test Test substance: yes Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

Paraxylene

Version 1.3

Revision Date 2014-08-22

Ethylbenzene : NOEC: 1 mg/l
 Exposure time: 7 d
 Species: Daphnia pulex (Water flea)
 semi-static test
 Analytical monitoring: yes

Elimination information (persistence and degradability)

Bioaccumulation : Does not significantly accumulate in organisms.

Biodegradability : This material is expected to be readily biodegradable.

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity
 Ethylbenzene : Harmful to aquatic life with long lasting effects.

Results of PBT assessment : This substance is not considered to be persistent, bioaccumulating nor toxic (PBT)., This substance is not considered to be very persistent nor very bioaccumulating (vPvB).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the MSDS and

Paraxylene

Version 1.3

Revision Date 2014-08-22

the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1307, XYLENES, 3, III, RQ (P-XYLENE)

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1307, XYLENES, 3, III, (27 °C), RQ (P-XYLENE)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1307, XYLENES, 3, III

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1307, XYLENES, 3, III, (D/E)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN1307, XYLENES, 3, III

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1307, XYLENES, 3, III

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**National legislation**

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

CERCLA Reportable
Quantity :
p-xylene

SARA 302 Threshold
Planning Quantity : SARA 302: No chemicals in this material are subject to the
reporting requirements of SARA Title III, Section 302.

SARA 313 Ingredients :
: Ethylbenzene - 100-41-4

Paraxylene

Version 1.3

Revision Date 2014-08-22

m-xylene - 108-38-3
 o-xylene - 95-47-6
 p-xylene - 106-42-3

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

US State Regulations

Pennsylvania Right To Know

: p-xylene - 106-42-3
 o-xylene - 95-47-6
 m-xylene - 108-38-3
 Ethylbenzene - 100-41-4

New Jersey Right To Know

: p-xylene - 106-42-3
 o-xylene - 95-47-6
 m-xylene - 108-38-3
 Ethylbenzene - 100-41-4

California Prop. 65
Ingredients

: WARNING! This product contains a chemical known in the State of California to cause cancer.

Notification status

Europe REACH : Not in compliance with the inventory
 United States of America TSCA : On TSCA Inventory
 Canada DSL : All components of this product are on the Canadian DSL.
 Australia AICS : On the inventory, or in compliance with the inventory
 New Zealand NZIoC : On the inventory, or in compliance with the inventory
 Japan ENCS : On the inventory, or in compliance with the inventory
 Korea KECI : On the inventory, or in compliance with the inventory
 Philippines PICCS : On the inventory, or in compliance with the inventory
 China IECSC : On the inventory, or in compliance with the inventory


Paraxylene

Version 1.3

Revision Date 2014-08-22

SECTION 16: Other information

NFPA Classification : Health Hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 700

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical	TWA	Time Weighted Average

Paraxylene

Version 1.3

Revision Date 2014-08-22

	Substances in China		
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		