

**Orfom® SX-AP (Solvent Extraction Diluent)**

Version 1.0

Revision Date 2014-04-17

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Trade name : Orfom® SX-AP (Solvent Extraction Diluent)

Use : Mineral Processing Aide

Company : Chevron Phillips Chemical Company LP
10001 Six Pines Drive
The Woodlands, TX 77380

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

North America: CHEMTREC 800.424.9300 or 703.527.3887

Asia: +800 CHEMCALL (+800 2436 2255)

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group
E-mail address : MSDS@CPChem.com
Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Emergency Overview**Danger****Form:** Liquid **Physical state:** Liquid **Color:** Clear, colorless **Odor:** Mild

OSHA Hazards : Aspiration hazard

Classification


: Aspiration hazard, Category 1

Labeling

Orfom® SX-AP (Solvent Extraction Diluent)

Version 1.0

Revision Date 2014-04-17

Symbol(s) : 

Signal Word : Danger

Hazard Statements : H304: May be fatal if swallowed and enters airways.

Precautionary Statements : **Response:**
P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P331: Do NOT induce vomiting.
Storage:
P405: Store locked up.
Disposal:
P501: Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity:**IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

ACGIH

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

SECTION 3: Composition/information on ingredients

Component	CAS-No.	Weight %
Distillates (petroleum), catalytic dewaxed middle	64742-72-9	100

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to

Orfom® SX-AP (Solvent Extraction Diluent)

Version 1.0

Revision Date 2014-04-17

an unconscious person. If symptoms persist, call a physician.
Take victim immediately to hospital.

SECTION 5: Firefighting measures

- | | | |
|--|---|--|
| Flash point | : | 96 °C (205 °F)
Method: ASTM D 56 |
| Unsuitable extinguishing media | : | High volume water jet. |
| Special protective equipment for fire-fighters | : | Wear self contained breathing apparatus for fire fighting if necessary. |
| Further information | : | Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Fire and explosion protection | : | Normal measures for preventive fire protection. |

SECTION 6: Accidental release measures

- | | | |
|---------------------------|---|---|
| Personal precautions | : | Use personal protective equipment. Ensure adequate ventilation. |
| Environmental precautions | : | Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods for cleaning up | : | Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. |

SECTION 7: Handling and storage**Handling**

- | | | |
|---|---|---|
| Advice on safe handling | : | Do not breathe vapors/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. |
| Advice on protection against fire and explosion | : | Normal measures for preventive fire protection. |

Storage

- | | | |
|---|---|--|
| Requirements for storage areas and containers | : | Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards. |
|---|---|--|

Orfom® SX-AP (Solvent Extraction Diluent)

Version 1.0

Revision Date 2014-04-17

SECTION 8: Exposure controls/personal protection**Engineering measures**

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

- | | |
|--------------------------|---|
| Respiratory protection | : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Air-Purifying Respirator for Organic Vapors, Dusts and Mists. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection. |
| Hand protection | : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. |
| Eye protection | : Eye wash bottle with pure water. Tightly fitting safety goggles. |
| Skin and body protection | : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Protective suit. Safety shoes. |
| Hygiene measures | : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. |

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- | | |
|----------------|--------------------|
| Form | : Liquid |
| Physical state | : Liquid |
| Color | : Clear, colorless |
| Odor | : Mild |

Safety data

- | | |
|-----------------------|---------------------------------------|
| Flash point | : 96 °C (205 °F)
Method: ASTM D 56 |
| Lower explosion limit | : No data available |

Orfom® SX-AP (Solvent Extraction Diluent)

Version 1.0

Revision Date 2014-04-17

Upper explosion limit	: No data available
Molecular weight	: Not applicable
pH	: Not applicable
pour point	: -42 °C (-44 °F)
Melting point/range	No data available
Boiling point/boiling range	: 200 - 320 °C (392 - 608 °F) Method: ASTM D 86
Vapor pressure	: 0.01 PSI at 38 °C (100 °F) Method: Reid
Density	: 0.820 G/ML at 15 °C (59 °F) Method: ASTMD 4052
Water solubility	: Negligible
Solubility in other solvents	: Medium: Hydrocarbons Soluble
Viscosity, kinematic	: 3.18 cSt at 25 °C (77 °F)

SECTION 10: Stability and reactivity

Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
--------------------	--

Possibility of hazardous reactions

Conditions to avoid	: No data available.
Other data	: No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Acute oral toxicity**

Distillates (petroleum), catalytic dewaxed middle	: LD50: > 5,000 mg/kg Species: rat Information given is based on data obtained from similar substances.
--	---

Orfom® SX-AP (Solvent Extraction Diluent)

Version 1.0

Revision Date 2014-04-17

Acute inhalation toxicity

Distillates (petroleum),
catalytic dewaxed middle : LC50: > 5 mg/l
Species: rat
Information given is based on data obtained from similar substances.

Acute dermal toxicity

Distillates (petroleum),
catalytic dewaxed middle : LD50: > 2,000 mg/kg
Information given is based on data obtained from similar substances.

Skin irritation

Distillates (petroleum),
catalytic dewaxed middle : No skin irritation
Information given is based on data obtained from similar substances.

Eye irritation

Distillates (petroleum),
catalytic dewaxed middle : No eye irritation
Information given is based on data obtained from similar substances.

Sensitization

Distillates (petroleum),
catalytic dewaxed middle : Did not cause sensitization on laboratory animals.
Information given is based on data obtained from similar substances.

Repeated dose toxicity

Distillates (petroleum),
catalytic dewaxed middle : No adverse effects expected
Information given is based on data obtained from similar substances.

Reproductive toxicity

Distillates (petroleum),
catalytic dewaxed middle : Species: rat
Application Route: oral gavage
Method: OECD Guideline 421
NOAEL Parent: 1,000 mg/kg
No adverse effects expected
Information given is based on data obtained from similar substances.

Developmental Toxicity

Distillates (petroleum),
catalytic dewaxed middle : This information is not available.

Aspiration toxicity

Distillates (petroleum),
catalytic dewaxed middle : May be fatal if swallowed and enters airways.

Orfom® SX-AP (Solvent Extraction Diluent)

Further information : Solvents may degrease the skin.

Orfom® SX-AP (Solvent Extraction Diluent)

Version 1.0

Revision Date 2014-04-17

SECTION 12: Ecological information**Toxicity to fish**

Distillates (petroleum),
catalytic dewaxed middle : LL50: > 10,000 mg/l
Exposure time: 96 h
Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates

Distillates (petroleum),
catalytic dewaxed middle : EL50: > 100 mg/l
Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

Distillates (petroleum),
catalytic dewaxed middle : NOEL: 10 mg/l
Species: Daphnia magna (Water flea)
Information given is based on data obtained from similar substances.

Bioaccumulation

Distillates (petroleum),
catalytic dewaxed middle : Accumulation in aquatic organisms is expected.

Biodegradability

Distillates (petroleum),
catalytic dewaxed middle : Expected to be inherently biodegradable.
Information given is based on data obtained from similar substances.

Additional ecological
information : This material is not expected to be harmful to aquatic organisms.

SECTION 13: Disposal considerations

The information in this MSDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

Orfom® SX-AP (Solvent Extraction Diluent)

Version 1.0

Revision Date 2014-04-17

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the MSDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**National legislation**

CERCLA Reportable Quantity : This material does not contain any components with a CERCLA RQ.

Orfom® SX-AP (Solvent Extraction Diluent)

Version 1.0

Revision Date 2014-04-17

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Ingredients : SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

US State Regulations

Pennsylvania Right To Know : No components are subject to the Pennsylvania Right to Know Act.

New Jersey Right To Know : No components are subject to the New Jersey Right to Know Act.

Orfom® SX-AP (Solvent Extraction Diluent)

Version 1.0

Revision Date 2014-04-17


California Prop. 65 Ingredients : This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

Notification status

Europe REACH : Not in compliance with the inventory
 United States of America TSCA : On TSCA Inventory
 Canada DSL : All components of this product are on the Canadian DSL.
 Australia AICS : On the inventory, or in compliance with the inventory
 New Zealand NZIoC : Not in compliance with the inventory
 Japan ENCS : Not in compliance with the inventory
 Korea KECI : On the inventory, or in compliance with the inventory
 Philippines PICCS : Not in compliance with the inventory
 China IECSC : On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 0
 Fire Hazard: 1
 Reactivity Hazard: 0

**Further information**

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this MSDS pertains only to the product as shipped.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect

Orfom® SX-AP (Solvent Extraction Diluent)

Version 1.0

Revision Date 2014-04-17

			Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		