



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Material name	KEROSENE
Version #	05
Issue date	23-October-2010
Revision date	03-September-2014
Supersedes date	16-December-2013
MSDS Number	105
Product use	Refinery feedstock.
Synonym(s)	K-1 Kerosene, K-2 Kerosene, Paraffinic Kerosene, Petroleum Distillate-Kerosene, Low- Sulfur Kerosene, Ultra Low Sulfur Kerosene, ULSK See section 16 for complete information.
Manufacturer/Supplier	Valero Marketing & Supply Company and Affiliates P.O. Box 696000 San Antonio, TX 78269-6000
General Assistance	210-345-4593
Emergency	24 Hour Emergency 866-565-5220 1-800-424-9300 (CHEMTREC USA)

2. Hazards Identification

Physical state	Liquid.
Appearance	Liquid (may be dyed red).
Emergency overview	DANGER! Combustible liquid and vapor. Will be easily ignited by heat, spark or flames. Heat may cause the containers to explode. Harmful if inhaled, absorbed through skin, or swallowed. Aspiration may cause lung damage. Irritating to eyes, respiratory system and skin. In high concentrations, vapors and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Exhaust Fumes have been reported to be an occupational hazard due to NIOSH-reported potential carcinogenic properties. Contains benzene. Cancer hazard. Mutagen. May cause heritable genetic damage. May cause adverse reproductive effects - such as birth defects, miscarriages, or infertility. Prolonged exposure may cause chronic effects. Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Static accumulating flammable materials can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite material and vapor may cause flash fire (or explosion).
OSHA regulatory status	This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).
Potential health effects	
Routes of exposure	Inhalation. Ingestion. Skin contact. Eye contact.
Eyes	Contact may irritate or burn eyes. Eye contact may result in corneal injury.
Skin	Harmful if absorbed through skin. Irritating to skin. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. High pressure skin injections are SERIOUS MEDICAL EMERGENCIES . Injuries may not appear serious at first. Within a few hours, tissues will become swollen, discolored and extremely painful.
Inhalation	Harmful if inhaled. Irritating to respiratory system. In high concentrations, vapors and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. May cause breathing disorders and lung damage. May cause cancer by inhalation. Prolonged inhalation may be harmful.
Ingestion	Harmful if swallowed. Ingestion may result in vomiting; aspiration (breathing) of vomitus into lungs must be avoided as even small quantities may result in aspiration pneumonitis. Irritating to mouth, throat, and stomach.
Target organs	Blood. Eyes. Liver. Respiratory system. Skin. Kidneys. Central nervous system.

Chronic effects	Cancer hazard. Contains material which may have reproductive toxicity, teratogenetic or mutagenic effects. Liver injury may occur. Kidney injury may occur. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Signs and symptoms	Irritation of nose and throat. Irritation of eyes and mucous membranes. Skin irritation. Unconsciousness. Corneal damage. Narcosis. Cyanosis (blue tissue condition, nails, lips, and/or skin). Decrease in motor functions. Behavioral changes. Edema. Liver enlargement. Jaundice. Conjunctivitis. Proteinuria. Defatting of the skin. Rash.
Potential environmental effects	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Kerosene	8008-20-6	0 - 100
Distillates, petroleum residues vacuum	68955-27-1	0 - 100
Naphthalene	91-20-3	0 - 3
Xylene (o, m, p isomers)	1330-20-7	0 - 2
Ethylbenzene	100-41-4	0 - 1
Toluene	108-88-3	0 - 1
Cyclohexane	110-82-7	0 - 1
Benzene	71-43-2	0 - 0.5
Hydrogen sulfide	7783-06-4	< 0.1

Composition comments	Small amount of hydrogen sulfide, a highly toxic gas, may be present, especially in the headspace of containers.
-----------------------------	--

4. First Aid Measures

First aid procedures

Inhalation	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention if discomfort develops or persists.
Skin contact	Remove contaminated clothing and shoes. Wash off immediately with soap and plenty of water. Get medical attention if irritation develops or persists. Wash clothing separately before reuse. Destroy or thoroughly clean contaminated shoes.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
Ingestion	Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Get medical attention immediately.

Notes to physician	In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
---------------------------	--

General advice	If exposed or concerned: get medical attention/advice. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use.
-----------------------	--

5. Fire Fighting Measures

Flammable properties	Combustible by OSHA criteria. Containers may explode when heated.
-----------------------------	---

Extinguishing media

Suitable extinguishing media	Water. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.

Protection of firefighters

Specific hazards arising from the chemical	Vapor may cause flash fire. Vapors can flow along surfaces to distant ignition source and flash back. Sensitive to static discharge.
Protective equipment and precautions for firefighters	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

**Fire fighting
equipment/instructions**

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do it without risk. In the event of fire, cool tanks with water spray. Cool containers exposed to flames with water until well after the fire is out. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Vapors may form explosive air mixtures even at room temperature. Prevent buildup of vapors or gases to explosive concentrations. Some of these materials, if spilled, may evaporate leaving a flammable residue. Water runoff can cause environmental damage. Use compatible foam to minimize vapor generation as needed.

Specific methods

In the event of fire and/or explosion do not breathe fumes. Use water spray to cool unopened containers.

**Hazardous combustion
products**

Carbon monoxide. Carbon dioxide. Sulfur oxides. Nitrogen oxides (NOx). Hydrocarbons.

6. Accidental Release Measures

Personal precautions

Keep unnecessary personnel away. Local authorities should be advised if significant spills cannot be contained. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. See Section 8 of the MSDS for Personal Protective Equipment.

Environmental precautions

If facility or operation has an "oil or hazardous substance contingency plan", activate its procedures. Stay upwind and away from spill. Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not enter or stay in area unless monitoring indicates that it is safe to do so. Isolate hazard area and restrict entry to emergency crew. Flammable. Review Firefighting Measures, Section 5, before proceeding with clean up. Keep all sources of ignition (flames, smoking, flares, etc.) and hot surfaces away from release. Contain spill in smallest possible area. Recover as much product as possible (e.g. by vacuuming). Stop leak if it can be done without risk. Use water spray to disperse vapors. Use compatible foam to minimize vapor generation as needed. Spilled material may be absorbed by an appropriate absorbent, and then handled in accordance with environmental regulations. Prevent spilled material from entering sewers, storm drains, other unauthorized treatment or drainage systems and natural waterways. Contact fire authorities and appropriate federal, state and local agencies. If spill of any amount is made into or upon navigable waters, the contiguous zone, or adjoining shorelines, contact the National Response Center at 1-800-424-8802. For highway or railways spills, contact Chemtrec at 1-800-424-9300.

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up

Small Spills: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination. This material and its container must be disposed of as hazardous waste.

Large Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Do not allow material to contaminate ground water system. Should not be released into the environment.

Other information

Clean up in accordance with all applicable regulations.

7. Handling and Storage

Handling

Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity.

Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid prolonged exposure. Use only with adequate ventilation. Wash thoroughly after handling. The product is flammable, and heating may generate vapors which may form explosive vapor/air mixtures. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. When using, do not eat, drink or smoke. Avoid release to the environment.

Storage

Flammable liquid storage. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. The pressure in sealed containers can increase under the influence of heat. Keep container tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedings. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Benzene (CAS 71-43-2)	STEL	2.5 ppm	Non-aerosol.
	TWA	0.5 ppm	
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Hydrogen sulfide (CAS 7783-06-4)	STEL	5 ppm	
	TWA	1 ppm	
Kerosene (CAS 8008-20-6)	TWA	200 mg/m3	
Naphthalene (CAS 91-20-3)	TWA	10 ppm	
Toluene (CAS 108-88-3)	TWA	20 ppm	
Xylene (o, m, p isomers) (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
Benzene (CAS 71-43-2)	STEL	5 ppm
	TWA	1 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3
		300 ppm
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3
		100 ppm
Naphthalene (CAS 91-20-3)	PEL	50 mg/m3
		10 ppm
Xylene (o, m, p isomers) (CAS 1330-20-7)	PEL	435 mg/m3
		100 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Benzene (CAS 71-43-2)	Ceiling	25 ppm
	TWA	10 ppm
Hydrogen sulfide (CAS 7783-06-4)	Ceiling	20 ppm
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Benzene (CAS 71-43-2)	STEL	8 mg/m3	
		2.5 ppm	
	TWA	1.6 mg/m3	
		0.5 ppm	
Cyclohexane (CAS 110-82-7)	TWA	344 mg/m3	
		100 ppm	
Ethylbenzene (CAS 100-41-4)	STEL	543 mg/m3	
		125 ppm	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Hydrogen sulfide (CAS 7783-06-4)	TWA	434 mg/m3	Vapor.
		100 ppm	
	Ceiling	21 mg/m3	
Kerosene (CAS 8008-20-6)		15 ppm	
	TWA	14 mg/m3	
		10 ppm	
Naphthalene (CAS 91-20-3)	TWA	200 mg/m3	
	STEL	79 mg/m3	
		15 ppm	
Toluene (CAS 108-88-3)	TWA	52 mg/m3	
		10 ppm	
		188 mg/m3	
Xylene (o, m, p isomers) (CAS 1330-20-7)		50 ppm	
	STEL	651 mg/m3	
		150 ppm	
	TWA	434 mg/m3	
		100 ppm	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Benzene (CAS 71-43-2)	STEL	2.5 ppm	Non-aerosol.
	TWA	0.5 ppm	
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Hydrogen sulfide (CAS 7783-06-4)	Ceiling	10 ppm	
Kerosene (CAS 8008-20-6)	TWA	200 mg/m3	
Naphthalene (CAS 91-20-3)	STEL	15 ppm	
	TWA	10 ppm	
Toluene (CAS 108-88-3)	TWA	20 ppm	
Xylene (o, m, p isomers) (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Benzene (CAS 71-43-2)	STEL	2.5 ppm	Non-aerosol.
	TWA	0.5 ppm	
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Hydrogen sulfide (CAS 7783-06-4)	STEL	5 ppm	
	TWA	1 ppm	
Kerosene (CAS 8008-20-6)	TWA	200 mg/m3	
Naphthalene (CAS 91-20-3)	STEL	15 ppm	
	TWA	10 ppm	
Toluene (CAS 108-88-3)	TWA	20 ppm	
Xylene (o, m, p isomers) (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
Benzene (CAS 71-43-2)	STEL	2.5 ppm	Non-aerosol.
	TWA	0.5 ppm	
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
	STEL	125 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	100 ppm	
	STEL	15 ppm	
Hydrogen sulfide (CAS 7783-06-4)	TWA	10 ppm	
	TWA	200 mg/m3	
Kerosene (CAS 8008-20-6)	STEL	15 ppm	
	TWA	10 ppm	
Naphthalene (CAS 91-20-3)	TWA	20 ppm	
	STEL	150 ppm	
Toluene (CAS 108-88-3)	TWA	100 ppm	
Xylene (o, m, p isomers) (CAS 1330-20-7)			

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
Benzene (CAS 71-43-2)	STEL	15.5 mg/m3
		5 ppm
	TWA	3 mg/m3
		1 ppm
Cyclohexane (CAS 110-82-7)	TWA	1030 mg/m3
		300 ppm
Ethylbenzene (CAS 100-41-4)	STEL	543 mg/m3
		125 ppm
	TWA	434 mg/m3
		100 ppm
Hydrogen sulfide (CAS 7783-06-4)	STEL	21 mg/m3
		15 ppm
	TWA	14 mg/m3
		10 ppm
Naphthalene (CAS 91-20-3)	STEL	79 mg/m3
		15 ppm
	TWA	52 mg/m3
		10 ppm
Toluene (CAS 108-88-3)	TWA	188 mg/m3
		50 ppm
Xylene (o, m, p isomers) (CAS 1330-20-7)	STEL	651 mg/m3
		150 ppm
	TWA	434 mg/m3
		100 ppm

Mexico. Occupational Exposure Limit Values

Components	Type	Value
Benzene (CAS 71-43-2)	STEL	16 mg/m3
		5 ppm
	TWA	3.2 mg/m3
		1 ppm
Cyclohexane (CAS 110-82-7)	STEL	1300 mg/m3
		375 ppm
	TWA	1050 mg/m3

Mexico. Occupational Exposure Limit Values

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	300 ppm
		545 mg/m3
	TWA	125 ppm
		435 mg/m3
Hydrogen sulfide (CAS 7783-06-4)	STEL	100 ppm
		21 mg/m3
	TWA	15 ppm
		14 mg/m3
Naphthalene (CAS 91-20-3)	STEL	10 ppm
		75 mg/m3
	TWA	15 ppm
		50 mg/m3
Toluene (CAS 108-88-3)	TWA	10 ppm
		188 mg/m3
Xylene (o, m, p isomers) (CAS 1330-20-7)	STEL	50 ppm
		655 mg/m3
	TWA	150 ppm
		435 mg/m3
		100 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Benzene (CAS 71-43-2)	25 µg/g	S-Phenylmercapturic acid	Creatinine in urine	*
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (o, m, p isomers) (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

Canada - Alberta OELs: Skin designation

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Kerosene (CAS 8008-20-6)	Can be absorbed through the skin.
Naphthalene (CAS 91-20-3)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Kerosene (CAS 8008-20-6)	Can be absorbed through the skin.
Naphthalene (CAS 91-20-3)	Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Kerosene (CAS 8008-20-6)	Can be absorbed through the skin.
Naphthalene (CAS 91-20-3)	Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Kerosene (CAS 8008-20-6)	Can be absorbed through the skin.
Naphthalene (CAS 91-20-3)	Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Kerosene (CAS 8008-20-6)

Can be absorbed through the skin.

Naphthalene (CAS 91-20-3)

Can be absorbed through the skin.

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

Mexico OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

US - California OELs: Skin designation

Benzene (CAS 71-43-2)

Can be absorbed through the skin.

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Benzene (CAS 71-43-2)

Can be absorbed through the skin.

Kerosene (CAS 8008-20-6)

Can be absorbed through the skin.

Naphthalene (CAS 91-20-3)

Can be absorbed through the skin.

Engineering controls

Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment.

Personal protective equipment**Eye / face protection**

Wear safety glasses. If splash potential exists, wear full face shield or chemical goggles.

Skin protection

Wear chemical-resistant, impervious gloves. Full body suit and boots are recommended when handling large volumes or in emergency situations. Flame retardant protective clothing is recommended.

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workplace exposure limits for product or components are exceeded, NIOSH approved equipment should be worn. Proper respirator selection should be determined by adequately trained personnel, based on the contaminants, the degree of potential exposure and published respiratory protection factors. This equipment should be available for nonroutine and emergency use.

Hand protection

Avoid exposure - obtain special instructions before use. Wear protective gloves.

General hygiene considerations

Avoid contact with skin. Keep away from food and drink. Provide eyewash station and safety shower. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties**Appearance**

Liquid (may be dyed red).

Physical state

Liquid.

Form

Liquid.

Color

Clear. Straw. Yellow or brown.

Odor

Kerosene (strong).

Odor threshold

Not available.

pH

Not available.

Vapor pressure

< 0.7 kPa at 20 deg C

Vapor density

3 (Air = 1)

Boiling point

219.92 - 579.92 °F (104.4 - 304.4 °C)

Melting point/Freezing point

-60.07 °F (-51.15 °C) Estimated

Solubility (water)

Not available.

Specific gravity

0.79 - 0.9 at 60 deg F

Flash point

> 100.0 °F (> 37.8 °C) Closed Cup

Flammability limits in air, upper, % by volume

6 %

Flammability limits in air, lower, % by volume

0.7 %

Auto-ignition temperature

399.92 °F (204.4 °C)

VOC

Negligible

Other data**Flash point class**

Flammable IB

10. Chemical Stability & Reactivity Information**Chemical stability**

Stable under normal temperature conditions and recommended use.

Conditions to avoid

Heat, flames and sparks. Ignition sources. Contact with incompatible materials. Do not pressurize, cut, weld, braze, solder, drill, grind or expose empty containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

Trace amounts of: Hydrogen sulfide.

Possibility of hazardous reactions

Hazardous polymerization does not occur.

11. Toxicological Information**Toxicological data**

Components	Species	Test Results
Benzene (CAS 71-43-2)		
Acute		
<i>Dermal</i>		
LD50	Guinea pig; Rabbit	> 9.4 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Mouse	9980 ppm
		9980 ppm, 7 Hours
	Rat	43767 mg/m3, 4 Hours
		13700 ppm, 4 Hours
		10000 ppm, 7 Hours
<i>Oral</i>		
LD50	Rat	5970 mg/kg
		930 mg/kg
Cyclohexane (CAS 110-82-7)		
Acute		
<i>Oral</i>		
LD50	Rat	12705 mg/kg
Distillates, petroleum residues vacuum (CAS 68955-27-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 320 mg/m3, 4 Hours
<i>Oral</i>		
LD50	Rat	4320 mg/kg
Ethylbenzene (CAS 100-41-4)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg
		17.8 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Mouse	> 8000 ppm, 20 Minutes
	Rat	4000 ppm
<i>Oral</i>		
LD50	Rat	5.46 g/kg

Components	Species	Test Results
<i>Other</i>		
LD50	Mouse	17.81 mm/kg
Hydrogen sulfide (CAS 7783-06-4)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 0.38 mg/l, 960 Minutes
Kerosene (CAS 8008-20-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 4.3 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Naphthalene (CAS 91-20-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2 g/kg
<i>Oral</i>		
LD50	Rat	490 mg/kg
Toluene (CAS 108-88-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Mouse	6405 - 7436 ppm, 6 Hours 5320 ppm, 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours 8000 mg/l, 4 Hours 5879 - 6281 ppm, 6 Hours 25.7 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	5580 mg/kg 2.6 g/kg
Xylene (o, m, p isomers) (CAS 1330-20-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	12126 mg/kg, 24 Hours > 5000 ml/kg, 4 Hours
<i>Inhalation</i>		
LC50	Mouse	5300 ppm, 6 Hours
	Rat	5922 ppm, 4 Hours
<i>Oral</i>		
LD50	Mouse	5251 mg/kg

KEROSENE

3524 Version #: 05 Revision date: 03-September-2014 Print date: 03-September-2014

Prepared by 3E Company

Components	Species	Test Results
	Rat	3523 mg/kg 10 ml/kg
Sensitization	This substance may have a potential for sensitization which may provoke an allergic reaction among sensitive individuals.	
Acute effects	Harmful if inhaled, absorbed through skin, or swallowed. Harmful: may cause lung damage if swallowed. Irritating to eyes, respiratory system and skin. In high concentrations, vapors and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea.	
Chronic effects	Prolonged and repeated exposure to benzene may cause serious injury to blood forming organs and is associated with anemia and to the later development of acute myelogenous leukemia (AML). Toluene has been reported to decrease immunological responses and cause recordable hearing loss in laboratory animals. Repeated exposure to naphthalene may cause cataracts, allergic skin rashes, destruction of red blood cells, and anemia, jaundice, kidney and liver damage. Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication. Danger of serious damage to health by prolonged exposure. Prolonged or repeated overexposure may cause central nervous system, kidney, liver, and lung damage.	
Subchronic effects	Subchronic inhalation of benzene by rats produced decreased white blood cell counts, decreased bone marrow cell activity, increased red blood cell activity and cataracts. Blood disorders may occur after prolonged inhalation, prolonged skin contact and/or ingestion. Liver and kidney damage may occur after prolonged and repeated exposure.	
Carcinogenicity		
ACGIH Carcinogens		
Benzene (CAS 71-43-2)	A1 Confirmed human carcinogen.	
Ethylbenzene (CAS 100-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
Kerosene (CAS 8008-20-6)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
Naphthalene (CAS 91-20-3)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
Toluene (CAS 108-88-3)	A4 Not classifiable as a human carcinogen.	
Xylene (o, m, p isomers) (CAS 1330-20-7)	A4 Not classifiable as a human carcinogen.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Benzene (CAS 71-43-2)	1 Carcinogenic to humans.	
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.	
Naphthalene (CAS 91-20-3)	2B Possibly carcinogenic to humans.	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.	
Xylene (o, m, p isomers) (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Benzene (CAS 71-43-2)	Cancer	
US NTP Report on Carcinogens: Anticipated carcinogen		
Naphthalene (CAS 91-20-3)	Reasonably Anticipated to be a Human Carcinogen.	
US NTP Report on Carcinogens: Known carcinogen		
Benzene (CAS 71-43-2)	Known To Be Human Carcinogen.	
Epidemiology	Contains benzene. Human epidemiology studies indicate that prolonged and/or repeated overexposure to benzene may cause damage to the blood-producing system and serious blood disorders, including leukemia. Animal tests suggest that prolonged and/or repeated overexposure to benzene may damage the embryo/fetus. The relevance of these animal studies to humans has not been fully established.	
Mutagenicity	Some middle distillate fuels have caused chromosome damage in the in-vivo rat bone marrow cytogenetics assay and caused mutagenic effects in the L5178Y mouse lymphoma assay. In in-vitro experiments, neither benzene, toluene nor xylene changed the number of sister-chromatid exchanges (SCEs) or the number of chromosomal aberrations in human lymphocytes. However, toluene and xylene caused a significant cell growth inhibition which was not observed with benzene in the same concentrations. In in-vivo experiments, toluene changed the number of sister-chromatid exchanges (SCEs) in human lymphocytes. Toluene may cause heritable genetic damage.	
Neurological effects	Central and/or peripheral nervous system damage. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue) and/or damage.	

Reproductive effects	Benzene, xylene and toluene have demonstrated animal effects of reproductive toxicity. Animal studies of benzene have shown testicular effects, alterations in reproductive cycles, chromosomal aberrations and embryo/fetotoxicity. Napthalene interferes with embryo development in experimental animals at dose levels that cause maternal toxicity. In humans, excessive exposure to this agent may cause hemolytic anemia in the mother and fetus. May damage fertility or the unborn child. Can cause adverse reproductive effects - such as birth defects, miscarriages, or infertility. Avoid exposure to women during early pregnancy. Avoid contact during pregnancy/while nursing.
Teratogenicity	Abusive inhalation of toluene ("glue sniffing") has been reported to be associated with birth defects in the offspring of abusers. Rats exposed to benzene and xylene vapor during pregnancy showed embryo/fetotoxic effects.
Further information	Symptoms may be delayed.

12. Ecological Information

Ecotoxicological data

Components			Species	Test Results
Benzene (CAS 71-43-2)				
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	8.76 - 15.6 mg/l, 48 Hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	5.3 mg/l, 96 hours	
Cyclohexane (CAS 110-82-7)				
Aquatic				
Fish	LC50	Fathead minnow (Pimephales promelas)	3.961 - 5.181 mg/l, 96 hours	
Ethylbenzene (CAS 100-41-4)				
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	1 - 4 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4 mg/l, 96 hours	
Hydrogen sulfide (CAS 7783-06-4)				
Aquatic				
Fish	LC50	Lake whitefish (Coregonus clupeaformis)	0.002 mg/l, 96 hours	
Naphthalene (CAS 91-20-3)				
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	1.09 - 3.4 mg/l, 48 hours	
Fish	LC50	Pink salmon (Oncorhynchus gorbuscha)	0.95 - 1.62 mg/l, 96 hours	
Toluene (CAS 108-88-3)				
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	5.8 mg/l, 96 hours	
Xylene (o, m, p isomers) (CAS 1330-20-7)				
Aquatic				
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8 mg/l, 96 Hours	

Ecotoxicity	Contains a substance which causes risk of hazardous effects to the environment.
Environmental effects	The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
Aquatic toxicity	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.
Persistence and degradability	Not available.
Bioaccumulation / accumulation	

Bioaccumulative potential

Octanol/water partition coefficient log Kow

Benzene (CAS 71-43-2)	2.13
Cyclohexane (CAS 110-82-7)	3.44

Bioaccumulative potential**Octanol/water partition coefficient log Kow**

Ethylbenzene (CAS 100-41-4)	3.15
Toluene (CAS 108-88-3)	2.73
Xylene (o, m, p isomers) (CAS 1330-20-7)	3.2

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 °F
D018: Waste Benzene

US RCRA Hazardous Waste U List: Reference

Benzene (CAS 71-43-2)	U019
Cyclohexane (CAS 110-82-7)	U056
Hydrogen sulfide (CAS 7783-06-4)	U135
Naphthalene (CAS 91-20-3)	U165
Toluene (CAS 108-88-3)	U220
Xylene (o, m, p isomers) (CAS 1330-20-7)	U239

Disposal instructions Dispose in accordance with all applicable regulations. Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container.

14. Transport Information**DOT****Basic shipping requirements:**

UN number UN1223
Proper shipping name Kerosene
Hazard class - Combustible Liquid
Labels required 3
Packing group III
Environmental hazards

Marine pollutant Yes

Additional information:

Special provisions 144, B1, IB3, T2, TP2
Packaging exceptions 150
Packaging non bulk 203
Packaging bulk 242

IATA

UN number UN1223
UN proper shipping name Kerosene
Transport hazard class(es) 3
Packing group III
Environmental hazards Yes
ERG code 3L

IMDG

UN number UN1223
UN proper shipping name KEROSENE
Transport hazard class(es) 3
Packing group III
Environmental hazards
Marine pollutant Yes
EmS F-E, S-E

TDG

UN number UN1223
Proper shipping name KEROSENE
Hazard class 3
Packing group III
Marine pollutant Yes

15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Benzene (CAS 71-43-2)

Ethylbenzene (CAS 100-41-4)

Naphthalene (CAS 91-20-3)

Toluene (CAS 108-88-3)

Xylene (o, m, p isomers) (CAS 1330-20-7)

US EPCRA (SARA Title III) Section 302 - Extremely Hazardous Spill: Reportable quantity

Hydrogen sulfide (CAS 7783-06-4) 100 LBS

US EPCRA (SARA Title III) Section 302 - Extremely Hazardous Substance: Threshold Planning Quantity

Hydrogen sulfide (CAS 7783-06-4) 500 LBS

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Benzene (CAS 71-43-2) 0.1 %

Cyclohexane (CAS 110-82-7) 1.0 %

Ethylbenzene (CAS 100-41-4) 0.1 %

Hydrogen sulfide (CAS 7783-06-4) 1.0 %

Naphthalene (CAS 91-20-3) 0.1 %

Toluene (CAS 108-88-3) 1.0 %

Xylene (o, m, p isomers) (CAS 1330-20-7) 1.0 %

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Benzene (CAS 71-43-2) Listed.

Cyclohexane (CAS 110-82-7) Listed.

Ethylbenzene (CAS 100-41-4) Listed.

Hydrogen sulfide (CAS 7783-06-4) Listed.

Naphthalene (CAS 91-20-3) Listed.

Toluene (CAS 108-88-3) Listed.

Xylene (o, m, p isomers) (CAS 1330-20-7) Listed.

CERCLA (Superfund) reportable quantity (lbs) (40 CFR 302.4)

Naphthalene: 100

Xylene (o, m, p isomers): 100

Ethylbenzene: 1000

Toluene: 1000

Cyclohexane: 1000

Benzene: 10

Hydrogen sulfide: 100

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes

Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - No

Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
Hydrogen sulfide	7783-06-4	100	500 lbs		

SARA 311/312 Hazardous chemical No

Drug Enforcement Administration (DEA) (21 CFR 1308.11-15)

Not controlled

Canadian regulations

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS status

Controlled

WHMIS classification

B3 - Combustible Liquids
 D2A - Other Toxic Effects-VERY TOXIC
 D2B - Other Toxic Effects-TOXIC

WHMIS labeling**Inventory status**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

State regulations

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Hazardous Substances (Director's): Listed substance

Benzene (CAS 71-43-2)	Listed.
Cyclohexane (CAS 110-82-7)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Hydrogen sulfide (CAS 7783-06-4)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (o, m, p isomers) (CAS 1330-20-7)	Listed.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Benzene (CAS 71-43-2)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Toluene (CAS 108-88-3)	Listed.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2)	Listed: February 27, 1987 Carcinogenic.
Ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004 Carcinogenic.
Naphthalene (CAS 91-20-3)	Listed: April 19, 2002 Carcinogenic.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2)	Listed: December 26, 1997 Developmental toxin.
Toluene (CAS 108-88-3)	Listed: January 1, 1991 Developmental toxin.

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3)	Listed: August 7, 2009 Female reproductive toxin.
------------------------	---

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2)	Listed: December 26, 1997 Male reproductive toxin.
-----------------------	--

US. Massachusetts RTK - Substance List

Benzene (CAS 71-43-2)	Listed.
Cyclohexane (CAS 110-82-7)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Hydrogen sulfide (CAS 7783-06-4)	Listed.
Kerosene (CAS 8008-20-6)	Listed.
Naphthalene (CAS 91-20-3)	Listed.

Toluene (CAS 108-88-3) Listed.
Xylene (o, m, p isomers) (CAS 1330-20-7) Listed.

US. New Jersey Worker and Community Right-to-Know Act

Benzene (CAS 71-43-2)
Cyclohexane (CAS 110-82-7)
Ethylbenzene (CAS 100-41-4)
Hydrogen sulfide (CAS 7783-06-4)
Kerosene (CAS 8008-20-6)
Naphthalene (CAS 91-20-3)
Toluene (CAS 108-88-3)
Xylene (o, m, p isomers) (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Benzene (CAS 71-43-2)
Cyclohexane (CAS 110-82-7)
Ethylbenzene (CAS 100-41-4)
Hydrogen sulfide (CAS 7783-06-4)
Kerosene (CAS 8008-20-6)
Naphthalene (CAS 91-20-3)
Toluene (CAS 108-88-3)
Xylene (o, m, p isomers) (CAS 1330-20-7)

16. Other Information

Further information

HMIS® is a registered trade and service mark of the NPCA.

Other information

Note: This material Safety Data Sheet applies to the listed products and synonym descriptions for Hazard Communication purposes only. Technical Specifications vary greatly depending on the products and are not reflected in this document. Consult specification sheets for technical information.

HMIS® ratings

Health: 2*
Flammability: 2
Physical hazard: 0

NFPA ratings



Disclaimer

This Material Safety Data Sheet (MSDS) was prepared in accordance with 29 CFR 1910.1200 by Valero Marketing & Supply Co., ("VALERO"). VALERO does not assume any liability arising out of product use by others. The information, recommendations, and suggestions presented in this MSDS are based upon test results and data believed to be reliable. The end user of the product has the responsibility for evaluating the adequacy of the data under the conditions of use, determining the safety, toxicity and suitability of the product under these conditions, and obtaining additional or clarifying information where uncertainty exists. No guarantee expressed or implied is made as to the effects of such use, the results to be obtained, or the safety and toxicity of the product in any specific application. Furthermore, the information herein is not represented as absolutely complete, since it is not practicable to provide all the scientific and study information in the format of this document, plus additional information may be necessary under exceptional conditions of use, or because of applicable laws or government regulations.

Prepared by

Not available.