# **SAFETY DATA SHEET**

NAME OF PRODUCT: SOFTONE™ Liquid **SDS DATE:** 06/19/2014

#### **SECTION 1: IDENTIFICATION**

PRODUCT NAME: **SOFTONE Liquid** 

PRODUCT CODES: 0921775, 0921777, 0921778, 0921780

**IDENTIFIED USES:** Dentistry **USES ADVISED AGAINST:** Non-dental use

MANUFACTURER: Harry J. Bosworth Company

ADDRESS: 7227 North Hamlin Avenue, Skokie, Illinois 60076-3999, USA

**TELEPHONE:** 847-679-3400 FAX: 847-679-2080 FMAII · hjbinfo@bosworth.com **EMERGENCY PHONE:** 

800-535-5053 (US and Canada) 352-323-3500 (International)

#### **SECTION 2: HAZARDS IDENTIFICATION**

CLASSIFICATION: Flammable liquids (Category 3)

Reproductive toxicity (Category 1B) Acute aquatic toxicity (Category 1) Chronic aquatic toxicity (Category 1)

LABELING: FDA regulated device - exempt from Regulation (US) 29 CFR 1910.1200.

PICTOGRAM:

SIGNAL WORD: Danger **HAZARD STATEMENTS:** 

H226 Flammable liquid and vapor. H360 May damage fertility or the unborn child.

H410 Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS: P201 Obtain special instructions before use.

P308+P313

Do not handle until all safety precautions have been read and understood. P202 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

FILE NO.: SDS777

P234 Keep only in original container. P235+P410 Keep cool. Protect from sunlight.

P240 Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment. P241

P242 Use only non-sparking tools.

Take precautionary measures against static discharge. P243 P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling. P264

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

Wear protective gloves/ protective clothing/ eye protection/ face protection. P280

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for P304+P340

breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/ attention.

P321 Specific treatment (see supplemental first aid instructions on this label).

P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P313 If experiencing respiratory symptoms: Get medical advice/attention.

P370+P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide

for extinction.


P391 Collect spillage. P402 Store in a dry place.

P403+P233 Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container to an approved waste disposal plant. P501

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

COMPONENT	CAS NO.	%WT	OSHA PEL - TWA	ACGIH TLV - TWA	CLASSIFICATION
Dibutyl	84-74-2	45-55	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	Repr. 1B; Aquatic Acute 1; Aquatic

PREPARED BY: SS PAGE 1 OF 4



# SAFETY DATA SHEET

NAME OF PRODUCT: SOFTONE™ Liquid

phthalate					Chronic 1; H360, H410
Diethyl	84-66-2	15-25	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	Aquatic Acute 3; H402
phthalate					
Ethanol	64-17-5	15-25	1000 ppm	1000 ppm	Flam. Liq. 2; H225

For full text of H-statements mentioned in this section, see section 16.

#### **SECTION 4: FIRST-AID MEASURES**

**INHALATION:** Move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

**SKIN:** Wash off with soap and plenty of water. Consult a physician.

**EYE:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**INGESTION:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water.

Consult a physician.

#### **SECTION 5: FIRE-FIGHTING MEASURES**

SUITABLE EXTINGUISHING MEDIA: Water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon.

**SPECIAL HAZARDS:** Vapors are heavier than air and may travel to ignition source.

ADVICE FOR FIREFIGHTERS: Fight fires from safe distance or protected areas. Cool containers of material exposed to heat with cold water

spray. Wear self contained breathing apparatus for firefighting if necessary.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

**PERSONAL PRECAUTIONS:** Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form

FILE NO.: SDS777

**SDS DATE:** 06/19/2014

explosive concentrations. Vapors can accumulate in low areas.

ENVIRONMENTAL PRECAUTIONS: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the

environment must be avoided.

CONTAINMENT AND CLEANUP: Soak up with inert absorbent material and collect with an electrically protected vacuum cleaner or by wet-

brushing. Place in suitable, closed container for disposal according to official regulations.

## **SECTION 7: HANDLING AND STORAGE**

PRECAUTIONS FOR SAFE HANDLING: Product is intended for dental use only. Handling of this product should be by trained dental healthcare

professionals only. Observe normal care for working with chemicals. Avoid contact with the eyes and skin. Avoid inhalation of vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. Keep away from foodstuffs, beverages and animal feed.

**CONDITIONS FOR SAFE STORAGE:** Store only in the original package. Keep container tightly sealed in a dry and well-ventilated place. Protect

from heat and direct sunlight. Store away from food and beverages.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**ENGINEERING CONTROLS:** Handle in accordance with good industrial hygiene and safety practice. Use with adequate general or local

exhaust ventilation to maintain exposure levels below the occupational exposure limits. Local exhaust ventilation is preferred since it prevents contamination dispersion into the work area by controlling it at its source. Provide eyewash and safety shower if contact or splash hazard exists. Wash hands before breaks and

at the end of work.

**EYE/FACE PROTECTION:** Safety glasses.

**SKIN PROTECTION:** Glove material impermeable and resistant to the product.

**BODY PROTECTION:** Protective work clothing.

RESPIRATORY PROTECTION: NIOSH (US) or CEN (EU) approved respirators and components.

ENVIRONMENTAL EXPOSURE: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the

environment must be avoided.

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE/COLOR: Clear, colorless liquid

ODOR: Characteristic
INITIAL BOILING POINT: 567°F (297°C)
FLASH POINT: 125°F (52°C)
UPPER FLAMMABILITY LIMIT: 19.0
LOWER FLAMMABILITY LIMIT: 3.3

PREPARED BY: SS PAGE 2 OF 4

NAME OF PRODUCT: SOFTONE™ Liquid

VAPOR PRESSURE: 44.6 mmHg

VAPOR DENSITY (AIR=1.0): 1.59

RELATIVE DENSITY (H2O=1.0): 1.01 g/cm³

WATER SOLUBILITY: Slightly soluble

#### **SECTION 10: STABILITY AND REACTIVITY**

**CHEMICAL STABILITY:** Stable under recommended storage conditions. **HAZARDOUS REACTIONS:** Vapors may form explosive reactions with air.

**CONDITIONS TO AVOID:** Heat, flames and sparks. Light. Extremes of temperature and direct sunlight. **INCOMPATIBLE MATERIALS:** Alkali metals, ammonia, peroxides, strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon.

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

POTENTIAL HEALTH EFFECTS: EYES: May cause eye irritation with redness, tearing and stinging.

SKIN: May cause skin irritation with redness, swelling and itching. Repeated or prolonged contact may cause

FILE NO.: SDS777

**SDS DATE:** 06/19/2014

drying, defatting of the skin and dermatitis.

**INGESTION:** May cause mucous membrane and gastrointestinal irritation with nausea, vomiting and diarrhea. May cause nervous system depression with symptoms of headache, dizziness, nausea, vomiting, weakness,

fatigue, confusion, and unconsciousness.

<u>INHALATION:</u> May cause mucous membrane and respiratory irritation and central nervous system depression with symptoms of headache, dizziness, drowsiness, nausea, vomiting, and unconsciousness. High vapor

concentrations may cause burning sensation of the nose and throat and watering of the eyes.

**CARCINOGENICITY:** OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or possible carcinogen by OSHA.

**<u>ACGIH:</u>** Ethanol is identified as a confirmed animal carcinogen with unknown relevance to humans by ACGIH.

NTP: Ethanol is identified as a known human carcinogen by NTP.

IARC: Ethanol is identified as a human carcinogen by IARC.

**REPRODUCTIVE TOXICITY:** Dibutyl phthalate and diethyl phthalate are presumed human reproductive toxicants. Overexposure may

cause reproductive disorders based on tests with laboratory animals.

#### **SECTION 12: ECOLOGICAL INFORMATION**

ADVERSE EFFECTS: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic

to aquatic life with long lasting effects. Avoid release to the environment.

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

PRODUCT: Contact a licensed professional waste disposal service to dispose of this material. Burn in a chemical

incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Disposal must be made

according to official regulations.

CONTAMINATED PACKAGING: Dispose of as unused product.

#### **SECTION 14: TRANSPORT INFORMATION**

UN NUMBER: UN1993

PROPER SHIPPING NAME: Flammable liquid, n.o.s. (contains Ethanol)

HAZARD CLASS: 3
PACKING GROUP: III

LABEL STATEMENT: Flammable Liquid

## **SECTION 15: REGULATORY INFORMATION**

#### **US FEDERAL REGULATIONS**

TSCA: This product is an FDA regulated device and not subject to TSCA regulations.

CERCLA: This product is an FDA regulated device and not subject to reporting requirements. There may be specific

reporting requirements at the local, regional, or state level.

SARA 313 TOXIC CHEMICALS: The following components are subject to reporting levels established by SARA Title III, Section 313 (40 CFR

372): Dibutyl Phthalate, CAS NO. 84-74-2.

PREPARED BY: SS PAGE 3 OF 4



# SAFETY DATA SHEET

NAME OF PRODUCT: SOFTONE™ Liquid SDS DATE: 06/19/2014

SARA 311/312 HAZARDS: This product is an FDA regulated device and not subject to reporting requirements.

**US STATE REGULATIONS** 

CALIFORNIA PROPOSITION 65: This product may contain a chemical known to the State of California to cause cancer and/or reproductive

FILE NO.: SDS777

toxicity

**INTERNATIONAL REGULATIONS** 

**CANADIAN ENVIRONMENTAL** 

**PROTECTION ACT:** This product is a medical device and not subject to chemical notification requirements.

EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES

(EINECS): This product is a medical device and not subject to chemical notification requirements.

#### **SECTION 16: OTHER INFORMATION**

#### **FULL TEXT OF H STATEMENTS REFERRED TO UNDER SECTION 3**

Aquatic Acute Acute aquatic toxicity
Aquatic Chronic Chronic aquatic toxicity
Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapor.
H360 May damage fertility or the unborn child.

H402 Harmful to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Repr. Reproductive toxicity

NFPA RATING

Health Hazard 2
Fire Hazard 2
Reactivity Hazard 0

**PREPARATION INFORMATION:** This SDS was prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200) and is to be used only for this product.

**DISCLAIMER:** To the best of our knowledge, the information contained herein is accurate. However, The Harry J. Bosworth Company does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

PREPARED BY: SS PAGE 4 OF 4

**SAFETY DATA SHEET** 

NAME OF PRODUCT: SOFTONE™ Powder WHITE SDS DATE: 06/19/2014

# **SECTION 1: IDENTIFICATION**

**PRODUCT NAME:** SOFTONE Powder WHITE

**PRODUCT CODES:** 0921775, 0921776, 0921778, 0921779

IDENTIFIED USES: Dentistry
USES ADVISED AGAINST: Non-dental use

MANUFACTURER: Harry J. Bosworth Company

ADDRESS: 7227 North Hamlin Avenue, Skokie, Illinois 60076-3999, USA

 TELEPHONE:
 847-679-3400

 FAX:
 847-679-2080

 EMAIL:
 hjbinfo@bosworth.com

 EMERGENCY PHONE:
 800-535-5053 (US and C.)

IERGENCY PHONE: 800-535-5053 (US and Canada) 352-323-3500 (International)

#### **SECTION 2: HAZARDS IDENTIFICATION**

**CLASSIFICATION:** Skin sensitization (Category 1)

Eye irritation (Category 2B)

Acute toxicity, Inhalation (Category 5)

Specific target organ toxicity - single exposure (Category 3), Respiratory system

LABELING: FDA regulated device - exempt from Regulation (US) 29 CFR 1910.1200.

PICTOGRAM:

SIGNAL WORD: Warning

PRECAUTIONARY STATEMENTS:

**HAZARD STATEMENTS:** H317 May cause an allergic skin reaction.

H320 Causes eye irritation.
H333 May be harmful if inhaled.
H335 May cause respiratory irritation.
P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P234 Keep only in original container. P235+P410 Keep cool. Protect from sunlight.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301+P330 IF SWALLOWED: Rinse mouth.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

FILE NO.: SDS776

breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see supplemental first aid instructions on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P313 If experiencing respiratory symptoms: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P391 Collect spillage.
P402 Store in a dry place.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container to an approved waste disposal plant.

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

COMPONENT	CAS NO.	%WT	OSHA PEL - TWA	ACGIH TLV - TWA	CLASSIFICATION
Poly(ethyl	9003-42-3	60-100	15 mg/m <sup>3</sup> (T); 5 mg/m <sup>3</sup> (R)	10 mg/m <sup>3</sup> (T); 3 mg/m <sup>3</sup> (R)	N/A
methacrylate)					
Benzoyl	94-36-0	0.5-2.0	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	Org. Perox. B; Eye Irrit. 2A; Skin Sens.
Peroxide					1; H241, H317, H319
Titanium	13463-67-7	0.1-1.0	15 mg/m <sup>3</sup> (T)	10 mg/m <sup>3</sup>	Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2A;
Dioxide					STOT SE 3; H315, H319, H332, H335

PREPARED BY: SS PAGE 1 OF 4

**NAME OF PRODUCT:** SOFTONE™ Powder WHITE For full text of H-statements mentioned in this section, see section 16.

**SECTION 4: FIRST-AID MEASURES** 

**INHALATION:** Move person into fresh air. If not breathing, give artificial respiration. If symptoms persist, get medical

attention.

**SKIN:** Wash off with soap and plenty of water. Get medical attention if irritation develops and persists.

**EYE:** Flush eyes with water for 15 minutes as a precaution. Get medical attention if irritation develops and persists. **INGESTION:** Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

**SECTION 5: FIRE-FIGHTING MEASURES** 

SUITABLE EXTINGUISHING MEDIA: Water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

HAZARDOUS DECOMPOSITION PRODUCTS: Methacrylate monomers and oxides of carbon.

SPECIAL HAZARDS: Polymer dust is combustible. The explosive limits of the polymer particles suspended in air are approximately

those of coal dust.

ADVICE FOR FIREFIGHTERS: Avoid extinguishing methods which may generate dust clouds. Water stream can disperse dust into air,

producing a fire hazard and possible explosion hazard if exposed to ignition source. Wear self contained

FILE NO.: SDS776

**SDS DATE:** 06/19/2014

breathing apparatus for firefighting if necessary.

**SECTION 6: ACCIDENTAL RELEASE MEASURES** 

PERSONAL PRECAUTIONS: Use personal protective equipment. Avoid dust formation. Avoid breathing vapors, mist or gas. Ensure

adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

CONTAINMENT AND CLEANUP: Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers

for disposal.

**SECTION 7: HANDLING AND STORAGE** 

**ENVIRONMENTAL PRECAUTIONS:** 

**PRECAUTIONS FOR SAFE HANDLING:** Product is intended for dental use only. Handling of this product should be by trained dental healthcare

professionals only. Observe normal care for working with chemicals. Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Avoid inhalation of dust. Provide appropriate exhaust ventilation at places

where dust is formed. Keep away from foodstuffs, beverages and animal feed.

**CONDITIONS FOR SAFE STORAGE:** Store only in the original package. Keep container tightly closed in a dry and well-ventilated place. Protect

from heat and direct sunlight. Store away from food and beverages.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION** 

ENGINEERING CONTROLS: Handle in accordance with good industrial hygiene and safety practice. Use with adequate general or local

exhaust ventilation to maintain exposure levels below the occupational exposure limits. Local exhaust ventilation is preferred since it prevents contamination dispersion into the work area by controlling it at its source. Provide eyewash and safety shower if contact or splash hazard exists. Wash hands before breaks and

at the end of work.

**EYE/FACE PROTECTION:** Safety glasses.

**SKIN PROTECTION:** Glove material impermeable and resistant to the product.

**BODY PROTECTION:** Protective work clothing.

**RESPIRATORY PROTECTION:** NIOSH (US) or CEN (EU) approved respirators and components.

**ENVIRONMENTAL EXPOSURE:** Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES** 

APPEARANCE/COLOR: Fine white powder ODOR: Faint odor in bulk FLASH POINT: 579°F (304°C) WATER SOLUBILITY: Insoluble

**SECTION 10: STABILITY AND REACTIVITY** 

CHEMICAL STABILITY: Stable under recommended storage conditions.

HAZARDOUS REACTIONS: No further relevant information available.

CONDITIONS TO AVOID: Temperatures above 464°F (240°C).

INCOMPATIBLE MATERIALS: Strong oxidizing agents.

PREPARED BY: SS PAGE 2 OF 4

SAFETY DATA SHEET

NAME OF PRODUCT: SOFTONE™ Powder WHITE

HAZARDOUS DECOMPOSITION PRODUCTS: Methacrylate monomers and oxides of carbon.

FILE NO.: SDS776 SDS DATE: 06/19/2014

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

POTENTIAL HEALTH EFFECTS: EYES: May cause eye irritation.

**SKIN:** May be harmful if absorbed through skin. May cause skin irritation.

**INGESTION:** May be harmful if swallowed.

**INHALATION:** May be harmful if inhaled. May cause respiratory tract irritation.

**CARCINOGENICITY:** OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or possible carcinogen by OSHA.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by ACGIH.

NOTE: No component of this product present at levels greater than or equal to 0.1% is identified as a known or

anticipated carcinogen by NTP.

IARC: Titanium dioxide is identified as a possible human carcinogen by IARC. Benzoyl peroxide is identified as

not classifiable as to its carcinogenicity to humans by IARC.

#### **SECTION 12: ECOLOGICAL INFORMATION**

ADVERSE EFFECTS: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

PRODUCT: Offer surplus and non-recyclable solutions to a licensed disposal company. Must not be disposed of together

with household garbage. Do not allow product to reach sewage system. Disposal must be made according to

official regulations.

CONTAMINATED PACKAGING: Dispose of as unused product.

#### **SECTION 14: TRANSPORT INFORMATION**

UN NUMBER: N/A
PROPER SHIPPING NAME: N/A
HAZARD CLASS: N/A
PACKING GROUP: N/A
LABEL STATEMENT: N/A

# **SECTION 15: REGULATORY INFORMATION**

#### **US FEDERAL REGULATIONS**

TSCA: This product is an FDA regulated device and not subject to TSCA regulations.

CERCLA: This product is an FDA regulated device and not subject to reporting requirements. There may be specific

reporting requirements at the local, regional, or state level.

SARA 313 TOXIC CHEMICALS: The following components are subject to reporting levels established by SARA Title III, Section 313 (40 CFR

372): Benzoyl Peroxide, CAS NO. 94-36-0.

SARA 311/312 HAZARDS: This product is an FDA regulated device and not subject to reporting requirements.

**US STATE REGULATIONS** 

CALIFORNIA PROPOSITION 65: This product may contain a chemical known to the State of California to cause cancer and/or reproductive

toxicity.

# INTERNATIONAL REGULATIONS

CANADIAN ENVIRONMENTAL

**PROTECTION ACT:** This product is a medical device and not subject to chemical notification requirements.

EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES

(EINECS): This product is a medical device and not subject to chemical notification requirements.

# **SECTION 16: OTHER INFORMATION**

# FULL TEXT OF H STATEMENTS REFERRED TO UNDER SECTION 3

PREPARED BY: SS PAGE 3 OF 4

# **SAFETY DATA SHEET**

NAME OF PRODUCT: SOFTONE™ Powder WHITE

Acute Tox. Acute toxicity
Eye Irrit. Eye irritation

H241 Heating may cause a fire or explosion.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

Org. Perox. Organic peroxides
Skin Irrit. Skin irritation
Skin Sens. Skin sensitization

STOT RE Specific target organ toxicity – repeated exposure STOT SE Specific target organ toxicity – single exposure

#### NFPA RATING

Health Hazard 1
Fire Hazard 1
Reactivity Hazard 0

**PREPARATION INFORMATION:** This SDS was prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200) and is to be used only for this product.

**DISCLAIMER:** To the best of our knowledge, the information contained herein is accurate. However, The Harry J. Bosworth Company does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

FILE NO.: SDS776

**SDS DATE:** 06/19/2014

PREPARED BY: SS PAGE 4 OF 4