



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Easy-Mix S 50 Resin

Article number 106501

Revision date: Feb/9/2016

Version: 1

Language: en-US

Date of print: Feb/10/2016

Page: 1 of 8

1. Product and company identification

Product identifier

Trade name: Easy-Mix S 50 Resin

Relevant identified uses of the substance or mixture and uses advised against

General use: Resin for 2 component adhesive (epoxy resin).
Reserved for industrial and professional use.

Details of the supplier of the safety data sheet

Company name: WEICON Inc.
Street/POB-No.: 20 Steckle Place, Unit 20
Postal Code, city: Kitchener, Ontario N2E 2C3, CA
WWW: www.weicon.ca
E-mail: info@weicon.ca
Telephone: +1-519-896-5252
Telefax: +1-519-896-5254
Dept. responsible for information:
Product-Safety-Department
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de
Additional information: WEICON GmbH & Co. KG
Königsberger Straße 255
Münster 48157
www.weicon.de
info@weicon.de
+49(0)251 / 9322 - 0
+49(0)251 / 9322 - 244

Emergency phone number

GLZ, Bonn Germany (English)
Telephone: +49(0)228 / 19 240

2. Hazards identification

Emergency overview

Appearance: Physical state at 68 °F and 101.3 kPa: liquid
Color: yellow, clear
Odor: slightly perceptible
Classification: Skin Irritation - Category 2; Eye Irritation - Category 2A; Sensitization - skin - Category 1; Aquatic toxicity - chronic - Category 2;

Hazard symbols:



Signal word:

Warning

Hazard statements: Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Toxic to aquatic life with long lasting effects.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Easy-Mix S 50 Resin

Article number 106501

Revision date: Feb/9/2016
Version: 1
Language: en-US
Date of print: Feb/10/2016

Page: 2 of 8

Precautionary statements: Do not breathe vapors/dust/ aerosols.
Wash hands and face thoroughly after handling.
Contaminated work clothing should not be allowed out of the workplace.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection.
IF ON SKIN: Wash with plenty of water/soap.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see ' First aid ' on this label).
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing.
Wash contaminated clothing before reuse.
Collect spillage.
Dispose of contents/container to hazardous or special waste collection point.

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

Contains epoxy constituents with an average molecular weight of ≤ 700 . May produce an allergic reaction.
see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterization: Resin for 2 component adhesive (epoxy resin).

Hazardous ingredients:

CAS No.	Designation	Content	Classification
CAS 25068-38-6	Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	70 - 90 %	Skin Irritation - Category 2. Eye Irritation - Category 2A. Sensitization - skin - Category 1. Aquatic toxicity - chronic - Category 2.
CAS 28064-14-4	Bisphenol-F epoxy resin with average molecular weight ≤ 700	5 - 10 %	Skin Irritation - Category 2. Eye Irritation - Category 2A. Sensitization - skin - Category 1. Aquatic toxicity - chronic - Category 2.

4. First aid measures

General information: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash contaminated clothing before reuse.

In case of inhalation: Provide fresh air. Seek medical treatment in case of troubles.

Following skin contact: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Wash contaminated clothing before reuse. Consult a doctor if skin irritation persists.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Easy-Mix S 50 Resin

Article number 106501

Revision date: Feb/9/2016

Version: 1

Language: en-US

Date of print: Feb/10/2016

Page: 3 of 8

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.

After swallowing: Do not induce vomiting. Rinse mouth with water. Immediately get medical attention.

Most important symptoms/effects, acute and delayed

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. respiratory complaints, nausea, vomiting, drowsiness.

Information to physician

Treat symptomatically. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

5. Fire fighting measures

Flash point/flash point range:

> 302 °F

Auto-ignition temperature: not determined

Suitable extinguishing media:

Alcohol resistant foam, dry chemical powder, carbon dioxide, water spray jet.

Extinguishing media which must not be used for safety reasons:

High power water jet

Specific hazards arising from the chemical

Hazardous vapors may form during fires. In case of fire may be liberated: nitrogen oxides (NOx), carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing. In case of fire and/or explosion do not breathe fumes.

Additional information:

Cool endangered containers with water jetspray. You have to dispose of contaminated extinguishing water according to the regulations of the authorities.

6. Accidental release measures

Personal precautions:

Provide adequate ventilation. Use a breathing protection against vapors/aerosol. Do not breathe vapor or spray. Wear protective equipment. Take off contaminated clothing and wash it before reuse. Keep unprotected people away. Avoid contact with skin and eyes.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains. Do not allow to enter into soil/subsoil. If necessary notify appropriate authorities.

Methods for clean-up:

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents) and place in closed containers for disposal. Thoroughly clean surrounding area.

7. Handling and storage

Handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed. Avoid the formation of aerosol. Do not breathe vapor or spray. Wear protective equipment. Avoid contact with skin and eyes. Take off contaminated clothing and wash it before reuse. When using do not eat, drink or smoke. Wash hands before breaks and after work.

Precautions against fire and explosion:

Take care of general rules for industrial preventive fire protection.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Easy-Mix S 50 Resin

Article number 106501

Revision date: Feb/9/2016

Version: 1

Language: en-US

Date of print: Feb/10/2016

Page: 4 of 8

Storage

Requirements for storerooms and containers:

Keep only in the original container. Protect from heat and direct sunlight. Store in a dry place.

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage:

Keep away from strong acids, strong alkalis and strong oxidizing agents.

Keep away from food, drink and animal feedingstuffs.

8. Exposure controls / personal protection

Engineering controls

Provide good ventilation and/or an exhaust system in the work area.

See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection: Wear suitable protective clothing.
Protective gloves according to OSHA Standard - 29 CFR: 1910.138.
Glove material: natural latex - Layer thickness: 0.6 mm
Breakthrough time: > 480 min
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Use a breathing protection against vapors/aerosol.
The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product.

General hygiene considerations:

Avoid contact with skin and eyes. Eye wash facility must be provided. Do not breathe vapor or spray.

Take off immediately all contaminated clothing and wash it before reuse.

When using do not eat, drink or smoke. Wash hands before breaks and after work.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance: Physical state at 68 °F and 101.3 kPa: liquid
Color: yellow, clear

Odor: slightly perceptible

Odor threshold: not determined

pH value: not determined

Melting point/freezing point: not determined

Initial boiling point and boiling range: > 392 °F

Flash point/flash point range: > 302 °F

Evaporation rate: no data available

Flammability: not determined

Explosion limits: LEL (Lower Explosion Limit): not determined

UEL (Upper Explosive Limit): not determined

Vapor pressure: no data available

Vapor density: no data available

Density: at 68 °F: 1.17 g/mL

Water solubility: insoluble



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Easy-Mix S 50 Resin

Article number 106501

Revision date: Feb/9/2016

Version: 1

Language: en-US

Date of print: Feb/10/2016

Page: 5 of 8

Partition coefficient: n-octanol/water: no data available
Auto-ignition temperature: not determined
Thermal decomposition: No decomposition when used properly.
Viscosity, kinematic: at 77 °F: 8000 - 15000 mPa*s
Ignition temperature: not determined

10. Stability and reactivity

Reactivity: no data available
Chemical stability: Stable under recommended storage conditions.
Possibility of hazardous reactions: Reacts with strong acids, strong alkalis, and strong oxidizing agents.
Conditions to avoid: Protect from heat and direct sunlight.
Incompatible materials: Strong acids, alkalis and strong oxidizing agents
Hazardous decomposition products: In case of fire may be liberated: nitrogen oxides (NOx), carbon monoxide and carbon dioxide.
Thermal decomposition: No decomposition when used properly.

11. Toxicological information

Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.
Acute toxicity (oral): Lack of data.
Acute toxicity (dermal): Lack of data.
Acute toxicity (inhalative): Lack of data.
Skin corrosion/irritation: Skin Irritation - Category 2 = Causes skin irritation.
Eye damage/irritation: Eye Irritation - Category 2A = Causes serious eye irritation.
Sensitisation to the respiratory tract: Lack of data.
Skin sensitisation: Sensitization - skin - Category 1 = May cause an allergic skin reaction.
Germ cell mutagenicity/Genotoxicity: Lack of data.
Carcinogenicity: Lack of data.
Reproductive toxicity: Lack of data.
Effects on or via lactation: Lack of data.
Specific target organ toxicity (single exposure): Lack of data.
Specific target organ toxicity (repeated exposure): Lack of data.
Aspiration hazard: Lack of data.

Symptoms

Respiratory complaints, nausea, vomiting, drowsiness.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Easy-Mix S 50 Resin

Article number 106501

Revision date: Feb/9/2016

Version: 1

Language: en-US

Date of print: Feb/10/2016

Page: 6 of 8

12. Ecological information

Ecotoxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.

Mobility in soil

no data available

Persistence and degradability

Further details: Product is not biodegradable.

Additional ecological information

General information: Do not allow to penetrate into soil, waterbodies or drains. Do not allow uncontrolled discharge of product into the environment.

13. Disposal considerations

Product

Recommendation: Dispose of waste according to applicable legislation.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself. Uncontaminated packaging may be treated as household waste.

14. Transport information

USA: Department of Transportation (DOT)

Identification numbers: UN3082
Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
DOT hazard class or division: 9
PG: III
Label codes: 9
Symbols: G
Special provisions: 8, 146, 173, 335, IB3, T4, TP1, TP29
Packaging - Exceptions: 155
Packaging - Non-bulk: 203
Packaging - Bulk: 241
Quantity limitations - Passenger aircraft / rail: No limit
Quantity limitations - Cargo only: No limit
Vessel stowage - Location: A





SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Feb/9/2016
Version: 1
Language: en-US
Date of print: Feb/10/2016

Easy-Mix S 50 Resin

Article number 106501

Page: 7 of 8

Sea transport (IMDG)

UN number: UN 3082
Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
IMDG: Class 9, Subrisk -
Packing Group: III
EmS: F-A, S-F
Special provisions: 274, 335, 969
Limited quantities: 5 L
EQ: E1
Contaminated packaging - Instructions: P001, LP01
Contaminated packaging - Provisions: PP1
IBC - Instructions: IBC03
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T4
Tank instructions - Provisions: TP2, TP29
Stowage and handling: Category A.
Properties and observations: -
Marine pollutant: yes
Segregation group: none

Air transport (IATA)

UN/ID number: UN 3082
Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
ICAO/IATA: Class 9
PG: III
Hazard: Miscellaneous
EQ: E1
Passenger Ltd.Qty.: Pack.Instr. Y964 - Max. Net Qty/Pkg. 30 kg G
Passenger: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L
Cargo: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L
Special Provisioning: A97 A158 A197
ERG: 9L

15. Regulatory information

National regulations - U.S. Federal Regulations

Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin
(number average molecular weight ≤ 700):

Bisphenol-F epoxy resin with average molecular weight
 ≤ 700 :

TSCA Inventory: listed; EPA flags XU
TSCA HPVC: not listed

TSCA Inventory: listed; UVCB; EPA flags XU
TSCA HPVC: not listed

National regulations - Great Britain

Hazchem-Code: •3Z



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Easy-Mix S 50 Resin

Article number 106501

Revision date: Feb/9/2016

Version: 1

Language: en-US

Date of print: Feb/10/2016

Page: 8 of 8

16. Other information

Text for labeling: Contains 70 - 90 % Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), 5 - 10 % Bisphenol-F epoxy resin with average molecular weight ≤ 700 . Safety data sheet available on request.

Hazard rating systems: HMIS Version III Rating:
Health: 1 (Slight)
Flammability: 1 (Slight)
Physical Hazard: 0 (Minimal)
Personal Protection: X = Consult your supervisor

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
	X

Date of first version: Feb/9/2016

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.