

KEM CANADA MFG.
4 BLAIR DRIVE
BRAMPTON, ONTARIO
L6T 2H5
TEL# (905) 456-9444

EMERGENCY # CANUTEC (613) 996-6666

"USE IN CASE OF CHEMICAL EMERGENCY ONLY"

W.H.M.I.S. CLASSIFICATION: NOT CONTROLLED

MATERIAL REFERENCE NO: 117500 SECTION I - MATERIAL IDENTIFICATION AND USE |MATERIAL NAME/I.D.: DURAKEM 85-140 |CHEMICAL NAME: LUBRICATING OIL | CHEMICAL FAMILY: HYDROCARBONS | _____ |CHEMICAL FORMULA: NOT APPLICABLE | MOLECULAR WEIGHT: NOT APPLICABLE| |SYNONYMS: NONE _____ |MATERIAL USE: ALL RANGE AND ALL WEATHER GEAR OIL SECTION II - HAZARDOUS INGREDIENTS OF MATERIAL |NOT APPLICABLE SECTION III - PHYSICAL DATA FOR MATERIAL |PHYSICAL STATE: LIQUID |ODOUR AND APPEARANCE: DARK, BROWN LIQUID; TERPENE ODOUR ______ |ODOUR THRESHOLD (PPM) | SPECIFIC GRAVITY | VAPOUR PRESSURE (MM)| |5 MG/M3 FOR MINERAL OIL| 0.916 AT 16 (C) | NOT AVAILABLE | ______ |VAPOUR DENSITY (AIR=1) | EVAPORATION RATE | SOLUBILITY IN WATER | NOT AVAILABLE | NOT APPLICABLE | (20 Ø C) NIL BOILING POINT (C) | FREEZING POINT (C) |% VOLATILE (BY WEIGHT)| 371 | -15.0 | 0 ______ | DENSITY (G/ML) | COEF.OF WATER/OIL DISTR| NOT APPLICABLE | NOT APPLICABLE | NOT AVAILABLE |



MATERIAL REFERENCE NO: 117500



MATERIAL REFERENCE NO: 117500

	_
EFFECTS OF ACUTE EXPOSURE TO MATERIAL: EYES-MAY CAUSE MILD TRANSIENT IRRITATION. SKIN-MAY CAUSE MILD TRANSIENT IRRITATION. INHALATION-EXCESSIVE BREATHING OF MISTS OR VAPOURS MAY CAUSE RESPIRATORY TRACT IRRITATION. INGESTION-MAY CAUSE NAUSEA, VOMITING, DIARRHEA.	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: NO ADDITIONAL INFORMATION AVAILABLE.	
LD 50 OF MATL. LC 50 OF MATL. EXPOSURE LIMIT(S) IRRITANCY OF MATL NOT AVAILABLE MILD	
SENSITIZATION OF MATERIAL SYNERGISTIC MATERIALS NONE NOT AVAILABLE	
CARCINOGENICITY, REPRODUCTIVE EFFECTS, TERATOGENICITY, MUTAGENICITY: THIS PRODUCT CONTAINS NO KNOWN CARCINOGENS OR MUTAGENS AS DEFINED BY OSHA OR IARC.	
SECTION VII - PREVENTIVE MEASURES	
PERSONAL PROTECTIVE EQUIPMENT:	
GLOVES: NEOPRENE RESPIRATORY: NOT REQUIRED EYE: FACE SHIELD FOOTWEAR: NO SPECIAL REQUIREMENTS CLOTHING: NO SPECIAL REQUIREMENTS OTHER: EYE WASH AND SAFETY SHOWER ENGINEERING CONTROLS (EG VENTILATION, ENCLOSED PROCESS): USE WITH ADEQUATE VENTILATION.	
LEAK AND SPILL PROCEDURE: CONTAIN SPILL. TRANSFER MATERIAL TO SUITABLE CONTAINER FOR REUSE OR DISPOSAL. ABSORB REMAINING MATERIAL ONTO SAND OR INERT MATERIAL. SCOOP UP AND PLACE IN DISPOSAL CONTAINER.	
WASTE DISPOSAL: INCINERATE IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.	



MATERIAL REFERENCE NO: 117500

SECTION VIII - FIRST AID MEASURES

PROCEDURES: EYES-IMMEDIATELY FLUSH WITH RUNNING WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN-WASH THOROUGHLY WITH SOAP AND WATER. REMOVE AND LAUNDER CONTAMINATED CLOTHING. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. INGESTION-DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.
SOURCES USED: RAW MATERIAL SUPPLIER'S MATERIAL SAFETY DATA SHEETS
ADDITIONAL INFORMATION: NONE
SECTION IX - TDG SHIPPING INFORMATION
SHIPPING NAME CLASS UN NO. PACKING GROUP NOT REGULATED
HANDLING PROCEDURES AND EQUIPMENT: WASH THOROUGHLY AFTER HANDLING. DO NOT GET IN EYES OR ON CLOTHING. KEEP AWAY FROM SPARKS OR OPEN FLAMES.
STORAGE REQUIREMENTS: KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT STORE NEAR INCOMPATIBLE MATERIALS.
SPECIAL SHIPPING INFORMATION: NONE
SECTION X - HMIS HAZARD RATING INFORMATION
FLAMMABILITY REACTIVITY HEALTH 0 1
SECTION XI - PREPARATION DATE OF MSDS
PREPARED BY: TECHNICAL DEPARTMENT TELEPHONE # (905) 456-9444 REVIEWED: OCTOBER 2, 2009 REPLACES: JANUARY 26, 2006
DISCLAIMER: THE INFORMATION CONTAINED HEREIN IS COMPILED FROM SOURCES BELIEVED TO BE RELIABLE. THE MANNER AND CONDITIONS OF USE AND HANDLING MAY INVOLVE OTHER AND ADDITIONAL CONSIDERATIONS. WE ACCEPT NO RESPONSIBILTY FOR THE

ACCURACY, SUFFICIENCY, RELIABILITY OR FOR ANY LOSS OR INJURY RESULTING

FROM THE USE OF THE INFORMATION.