



MATERIAL SAFETY DATA SHEET

Jordan Power Equipment Co.
281 Southwest Ave., Tallmadge, OH 44278
Phone: 330-630-9444 FAX: 330-630-3913

SECTION 1 GENERAL INFORMATION & PRODUCT IDENTIFICATION

Product Name: 1202

EMERGENCY CONTACT: INFOTRAC 1-800-535-5053 (North America)

This number is to be used ONLY in case of emergencies involving a spill, leak, fire exposure or accident involving chemicals.

MSDS Prepared By: Russell Wightman

Version Number: 1
Supersedes: 01/27/1997
Form Revision Date: 11/25/2003
Data Revision Date: 04/30/2004
Formula: Proprietary
Chemical Family: Cleaning Compound, Liquid
Packing Group: III
Proper DOT Shipping Name: Cleaning compound, liquid, n.o.s.
DOT Hazard Classification: Not Regulated
DOT Hazard Label: Not Regulated
Identification Number: None

HMIS Hazard Rating

Health:	2	(Moderate)
Flammability:	0	(Minimal)
Reactivity:	0	(Minimal)
Special:		None

SECTION 2 HAZARDOUS INGREDIENTS (29CFR 1910.1200)

Chemical Name	CAS Number	%	OSHA (PEL) TWA	ACGIH (TLV) TWA	OSHA (STEL) TWA
Ethylene Glycol Butyl Ether	000111-76-2	7.0	50 ppm	25 ppm	N/E

N/E = None Established N/A = Not Applicable

NOTE: If this product contains chemical subject to the reporting requirements of Section 313 of EPCRA of 1986, They will be listed in Section 11.

SECTION 3 PHYSICAL PROPERTIES

Appearance: Clear light blue liquid with mild glycol ether odor.
Boiling Range (760 mm Hg): > 121 °F
Melting Range (760 mm Hg): Not Determined
Vapor Pressure (mm Hg): < 1 @ 20°C (63°F)
Vapor Density (Air = 1): > 1
Specific Gravity (Water = 1): 1.000 - 1.020 (1.010 Nominal)
% Volatile (By Weight, Excluding Water): 7
Evaporation Rate (BuAc = 1): < 1
Solubility (In Water): Complete
pH (Concentrate): Not Determined
pH (1% Aqueous Solution): 6.50 - 8.50

SECTION 4 FIRE & EXPLOSION HAZARD DATA

Flash Point (TAG Closed Cup): > 200 °F (ASTM D93)
Upper Flammable Limit (% in Air): Not Determined
Lower Flammable Limit (% in Air): Not Determined

Extinguishing Media:	Water spray, dry chemical, carbon dioxide. Use water spray to cool nearby containers and structures exposed to fire.
Special Fire-Fighting Procedures:	Evacuate non-emergency personnel to a safe area. Contact emergency personnel as necessary. Avoid breathing smoke, fumes and decomposition products. As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear.
Unusual Fire & Explosion Hazards:	None known.

SECTION 5 REACTIVITY DATA

Stability:	Stable under normal use and storage conditions.
Conditions to Avoid:	Excessive heat, open flames, sparks or any other ignition source.
Materials to Avoid:	Contact with strong oxidizing or reducing agents.
Hazardous Decomposition Products:	Burning can produce the following decomposition products: Oxides of carbon, silicon and nitrogen. Carbon monoxide is highly toxic if inhaled; carbon dioxide in sufficient concentrations can act as an asphyxiant. Acute overexposure to the products of combustion may result in irritation of the respiratory tract.
Hazardous Polymerization:	Will Not Occur

SECTION 6 HEALTH HAZARD DATA

Threshold Limit Value (TLV):	None Established. See SECTION 2 for TLV's of Hazardous Ingredients in this product.
Permissible Exposure Level (PEL):	None Established. See SECTION 2 for PEL's of Hazardous Ingredients in this product.
Primary Route(s) of Exposure:	Skin and eye contact. Inhalation of vapors and mists.
Eye Contact:	Eye contact can cause mild to moderate irritation, redness and itching.
Skin Contact:	Prolonged exposure can cause skin irritation. May cause red blood cell hemolysis and possible liver and kidney injury from glycol ether component.
Ingestion:	Can cause nausea, vomiting and gastrointestinal upset (e.g. diarrhea). May cause red blood cell hemolysis and possible liver and kidney injury from glycol ether component.
Inhalation:	High vapor concentrations can be irritating to the throat and nose, causing stinging and watering of the eyes. At concentrations which cause irritation, dizziness, faintness, drowsiness, nausea and vomiting may also occur. Inhalation of aerosols may cause irritant effects including nasal discomfort and discharge, cough, production of sputum, discomfort in the chest and possibly difficulty with breathing. May cause red blood cell hemolysis and possible liver and kidney injury from glycol ether component.
Chronic Effects of Exposure:	Repeated contact with the skin may cause a severe cumulative dermatitis. Long term repeated exposure to aerosols from undiluted or aqueous material may result in irritation and injury of the respiratory tract. May cause red blood cell hemolysis and possible liver and kidney injury from glycol ether component.
Medical Conditions Generally Aggravated by Exposure:	Skin contact may aggravate an existing dermatitis. May cause red blood cell hemolysis and possible liver and kidney injury from glycol ether component.

SECTION 7 EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT:	Immediately flush eyes with plenty of water for at least 15 minutes. Hold eyelids open during this flushing with water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. GET IMMEDIATE MEDICAL ATTENTION
SKIN CONTACT:	Immediately wash thoroughly with soap and water, then flush with plenty of water. Remove contaminated clothing and do not reuse before washing. GET IMMEDIATE MEDICAL ATTENTION
INGESTION:	CALL A PHYSICIAN. Unless otherwise advised by a physician, induce vomiting by giving syrup of ipecac followed by two glasses of water or by sticking finger down throat. GET IMMEDIATE MEDICAL ATTENTION
INHALATION:	Remove to fresh air. If not breathing, administer artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. GET IMMEDIATE MEDICAL ATTENTION
NOTE TO PHYSICIAN:	No specific antidote is known. Therapy is directed at preventing absorption, administering to the symptoms as they occur and providing supportive therapy.

SECTION 8 TOXICITY DATA - INGREDIENTS LISTED AS CARCINOGENS

Chemical Name	CAS Number	NTP	IARC	ACGIH	SUBPART Z	OSHA
Ethylene Glycol Butyl Ether	000111-76-2	No	No	No	No	No

SECTION 9 PERSONAL PROTECTION EQUIPMENT INFORMATION

RESPIRATORY PROTECTION:	Use NIOSH/NSHA approved dust/mist filter respirator for routine work purposes when exposure to dusts or mists exceed the permissible exposure level (PEL). The respirator use limitations made my NIOSH/NHSA 20 CFR 1910.134.
VENTILATION:	Use ventilation adequate to keep exposures to hazardous ingredients below their Threshold Limit Values (TLV) or Permissible Exposure Levels (PEL). See Section 2. Local exhaust should be sufficient to maintain dust and mist levels below the PEL.
EYE PROTECTION:	Chemical splash goggles if eye contact is likely.
PROTECTIVE GLOVES:	Impervious gloves (rubber, nitrile or neoprene).
OTHER PROTECTIVE EQUIPMENT:	Appropriate protective clothing if working with concentrated products. Products at use dilution MAY present less risk but protective clothing should still be worn.

SECTION 10 DISPOSAL INFORMATION

MATERIAL SPILL OR RELEASE:	STEPS TO BE TAKEN: Wear protective equipment including rubber boots, rubber gloves, rubber apron and a self contained breathing apparatus in the pressure demand mode or a supplied-air respirator. If the spill or leak is small, a full face piece air-purifying cartridge respirator equipped for organic vapors may be satisfactory. In any event, always wear eye protection. For large spills, contain by diking with soil or other noncombustible sorbent material and then pump into DOT approved waste containers; or absorb with noncombustible sorbent material, place in DOT approved waster containers. KEEP OUT OF SEWERS, STORM DRAINS, SURFACE WATERS AND SOILS. Comply with all applicable governmental regulations on spill reporting, handling and disposal of waste.
WASTE DISPOSAL METHOD:	Dispose of contaminated material in accordance with all Federal, State, and Local regulations. Recycle if feasible or treat at an industrial or liquid waste facility.

SECTION 11 FEDERAL REGULATORY INFORMATION

Chemical Name	CAS Number	%	Clean Air Act	313 Toxic Chemicals	CERCLA Reportable Quantity (Pounds)	Reportable Product quantity (Pounds)
Ethylene Glycol Butyl Ether	000111-76-2	7.0	Yes	Yes	None	0

SECTION 12 STATE REGULATORY INFORMATION

Chemical Name	CAS Number	%	State Lists	Miscellaneous	Proposition 65
Ethylene Glycol Butyl Ether	000111-76-2	7.0	MA1, NJ1, PA1	None	No

SECTION 13 HANDLING PRECAUTIONS

PRECAUTIONS TO BE TAKEN	Avoid skin and eye contact.
DURING HANDLING AND STORAGE:	Avoid excessive inhalation of vapors and mists. Wash thoroughly after handling. Clean contaminated clothing before reuse. Store in cool, well ventilated place away from incompatible chemicals and materials.
OTHER PRECAUTIONS:	An eye/face fountain and deluge shower should be available in the work area. Empty containers may retain vapors or product residue. Always obey hazard warnings and handle empty containers as if they were full. Do not get in eyes, on skin or on clothing. Do not swallow. Do not breath vapors or mists. Do not eat, drink or smoke in work area containing chemicals.

SECTION 14 USERS RESPONSIBILITY

The information contained herein is derived from upstream Material Safety Data Sheets and other references, considered, to the best of our knowledge and belief, to be accurate and reliable, but not guaranteed to be so. Since conditions of handling and use are beyond our control, no warranties, express or implied, are made.

The responsibility to provide a safe workplace remains with the user. The user should review the health hazards and safety information presented in this Material Safety Data Sheet and implement those safety procedures that are needed to insure a safe work environment in your facility.

It is also the responsibility of the user to comply with all applicable Federal, State and Local laws and regulations.