

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 01/15/2015 Supersedes: 12/29/2014 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Nitrogen Dioxide (11.50% - 57.49%) in Air

Product code : SG-2002-00424

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Details of the supplier of the safety data sheet

Air Liquide America Specialty Gases 6141 Easton Rd Plumsteadville, PA 18949 - USA T 1.800.217.2688

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

www.airliquide.com

 Ox. Gas 1
 H270

 Compressed gas
 H280

 Acute Tox. 2 (Inhalation:gas)
 H330

 Skin Corr. 1B
 H314

 Eye Dam. 1
 H318

 STOT SE 2
 H371

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



 \Diamond

GHS04







Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H270 - May cause or intensify fire; oxidizer

H280 - Contains gas under pressure; may explode if heated

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H371 - May cause damage to organs (lung) (Inhalation)

CGA-HG11 - Symptoms may be delayed CGA-HG22 - Corrosive to the respiratory tract.

Precautionary statements (GHS-US) : P202 - Do not handle until all safety precautions have been read and understood

P220 - Keep/Store away from clothing, combustible materials

P244 - Keep reduction valves/valves and fittings free from oil and grease

P260 - Do not breathe gas

P262 - Do not get in eyes, on skin, or on clothing P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves, protective clothing, eye protection, face protection

P284 - Wear respiratory protection. Consult respirator supplier's product information for the

selection of the appropriate respiratory protection. P302+P352 - If on skin: Wash with plenty of water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

01/29/2015 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

P337+P313 - If eye irritation persists: Get medical advice/attention

P370+P376 - In case of fire: Stop leak if safe to do so

P403 - Store in a well-ventilated place

P405 - Store locked up

 $P501-Dispose\ of\ contents/container\ in\ accordance\ with\ local/regional/national/international$

regulations

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)

CGA-PG05 - Use a back flow preventive device in the piping CGA-PG06 - Close valve after each use and when empty CGA-PG10 - Use only with equipment rated for cylinder pressure CGA-PG14 - Approach suspected leak area with caution

CGA-PG18 - When returning cylinder, install leak tight valve outlet cap or plug CGA-PG20 - Use only with equipment of compatible materials of construction

CGA-PG21 - Open valve slowly

CGA-PG22 - Use only with equipment cleaned for oxygen service

2.3. Other hazards

Other hazards not contributing to the : None. classification

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Compressed air	(CAS No) 132259-10-0	42.51 - 88.5	Compressed gas, H280
Nitrogen dioxide	(CAS No) 10102-44-0	11.5 - 57.49	Ox. Gas 1, H270 Liquefied gas, H280 Acute Tox. 1 (Inhalation:gas), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 2, H371

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact : If skin irritation or rash occurs: Rinse skin with water/shower, Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. If eye irritation develops,

seek medical attention.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : Fatal if inhaled. May cause damage to organs (lung) through single exposure (inhalation). If you

feel unwell, seek medical advice.

Symptoms/injuries after skin contact : CAUSES (SEVERE) SKIN BURNS.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous

administration

: Not known.

Chronic symptoms : None known.

4.3. Indication of any immediate medical attention and special treatment needed

If breathing is difficult, give oxygen. Obtain medical attention if breathing difficulty persists.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet to extinguish.

01/29/2015 EN (English US) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Special hazards arising from the substance or mixture

Fire hazard : The product is not flammable.

Explosion hazard : Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire

and increasing risk of burns and injuries.

Reactivity : None known.

5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray

or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Do not enter fire area without proper protective equipment, including respiratory

protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment consistent with the site emergency plan.

Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent

premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep

upwind.

6.1.2. For emergency responders

Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Equip cleanup crew with proper protection.

Emergency procedures : Evacuate and limit access. Ventilate area.

6.2. Environmental precautions

Try to stop release if safe to do so.

6.3. Methods and material for containment and cleaning up

For containment : Try to stop release if safe to do so.

Methods for cleaning up : Dispose of this material and its container in accordance with local regulations.

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder

pressure.

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or

in a well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Store locked up. Do not expose to temperatures exceeding 52°C (125°F). Keep container

closed when not in use. Protect cylinder from physical damage. Store in well ventilated area.

Incompatible products : None known.

Incompatible materials : Flammable materials. Combustible materials.

7.3. Specific end use(s)

Test gas/Calibration gas.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Nitrogen Dioxide (11.50% - 57.49%) in Air	
ACGIH	Not applicable
OSHA	Not applicable

01/29/2015 EN (English US) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nitrogen dioxide (10102-44-0)		
ACGIH	ACGIH TWA (ppm)	0.2 ppm
OSHA	OSHA PEL (Ceiling) (mg/m³)	9 mg/m³
OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm

Compressed air (132259-10-0	0)
ACGIH	Not applicable
OSHA	Not applicable

8.2. Exposure controls

Appropriate engineering controls : Ensure exposure is below occupational exposure limits. Provide adequate general and local

exhaust ventilation. Systems under pressure should be regularly checked for leakages. Alarm detectors should be used when toxic gases may be released. Consider work permit system e.g.

for maintenance activities.

Hand protection : Wear working gloves when handling gas containers. 29CFR 1910.138: Hand Protection. In

addition wear chemically resistant protective gloves when making or breaking process

connections.

Eye protection : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection. Wear

goggles and faceshield when transfilling or breaking transfer connections.

Skin and body protection : Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.

Respiratory protection : Wear a respirator when performing non-routine tasks not limited to line breaking or sampling.

Wear a respirator during routine operations if determined to be necessary during a processspecific review. Consult respirator suppliers' product information or their representatives for the

selection of the appropriate respirator.

Thermal hazard protection : None necessary.

Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

specific methods for waste gas treatment.

Other information : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Reddish brown.

Molecular mass : Not applicable for gas-mixtures.

Color : Reddish brown Odor : Pungent.

Odor threshold : No data available

pH : Not applicable for gas-mixtures.

Relative evaporation rate (butyl acetate=1) : No data available

Relative evaporation rate (ether=1) : Not applicable for gas-mixtures.

Melting point : Not applicable for gas-mixtures.

Freezing point : No data available

Boiling point : Not applicable for gas-mixtures.

Flash point : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : See Section 2.1 and 2.2

Vapor pressure : Not applicable.

Relative vapor density at 20 °C : No data available

Relative density : No data available

Relative gas density : Similar to air.

Solubility : Water: Solubility in water of component(s) of the mixture :

•: •

Log Pow : Not applicable for gas-mixtures.
Log Kow : Not applicable for gas-mixtures.

01/29/2015 EN (English US) 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic : Not applicable.

Viscosity, dynamic : Not applicable.

Explosive properties : Not flammable.

Oxidizing properties : Not combustible but enhances combustion of other substances. May intensify fire. Oxidizer.

Explosive limits : Not applicable - not flammable

9.2. Other information

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Symptoms/injuries after inhalation

Symptoms/injuries after skin contact Symptoms/injuries after eye contact

Flammable materials. combustible materials.

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:gas: Fatal if inhaled

Acute toxicity	. IIIIlalation.gas. Fatai ii iiiilaleu.
Nitrogen Dioxide (11.50% - 57.49%) in Air	
ATE US (gases)	173.943 ppmV/4h
Nitrogen dioxide (10102-44-0)	
LC50 inhalation rat (ppm)	57.5 ppm/4h
ATE US (gases)	10.000 ppmV/4h
Compressed air (132259-10-0)	
LC50 inhalation rat (ppm)	820000 ppm/4h
ATE US (gases)	820000.000 ppmV/4h
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
	pH: Not applicable for gas-mixtures.
Serious eye damage/irritation	: Causes serious eye damage.
	pH: Not applicable for gas-mixtures.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause damage to organs (lung) (Inhalation).
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

01/29/2015 EN (English US) 5/9

feel unwell, seek medical advice.

: CAUSES (SEVERE) SKIN BURNS.

: Causes serious eye damage.

Fatal if inhaled. May cause damage to organs (lung) through single exposure (inhalation). If you

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous

administration

: Not known.

Chronic symptoms : None known.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Classification criteria are not met.

12.2. Persistence and degradability

Nitrogen Dioxide (11.50% - 57.49%) in Air		
Persistence and degradability No data available.		
Nitrogen dioxide (10102-44-0)		
Persistence and degradability Not applicable for inorganic gases.		
Compressed air (132259-10-0)		
Persistence and degradability	No ecological damage caused by this product.	

12.3. Bioaccumulative potential

Nitrogen Dioxide (11.50% - 57.49%) in Air		
Log Pow	Not applicable for gas-mixtures.	
Log Kow	Not applicable for gas-mixtures.	
Bioaccumulative potential	No data available.	
Nitrogen dioxide (10102-44-0)		
Log Pow	Not applicable for inorganic gases.	
Bioaccumulative potential	No data available.	
Compressed air (132259-10-0)		
Log Pow	Not applicable for inorganic gases.	
Bioaccumulative potential	No ecological damage caused by this product.	

12.4. Mobility in soil

Nitrogen Dioxide (11.50% - 57.49%) in Air		
Mobility in soil	No data available.	
Nitrogen dioxide (10102-44-0)		
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.	
Compressed air (132259-10-0)		
Ecology - soil	No ecological damage caused by this product.	

12.5. Other adverse effects

Effect on ozone layer : None.

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its

accumulation could be dangerous. Ensure that the emission levels from local regulations or

operating permits are not exceeded.

Waste disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more

guidance on suitable disposal methods.

Additional information : None.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN3303 Compressed gas, toxic, oxidizing, n.o.s. (Nitrogen Dioxide, Compressed Air), 2.3

UN-No.(DOT) : UN33

Proper Shipping Name (DOT) : Compressed gas, toxic, oxidizing, n.o.s.

01/29/2015 EN (English US) 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Department of Transportation (DOT) Hazard

Hazard labels (DOT)

: 2.3 - Class 2.3 - Poisonous gas 49 CFR 173.115

: 2.3 - Poison gas 5.1 - Oxidizer



DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102)

3 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone C (see 173.116(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter.

B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per square foot per degree Fahrenheit) temperature differential. Insulating materials must not promote corrosion to steel when wet.

DOT Packaging Exceptions (49 CFR 173.xxx) : None DOT Packaging Non Bulk (49 CFR 173.xxx) : 302:305 DOT Packaging Bulk (49 CFR 173.xxx) 314;315 DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : Forbidden

CFR 175.75)

DOT Vessel Stowage Location

: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other 40 - Stow "clear of living quarters"

Additional information

Other information

: No supplementary information available.

Special transport precautions

: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

ADR

Transport document description : UN 3306, 2.3 (5.1+8), (C/D)

: 2 - Gases Class (ADR) Hazard identification number (Kemler No.) : 265 Classification code (ADR) : 1TOC

Hazard labels (ADR) 2.3 - Toxic gases

5.1 - Oxidizer

8 - Corrosive substances



Orange plates

265 3306

Tunnel restriction code (ADR) C/D : 0 Excepted quantities (ADR) · F0

01/29/2015 EN (English US) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

UN-No. (IMDG) : 3306 Class (IMDG) : 2 - Gases

Air transport

UN-No.(IATA) : 3306 Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Nitrogen dioxide (10102-44-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302	
SARA Section 302 Threshold Planning Quantity (TPQ)	100

15.2. International regulations

CANADA

Nitrogen dioxide (10102-44-0)	
Listed on the Canadian DSL (Domest	ic Sustances List)
WHMIS Classification	Class A - Compressed Gas Class C - Oxidizing Material Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material
Compressed air (132259-10-0)	
WHMIS Classification	Class A - Compressed Gas

EU-Regulations

Nitrogen dioxide (10102-44-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

Nitrogen dioxide (10102-44-0)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

Compressed air (132259-10-0)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on NZIoC (New Zealand Inventory of Chemicals)

15.3. US State regulations

Nitrogen dioxide (10102-44-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

01/29/2015 EN (English US) 8/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Indication of changes

: Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.

Other information

: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Full text of H-phrases:

At of 11-philases.	
Acute Tox. 1 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 1
Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Compressed gas	Gases under pressure Compressed gas
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Liquefied gas	Gases under pressure Liquefied gas
Ox. Gas 1	Oxidizing gases Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT SE 2	Specific target organ toxicity (single exposure) Category 2
H270	May cause or intensify fire; oxidizer
H280	Contains gas under pressure; may explode if heated
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H330	Fatal if inhaled
H371	May cause damage to organs

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

01/29/2015 EN (English US) 9/9