

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Nitrogen Dioxide (90.39% - 99.99%) in Nitrogen
Product code : SG-2002-00383

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Details of the supplier of the safety data sheet

Air Liquide America Specialty Gases
6141 Easton Rd
Plumsteadville, PA 18949 - USA
T 1.800.217.2688
www.airliquide.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)


Ox. Gas 1	H270
Liquefied gas	H280
Acute Tox. 1 (Inhalation:gas)	H330
Skin Corr. 1B	H314
Eye Dam. 1	H318
STOT SE 2	H371

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H270 - May cause or intensify fire; oxidizer
H280 - Contains gas under pressure; may explode if heated
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H330 - Fatal if inhaled
H371 - May cause damage to organs (lung) (Inhalation)
CGA-HG11 - Symptoms may be delayed
CGA-HG22 - Corrosive to the respiratory tract.

Precautionary statements (GHS-US) :

P202 - Do not handle until all safety precautions have been read and understood
P220 - Keep/Store away from clothing, combustible materials, combustibles
P244 - Keep reduction valves/valves and fittings free from oil and grease
P260 - Do not breathe gas
P262 - Do not get in eyes, on skin, or on clothing
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P284 - Wear respiratory protection. Consult respirator supplier's product information for the selection of the appropriate respiratory protection.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P308+P313 - If exposed or concerned: Get medical advice/attention
P370+P376 - In case of fire: Stop leak if safe to do so
P403 - Store in a well-ventilated place

Nitrogen Dioxide (90.39% - 99.99%) in Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)
CGA-PG05 - Use a back flow preventive device in the piping
CGA-PG06 - Close valve after each use and when empty
CGA-PG10 - Use only with equipment rated for cylinder pressure
CGA-PG14 - Approach suspected leak area with caution
CGA-PG18 - When returning cylinder, install leak tight valve outlet cap or plug
CGA-PG20 - Use only with equipment of compatible materials of construction
CGA-PG21 - Open valve slowly
CGA-PG22 - Use only with equipment cleaned for oxygen service

2.3. Other hazards

Other hazards not contributing to the classification : None.

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Nitrogen dioxide	(CAS No) 10102-44-0	90.39 - 99.99	Ox. Gas 1, H270 Liquefied gas, H280 Acute Tox. 1 (Inhalation:gas), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 2, H371
Nitrogen	(CAS No) 7727-37-9	0.01 - 9.61	Compressed gas, H280

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : If skin irritation or rash occurs: Rinse skin with water/shower, Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. If eye irritation develops, seek medical attention.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : Fatal if inhaled. May cause damage to organs (lung) through single exposure (inhalation). If you feel unwell, seek medical advice.

Symptoms/injuries after skin contact : Causes severe skin burns and eye damage.

Symptoms/injuries after eye contact : Causes severe skin burns and eye damage.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous administration : Not known.

Chronic symptoms : None known.

4.3. Indication of any immediate medical attention and special treatment needed

If breathing is difficult, give oxygen. Obtain medical attention if breathing difficulty persists.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Fire hazard : The product is not flammable.

Nitrogen Dioxide (90.39% - 99.99%) in Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion hazard	: Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Reactivity	: None known.

5.3. Advice for firefighters

Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
Protection during firefighting	: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Ensure adequate ventilation.
------------------	--------------------------------

6.1.1. For non-emergency personnel

Protective equipment	: Wear protective equipment consistent with the site emergency plan.
Emergency procedures	: Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

6.1.2. For emergency responders

Protective equipment	: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.
Emergency procedures	: Evacuate and limit access. Ventilate area.

6.2. Environmental precautions

Try to stop release if safe to do so.

6.3. Methods and material for containment and cleaning up

For containment	: Try to stop release if safe to do so.
Methods for cleaning up	: Dispose of this material and its container in accordance with local regulations.

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure.
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Comply with applicable regulations.
Storage conditions	: Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area. Store locked up.
Incompatible products	: Reducing agents.
Incompatible materials	: Flammable materials.

7.3. Specific end use(s)

Test gas/Calibration gas.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Nitrogen Dioxide (90.39% - 99.99%) in Nitrogen	
ACGIH	Not applicable
OSHA	Not applicable
Nitrogen (7727-37-9)	
ACGIH	Not applicable
OSHA	Not applicable

Nitrogen Dioxide (90.39% - 99.99%) in Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nitrogen dioxide (10102-44-0)		
ACGIH	ACGIH TWA (ppm)	0.2 ppm
OSHA	OSHA PEL (Ceiling) (mg/m³)	9 mg/m³
OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm

8.2. Exposure controls

Appropriate engineering controls	: Ensure exposure is below occupational exposure limits. Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Alarm detectors should be used when toxic gases may be released. Consider work permit system e.g. for maintenance activities.
Hand protection	: Wear working gloves when handling gas containers. 29CFR 1910.138: Hand Protection. In addition wear chemically resistant protective gloves when making or breaking process connections.
Eye protection	: Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection. Wear goggles and faceshield when transfilling or breaking transfer connections.
Skin and body protection	: Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.
Respiratory protection	: Wear a respirator when performing non-routine tasks not limited to line breaking or sampling. Wear a respirator during routine operations if determined to be necessary during a process-specific review. Consult respirator suppliers' product information or their representatives for the selection of the appropriate respirator.
Thermal hazard protection	: None necessary.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
Other information	: Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Reddish brown.
Molecular mass	: Not applicable for gas-mixtures.
Color	: Reddish brown
Odor	: Pungent.
Odor threshold	: No data available
pH	: Not applicable for gas-mixtures.
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable for gas-mixtures.
Melting point	: Not applicable for gas-mixtures.
Freezing point	: No data available
Boiling point	: Not applicable for gas-mixtures.
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: See Section 2.1 and 2.2
Vapor pressure	: Not applicable.
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Relative gas density	: Heavier than air.
Solubility	: Water: Solubility in water of component(s) of the mixture : • : 20 mg/l • :
Log Pow	: Not applicable for gas-mixtures.
Log Kow	: Not applicable for gas-mixtures.
Viscosity, kinematic	: Not applicable.
Viscosity, dynamic	: Not applicable.
Explosive properties	: Not flammable.
Oxidizing properties	: May cause or intensify fire; oxidizer.

Nitrogen Dioxide (90.39% - 99.99%) in Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive limits : Not applicable - not flammable

9.2. Other information

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

May react violently with reducing agents.

10.4. Conditions to avoid

Refer to Section 10 on Incompatible Materials.

10.5. Incompatible materials

Flammable materials. Reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:gas: Fatal if inhaled.

Nitrogen Dioxide (90.39% - 99.99%) in Nitrogen	
ATE US (gases)	57.506 ppmV/4h
Nitrogen (7727-37-9)	
LC50 inhalation rat (ppm)	820000 ppm/4h
Nitrogen dioxide (10102-44-0)	
LC50 inhalation rat (ppm)	57.5 ppm/4h
ATE US (gases)	57.500 ppm/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.
pH: Not applicable for gas-mixtures.

Serious eye damage/irritation : Causes serious eye damage.
pH: Not applicable for gas-mixtures.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause damage to organs (lung) (Inhalation).

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : Fatal if inhaled. May cause damage to organs (lung) through single exposure (inhalation). If you feel unwell, seek medical advice.

Symptoms/injuries after skin contact : Causes severe skin burns and eye damage.

Symptoms/injuries after eye contact : Causes severe skin burns and eye damage.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous administration : Not known.

Chronic symptoms : None known.

Nitrogen Dioxide (90.39% - 99.99%) in Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Classification criteria are not met.

12.2. Persistence and degradability

Nitrogen Dioxide (90.39% - 99.99%) in Nitrogen	
Persistence and degradability	No data available.
Nitrogen (7727-37-9)	
Persistence and degradability	No ecological damage caused by this product.
Nitrogen dioxide (10102-44-0)	
Persistence and degradability	Not applicable for inorganic gases.

12.3. Bioaccumulative potential

Nitrogen Dioxide (90.39% - 99.99%) in Nitrogen	
Log Pow	Not applicable for gas-mixtures.
Log Kow	Not applicable for gas-mixtures.
Bioaccumulative potential	No data available.
Nitrogen (7727-37-9)	
Log Pow	Not applicable for inorganic gases.
Bioaccumulative potential	No ecological damage caused by this product.
Nitrogen dioxide (10102-44-0)	
Log Pow	Not applicable for inorganic gases.
Bioaccumulative potential	No data available.

12.4. Mobility in soil

Nitrogen Dioxide (90.39% - 99.99%) in Nitrogen	
Mobility in soil	No data available.
Nitrogen (7727-37-9)	
Ecology - soil	No ecological damage caused by this product.
Nitrogen dioxide (10102-44-0)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5. Other adverse effects

Effect on ozone layer : None.

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded.

Waste disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods.

Additional information : None.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN3303 Compressed gas, toxic, oxidizing, n.o.s. (Nitrogen Dioxide, Nitrogen)

UN-No.(DOT) : UN3303

Proper Shipping Name (DOT) : Compressed gas, toxic, oxidizing, n.o.s.

Nitrogen Dioxide (90.39% - 99.99%) in Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT)	: 2.3 - Poison gas 5.1 - Oxidizer
	 
DOT Symbols	: G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102)	: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Additional information

Other information	: No supplementary information available.
Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

ADR

Transport document description	: UN 3306, 2.3 (5.1+8), (E)
Class (ADR)	: 2 - Gases
Hazard identification number (Kemler No.)	: 25
Classification code (ADR)	: 10
Hazard labels (ADR)	: 2.3 - Toxic gases 5.1 - Oxidizer 8 - Corrosive substances



Orange plates	: 
---------------	---

Tunnel restriction code (ADR)	: E
LQ	: 0
Excepted quantities (ADR)	: E0

Transport by sea

UN-No. (IMDG)	: 3306
Proper Shipping Name (IMDG)	: COMPRESSED GAS, TOXIC, OXIDIZING, CORROSIVE, N.O.S.
Class (IMDG)	: 2 - Gases

Air transport

UN-No.(IATA)	: 3306
Proper Shipping Name (IATA)	: COMPRESSED GAS, TOXIC, OXIDIZING, CORROSIVE, N.O.S.
Class (IATA)	: 2

Nitrogen Dioxide (90.39% - 99.99%) in Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Nitrogen (7727-37-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Nitrogen dioxide (10102-44-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on the United States SARA Section 302

SARA Section 302 Threshold Planning Quantity (TPQ)	100
--	-----

15.2. International regulations

CANADA

Nitrogen (7727-37-9)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class A - Compressed Gas
----------------------	--------------------------

Nitrogen dioxide (10102-44-0)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class A - Compressed Gas Class C - Oxidizing Material Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material
----------------------	---

EU-Regulations

Nitrogen (7727-37-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Nitrogen dioxide (10102-44-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

Nitrogen (7727-37-9)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Nitrogen dioxide (10102-44-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

Nitrogen (7727-37-9)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Nitrogen Dioxide (90.39% - 99.99%) in Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nitrogen dioxide (10102-44-0)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.

Other information : This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Full text of H-phrases:

Acute Tox. 1 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 1
Compressed gas	Gases under pressure Compressed gas
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Liquefied gas	Gases under pressure Liquefied gas
Ox. Gas 1	Oxidizing gases Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT SE 2	Specific target organ toxicity (single exposure) Category 2
H270	May cause or intensify fire; oxidizer
H280	Contains gas under pressure; may explode if heated
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H330	Fatal if inhaled
H371	May cause damage to organs

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.