Safety Data Sheet



Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name

 Non-Flammable Gas Mixture Containing The following Component In a Nitrogen Balance Gas: Nitric Oxide: 0.0005-0.02

Product Code 50026

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Manufacturer • Air Liquide

2700 Post Oak Blvd. Houston, TX 77056 United States

www.us.airliquide.com sds@airliquide.com

Telephone (Technical) • 713-896-2896 Telephone (Technical) • 800-819-1704

1.4 Emergency telephone number

Manufacturer 800-424-9300 - CHEMTREC

Manufacturer +1 703-527-3887 - Outside United States

Section 2: Hazards Identification

EU/EEC

According to Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010] According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

CLP Compressed Gas - H280

DSD/DPD • Not classified

2.2 Label Elements

CLP

WARNING



Hazard statements • H280 - Contains gas under pressure; may explode if heated

Preparation Date: 17/October/2014 Revision Date: 17/October/2014

Precautionary statements

Storage/Disposal • P403 - Store in a well-ventilated place.

DSD/DPD

Risk phrases . No label element(s) required

2.3 Other Hazards

CLP

 This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces.
 According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

DSD/DPD

 This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces.
 According to European Directive 1999/45/EC this preparation is not considered dangerous.

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

OSHA HCS 2012

 Compressed Gas - H280 Simple Asphyxiant

2.2 Label elements OSHA HCS 2012

WARNING



Hazard statements • Contains gas under pressure; may explode if heated - H280 May displace oxygen and cause rapid suffocation.

Precautionary statements

Storage/Disposal Store in a well-ventilated place. - P403

2.3 Other hazards

OSHA HCS 2012

 Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to WHMIS

2.1 Classification of the substance or mixture

WHMIS

Compressed Gas - A

2.2 Label elements

WHMIS



Compressed Gas - A

2.3 Other hazards

WHMIS

 This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces.
 In Canada, the product mentioned above is considered hazardous under the

Workplace Hazardous Materials Information System (WHMIS).

2.4 Other information

NFPA



Section 3 - Composition/Information on Ingredients

3.1 Substances

 Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

3.2 Mixtures

	Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive		
Nitric oxide	CAS:10102- 43-9 EINECS:233- 271-0	0.0005% TO 0.02%	Inhalation-Rat LC50 • 1068 mg/kg	EU DSD/DPD: Self Classified - O, R8, T+ R26, C, R34 EU CLP: Self Classified - Press. Gas - Comp., H280; Ox. Gas 1, H270; STOT SE 1 (Lung, Blood (Methemoglobin former)), H370; Acute Tox 1 (Inhl), H330; Skin Corr. 1A, H314; Eye Dam. 1, H318 OSHA HCS 2012: Press. Gas - Comp.; Ox. Gas 1; STOT SE 1 (Lung, Bood (Methemoglobin former)); Acute Tox. 1 (Inhl); Skin Corr. 1; Eye Dam. 1		
Nitrogen	CAS:7727-37- 9 EINECS:231- 783-9	Balance	NDA	EU DSD/DPD: Not Classified EU CLP: Self Classified - Press. Gas - Comp., H280 OSHA HCS 2012: Press. Gas - Comp.; Simp. Asphyx.		

See Section 16 for full text of H-statements and R-phrases.

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

• IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

 Although exposure is unlikely, in case of contact immediately flush skin with running water. If skin irritation develops get medical advice/attention.

Skin Eye

• First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. If irritation develops and persists, get medical attention.

Ingestion

• Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed

• Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. A potential health hazard associated with this gas is anoxia.

4.4 Other information

Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. RESCUERS SHOULD NOT ATTEMPT TO RETRIEVE VICTIMS OF EXPOSURE TO GASES WITHOUT ADEQUATE PERSONAL PROTECTIVE EQUIPMENT. At a minimum, Self-Contained Breathing Apparatus must be worn. Victim(s) who experience any adverse effect after overexposure to this gas mixture must be taken for medical attention. Rescuers should be taken for medical attention if necessary. Take a copy of the label and the MSDS to physician or other health professional with victim(s).

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media . Use extinguishing agent suitable for type of surrounding fire.

Unsuitable Extinguishing Media

No data available

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion

Hazards

Containers may explode when heated. Ruptured cylinders may rocket.

Hazardous Combustion Products

No data available

5.3 Advice for firefighters

Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

Always wear thermal protective clothing when handling refrigerated/cryogenic liquids. Wear positive pressure self-contained breathing apparatus (SCBA).

Move containers from fire area if you can do it without risk.

FIRE: If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

FIRE INVOLVING TANKS: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.

FIRE INVOLVING TANKS: Cool containers with flooding quantities of water until well after fire is out.

FIRE INVOLVING TANKS: Do not direct water at source of leak or safety devices; icing may occur.

FIRE INVOLVING TANKS: Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.

FIRE INVOLVING TANKS: ALWAYS stay away from tanks engulfed in fire.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Ventilate the area before entry.

Emergency Procedures

Stop leak if you can do it without risk. Keep unauthorized personnel away. Keep out of low areas. Stay upwind. Do not direct water at spill or source of leak. LARGE SPILL: Consider initial downwind evacuation for at least 500 meters (1/3 mile)

6.2 Environmental precautions

Format: EU CLP/REACH Language: English (US) WHMIS, EU CLP, EU DSD/DPD, OSHA HCS 2012 Prevent spreading of vapors through sewers, ventilation systems and confined areas.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

• Stop leak if you can do it without risk.

Do not direct water at spill or source of leak. Use water spray to reduce vapors; do not put water directly on leak, spill area or

inside container.

If possible, turn leaking containers so that gas escapes rather than liquid.

Isolate area until gas has dispersed.

Ventilate the area.

6.4 Reference to other sections

 Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

• Use only with adequate ventilation. Ventilate closed spaces before entering. Be aware of any signs of dizziness or fatigue, especially if work is done in a poorly ventilated area; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms, due to olfactory fatigue or oxygen deficiency. Wear appropriate personal protective equipment, avoid direct contact. Cylinders should be firmly secured to prevent falling or being knocked-over. Do not attempt to repair, adjust, or in any other way modify cylinders. If there is a malfunction or another type of operational problem, contact nearest distributor immediately. Empty containers retain product residue and can be hazardous. Do not cut, weld, puncture or incinerate container.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Store in a cool, dry, well-ventilated place. Protect cylinders against physical damage. Cylinders should be firmly secured to prevent falling or being knocked-over.

7.3 Specific end use(s)

Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

			Exposure Limits	s/Guidelines				
	Result	ACGIH	Canada Ontario	Canada Quebec	China	France		
Alto Control	STELs	Not established	Not established	Not established	30 mg/m3 STEL	Not established		
Nitric oxide (10102-43-9)	TWAs	25 ppm TWA	25 ppm TWA	25 ppm TWAEV; 31 mg/m3 TWAEV	15 mg/m3 TWA	25 ppm TWA [VME]; 30 mg/m3 TWA [VME]		
	Exposure Limits/Guidelines (Con't.)							
	Result Germany DFG Ireland Israel NIOSH OSHA							
	STELs	Not established	35 ppm STEL; 45 mg/m3 STEL	Not established	Not established	Not established		
Nitale avide	TWAs	Not established	25 ppm TWA; 30 mg/m3 TWA	25 ppm TWA	25 ppm TWA; 30 mg/m3 TWA	25 ppm TWA; 30 mg/m3 TWA		
Nitric oxide (10102-43-9)	Ceilings	1 ppm Peak; 1.26 mg/m3 Peak	Not established	Not established	Not established	Not established		
	MAKs	0.5 ppm TWA MAK; 0.63 mg/m3 TWA MAK	Not established	Not established	Not established	Not established		

Exposure Limits/Guidelines (Con't.)								
	Result OSHA Vacated Portugal Spain Sweden							
Nitric oxide (10102-43-9)	IVVAC	25 ppm TWA; 30 mg/m3 TWA	25 ppm TWA [VLE-MP]	25 ppm TWA [VLA-ED]; 31 mg/m3 TWA [VLA- ED]	25 ppm LLV; 30 mg/m3 LLV			
(10102-43-9)	STELs	Not established	Not established	Not established	50 ppm STV; 60 mg/m3 STV			

Exposure Control Notations

Portugal

•Nitrogen (7727-37-9): Simple Asphyxiants: (Simple Asphyxiant)

Ireland

Nitrogen (7727-37-9): Simple Asphyxiants: (Asphyxiant)

Spain

Nitrogen (7727-37-9): Simple Asphyxiants: (simple asphyxiant)

Germany DFG

•Nitric oxide (10102-43-9): **Pregnancy:** (classification not yet possible)

8.2 Exposure controls

Engineering Measures/Controls

 Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level

Personal Protective Equipment

Respiratory

 Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eve/Face

Skin/Body

Wear safety glasses.

Wear leather gloves when handling cylinders.

Environmental Exposure Controls

 Follow best practice for site management and disposal of waste. Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

Key to abbreviations

LLV = Limit Level Value is the exposure limit for 8-hour work day

STEL = Short Term Exposure Limits are based on 15-minute exposures

 $\label{eq:MAK} \mathsf{MAK} \quad = \begin{matrix} \mathsf{Maximale \ Arbeitsplatz \ Konzentration} \ \mathsf{is \ the \ maximum \ permissible} \\ \mathsf{concentration} \end{matrix}$

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

NIOSH = National Institute of Occupational Safety and Health OSHA = Occupational Safety and Health Administration

TWAEV = Time-Weighted Average Exposure Value

Section 9 - Physical and Chemical Properties

9.1 Information on Physical and Chemical Properties

Material Description						
Physical Form	Gas	Appearance/Description	Colorless gas with an irritating odor.			
Color	Colorless	Odor	Irritating			
Odor Threshold	Data lacking					
General Properties	•	•				
Boiling Point	-195.8 C(-320.44 F) (Nitrogen)	Melting Point	-210 C(-346 F) (Nitrogen)			

Preparation Date: 17/October/2014 Revision Date: 17/October/2014

Decomposition Temperature	Data lacking	рН	Data lacking		
Specific Gravity/Relative Density	0.906 Water=1 (Nitrogen)	Water Solubility	Data lacking		
Viscosity	Data lacking	Explosive Properties	Data lacking		
Oxidizing Properties:	Data lacking				
Volatility					
Vapor Pressure	Data lacking	Vapor Density	Data lacking		
Evaporation Rate	Data lacking				
Flammability					
Flash Point	Data lacking	UEL	Data lacking		
LEL	Data lacking	Autoignition	Data lacking		
Flammability (solid, gas)	Data lacking				
Environmental					
Octanol/Water Partition coefficient	Data lacking				

9.2 Other Information

No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4 Conditions to avoid

Excess heat.

10.5 Incompatible materials

Nitrogen reacts with Li, Nd, and Ti at high temperatures.

10.6 Hazardous decomposition products

Nitric Oxide will react with water or moist air to form nitrogen dioxide and other oxides
of nitrogen. Nitric Oxide can produce brownish Nitrogen Dioxide after reaction with
oxygen.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Components					
Nitric oxide (0.0005% TO 0.02%)	10102 42 0	Acute Toxicity: Inhalation-Rat LC50 • 160 mg/m³;			
Nittic Oxide (0.0005% 10 0.02%)	10102-43-9	Mutagen: Mutation in Mammalian Somatic Cells • Inhalation-Rat • 27 ppm 3 Hour(s)-Continuous			

GHS Properties	Classification
A cute to visitu	EU/CLP • Classification criteria not met
Acute toxicity	OSHA HCS 2012 Classification criteria not met

No data available

Aspiration Hazard	EU/CLP Classification criteria not met OSHA HCS 2012 Classification criteria not met
Carcinogenicity	EU/CLP Classification criteria not met OSHA HCS 2012 Classification criteria not met
Germ Cell Mutagenicity	EU/CLP Classification criteria not met OSHA HCS 2012 Classification criteria not met
Skin corrosion/Irritation	EU/CLP Classification criteria not met OSHA HCS 2012 Classification criteria not met
Skin sensitization	EU/CLP Classification criteria not met OSHA HCS 2012 Classification criteria not met
STOT-RE	EU/CLP Classification criteria not met OSHA HCS 2012 Classification criteria not met
STOT-SE	EU/CLP ◆ Classification criteria not met OSHA HCS 2012 ◆ Classification criteria not met
Toxicity for Reproduction	EU/CLP Classification criteria not met OSHA HCS 2012 Classification criteria not met
Respiratory sensitization	EU/CLP ◆ Classification criteria not met OSHA HCS 2012 ◆ Classification criteria not met
Serious eye damage/Irritation	EU/CLP Classification criteria not met OSHA HCS 2012 Classification criteria not met

Potential Health Effects Inhalation

Acute (Immediate)

• This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces. If this material is released in a small, poorly ventilated area (i.e. an enclosed or confined space), an oxygen-deficient environment may occur. Individuals breathing such an atmosphere may experience symptoms which include headaches, ringing in ears, dizziness, drowsiness, unconsciousness, nausea, vomiting, and depression of all the senses. Under some circumstances of over-exposure, death may occur. The following effects associated with decreased levels of oxygen: increase in breathing and pulse rate, emotional upset, abnormal fatigue, nausea, vomiting, collapse, loss of consciousness, convulsive movements, respiratory collapse and death.

Chronic (Delayed)

Skin

Acute (Immediate)

Chronic (Delayed)

Eye

Acute (Immediate)

Chronic (Delayed)

Ingestion

Acute (Immediate)

Chronic (Delayed)

Under normal conditions of use, no health effects are expected.

Under normal conditions of use, no health effects are expected.

Under normal conditions of use, no health effects are expected.

Under normal conditions of use, no health effects are expected.

- Ingestion is not anticipated to be a likely route of exposure to this product.
- Ingestion is not anticipated to be a likely route of exposure to this product.

Key to abbreviations

LC = Lethal Concentration

Section 12 - Ecological Information

Format: EU CLP/REACH Language: English (US) WHMIS, EU CLP, EU DSD/DPD, OSHA HCS 2012

12.1 Toxicity

Material data lacking.

12.2 Persistence and degradability

Material data lacking.

12.3 Bioaccumulative potential

Material data lacking.

12.4 Mobility in Soil

Material data lacking.

12.5 Results of PBT and vPvB assessment

PBT and vPvB assessment has not been conducted for this material.

12.6 Other adverse effects

No studies have been found.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1956	Compressed gas, n.o.s (Nitric Oxide, Nitrogen)	2.2	NDA	NDA
TDG	UN1956	COMPRESSED GAS, N.O.S. (Nitric Oxide, Nitrogen)	2.2	NDA	Potential Marine Pollutant
IMO/IMDG	UN1956	COMPRESSED GASES, N.O.S., (Nitric Oxide, Nitrogen)	2.2	NDA	NDA
IATA/ICAO	UN1956	Compressed gases, n.o.s. (Nitric Oxide, Nitrogen)	2.2	NDA	NDA

14.6 Special precautions for user

Cylinders should be transported in a secure position, in a well-ventilated vehicle. The
transportation of compressed gas cylinders in automobiles or in closed-body vehicles
can present serious safety hazards. If transporting these cylinders in vehicles, ensure
these cylinders are not exposed to extremely high temperatures (as may occur in an
enclosed vehicle on a hot day). Additionally, the vehicle should be well-ventilated
during transportation.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Pressure(Sudden Release of), Acute

State Right To Know						
Component CAS MA NJ PA						
Nitrogen	7727-37-9	Yes	Yes	Yes		
Nitric oxide	10102-43-9	Yes	Yes	Yes		

Inventory						
Component	CAS	Canada DSL	Canada NDSL	China	EU EINECS	EU ELNICS
Nitrogen	7727-37-9	Yes	No	Yes	Yes	No
Nitric oxide	10102-43-9	Yes	No	Yes	Yes	No
			Inventory (Cor	า't.)		
Component	Component CAS TSCA					
Nitrogen			7727-37-9		Yes	
Nitric oxide		101	02-43-9		Yes	

Canada

Canada - WHMIS - Classifications of Substances		
Nitric oxide	10102-43-9	A, C, D1A, E
Nitrogen	7727-37-9	A
Canada - WHMIS - Ingredient Disclosure List		
Nitric oxide	10102-43-9	1 %
Nitrogen	7727-37-9	Not Listed

Environment Canada - CEPA - Priority Substances List		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed

China

China - Ozone Depleting Substances - First Schedule		
Nitric oxide	10102-43-9	Not Listed
• Nitrogen	7727-37-9	Not Listed
China - Ozone Depleting Substances - Second Schedule		
Nitric oxide	10102-43-9	Not Listed
• Nitrogen	7727-37-9	Not Listed
China - Ozone Depleting Substances - Third Schedule		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed

Other

China - Annex I & II - Controlled Chemicals Lists

• Nitric oxide 10102-43-9 Not Listed

Nitrogen	7727-37-9 Not Listed	
China - Dangerous Goods List		
Nitric oxide	10102-43-9	
Nitrogen	7727-37-9 (compressed or refrigerated liquid)	
China - Export Control List - Part I Chemicals		
Nitric oxide	10102-43-9 Not Listed	
Nitrogen	7727-37-9 Not Listed	

Europe

other		
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification		
Nitric oxide	10102-43-9	Not Listed
• Nitrogen	7727-37-9	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases		
Nitric oxide	10102-43-9	Not Listed
• Nitrogen	7727-37-9	Not Listed

Germany

Nitric oxide	10102-43-9	inorganic gas Substance:
THIRD OXIGO	10102 10 0	5.2.4, Class IV
• Nitrogen	7727-37-9	Not Listed
Germany - Water Classification (VwVwS) - Annex 1		
Nitric oxide	10102-43-9	Not Listed
		ID Number 1351, not
Nitrogen	7727-37-9	considered hazardous to water
Germany - Water Classification (VwVwS) - Annex 2 - Water Hazard Classes		
Nitric oxide	10102-43-9	ID Number 285, hazard clas - low hazard to waters
Nitrogen	7727-37-9	Not Listed
Germany - Water Classification (VwVwS) - Annex 3		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed

Other		
Germany - Specifically Regulated Chemicals in TRGS		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed
Portugal		
Other		
Portugal - Prohibited Substances		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed
Jnited Kingdom		
Environment United Kingdom - Pollution Inventory - Schedule 1 - Thresholds for Releases to	Air	
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed
Other		
United Kingdom - Workplace Exposure Limits (WELs) - Substances in Review		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed
United Kingdom - List of Dangerous Substances in Water		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed
Jnited States		
Labor		
U.S OSHA - Process Safety Management - Highly Hazardous Chemicals	10100 10 0	
Nitric oxide	10102-43-9	250 lb TQ
Nitrogen	7727-37-9	Not Listed
U.S OSHA - Specifically Regulated Chemicals		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed
Environment		
U.S CAA (Clean Air Act) - 1990 Hazardous Air Pollutants		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed
U.S CERCLA/SARA - Hazardous Substances and their Reportable Quantities		
Nitric oxide	10102-43-9	10 lb final RQ (releases to the air in amounts <1000 pounds per 24 hours which are the result of combustion and combustion-related activities are exempt from the notification requirements per 40 CFR 302.6); 4.54 kg final RQ (releases to the air in

Preparation Date: 17/October/2014 Revision Date: 17/October/2014 amounts <1000 pounds per 24 hours which are the result of

 Nitrogen U.S CERCLA/SARA - Radionuclides and Their Reportable Quantities Nitric oxide Nitrogen 	7727-37-9 10102-43-9 7727-37-9	combustion and combustion- related activities are exempt from the notification requirements per 40 CFR 302.6) Not Listed Not Listed Not Listed
Tallogon	1121 31 3	Not Elated
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs		
• Nitric oxide	10102-43-9	10 lb EPCRA RQ (Releases to the air in amounts <1000 pounds per 24 hours which are the result of combustion and combustion-related activities are exempt from the notification requirements per 40 CFR 355.31)
Nitrogen	7727-37-9	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs		
Nitric oxide	10102-43-9	100 lb TPQ
Nitrogen	7727-37-9	Not Listed
U.S CERCLA/SARA - Section 313 - Emission Reporting		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed
U.S CERCLA/SARA - Section 313 - PBT Chemical Listing		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed
U.S RCRA (Resource Conservation & Recovery Act) - Hazardous Constituents - A	Annendiy VIII to	40 CER 261
Nitric oxide	10102-43-9	waste number P076
Nitrogen	7727-37-9	Not Listed
U.S RCRA (Resource Conservation & Recovery Act) - P Series Wastes - Acutely	Toxic Wastes	
Nitric oxide	10102-43-9	waste number P076
Nitrogen	7727-37-9	Not Listed

United States - California

Environment U.S California - Proposition 65 - Carcinogens List			
Nitric oxide	10102-43-9	Not Listed	
• Nitrogen	7727-37-9	Not Listed	
U.S California - Proposition 65 - Developmental Toxicity			
Nitric oxide	10102-43-9	Not Listed	
• Nitrogen	7727-37-9	Not Listed	
U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL	-)		
Nitric oxide	10102-43-9	Not Listed	
Nitrogen	7727-37-9	Not Listed	

Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Female		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Male		
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed

United States - Pennsylvania

r Pennsylvania - RTK (Right to Know) - Environmental H	lazard List	
• Nitric oxide	10102-43-9	
Nitrogen	7727-37-9	Not Listed
J.S Pennsylvania - RTK (Right to Know) - Special Hazardo	us Substances	
Nitric oxide	10102-43-9	Not Listed
Nitrogen	7727-37-9	Not Listed

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out.

Section 16 - Other Information

Relevant Phrases (code & full text)

- H314 Causes severe skin burns and eye damage.
 - H318 Causes serious eye damage
 - H370 Causes damage to organs.
 - R8 Contact with combustible material may cause fire.
 - R34 Causes burns.
- **Last Revision Date**
- **Preparation Date**
- Disclaimer/Statement of Liability
- 17/October/2014
- 17/October/2014
- To the best of Air Liquide's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this gas mixture is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

Key to abbreviations

NDA = No Data Available