SUPPLIER MATERIAL SAFETY DATA SHEET (MSDS)

N/A=Not Applicable Flammability: **Manufacturer: ESTEAM Product: ULTRA RELEASE** Reactivity: 0

Use: Rinse extraction concentrate

N/D=Not Determined

NFPA LEAST=0, SLIGHT=1, MODERATE=2, HIGH=3, EXTREME=4

Freeze/Thaw

N/D

Trade Name: Ultra Release Chem. Name: N/A Health: **Protection:** Chem. Family: Mixture

HAZARDOUS INGREDIENTS CAS# % WT **EXPOSURE LIMITS (TLV)** HAZARD DATA

Hydroxyacetic Acid LD50 50 4240 mg/kg (oral-rat) 79-14-1 30-80 N/A

PHYSICAL DATA

Stable: Physical Liquid Solubility Boiling **Evaporation** Percent State: Point (C): N/D in Water: 100% Rate: N/D Volatile (vol): N/D Odor/ Blue, clear, floral

Specific **Freezing** Vapor Appearance: Point (Č): N/D (undiluted): 2.2 N/D **Gravity:** Pressure:

FIRE & EXPLOSION HAZARD Conditions: N/A

Hazardous Combustion Products: May generate H2 on metal contact. Flammability: N

Means of Extinction: Upper Explosion Limit (% by vol): Lower Explosion Limit (% by vol): Special Procedures: N/A N/A

Corrosive Liquid N.O.S. Auto-ignition: Explosion Sensitivity to Impact: N/A (Glycolic Acid) Class 8 UN#

TDG/WHMIS: 1760 PG II / E, D2B Rate of Burning: N/A Chemical Sensitivity to Static Discharge: N/A **Explosive Power:** N/A Flashpoint (C) & Method: N/A

REACTIVITY DATA Chemical Stability: Stable

Incompatible Substances: Most metals, yielding hydrogen gas. Hazardous Decomposition Product: N/D

N/D

TOXICOLOGICAL PROPERTIES

Vapour may be irritating to nose, throat. Eyes: product can cause Reproductive Effects Y/N: N Route of Entry - Skin Contact: severe burns. Skin: prolonged contact can cause burns. Ingestion: Route of Entry - Skin Absorption: Carcinogenicity Y/N: Ν Υ may cause corrosion of mucous membranes with stomach Route of Entry - Eye Contact: Mutagenicity Y/N: Ν Υ

discomfort, nausea and prostration. Route of Entry - Inhalation: Teratogenicity Y/N: Ν Υ Chronic Effects:

PREVENTATIVE Gloves: Impervious Footwear: Boots Clothing: N/A **MEASURES** Eyes: Safety glasses Respirator: N/A Other:

N/A Special Handling Procedures:

Recommended Engineered Controls: Leak & Spill Procedures: Waste Disposal Methods: Use with adequate ventilation. Neutralize with alkaline material. According to federal, provincial and

Flush area with water. municipal regulations.

Keep container tightly closed. Store in a cool, dry place away from children.

Effects of Overexposure:

Acute Effects:

FIRST AID MEASURES

CLEANING SYSTEMS

Source Material:

Route of Entry - Ingestion:

Inhalation: Move person to fresh air. If necessary give artificial respiration or oxygen. Call a doctor if in distress.

Ingestion: Contact a physician. Do not induce vomiting. Give large quantities of water.

Eye Contact: Immediately flush eyes with running water for at least 15 minutes. Contact a physician if irritation persists.

Skin Contact: Immediately flush skin for at least 15 minutes. Launder clothing before reuse. Contact a physician if irritation persists.

Prep./Revised Date: Mailing Address: Esteam Manufacturing Ltd. January 15, 2015

3750-19th Street NE Calgary, AB T2E 6V2 Prepared By:

R. Russell

Emergency Response: 1-613-996-6666 (Transport Emergencies)

Manufacturer's MSDS

This information is complete to the best of our knowledge, however, users are encouraged to make their own investigations into the suitability of the information to their particular purposes. READ THE LABEL before using this or any product, and take any necessary precautions, dictated by the label or by common sense to ensure that your health is protected.