

# Hydrogen (0.0001% - 99.0000%), Hydrogen Sulfide (0.0001% - 0.9999%) in Methane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 10/22/2014

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Product name : Hydrogen (0.0001% - 99.0000%), Hydrogen Sulfide (0.0001% - 0.9999%) in Methane  
 Product code : SG-2003-00612

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

#### 1.3. Details of the supplier of the safety data sheet

Air Liquide America Specialty Gases  
 6141 Easton Rd  
 Plumsteadville, PA 18949 - USA  
 T 1.800.217.2688  
[www.airliquide.com](http://www.airliquide.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Gas 1 H220  
 Compressed gas H280

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US)



GHS02

GHS04

Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H220 - Extremely flammable gas  
 H280 - Contains gas under pressure; may explode if heated  
 OSHA-H01 - May displace oxygen and cause rapid suffocation  
 CGA-HG04 - May form explosive mixtures with air  
 CGA-HG16 - Extended exposure to gas reduces the ability to smell sulfides.

Precautionary statements (GHS-US)

: P202 - Do not handle until all safety precautions have been read and understood  
 P210 - Keep away from heat, open flames, sparks. - No smoking  
 P220 - Keep/Store away from clothing, combustible materials  
 P271 - Use only outdoors or in a well-ventilated area  
 P280 - Wear protective gloves, protective clothing, eye protection, face protection  
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
 P308+P313 - If exposed or concerned: Get medical advice/attention  
 P312 - Call a doctor if you feel unwell  
 P370+P376 - In case of fire: Stop leak if safe to do so  
 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely  
 P381 - Eliminate all ignition sources if safe to do so  
 P403 - Store in a well-ventilated place  
 P501 - Dispose of contents/container in accordance with local/regional/national/international regulations  
 CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)  
 CGA-PG05 - Use a back flow preventive device in the piping  
 CGA-PG06 - Close valve after each use and when empty  
 CGA-PG10 - Use only with equipment rated for cylinder pressure  
 CGA-PG14 - Approach suspected leak area with caution  
 CGA-PG21 - Open valve slowly

# Hydrogen (0.0001% - 99.0000%), Hydrogen Sulfide (0.0001% - 0.9999%) in Methane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Methane	(CAS No)74-82-8	0.0001 - 99.9998	Flam. Gas 1, H220 Compressed gas, H280
Hydrogen	(CAS No)1333-74-0	0.0001 - 99	Flam. Gas 1, H220 Compressed gas, H280
Hydrogen sulfide	(CAS No)7783-06-4	0.0001 - 0.9999	Flam. Gas 1, H220 Liquefied gas, H280 Acute Tox. 2 (Inhalation:gas), H330 STOT SE 3, H335

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : Adverse effects not expected from this product.
- First-aid measures after eye contact : Adverse effects not expected from this product.
- First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Symptoms similar to those listed under inhalation.
- Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation. If you feel unwell, seek medical advice.
- Symptoms/injuries after skin contact : Adverse effects not expected from this product.
- Symptoms/injuries after eye contact : Adverse effects not expected from this product.
- Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.
- Symptoms/injuries upon intravenous administration : Not known.
- Chronic symptoms : None known.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : This product is flammable. Extremely flammable gas.
- Explosion hazard : May form flammable/explosive vapor-air mixture. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Reactivity : None known.

### 5.3. Advice for firefighters

- Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

# Hydrogen (0.0001% - 99.0000%), Hydrogen Sulfide (0.0001% - 0.9999%) in Methane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation.

##### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment consistent with the site emergency plan.  
Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

##### 6.1.2. For emergency responders

Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.  
Emergency procedures : Evacuate and limit access. Ventilate area. Remove ignition sources. Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering atmospheres of unknown contaminant concentration until proven to be safe.

#### 6.2. Environmental precautions

Try to stop release if safe to do so.

#### 6.3. Methods and material for containment and cleaning up

For containment : Try to stop release if safe to do so.  
Methods for cleaning up : Dispose of this material and its container in accordance with local regulations.

#### 6.4. Reference to other sections

See also Sections 8 and 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Handle empty containers with care because residual vapors are flammable. In use, may form flammable vapor-air mixture. Close valve after each use and when empty.  
Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area.  
Hygiene measures : Do not eat, drink or smoke when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.  
Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage.  
Incompatible products : None known.  
Incompatible materials : Air. Oxidizing materials.

#### 7.3. Specific end use(s)

Test gas/Calibration gas.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Hydrogen (1333-74-0)

##### Methane (74-82-8)

USA ACGIH	ACGIH TWA (ppm)	1000 ppm
-----------	-----------------	----------

##### Hydrogen sulfide (7783-06-4)

USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA ACGIH	ACGIH STEL (ppm)	5 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	20 ppm

# Hydrogen (0.0001% - 99.0000%), Hydrogen Sulfide (0.0001% - 0.9999%) in Methane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.2. Exposure controls

Appropriate engineering controls	: Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Ensure exposure is below occupational exposure limits. Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit system e.g. for maintenance activities.
Hand protection	: Wear working gloves when handling gas containers. 29CFR 1910.138: Hand Protection.
Eye protection	: Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.
Respiratory protection	: None necessary during normal and routine operations.
Thermal hazard protection	: None necessary during normal and routine operations.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
Other information	: Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Clear, colorless gas.
Color	: Colorless
Odor	: odorless
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable for gas-mixtures.
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Relative gas density	: Lighter or similar to air.
Solubility	: Water: Solubility in water of component(s) of the mixture : • : 1.6 mg/l • : 3980 mg/l • : 26 mg/l
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: None.
Explosive limits	: No data available

### 9.2. Other information

Additional information	: None.
------------------------	---------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None known.

### 10.2. Chemical stability

Stable under normal conditions.

# Hydrogen (0.0001% - 99.0000%), Hydrogen Sulfide (0.0001% - 0.9999%) in Methane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.3. Possibility of hazardous reactions

Can form explosive mixture with air.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Air. Oxidizing materials.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Hydrogen (1333-74-0)	
LC50 inhalation rat (ppm)	410000 ppm/4h

Methane (74-82-8)	
LC50 inhalation rat (ppm)	410000 ppm/4h
ATE US (gases)	410000.00000000 ppmV/4h

Hydrogen sulfide (7783-06-4)	
LC50 inhalation rat (mg/l)	0.99 mg/l (Exposure time: 1 h)
LC50 inhalation rat (ppm)	356 ppm/4h
ATE US (gases)	356.00000000 ppmV/4h
ATE US (vapors)	0.99000000 mg/l/4h
ATE US (dust, mist)	0.99000000 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation. If you feel unwell, seek medical advice.

Symptoms/injuries after skin contact : Adverse effects not expected from this product.

Symptoms/injuries after eye contact : Adverse effects not expected from this product.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous administration : Not known.

Chronic symptoms : None known.

## SECTION 12: Ecological information

### 12.1. Toxicity

Hydrogen sulfide (7783-06-4)	
LC50 fish 1	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
EC50 Daphnia 1	0.022 mg/l (Exposure time: 96 h - Species: Gammarus pseudolimnaeus)
LC50 fish 2	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

# Hydrogen (0.0001% - 99.0000%), Hydrogen Sulfide (0.0001% - 0.9999%) in Methane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.2. Persistence and degradability

Hydrogen (1333-74-0)	
Persistence and degradability	No ecological damage caused by this product.
Methane (74-82-8)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist. No data available.
Hydrogen sulfide (7783-06-4)	
Persistence and degradability	Not applicable for inorganic gases.

### 12.3. Bioaccumulative potential

Hydrogen (1333-74-0)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	Not applicable for inorganic gases.
Bioaccumulative potential	No ecological damage caused by this product.
Methane (74-82-8)	
Log Pow	1.09
Log Kow	Not applicable for gas-mixtures.
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Hydrogen sulfide (7783-06-4)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	Not applicable for inorganic gases.
Bioaccumulative potential	No data available.

### 12.4. Mobility in soil

Hydrogen (1333-74-0)	
Ecology - soil	No ecological damage caused by this product.
Methane (74-82-8)	
Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Hydrogen sulfide (7783-06-4)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

### 12.5. Other adverse effects

Effect on ozone layer	: No additional information available
Effect on the global warming	: Contains greenhouse gas(es) not covered by 842/2006/EC.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into areas where there is a risk of forming an explosive mixture with air.
Waste disposal recommendations	: Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at <a href="http://www.cganet.com">www.cganet.com</a> for more guidance on suitable disposal methods.
Additional information	: None.

# Hydrogen (0.0001% - 99.0000%), Hydrogen Sulfide (0.0001% - 0.9999%) in Methane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1954 Compressed gas, flammable, n.o.s., 2.1  
UN-No.(DOT) : 1954  
DOT NA no. : UN1954  
Proper Shipping Name (DOT) : Compressed gas, flammable, n.o.s.  
Department of Transportation (DOT) Hazard Classes : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115  
Hazard labels (DOT) : 2.1 - Flammable gas



DOT Symbols : G - Identifies PSN requiring a technical name  
DOT Packaging Exceptions (49 CFR 173.xxx) : 306  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;305  
DOT Packaging Bulk (49 CFR 173.xxx) : 314;315  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Forbidden  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg  
DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.  
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

### Additional information

Other information : No supplementary information available.

### ADR

Transport document description : UN 1954, 2.1, (B/D)  
Class (ADR) : 2 - Gases  
Hazard identification number (Kemler No.) : 23  
Classification code (ADR) : 1F  
Hazard labels (ADR) : 2.1 - Flammable gases



Orange plates



Tunnel restriction code (ADR) : B/D  
LQ : 0  
Excepted quantities (ADR) : E0

### Transport by sea

UN-No. (IMDG) : 1954  
Proper Shipping Name (IMDG) : COMPRESSED GAS, FLAMMABLE, N.O.S.  
Class (IMDG) : 2.1 - Flammable gases

### Air transport

# Hydrogen (0.0001% - 99.0000%), Hydrogen Sulfide (0.0001% - 0.9999%) in Methane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No.(IATA)	: 1954
Proper Shipping Name (IATA)	: COMPRESSED GAS, FLAMMABLE, N.O.S.
Class (IATA)	: 2

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

Hydrogen sulfide (7783-06-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Listed on United States SARA Section 313	
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 313 - Emission Reporting	1.0 %

#### 15.2. International regulations

##### CANADA

Hydrogen (1333-74-0)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
Methane (74-82-8)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
Hydrogen sulfide (7783-06-4)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

##### EU-Regulations

Hydrogen sulfide (7783-06-4)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

##### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

#### 15.2.2. National regulations

Hydrogen sulfide (7783-06-4)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)

#### 15.3. US State regulations

Hydrogen (1333-74-0)
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
Methane (74-82-8)



# Hydrogen (0.0001% - 99.0000%), Hydrogen Sulfide (0.0001% - 0.9999%) in Methane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

<b>Hydrogen sulfide (7783-06-4)</b>
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

Indication of changes	: Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.
	:
Other information	: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Full text of H-phrases: see section 16:

Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Compressed gas	Gases under pressure Compressed gas
Flam. Gas 1	Flammable gases Category 1
Liquefied gas	Gases under pressure Liquefied gas
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H330	Fatal if inhaled
H335	May cause respiratory irritation

SDS US (GHS HazCom 2012)

*This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.*