## N/D=Not Determined SUPPLIER MATERIAL SAFETY DATA SHEET (MSDS)

N/A=Not Applicable Flammability: **Manufacturer: ESTEAM Product: CLEAN** Reactivity:

Trade Name: Clean Chem. Name: N/A Health: **Protection:** Chem. Family: Mixture Use: Carpet spotting compound

**HAZARDOUS INGREDIENTS** CAS # % WT HAZARD DATA **EXPOSURE LIMITS (TLV)** 

2-Butoxyethanol 111-76-2 .1-1 25 ppm TWA LD50 1746 mg/kg (oral-rat) N-Pentl Acetate 628-63-7 .1-1 100 ppm TWA LD50 6500 mg/kg (oral-rat)

Coconut Diethanolamide 68603-42-9 .1-1N/D LD50 2700 mg/kg (oral-rat)

Freeze/Thaw PHYSICAL DATA

Stable: Physical Liquid Solubility

Boiling **Evaporation** Percent State: Point (C): 102 in Water: 100% Rate: Volatile (vol): 95+ Odor/ Golden, candy Specific Freezing

Vapor Appearance: color Point (Č): N/D (undiluted): 9.0 **Gravity:** Approx 1 Pressure: As water

FIRE & EXPLOSION HAZARD Conditions: N/A

Hazardous Combustion Products: N/A Flammability: N Means of Extinction: N/A Upper Explosion Limit (% by vol):

Lower Explosion Limit (% by vol): Special Procedures: N/A N/A Auto-ignition: Explosion Sensitivity to Impact: N/A

Rate of Burning: TDG/WHMIS: Non Hazardous / D2B N/A Chemical Sensitivity to Static Discharge: N/A

**Explosive Power:** N/A Flashpoint (C) & Method: N/A

REACTIVITY DATA Chemical Stability: Stable

Hazardous Decomposition Product: Ammonia, CO, CO2 **Incompatable Substances:** Strong acids

TOXICOLOGICAL PROPERTIES

Reproductive Effects Y/N: N/D Route of Entry - Skin Contact: Carcinogenicity Y/N: Route of Entry - Skin Absorption: N/D Υ Route of Entry - Eye Contact: Mutagenicity Y/N: Υ N/D

Chronic Effects: Repeated or prolonged contact may cause defatting dermatitis. Route of Entry - Inhalation: Teratogenicity Y/N: N/D N

**PREVENTATIVE MEASURES** 

Route of Entry - Ingestion:

Gloves: Not required Footwear: N/A Clothing: N/A Eyes: Respirator: N/A Other: N/A

N/D

Recommended Engineered Controls: Use with adequate ventilation.

Local exhaust recommended.

Leak & Spill Procedures:

Mop up excess. Flush with water to a

sanitary sewer.

Waste Disposal Methods:

According to federal, provincial and

**Effects of Overexposure:** 

Acute Effects:

municipal regulations.

Special Handling Procedures: Keep container tightly closed. Store

in a cool dry place away from

0

NFPA LEAST=0, SLIGHT=1, MODERATE=2, HIGH=3, EXTREME=4

children.

May cause eye and skin irritation. May be harmful if swallowed.

FIRST AID MEASURES

Inhalation: No special procedures. Ingestion: Contact a physician.

**Eye Contact:** Immediately flush eyes with running water for at least 15 minutes. Contact a physician if irritation persists.

Skin Contact: Immediately flush skin for at least 15 minutes. Launder clothing before reuse. Contact a physician if irritation persists.

Prep./Revised Date: Mailing Address: Esteam Manufacturing Ltd. January 15, 2015

3750-19th Street NE Calgary, AB T2E 6V2 Prepared By: R. Russell

Source Material: Manufacturer's MSDS

Emergency Response: 1-613-996-6666 (Transport Emergencies)



This information is complete to the best of our knowledge, however, users are encouraged to make their own investigations into the suitability of the information to their particular purposes. READ THE LABEL before using this or any product, and take any necessary precautions, dictated by the label or by common sense to ensure that your health is protected.