## SUPPLIER MATERIAL SAFETY DATA SHEET (MSDS) N/D=Not Determine N/A=Not Applicable N/D=Not Determined

Manufacturer: ESTEAM Flammability: 1 Reactivity: 0 **Product: PRO GEL Health: Protection:** Use: Spotting agent

NFPA LEAST=0, SLIGHT=1, MODERATE=2, HIGH=3, EXTREME=4

**HAZARDOUS INGREDIENTS** %WT CAS# **HAZARD DATA EXPOSURE LIMITS (TLV)** 

5989-27-5 40-60 LD50 4400 mg/kg (oral-rat) N/D **D-limonene** 

Freeze/Thaw PHYSICAL DATA

Stable: Physical Gel Solubility Boiling **Evaporation** Percent **State:** Point (C): 100 in Water: N/A Rate: N/D Volatile (vol): N/D Odor/ Clear, citrus odor

**Freezing Specific** Vapor **Appearance:** (undiluted): N/A N/D N/D **Point** (**C**): -4 **Gravity: Pressure:** 

FIRE & EXPLOSION HAZARD Conditions: N/A

Hazardous Combustion Products: CO, CO2 Flammability: Yes **Upper Explosion Limit (% by vol):** Means of Extinction:

Special Procedures: Self contained breathing apparatus **Lower Explosion Limit (% by vol):** 

N/D **Auto-ignition: Explosion Sensitivity to Impact: N/A** 

TDG/WHMIS: Non hazardous / D2B, B2 Rate of Burning: N/D Chemical Sensitivity to Static Discharge: N/D

Explosive Power: N/D Flashpoint (C) & Method: N/D

Chemical Stability: Stable under normal conditions REACTIVITY DATA

Hazardous Decomposition Product: Oxides of carbon Incompatable Substances: Strong oxidizing agents

## TOXICOLOGICAL PROPERTIES

**Acute Effects:** Reproductive Effects Y/N:N/D **Route of Entry - Skin Contact:** Irritant to eyes and skin. Excessive inhalation of vapors may cause Carcinogenicity Y/N: nasal and respiratory irritation. If swallowed may cause Route of Entry - Skin Absorption: N N/D gastrointestinal irritation. **Route of Entry - Eye Contact:** Mutagenicity Y/N: N/D

**Chronic Effects: Route of Entry - Inhalation:** Teratogenicity Y/N: Υ N/D None known **Route of Entry - Ingestion:** N/D

**PREVENTATIVE MEASURES** 

Gloves: Impervious Footwear: Not normally required **Clothing: Eyes:** Chemical glasses Respirator: Not normally required Other: N/A

Recommended Engineered Controls: Use with adequate ventilation.

**Leak & Spill Procedures:** 

Soak up with inert absorbent and place in appropriate closed container

for disposal.

**Waste Disposal Methods:** 

According to federal, provincial and

**Effects of Overexposure:** 

municipal regulations.

**Special Handling Procedures:** 

Store in a cool, dry place. Keep

closed when not in use.

## FIRST AID MEASURES

Inhalation: Move person to fresh air. If necessary give artificial respiration or oxygen. Call a doctor if in distress.

**Ingestion:** Immediately rinse mouth and throat thoroughly with water. Call a physician.

**Eye Contact:** Immediately flush eyes with running water for at least 15 minutes. Contact a physician if irritation persists.

Skin Contact: Immediately flush skin with running water for at least 15 minutes. Launder clothing before reuse. If irritation persists get medical

**Prep./Revised Date:** Mailing Address: Esteam Manufacturing Ltd. January 15, 2017

**Prepared By:** R. Russell

3750-19th Street NE Calgary, AB T2E 6V2

Emergency Response: 1-613-996-6666 (Transport Emergencies)

Manufacturer's MSDS



**Source Material:** 

This information is complete to the best of our knowledge, however, users are encouraged to make their own investigations into the suitability of the information to their particular purposes. READ THE LABEL before using this or any product, and take any necessary precautions, dictated by the label or by common sense to ensure that your health is protected.