SUPPLIER MATERIAL SAFETY DATA SHEET (MSDS) N/D=Not Determined N/A=Not Applicable

Flammability: 0 Manufacturer: ESTEAM **Product: Tile & Grout Sealer Reactivity:** 0 Trade Name: Tile & Grout Sealer Chem. Name: N/A Health:

Protection: Chem. Family: Mixture Use: Tile & Grout Sealant NFPA LEAST=0, SLIGHT=1, MODERATE=2, HIGH=3, EXTREME=4

HAZARDOUS INGREDIENTS CAS# %WT **HAZARD DATA EXPOSURE LIMITS (TLV)**

Perfluoroalkyl Methacrylic Copolymer 1-3 LD50 11000 mg/kg (oral rat) 10 mg/m3

PHYSICAL DATA

Stable: stable Physical Liquid Solubility Boiling **Evaporation** Percent **State:** Point (C): N/D in Water: 100 % N/D Volatile (vol): N/D

Odor/ Slight odor, water Freezing **Specific** Vapor **Appearance:** Point (Č): 0 (undiluted): 4.3 1.01 N/D **Gravity: Pressure:**

FIRE & EXPLOSION HAZARD Conditions: N/A

Hazardous Combustion Products: N/A Flammability: N/A **Means of Extinction: Upper Explosion Limit (% by vol):** Special Procedures: N/A **Lower Explosion Limit (% by vol):** N/A

Auto-ignition: N/A **Explosion Sensitivity to Impact: N/A** N/A Rate of Burning:

Chemical Sensitivity to Static Discharge: N/A **Explosive Power:** N/A Flashpoint (C) & Method: N/D

Chemical Stability: Stable REACTIVITY DATA

Hazardous Decomposition Product: Carbon dioxide, hydrogen fluoride, Incompatable Substances: None known

TOXICOLOGICAL PROPERTIES

Reproductive Effects Y/N: N **Route of Entry - Skin Contact:** Carcinogenicity Y/N: Route of Entry - Skin Absorption: N **Route of Entry - Eye Contact:** Mutagenicity Y/N: Υ

Ν **Chronic Effects:** Route of Entry - Inhalation: Teratogenicity Y/N: Υ N/D

Route of Entry - Ingestion: N/D

PREVENTATIVE Gloves: Recommended Footwear: N/A Clothing: N/A

MEASURES Respirator: Air borne exposure. Other: chemical resistant glasses

Recommended Engineered Controls: Use with adequate ventilation.

Leak & Spill Procedures:

Waste Disposal Methods: Soak up with absorbent material. According to federal, provincial and

Ν

Industrial use only. Keep out of municipal regulations. reach of children.

Effects of Overexposure:

No information found.

Acute Effects:

Freeze/Thaw

Special Handling Procedures:

TDG/WHMIS: D2B

May cause eye & throat irritation. Large amount inhalation of

respirable particles may cause pulmonary edema.

FIRST AID MEASURES

Inhalation: Move person to fresh air. If necessary give artificial respiration or oxygen. Call doctor if in distress.

Ingestion: Immediately rinse mouth and throat thoroughly with water. Call a physician. Immediately flush eyes with water for at least 15 minutes. Call a physician. **Eye Contact:**

Skin Contact: Immediately flush skin with running water for at least 15 minutes. Launder clothing before reuse. Contact a physician if irritation persists.

Prep./Revised Date: Mailing Address: Esteam Manufacturing Ltd. January 15, 2017

3750-19th Street NE Calgary, AB T2E 6V2 **Prepared By:**

R. Russell

Emergency Response: 1-613-996-6666 (Transport Emergencies)

Manufacturer's MSDS

Source Material:

This information is complete to the best of our knowledge, however, users are encouraged to make their own investigations into the suitability of the information to their particular purposes. READ THE LABEL before using this or any product, and take any necessary precautions, dictated by the label or by common sense to ensure that your health is protected.