

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Isopropyl Alcohol (0.00001% - 1.00%) in Water
Product code : SG-2002-02462

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Details of the supplier of the safety data sheet

Air Liquide
2700 Post Oak Boulevard
Houston, TX 77056 - USA
T 1-800-819-1704
www.us.airliquide.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Liquefied gas H280

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS04

Signal word (GHS-US) : Warning
Hazard statements (GHS-US) : H280 - Contains gas under pressure; may explode if heated
Precautionary statements (GHS-US) : P202 - Do not handle until all safety precautions have been read and understood
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection, face protection, protective gloves, protective clothing
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P308+P313 - If exposed or concerned: Get medical advice/attention
P403 - Store in a well-ventilated place
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)
CGA-PG05 - Use a back flow preventive device in the piping
CGA-PG06 - Close valve after each use and when empty
CGA-PG10 - Use only with equipment rated for cylinder pressure
CGA-PG14 - Approach suspected leak area with caution
CGA-PG21 - Open valve slowly

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Isopropyl Alcohol (0.00001% - 1.00%) in Water

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Water	(CAS No) 7732-18-5	99 - 99.99999	Not classified
Isopropyl alcohol	(CAS No) 67-63-0	0.00001 - 1	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Adverse effects not expected from this product.
- First-aid measures after skin contact : Adverse effects not expected from this product.
- First-aid measures after eye contact : Adverse effects not expected from this product.
- First-aid measures after ingestion : Adverse effects not expected from this product.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Adverse effects not expected from this product.
- Symptoms/injuries after skin contact : Adverse effects not expected from this product.
- Symptoms/injuries after eye contact : Adverse effects not expected from this product.
- Symptoms/injuries after ingestion : Adverse effects not expected from this product.
- Symptoms/injuries upon intravenous administration : Not known.
- Chronic symptoms : Adverse effects not expected from this product.

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : The product is not flammable.
- Explosion hazard : Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Reactivity : None known.

5.3. Advice for firefighters

- Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Ensure adequate ventilation.

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment consistent with the site emergency plan.
- Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

6.1.2. For emergency responders

- Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.
- Emergency procedures : Evacuate and limit access. Ventilate area.

6.2. Environmental precautions

Try to stop release if safe to do so.

Isopropyl Alcohol (0.00001% - 1.00%) in Water

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

- For containment : Try to stop release if safe to do so.
Methods for cleaning up : Dispose of this material and its container in accordance with local regulations.

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Close valve after each use and when empty.
Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.
Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area.
Incompatible products : None known.
Incompatible materials : None known.

7.3. Specific end use(s)

See Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Isopropyl Alcohol (0.00001% - 1.00%) in Water		
ACGIH	Not applicable	
OSHA	Not applicable	
Isopropyl alcohol (67-63-0)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	400 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	400 ppm
Water (7732-18-5)		
ACGIH	Not applicable	
OSHA	Not applicable	

8.2. Exposure controls

- Appropriate engineering controls : Ensure exposure is below occupational exposure limits. Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Consider work permit system e.g. for maintenance activities.
Hand protection : Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection.
Eye protection : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection : Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.
Respiratory protection : None necessary during normal and routine operations. See Sections 5 & 6.
Thermal hazard protection : None necessary during normal and routine operations.
Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
Other information : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
Appearance : Clear, colorless liquid.

Isopropyl Alcohol (0.00001% - 1.00%) in Water

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Color	: Colorless
Odor	: Like rubbing alcohol
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: Not applicable - not flammable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: See Section 2.1 and 2.2
Explosion limits	: Not applicable - not flammable
Explosive properties	: Not applicable - not flammable.
Oxidizing properties	: None.
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Molecular mass	: No Data Available
Relative gas density	: Heavier than air
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Isopropyl alcohol (67-63-0)	
LD50 oral rat	4396 mg/kg
LD50 dermal rabbit	12800 mg/kg
LC50 inhalation rat (ppm)	22624 ppm/4h (Exposure time: 8 h)

Isopropyl Alcohol (0.00001% - 1.00%) in Water

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Isopropyl alcohol (67-63-0)	
ATE US (oral)	4396.000 mg/kg body weight
ATE US (dermal)	12800.000 mg/kg body weight
ATE US (gases)	22624.000 ppmV/4h

Water (7732-18-5)	
LC50 inhalation rat (ppm)	820000 ppm/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Isopropyl alcohol (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Adverse effects not expected from this product.
Symptoms/injuries after skin contact	: Adverse effects not expected from this product.
Symptoms/injuries after eye contact	: Adverse effects not expected from this product.
Symptoms/injuries after ingestion	: Adverse effects not expected from this product.
Symptoms/injuries upon intravenous administration	: Not known.
Chronic symptoms	: Adverse effects not expected from this product.

SECTION 12: Ecological information

12.1. Toxicity

Isopropyl alcohol (67-63-0)	
LC50 fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	> 1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
LC50 fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 other aquatic organisms 2	> 1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Isopropyl alcohol (67-63-0)	
Log Pow	0.05 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer	: No known effects from this product.
Effect on the global warming	: No known ecological damage caused by this product.

Isopropyl Alcohol (0.00001% - 1.00%) in Water

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded.
- Waste disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3500 Chemical under pressure, n.o.s. (Isopropyl Alcohol, Water), 2.2

UN-No.(DOT) : UN3500

Proper Shipping Name (DOT) : Chemical under pressure, n.o.s.

Transport hazard class(es) (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : 335

DOT Packaging Bulk (49 CFR 173.xxx) : 313;315

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) : None

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Additional information

Other information : No supplementary information available.

ADR

Transport document description : UN 3500 CHEMICAL UNDER PRESSURE, N.O.S., 2.2, (C/E)

Class (ADR) : 2 - Gases

Classification code (ADR) : 8A

Hazard labels (ADR) : 2.2 - Non-flammable compressed gas



Tunnel restriction code (ADR) : C/E

Limited quantities (ADR) : 0

Excepted quantities (ADR) : E0

Transport by sea

UN-No. (IMDG) : 3500

Isopropyl Alcohol (0.00001% - 1.00%) in Water

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (IMDG) : Chemical under pressure, n.o.s
Class (IMDG) : 2 - Gases

Air transport

UN-No. (IATA) : 3500
Proper Shipping Name (IATA) : Chemical under pressure, n.o.s
Class (IATA) : 2.2 - Gases : Non-flammable, non-toxic

SECTION 15: Regulatory information

15.1. US Federal regulations

Isopropyl alcohol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 % (only if manufactured by the strong acid process, no supplier notification)

Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	---

EU-Regulations

Isopropyl alcohol (67-63-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Water (7732-18-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

National regulations

Isopropyl alcohol (67-63-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)

Water (7732-18-5)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

Isopropyl Alcohol (0.00001% - 1.00%) in Water

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Isopropyl alcohol (67-63-0)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.

Other information : This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Full text of H-phrases:

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Liquefied gas	Gases under pressure Liquefied gas
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.