

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 06/05/2015 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Ozone (1.00% - 4.79%) in Oxygen

Product code : SG-2002-02448

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Details of the supplier of the safety data sheet

Air Liquide 2700 Post Oak Boulevard Houston, TX 77056 - USA T 1-800-819-1704 www.us.airliquide.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

 Ox. Gas 1
 H270

 Compressed gas
 H280

 Acute Tox. 2 (Inhalation:gas)
 H330

 Muta. 2
 H341

 STOT SE 3
 H335

 STOT RE 2
 H373

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS04







Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H270 - May cause or intensify fire; oxidizer

H280 - Contains gas under pressure; may explode if heated

H330 - Fatal if inhaled

H335 - May cause respiratory irritation

H341 - Suspected of causing genetic defects (Inhalation)

H373 - May cause damage to organs (lung, bronchial tubes) through prolonged or repeated

exposure (Inhalation)

Precautionary statements (GHS-US) : P202 - Do not handle until all safety precautions have been read and understood

P220 - Keep/Store away from combustible materials, clothing

P244 - Keep reduction valves/valves and fittings free from oil and grease

P260 - Do not breathe gas

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear eye protection, face protection, protective gloves, protective clothing

P284 - Wear respiratory protection. Consult respiratory device supplier's product information

for the selection of the appropriate device.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P307+P311 - If exposed: Call a poison center/doctor

P403 - Store in a well-ventilated place

P405 - Store locked up

P501 - Dispose of contents/container in accordance with local/regional/national/international

regulations

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)

06/05/2015 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CGA-PG05 - Use a back flow preventive device in the piping CGA-PG06 - Close valve after each use and when empty CGA-PG10 - Use only with equipment rated for cylinder pressure CGA-PG14 - Approach suspected leak area with caution

CGA-PG18 - When returning cylinder, install leak tight valve outlet cap or plug CGA-PG20 - Use only with equipment of compatible materials of construction

CGA-PG21 - Open valve slowly

CGA-PG22 - Use only with equipment cleaned for oxygen service

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Oxygen	(CAS No) 7782-44-7	95.21 - 99	Ox. Gas 1, H270 Compressed gas, H280
Ozone	(CAS No) 10028-15-6	1 - 4.79	Ox. Gas 1, H270 Acute Tox. 1 (Inhalation:gas), H330 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Muta. 2, H341 STOT SE 3, H335 STOT RE 2, H373 Aquatic Acute 1, H400

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Apply

artificial respiration with bag or mask if breathing stopped. Get immediate medical

advice/attention.

First-aid measures after skin contact : Adverse effects not expected from this product. First-aid measures after eye contact : Adverse effects not expected from this product.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : Fatal if inhaled. May cause respiratory irritation. Symptoms/injuries after skin contact : Adverse effects not expected from this product. Symptoms/injuries after eye contact : Adverse effects not expected from this product.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous

administration

: Not known.

Chronic symptoms : Suspected of causing genetic defects. May cause damage to organs (lung, bronchial tubes)

through prolonged or repeated exposure (Inhalation).

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Fire hazard : The product is not flammable.

Explosion hazard : Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire

and increasing risk of burns and injuries.

06/05/2015 EN (English US) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reactivity : None known.

5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray

or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Do not enter fire area without proper protective equipment, including respiratory

protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment consistent with the site emergency plan.

Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent

premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep

upwind.

6.1.2. For emergency responders

Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Equip cleanup crew with proper protection.

Emergency procedures : Evacuate and limit access. Ventilate area.

6.2. Environmental precautions

Try to stop release if safe to do so.

6.3. Methods and material for containment and cleaning up

For containment : Try to stop release if safe to do so.

Methods for cleaning up : Dispose of this material and its container in accordance with local regulations.

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder

pressure. Close valve after each use and when empty.

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or

in a well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in

use. Protect cylinder from physical damage. Store in well ventilated area. Store locked up.

Incompatible products : None known

Incompatible materials : Flammable materials. Combustible materials. Reducing agents.

7.3. Specific end use(s)

See Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ozone (1.00% - 4.79%) in Oxygen	
ACGIH	Not applicable
OSHA	Not applicable
Ozone (10028-15-6)	
Ozone (10028-15-6)	
Ozone (10028-15-6) ACGIH	Not applicable

06/05/2015 EN (English US) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxygen (7782-44-7)	
ACGIH	Not applicable
OSHA	Not applicable

8.2. Exposure controls

Appropriate engineering controls : Ensure exposure is below occupational exposure limits. Provide adequate general and local

exhaust ventilation. Systems under pressure should be regularly checked for leakages. Consider work permit system e.g. for maintenance activities. Alarm detectors should be used

when toxic gases may be released.

Hand protection : Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection.

Eye protection : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.

Respiratory protection : Wear a respirator when performing non-routine tasks not limited to line breaking or sampling.

Wear a respirator during routine operations if determined to be necessary during a processspecific review. Consult respirator suppliers' product information or their representatives for the

selection of the appropriate respirator.

Thermal hazard protection : None necessary during normal and routine operations.

Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

specific methods for waste gas treatment.

Other information : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Clear, colorless gas.

Color : Colorless

Odor : Irritating/pungent odour
Odor threshold : No data available
pH : No data available
Melting point : No data available
Frogring point : No data available

Freezing point : No data available
Boiling point : No data available

Flash point : Not applicable - not flammable

Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : See Section 2.1 and 2.2 Explosion limits : Not applicable - not flammable

Explosive properties : Not applicable - not flammable.

Oxidizing properties : Not combustible but enhances combustion of other substances. May cause or intensify fire; oxidizer.

OXIGIZOI

Vapor pressure : No data available Relative density : No data available Relative vapor density at 20 °C : No data available

Molecular mass : Not applicable for gas-mixtures.

Relative gas density Heavier than air Solubility No data available Log Pow No data available Log Kow No data available Auto-ignition temperature No data available Decomposition temperature No data available No data available Viscosity Viscosity, kinematic No data available No data available Viscosity, dynamic

9.2. Other information

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level.

06/05/2015 EN (English US) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Decomposes at room temperature.

10.3. Possibility of hazardous reactions

May react violently with reducing agents. Can form explosive mixtures with flammable materials.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Combustible materials. Flammable materials. Reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:gas: Fatal if inhaled.

Ozone (1.00% - 4.79%) in Oxygen	
ATE US (gases)	100.209 ppmV/4h
Ozone (10028-15-6)	
LC50 inhalation rat (ppm)	4.8 ppm/4h
ATE US (gases)	4.800 ppmV/4h
Oxygen (7782-44-7)	
LC50 inhalation rat (ppm)	800000 ppm/4h
Skin corrosion/irritation	: Not classified

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Suspected of causing genetic defects (Inhalation).

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: May cause damage to organs (lung, bronchial tubes) through prolonged or repeated exposure

(Inhalation).

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : Fatal if inhaled. May cause respiratory irritation.

Symptoms/injuries after skin contact : Adverse effects not expected from this product.

Symptoms/injuries after eye contact : Adverse effects not expected from this product.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous

administration

: Not known.

Chronic symptoms : Suspected of causing genetic defects. May cause damage to organs (lung, bronchial tubes)

through prolonged or repeated exposure (Inhalation).

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

06/05/2015 EN (English US) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxygen (7782-44-7)	
Persistence and degradability	No ecological damage caused by this product.

12.3. **Bioaccumulative potential**

Oxygen (7782-44-7)	
Log Pow	Not applicable for inorganic gases.
Bioaccumulative potential	No ecological damage caused by this product.

12.4. Mobility in soil

Oxygen (7782-44-7)	
Ecology - soil	No ecological damage caused by this product.

Other adverse effects

Effect on ozone layer : No known effects from this product.

: No known ecological damage caused by this product. Effect on the global warming

SECTION 13: Disposal considerations

Waste treatment methods

Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its

accumulation could be dangerous. Ensure that the emission levels from local regulations or

operating permits are not exceeded.

: Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more Waste disposal recommendations

guidance on suitable disposal methods.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3303 Compressed gas, toxic, oxidizing, n.o.s. (Ozone, Oxygen) Inhalation Hazard Zone B

UN-No.(DOT) · UN3303

Proper Shipping Name (DOT) : Compressed gas, toxic, oxidizing, n.o.s.

Inhalation Hazard Zone B

2.3 - Poison gas Hazard labels (DOT)

5.1 - Oxidizer





DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;305 DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102)

: 2 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone B (see 173.116(a) or 173.133(a) of this subchapter), and must be described as an inhalation

hazard under the provisions of this subchapter.

B9 - Bottom outlets are not authorized. B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per

square foot per degree Fahrenheit) temperature differential. Insulating materials must not promote corrosion to steel when wet.

DOT Packaging Exceptions (49 CFR 173.xxx)

DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : Forbidden

CFR 175.75)

06/05/2015 EN (English US) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location

: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

Other information : No supplementary information available.

ADR

Transport document description : UN 3303, 2.3 (5.1), (C/D)

Class (ADR) : 2 - Gases
Hazard identification number (Kemler No.) : 265
Classification code (ADR) : 1TO

Hazard labels (ADR) : 2.3 - Toxic gases

5.1 - Oxidizer



Orange plates

265 3303

Tunnel restriction code (ADR) : C/D
Limited quantities (ADR) : 0
Excepted quantities (ADR) : E0

Transport by sea

UN-No. (IMDG) : 3303

Proper Shipping Name (IMDG) : COMPRESSED GAS, TOXIC, OXIDIZING, N.O.S.

Class (IMDG) : 2 - Gases

Air transport

UN-No. (IATA) : 3303

Proper Shipping Name (IATA) : COMPRESSED GAS, TOXIC, OXIDIZING, N.O.S.

Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Oxygen (7782-44-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

Oxygen (7782-44-7)	
Listed on the Canadian DSL (Domestic Sustance	s List)
WHMIS Classification	Class A - Compressed Gas Class C - Oxidizing Material

EU-Regulations

No additional information available

Oxygen (7782-44-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

06/05/2015 EN (English US) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

National regulations

Oxygen (7782-44-7)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

Oxygen (7782-44-7)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with OSHA final rule on GHS implementation

promulgated March 26, 2012.

Other information : This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29

CFR, 1910.1200. Other government regulations must be reviewed for applicability to this

product.

Full text of H-phrases:

ι οι π-prirases.	
Acute Tox. 1 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 1
Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Muta. 2	Germ cell mutagenicity Category 2
Ox. Gas 1	Oxidizing gases Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H270	May cause or intensify fire; oxidizer
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation
H330	Fatal if inhaled
H335	May cause respiratory irritation
H341	Suspected of causing genetic defects
H373	May cause damage to organs through prolonged or repeated
	exposure
H400	Very toxic to aquatic life

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

06/05/2015 EN (English US) 8/8