



Ethyl Acetylene (0.00001% - 5.00%), 1,2-Butadiene (0.00001% - 5.00%), Vinyl Acetylene (0.00001% - 5.00%) in 1,3-Butadiene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 06/17/2015

Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Ethyl Acetylene (0.00001% - 5.00%), 1,2-Butadiene (0.00001% - 5.00%), Vinyl Acetylene (0.00001% - 5.00%) in 1,3-Butadiene
Product code : SG-2004-02528

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Details of the supplier of the safety data sheet

Air Liquide
2700 Post Oak Boulevard
Houston, TX 77056 - USA
T 1-800-819-1704
www.us.airliquide.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Gas 1	H220
Liquefied gas	H280
Muta. 1B	H340
Carc. 1A	H350

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H220 - Extremely flammable gas
H280 - Contains gas under pressure; may explode if heated
H340 - May cause genetic defects (Inhalation)
H350 - May cause cancer
OSHA-H01 - May displace oxygen and cause rapid suffocation
CGA-HG01 - May cause frostbite
CGA-HG04 - May form explosive mixtures with air
Precautionary statements (GHS-US) : P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection, face protection, protective gloves, protective clothing
P302 - IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area, Get immediate medical advice/attention
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely
P381 - Eliminate all ignition sources if safe to do so
P403 - Store in a well-ventilated place

Ethyl Acetylene (0.00001% - 5.00%), 1,2-Butadiene (0.00001% - 5.00%), Vinyl Acetylene (0.00001% - 5.00%) in 1,3-Butadiene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)
CGA-PG05 - Use a back flow preventive device in the piping
CGA-PG06 - Close valve after each use and when empty
CGA-PG10 - Use only with equipment rated for cylinder pressure
CGA-PG14 - Approach suspected leak area with caution
CGA-PG21 - Open valve slowly

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
1,3-Butadiene	(CAS No) 106-99-0	85 - 99.99997	Flam. Gas 1, H220 Liquefied gas, H280 Muta. 1B, H340 Carc. 1A, H350
VINYL ACETYLENE	(CAS No) 689-97-4	0.00001 - 5	Flam. Gas 1, H220 Compressed gas, H280
Butadiene 1,2-	(CAS No) 590-19-2	0.00001 - 5	Flam. Gas 1, H220 Liquefied gas, H280
Ethyl acetylene	(CAS No) 107-00-6	0.00001 - 5	Flam. Gas 1, H220 Liquefied gas, H280

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
- First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
- First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation.
- Symptoms/injuries after skin contact : May cause frostbite.
- Symptoms/injuries after eye contact : Contact with the product may cause cold burns or frostbite.
- Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.
- Symptoms/injuries upon intravenous administration : Not known.
- Chronic symptoms : May cause cancer. May cause genetic defects.

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : This product is flammable.

Ethyl Acetylene (0.00001% - 5.00%), 1,2-Butadiene (0.00001% - 5.00%), Vinyl Acetylene (0.00001% - 5.00%) in 1,3-Butadiene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. May form flammable/explosive vapor-air mixture.
Reactivity	: None known.

5.3. Advice for firefighters

Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
Protection during firefighting	: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Ensure adequate ventilation.
------------------	--------------------------------

6.1.1. For non-emergency personnel

Protective equipment	: Wear protective equipment consistent with the site emergency plan.
Emergency procedures	: Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

6.1.2. For emergency responders

Protective equipment	: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.
Emergency procedures	: Evacuate and limit access. Ventilate area. Remove ignition sources. Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering atmospheres of unknown contaminant concentration until proven to be safe.

6.2. Environmental precautions

Try to stop release if safe to do so.

6.3. Methods and material for containment and cleaning up

For containment	: Try to stop release if safe to do so.
Methods for cleaning up	: Dispose of this material and its container in accordance with local regulations.

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Handle empty containers with care because residual vapors are flammable. In use, may form flammable vapor-air mixture.
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use only non-sparking tools.
Hygiene measures	: Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area. Store locked up.
Incompatible products	: None known.
Incompatible materials	: Oxidizing materials. Air.

7.3. Specific end use(s)

See Section 1.2.

Ethyl Acetylene (0.00001% - 5.00%), 1,2-Butadiene (0.00001% - 5.00%), Vinyl Acetylene (0.00001% - 5.00%) in 1,3-Butadiene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethyl Acetylene (0.00001% - 5.00%), 1,2-Butadiene (0.00001% - 5.00%), Vinyl Acetylene (0.00001% - 5.00%) in 1,3-Butadiene		
ACGIH	Not applicable	
OSHA	Not applicable	
VINYL ACETYLENE (689-97-4)		
ACGIH	Not applicable	
OSHA	Not applicable	
Butadiene 1,2- (590-19-2)		
ACGIH	Not applicable	
OSHA	Not applicable	
Ethyl acetylene (107-00-6)		
ACGIH	Not applicable	
OSHA	Not applicable	
1,3-Butadiene (106-99-0)		
ACGIH	ACGIH TWA (ppm)	2 ppm
OSHA	OSHA PEL (TWA) (ppm)	1 ppm
OSHA	OSHA PEL (STEL) (ppm)	5 ppm (see 29 CFR 1910.1051)

8.2. Exposure controls

Appropriate engineering controls	: Ensure exposure is below occupational exposure limits. Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit system e.g. for maintenance activities.
Hand protection	: Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection.
Eye protection	: Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.
Respiratory protection	: None necessary during normal and routine operations. See Sections 5 & 6.
Thermal hazard protection	: None necessary during normal and routine operations.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
Other information	: Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Clear, colorless gas.
Color	: Colorless
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: See Section 2.1 and 2.2
Explosion limits	: No data available
Explosive properties	: Without adequate ventilation formation of explosive mixtures may be possible.

Ethyl Acetylene (0.00001% - 5.00%), 1,2-Butadiene (0.00001% - 5.00%), Vinyl Acetylene (0.00001% - 5.00%) in 1,3-Butadiene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxidizing properties	: None.
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Molecular mass	: No Data Available
Relative gas density	: Heavier than air
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

Additional information	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
------------------------	--

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Can form explosive mixture with air.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Oxidizing materials. Air.

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

Butadiene 1,2- (590-19-2)	
LC50 inhalation rat (ppm)	110000 ppm/4h
ATE US (gases)	110000.000 ppmV/4h
1,3-Butadiene (106-99-0)	
LD50 oral rat	5480 mg/kg
LC50 inhalation rat (mg/l)	285 g/m ³ (Exposure time: 4 h)
LC50 inhalation rat (ppm)	110000 ppm/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects (Inhalation).
Carcinogenicity	: May cause cancer.

Ethyl Acetylene (0.00001% - 5.00%), 1,2-Butadiene (0.00001% - 5.00%), Vinyl Acetylene (0.00001% - 5.00%) in 1,3-Butadiene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,3-Butadiene (106-99-0)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 2 - Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes
In OSHA Specifically Regulated Carcinogen list	Yes

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation.

Symptoms/injuries after skin contact : May cause frostbite.

Symptoms/injuries after eye contact : Contact with the product may cause cold burns or frostbite.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous administration : Not known.

Chronic symptoms : May cause cancer. May cause genetic defects.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

Butadiene 1,2- (590-19-2)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.
Ethyl acetylene (107-00-6)	
Persistence and degradability	No data available.
1,3-Butadiene (106-99-0)	
Persistence and degradability	Not readily biodegradable.

12.3. Bioaccumulative potential

Butadiene 1,2- (590-19-2)	
Log Pow	1.99
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Ethyl acetylene (107-00-6)	
Log Pow	1.46
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
1,3-Butadiene (106-99-0)	
BCF fish 1	13 - 19.1
Log Pow	1.99
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

12.4. Mobility in soil

Butadiene 1,2- (590-19-2)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Ethyl acetylene (107-00-6)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
1,3-Butadiene (106-99-0)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

Ethyl Acetylene (0.00001% - 5.00%), 1,2-Butadiene (0.00001% - 5.00%), Vinyl Acetylene (0.00001% - 5.00%) in 1,3-Butadiene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

- Effect on ozone layer : No known effects from this product.
- Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into areas where there is a risk of forming an explosive mixture with air.
- Waste disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

- Transport document description : UN3161 Liquefied gas, flammable, n.o.s.
- UN-No.(DOT) : UN3161
- Proper Shipping Name (DOT) : Liquefied gas, flammable, n.o.s.
- Hazard labels (DOT) : 2.1 - Flammable gas



- DOT Packaging Non Bulk (49 CFR 173.xxx) : 304
- DOT Packaging Bulk (49 CFR 173.xxx) : 314;315
- DOT Symbols : G - Identifies PSN requiring a technical name
- DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 306
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Forbidden
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
- DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
- DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

- Other information : No supplementary information available.

ADR

- Transport document description : UN 3161, 2, (B/D)
- Class (ADR) : 2 - Gases
- Hazard identification number (Kemler No.) : 23
- Classification code (ADR) : 2F

Ethyl Acetylene (0.00001% - 5.00%), 1,2-Butadiene (0.00001% - 5.00%), Vinyl Acetylene (0.00001% - 5.00%) in 1,3-Butadiene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Orange plates



Tunnel restriction code (ADR) : B/D
Limited quantities (ADR) : 0
Excepted quantities (ADR) : E0

Transport by sea

UN-No. (IMDG) : 3161
Proper Shipping Name (IMDG) : LIQUEFIED GAS, FLAMMABLE, N.O.S.
Class (IMDG) : 2 - Gases

Air transport

UN-No. (IATA) : 3161
Proper Shipping Name (IATA) : LIQUEFIED GAS, FLAMMABLE, N.O.S.
Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Butadiene 1,2- (590-19-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Ethyl acetylene (107-00-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,3-Butadiene (106-99-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

15.2. International regulations

CANADA

No additional information available

Butadiene 1,2- (590-19-2)

Listed on the Canadian DSL (Domestic Substances List)

Ethyl acetylene (107-00-6)

Listed on the Canadian DSL (Domestic Substances List)

1,3-Butadiene (106-99-0)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class F - Dangerously Reactive Material
----------------------	---

EU-Regulations

No additional information available

Butadiene 1,2- (590-19-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Ethyl acetylene (107-00-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

1,3-Butadiene (106-99-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Ethyl Acetylene (0.00001% - 5.00%), 1,2-Butadiene (0.00001% - 5.00%), Vinyl Acetylene (0.00001% - 5.00%) in 1,3-Butadiene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

National regulations

Butadiene 1,2- (590-19-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Ethyl acetylene (107-00-6)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

1,3-Butadiene (106-99-0)

Listed on IARC (International Agency for Research on Cancer)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed as carcinogen on NTP (National Toxicology Program)
Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

1,3-Butadiene (106-99-0)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	Yes	No	0.4 µg/day

Ethyl acetylene (107-00-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

1,3-Butadiene (106-99-0)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes

: Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.

Other information

: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Ethyl Acetylene (0.00001% - 5.00%), 1,2-Butadiene (0.00001% - 5.00%), Vinyl Acetylene (0.00001% - 5.00%) in 1,3-Butadiene

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

Carc. 1A	Carcinogenicity Category 1A
Compressed gas	Gases under pressure Compressed gas
Flam. Gas 1	Flammable gases Category 1
Liquefied gas	Gases under pressure Liquefied gas
Muta. 1B	Germ cell mutagenicity Category 1B
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H340	May cause genetic defects (Inhalation)
H350	May cause cancer

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.