

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 06/22/2015 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form : Mixture

Product name : 11 Components in n-Butane

Product code SG-2012-02555

Relevant identified uses of the substance or mixture and uses advised against

: Test gas/Calibration gas. Use of the substance/mixture

Details of the supplier of the safety data sheet

Air Liquide 2700 Post Oak Boulevard Houston, TX 77056 - USA T 1-800-819-1704 www.us.airliquide.com

Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS-US classification

Flam. Gas 1 H220 Liquefied gas H280 Repr. 2 H361 STOT SE 3 H336

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)







GHS07



: Danger

Signal word (GHS-US)

Hazard statements (GHS-US) : H220 - Extremely flammable gas

H280 - Contains gas under pressure; may explode if heated

H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child OSHA-H01 - May displace oxygen and cause rapid suffocation

CGA-HG01 - May cause frostbite

CGA-HG04 - May form explosive mixtures with air

P202 - Do not handle until all safety precautions have been read and understood Precautionary statements (GHS-US)

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

P261 - Avoid breathing gas

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear eye protection, face protection, protective gloves, protective clothing

P302 - IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area, Get

immediate medical advice/attention

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P308+P313 - If exposed or concerned: Get medical advice/attention

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely

P381 - Eliminate all ignition sources if safe to do so

P403 - Store in a well-ventilated place

P405 - Store locked up

P501 - Dispose of contents/container in accordance with local/regional/national/international

regulations

06/23/2015 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)

CGA-PG05 - Use a back flow preventive device in the piping CGA-PG06 - Close valve after each use and when empty CGA-PG10 - Use only with equipment rated for cylinder pressure

CGA-PG14 - Approach suspected leak area with caution

CGA-PG21 - Open valve slowly

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
n-Butane	(CAS No) 106-97-8	2.0001 - 64.89993	Flam. Gas 1, H220 Liquefied gas, H280
Ethylene	(CAS No) 74-85-1	20 - 40	Flam. Gas 1, H220 Liquefied gas, H280 STOT SE 3, H336
Propylene	(CAS No) 115-07-1	5 - 15	Flam. Gas 1, H220 Liquefied gas, H280
butene, mixed-1-and-2-isomers	(CAS No) 107-01-7	10 - 15	Flam. Gas 1, H220 Liquefied gas, H280
n-Pentane	(CAS No) 109-66-0	0.00001 - 5	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
1-Butene	(CAS No) 106-98-9	0.00001 - 5	Flam. Gas 1, H220 Liquefied gas, H280
Propane	(CAS No) 74-98-6	0.00001 - 5	Flam. Gas 1, H220 Liquefied gas, H280
Isobutylene	(CAS No) 115-11-7	0.00001 - 5	Flam. Gas 1, H220 Liquefied gas, H280
Isobutane	(CAS No) 75-28-5	5	Flam. Gas 1, H220 Liquefied gas, H280
Ethane	(CAS No) 74-84-0	0.00001 - 1	Flam. Gas 1, H220 Compressed gas, H280
Methane	(CAS No) 74-82-8	0.00001 - 1	Flam. Gas 1, H220 Compressed gas, H280
n-Hexane	(CAS No) 110-54-3	0.1 - 0.9999	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact : Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical

advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : May cause frostbite.

Symptoms/injuries after eye contact : Contact with the product may cause cold burns or frostbite.

06/23/2015 EN (English US) 2/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous

administration

Not known

Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child.

Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

SECTION 5: Firefighting measures

Extinguishing media 5.1.

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Fire hazard : This product is flammable.

Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of Explosion hazard

burns and injuries. May form flammable/explosive vapor-air mixture.

Reactivity

5.3. Advice for firefighters

Firefighting instructions

: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray

or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Protection during firefighting

Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory

protection.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures

: Ensure adequate ventilation.

6.1.1. For non-emergency personnel

Protective equipment

: Wear protective equipment consistent with the site emergency plan.

Emergency procedures

: Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep

upwind.

6.1.2. For emergency responders

Protective equipment

: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Equip cleanup crew with proper protection.

Emergency procedures

Evacuate and limit access. Ventilate area. Remove ignition sources. Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering atmospheres of unknown contaminant concentration until proven to be safe.

Environmental precautions

Try to stop release if safe to do so.

Methods and material for containment and cleaning up

For containment

: Try to stop release if safe to do so.

Methods for cleaning up

: Dispose of this material and its container in accordance with local regulations.

Reference to other sections

See also Sections 8 and 13

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed

: Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Handle empty containers with care because residual vapors are flammable. In use, may form flammable vapor-air mixture.

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use only non-sparking tools.

: Do not eat, drink or smoke when using this product. Hygiene measures

06/23/2015 EN (English US) 3/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity

should be followed.

Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in

use. Protect cylinder from physical damage. Store in well ventilated area. Store locked up.

Incompatible products : None known

Incompatible materials : Oxidizing materials. Air.

Not applicable

7.3. Specific end use(s)

See Section 1.2.

ACGIH

SECTION 8: Exposure controls/personal protection

8.1. Control parameters 11 Components in n-Butane

OSHA	Not applicable		
Propylene (115-07-1)			
ACGIH	ACGIH TWA (ppm)	500 ppm	
OSHA	Not applicable	'	

Propane (74-98-6)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	1800 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

Isobutylene (115-11-7)		
ACGIH	ACGIH TWA (ppm)	250 ppm
OSHA	Not applicable	

1-Butene (106-98-9)		
ACGIH	ACGIH TWA (ppm)	250 ppm
OSHA	Not applicable	

butene, mixed-1-and-2-isomers (107-01-7)	
ACGIH	Not applicable
OSHA	Not applicable

n-Pentane (109-66-0)		
ACGIH	ACGIH TWA (ppm)	600 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	2950 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

Ethylene (74-85-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm
OSHA	Not applicable	

Ethane (74-84-0)		
ACGIH TWA (ppm) 1000 ppm		
OSHA	Not applicable	

Methane (74-82-8)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
OSHA	Not applicable	

06/23/2015 EN (English US) 4/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-Hexane (110-54-3)		
ACGIH	ACGIH TWA (ppm)	50 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	1800 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm

Isobutane (75-28-5)		
ACGIH	ACGIH STEL (ppm)	1000 ppm
OSHA	Not applicable	

n-Butane (106-97-8)		
ACGIH STEL (ppm) 1000 ppm		
OSHA Not applicable		

8.2. Exposure controls

Appropriate engineering controls : Ensure exposure is below occupational exposure limits. Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Oxygen

detectors should be used when asphyxiating gases may be released. Consider work permit

system e.g. for maintenance activities.

Hand protection : Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection.

Eye protection : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing. Respiratory protection : None necessary during normal and routine operations. See Sections 5 & 6.

Respiratory protection : None necessary during normal and routine operations. See See Thermal hazard protection : None necessary during normal and routine operations.

Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

specific methods for waste gas treatment.

Other information : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Clear, colorless gas.

Color : Colorless

Odor No data available Odor threshold No data available рΗ No data available No data available Melting point Freezing point No data available **Boiling point** No data available No data available Flash point Relative evaporation rate (butyl acetate=1) No data available Flammability (solid, gas) See Section 2.1 and 2.2 **Explosion limits** No data available

Explosive properties : Without adequate ventilation formation of explosive mixtures may be possible.

: No data available

Oxidizing properties : None.

Decomposition temperature

Vapor pressure No data available : No data available Relative density Relative vapor density at 20 °C No data available Molecular mass No Data Available Relative gas density Heavier than air Solubility No data available Log Pow No data available : No data available Log Kow Auto-ignition temperature No data available

06/23/2015 EN (English US) 5/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

9.2. Other information

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Can form explosive mixture with air.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Oxidizing materials. Air.

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Propylene (115-07-1)		
LC50 inhalation rat (mg/l)	658 mg/l/4h	
LC50 inhalation rat (ppm)	49957.23 ppm/4h	
Propane (74-98-6)		
LC50 inhalation rat (mg/l)	658 mg/l/4h	
LC50 inhalation rat (ppm)	282800 ppm/4h	
Isobutylene (115-11-7)		
LC50 inhalation rat (mg/l)	620 mg/l/4h	
LC50 inhalation rat (ppm)	239620.46 ppm/4h	
ATE US (gases)	239620.460 ppmV/4h	
ATE US (vapors)	620.000 mg/l/4h	
ATE US (dust, mist)	620.000 mg/l/4h	
1-Butene (106-98-9)		
LC50 inhalation rat (ppm) 500000 ppm/4h		
butene, mixed-1-and-2-isomers (107-01-7)		
LC50 inhalation rat (ppm)	150307.38 ppm/4h	
ATE US (gases)	150307.380 ppmV/4h	
n-Pentane (109-66-0)		
LD50 dermal rabbit	3000 mg/kg	
LC50 inhalation rat (mg/l)	364 g/m³ (Exposure time: 4 h)	
LC50 inhalation rat (ppm)	123317.17 ppm/4h	
ATE US (dermal)	3000.000 mg/kg body weight	
ATE US (gases)	123317.170 ppmV/4h	
ATE US (vapors)	364.000 mg/l/4h	
ATE US (dust, mist)	364.000 mg/l/4h	
Ethylene (74-85-1)		
LC50 inhalation rat (ppm)	820000 ppm/4h	

06/23/2015 EN (English US) 6/16

Safety Data Sheet

Ethylene (74-85-1)				
ATE US (gases)	820000.000 ppmV/4h			
Ethane (74-84-0)				
LC50 inhalation rat (mg/l)	658 mg/l/4h			
LC50 inhalation rat (ppm)	820000 ppm/4h			
ATE US (gases)	820000.000 ppmV/4h			
ATE US (vapors)	658.000 mg/l/4h			
ATE US (dust, mist)	658.000 mg/l/4h			
Methane (74-82-8)				
LC50 inhalation rat (ppm)	820000 ppm/4h			
ATE US (gases)	820000.000 ppmV/4h			
n-Hexane (110-54-3)				
LD50 dermal rabbit	3000 mg/kg			
LC50 inhalation rat (ppm)	48000 ppm/4h			
ATE US (dermal)	3000.000 mg/kg body weight			
ATE US (gases)	48000.000 ppmV/4h			
Isobutane (75-28-5)				
LC50 inhalation rat (mg/l)	658 mg/l/4h			
LC50 inhalation rat (ppm)	276713.11 ppm/4h			
n-Butane (106-97-8)				
LC50 inhalation rat (mg/l) 658 g/m³ (Exposure time: 4 h)				
LC50 inhalation rat (ppm)	276789.28 ppm/4h			
kin corrosion/irritation	: Not classified			
Serious eye damage/irritation	: Not classified			
Respiratory or skin sensitization	: Not classified			
Germ cell mutagenicity	: Not classified			
Carcinogenicity	: Not classified			
Propylene (115-07-1)				
IARC group	3 - Not classifiable			
Isobutylene (115-11-7)				
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity			
realional Toxicology Frogram (1911) Status	1 - Evidence of Odrofflogenicity			
Ethylene (74-85-1)				
IARC group	3 - Not classifiable			
Reproductive toxicity : Suspected of damaging fertility or the unborn child.				
specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.			

Specific target organ toxicity (repeated exposure)

: Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : May cause frostbite.

Symptoms/injuries after eye contact : Contact with the product may cause cold burns or frostbite. Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous : Not known.

administration

: Suspected of damaging fertility. Suspected of damaging the unborn child. Chronic symptoms

06/23/2015 EN (English US) 7/16

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. **Toxicity**

n-Pentane (109-66-0)		
LC50 fish 1	9.87 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
EC50 Daphnia 1 9.74 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
LC50 fish 2	11.59 mg/l (Exposure time: 96 h - Species: Pimephales promelas)	

n-Hexane (110-54-3)	
LC50 fish 1	2.1 - 2.98 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

Persistence and degradability

Propylene (115-07-1)		
Persistence and degradability The substance is biodegradable. Unlikely to persist.		
Propane (74-98-6)		
Persistence and degradability	The substance is biodegradable. Unlikely to persist.	
Isobutylene (115-11-7)		
Persistence and degradability	The substance is biodegradable. Unlikely to persist.	
1-Butene (106-98-9)		
Persistence and degradability	Not readily biodegradable.	
Ethylene (74-85-1)		
Persistence and degradability The substance is biodegradable. Unlikely to persist.		
Ethane (74-84-0)		
Persistence and degradability	The substance is biodegradable. Unlikely to persist.	
Methane (74-82-8)		
Persistence and degradability	The substance is biodegradable. Unlikely to persist. No data available.	
Isobutane (75-28-5)		
Persistence and degradability	Persistence and degradability The substance is biodegradable. Unlikely to persist.	
n-Butane (106-97-8)		
Persistence and degradability No data available.		

12.3. **Bioaccumulative potential**

·			
Propylene (115-07-1)			
Log Pow	1.77		
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.		
Propane (74-98-6)			
Log Pow	2.36		
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.		
Isobutylene (115-11-7)			
Log Pow	2.35		
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.		
1-Butene (106-98-9)			
Log Pow	2.4		
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.		
n-Pentane (109-66-0)			
Log Pow	3.39		
Ethylene (74-85-1)			
BCF fish 1	4 - 4.6		
Log Pow	1.13		
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.		

EN (English US) 06/23/2015 8/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethane (74-84-0)		
Log Pow	1.81	
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.	
Methane (74-82-8)		
Log Pow	Not applicable for gas mixtures	
Log Kow	Not applicable for gas mixtures	
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.	
Isobutane (75-28-5)		
BCF fish 1	1.57 - 1.97	
Log Pow	2.76	
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.	
n-Butane (106-97-8)		
Log Pow	2.89	
Log Kow	Not applicable for gas-mixtures.	
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.	

12.4. Mobility in soil

Propylene (115-07-1)		
Ecology - soil Because of its high volatility, the product is unlikely to cause ground or water pollution.		
Propane (74-98-6)		
Ecology - soil Because of its high volatility, the product is unlikely to cause ground or water pollution.		
Isobutylene (115-11-7)		
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.	
1-Butene (106-98-9)		
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.	
Ethylene (74-85-1)		
Ecology - soil Because of its high volatility, the product is unlikely to cause ground or water pollution.		
Ethane (74-84-0)		
Ecology - soil Because of its high volatility, the product is unlikely to cause ground or water pollution.		
Methane (74-82-8)		
Mobility in soil	No data available.	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.	
Isobutane (75-28-5)		
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.	
n-Butane (106-97-8)		
Mobility in soil	No data available.	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.	

12.5. Other adverse effects

Effect on ozone layer : No known effects from this product.

Effect on the global warming : Contains greenhouse gas(es) not covered by 842/2006/EC.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

: Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into areas where there is a risk of forming an explosive

mixture with air.

Waste disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more

guidance on suitable disposal methods.

06/23/2015 EN (English US) 9/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3161 Liquefied gas, flammable, n.o.s.

UN-No.(DOT) : UN3161

Proper Shipping Name (DOT) : Liquefied gas, flammable, n.o.s.

Hazard labels (DOT) : 2.1 - Flammable gas

2

DOT Packaging Non Bulk (49 CFR 173.xxx) : 304 DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the

applicable liquefied compressed gases are authorized to be transported in portable tanks in

accordance with the requirements of 173.313 of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location

: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one

passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

Other information : No supplementary information available.

ADR

Transport document description : UN 3161 LIQUEFIED GAS, FLAMMABLE, N.O.S., 2.1, (B/D)

Class (ADR) : 2 - Gases

Hazard identification number (Kemler No.) : 23 Classification code (ADR) : 2F

Hazard labels (ADR) : 2.1 - Flammable gases



Orange plates

23 3161

Tunnel restriction code (ADR) : B/D Limited quantities (ADR) : 0 Excepted quantities (ADR) : E0

Transport by sea

UN-No. (IMDG) : 3161

Proper Shipping Name (IMDG) : LIQUEFIED GAS, FLAMMABLE, N.O.S.

Class (IMDG) : 2 - Gases

06/23/2015 EN (English US) 10/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport

UN-No. (IATA) : 3161

Proper Shipping Name (IATA) : LIQUEFIED GAS, FLAMMABLE, N.O.S.

Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Pro	pvlene	(115-07-1)	ı

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting 1.0 %

Propane (74-98-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Isobutylene (115-11-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1-Butene (106-98-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

n-Pentane (109-66-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

Ethylene (74-85-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting 1.0 %

Ethane (74-84-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Methane (74-82-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

n-Hexane (110-54-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting 1.0 %

Isobutane (75-28-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

n-Butane (106-97-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

c)ron	vlene	. /4	IE O	7 41
г	roo	viene	; (I)	เอ-บ	/-1)

Listed on the Canadian DSL (Domestic Sustances List)

WHMIS Classification Class A - Compressed Gas

Class B Division 1 - Flammable Gas

Propane (74-98-6)

Listed on the Canadian DSL (Domestic Sustances List)

WHMIS Classification Class A - Compressed Gas

Class B Division 1 - Flammable Gas

Isobutylene (115-11-7)

Listed on the Canadian DSL (Domestic Sustances List)

1-Butene (106-98-9)

Listed on the Canadian DSL (Domestic Sustances List)

06/23/2015 EN (English US) 11/16

Safety Data Sheet

ccording to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations			
n-Pentane (109-66-0)			
Listed on the Canadian DSL (Domestic Sustances List)			
WHMIS Classification Class B Division 2 - Flammable Liquid			
Ethylene (74-85-1)			
Listed on the Canadian DSL (Domestic	: Sustances List)		
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
Ethane (74-84-0)			
Listed on the Canadian DSL (Domestic	: Sustances List)		
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas		
Methane (74-82-8)			
Listed on the Canadian DSL (Domestic	Sustances List)		
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas		
n-Hexane (110-54-3)			
Listed on the Canadian DSL (Domestic	Sustances List)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
Isobutane (75-28-5)			
Listed on the Canadian DSL (Domestic	Sustances List)		
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas		
n-Butane (106-97-8)			
Listed on the Canadian DSL (Domestic Sustances List)			
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas		
EU-Regulations			
Propylene (115-07-1)			
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)			
Propose (74.09.5)			

Propane (74-98-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Isobutylene (115-11-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

1-Butene (106-98-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

n-Pentane (109-66-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Ethylene (74-85-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Ethane (74-84-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Methane (74-82-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

n-Hexane (110-54-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Isobutane (75-28-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

n-Butane (106-97-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

06/23/2015 EN (English US) 12/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

National regulations

Propylene (115-07-1)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Propane (74-98-6)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Isobutylene (115-11-7)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

1-Butene (106-98-9)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

n-Pentane (109-66-0)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

Ethylene (74-85-1)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Ethane (74-84-0)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

06/23/2015 EN (English US) 13/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methane (74-82-8)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

n-Hexane (110-54-3)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Pollutant Release and Transfer Register Law (PRTR Law)

Listed on the Canadian IDL (Ingredient Disclosure List)

Isobutane (75-28-5)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

n-Butane (106-97-8)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

Propylene (115-07-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Propane (74-98-6)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Isobutylene (115-11-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

1-Butene (106-98-9)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

n-Pentane (109-66-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

06/23/2015 EN (English US) 14/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylene (74-85-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Ethane (74-84-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Methane (74-82-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

n-Hexane (110-54-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Isobutane (75-28-5)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

n-Butane (106-97-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with OSHA final rule on GHS implementation

promulgated March 26, 2012.

Other information This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29

CFR, 1910.1200. Other government regulations must be reviewed for applicability to this

product.

Full text of H-phrases:

xt or H-phrases:	
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
Liquefied gas	Gases under pressure Liquefied gas
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated
	exposure
H411	Toxic to aquatic life with long lasting effects

SDS US (GHS HazCom 2012)

06/23/2015 EN (English US) 15/16

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

06/23/2015 EN (English US) 16/16