

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Hydrogen Sulfide (1.00% - 1.77%), Carbon Dioxide
Product code : SG-2002-01378

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Details of the supplier of the safety data sheet

Air Liquide America Specialty Gases
6141 Easton Rd
Plumsteadville, PA 18949 - USA
T 1.800.217.2688
www.airliquide.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Compressed gas H280
STOT SE 3 H335

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS04

GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) :

H280 - Contains gas under pressure; may explode if heated
H335 - May cause respiratory irritation
OSHA-H01 - May displace oxygen and cause rapid suffocation
CGA-HG16 - Extended exposure to gas reduces the ability to smell sulfides.
CGA-HG03 - May increase respiration and heart rate

Precautionary statements (GHS-US) :

P202 - Do not handle until all safety precautions have been read and understood
P271 - Use only outdoors or in a well-ventilated area
CGA-PG29 - Do not depend on odor to detect presence of gas
P261 - Avoid breathing gas, vapors
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P313 - Get medical advice/attention
CGA-PG05 - Use a back flow preventive device in the piping
CGA-PG21 - Open valve slowly
CGA-PG06 - Close valve after each use and when empty
CGA-PG10 - Use only with equipment rated for cylinder pressure
CGA-PG14 - Approach suspected leak area with caution
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)
P403 - Store in a well-ventilated place

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

Hydrogen Sulfide (1.00% - 1.77%), Carbon Dioxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Carbon dioxide	(CAS No)124-38-9	98.23 - 99	Simple Asphy, H380 Liquefied gas, H280
Hydrogen sulfide	(CAS No)7783-06-4	1 - 1.77	Flam. Gas 1, H220 Liquefied gas, H280 Acute Tox. 2 (Inhalation:gas), H330 STOT SE 3, H335

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Adverse effects not expected from this product.

First-aid measures after eye contact : Adverse effects not expected from this product.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Symptoms similar to those listed under inhalation.

Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation. May increase respiration and heart rate. May cause respiratory irritation.

Symptoms/injuries after skin contact : Adverse effects not expected from this product.

Symptoms/injuries after eye contact : Adverse effects not expected from this product.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous administration : Not known.

Chronic symptoms : Adverse effects not expected from this product.

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard : The product is not flammable.

Explosion hazard : Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity : None known.

5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment consistent with the site emergency plan.

Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

Hydrogen Sulfide (1.00% - 1.77%), Carbon Dioxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

- Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.
- Emergency procedures : Evacuate and limit access. Ventilate area.

6.2. Environmental precautions

Try to stop release if safe to do so.

6.3. Methods and material for containment and cleaning up

- For containment : Try to stop release if safe to do so.
- Methods for cleaning up : Dispose of this material and its container in accordance with local regulations.

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure.
- Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Observe very strict hygiene - avoid contact. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area.
- Incompatible products : None known.
- Incompatible materials : Nitric acid.

7.3. Specific end use(s)

Test gas/Calibration gas.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hydrogen sulfide (7783-06-4)		
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA ACGIH	ACGIH STEL (ppm)	5 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	20 ppm
Carbon dioxide (124-38-9)		
USA ACGIH	ACGIH TWA (ppm)	5000 ppm
USA ACGIH	ACGIH STEL (ppm)	30000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	9000 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm

Hydrogen Sulfide (1.00% - 1.77%), Carbon Dioxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls

Appropriate engineering controls	: Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Ensure exposure is below occupational exposure limits. Oxygen detectors should be used when asphyxiating gases may be released. Alarm detectors should be used when toxic gases may be released. Consider work permit system e.g. for maintenance activities.
Hand protection	: Wear working gloves when handling gas containers. 29CFR 1910.138: Hand Protection.
Eye protection	: Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.
Respiratory protection	: None necessary during normal and routine operations. See sections 5 & 6.
Thermal hazard protection	: None necessary during normal and routine operations.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
Other information	: Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Clear, colorless gas.
Molecular mass	: Not applicable for gas-mixtures.
Color	: Colourless.
Odor	: Rotten eggs.;Sulfide-like
Odor threshold	: No data available
pH	: Not applicable for gas-mixtures.
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable for gas-mixtures.
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not flammable - not combustible
Vapor pressure	: Not applicable.
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Relative gas density	: Heavier than air.
Solubility	: Water: Solubility in water of component(s) of the mixture : • : 3980 mg/l • : 2000 mg/l
Log Pow	: Not applicable for gas-mixtures.
Log Kow	: Not applicable for gas-mixtures.
Viscosity, kinematic	: Not applicable.
Viscosity, dynamic	: Not applicable.
Explosive properties	: Not applicable - not flammable.
Oxidizing properties	: None.
Explosive limits	: Not applicable - not flammable

9.2. Other information

Additional information	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
------------------------	--

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

Hydrogen Sulfide (1.00% - 1.77%), Carbon Dioxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hydrogen sulfide can form explosive compounds with nitric acid.

10.4. Conditions to avoid

Storage near nitric acid. See section 7.

10.5. Incompatible materials

Nitric acid.

10.6. Hazardous decomposition products

Sulfur Oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Hydrogen sulfide (7783-06-4)	
LC50 inhalation rat (mg/l)	0.99 mg/l (Exposure time: 1 h)
LC50 inhalation rat (ppm)	356 ppm/4h
ATE US (gases)	356.00000000 ppmV/4h
ATE US (vapors)	0.99000000 mg/l/4h
ATE US (dust, mist)	0.99000000 mg/l/4h

Skin corrosion/irritation : Not classified
pH: Not applicable for gas-mixtures.

Serious eye damage/irritation : Not classified
pH: Not applicable for gas-mixtures.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated exposure) : Not classified
No known effects from this product.

Aspiration hazard : Not classified
Not applicable for gases and gas-mixtures.

Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation. May increase respiration and heart rate. May cause respiratory irritation.

Symptoms/injuries after skin contact : Adverse effects not expected from this product.

Symptoms/injuries after eye contact : Adverse effects not expected from this product.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous administration : Not known.

Chronic symptoms : Adverse effects not expected from this product.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Classification criteria are not met.

Hydrogen sulfide (7783-06-4)	
LC50 fish 1	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
EC50 Daphnia 1	0.022 mg/l (Exposure time: 96 h - Species: Gammarus pseudolimnaeus)
LC50 fish 2	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

Hydrogen Sulfide (1.00% - 1.77%), Carbon Dioxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

Hydrogen Sulfide (1.00% - 1.77%), Carbon Dioxide

Persistence and degradability	No data available.
-------------------------------	--------------------

Hydrogen sulfide (7783-06-4)

Persistence and degradability	Not applicable for inorganic gases.
-------------------------------	-------------------------------------

Carbon dioxide (124-38-9)

Persistence and degradability	No ecological damage caused by this product.
-------------------------------	--

12.3. Bioaccumulative potential

Hydrogen Sulfide (1.00% - 1.77%), Carbon Dioxide

Log Pow	Not applicable for gas-mixtures.
---------	----------------------------------

Log Kow	Not applicable for gas-mixtures.
---------	----------------------------------

Bioaccumulative potential	No data available.
---------------------------	--------------------

Hydrogen sulfide (7783-06-4)

BCF fish 1	(no bioaccumulation expected)
------------	-------------------------------

Log Pow	Not applicable for inorganic gases.
---------	-------------------------------------

Bioaccumulative potential	No data available.
---------------------------	--------------------

Carbon dioxide (124-38-9)

BCF fish 1	(no bioaccumulation)
------------	----------------------

Log Pow	0.83
---------	------

Bioaccumulative potential	No ecological damage caused by this product.
---------------------------	--

12.4. Mobility in soil

Hydrogen Sulfide (1.00% - 1.77%), Carbon Dioxide

Mobility in soil	No data available.
------------------	--------------------

Hydrogen sulfide (7783-06-4)

Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
----------------	---

Carbon dioxide (124-38-9)

Ecology - soil	No ecological damage caused by this product.
----------------	--

12.5. Other adverse effects

Effect on ozone layer : None.

Effect on the global warming : Contains greenhouse gas(es) not covered by 842/2006/EC.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Must not be discharged to atmosphere. Toxic and corrosive gases formed during combustion should be scrubbed before discharge to atmosphere. Ensure that the emission levels from local regulations or operating permits are not exceeded. Waste gas should be flared through a suitable burner with flash back arrestor.

Waste disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods.

Ecology - waste materials : Avoid release to the environment.

Hydrogen Sulfide (1.00% - 1.77%), Carbon Dioxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1956 Compressed gas, n.o.s.
UN-No.(DOT) : 1956
DOT NA no. : UN1956
DOT Proper Shipping Name : Compressed gas, n.o.s.
Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Symbols : G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306;307
DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;305
DOT Packaging Bulk (49 CFR 173.xxx) : 314;315
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Additional information

Other information : No supplementary information available.
Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

ADR

Transport document description :

Transport by sea

UN-No. (IMDG) : 1956
Proper Shipping Name (IMDG) : COMPRESSED GAS, N.O.S.
Class (IMDG) : 2.2 - Non-flammable, non-toxic gases

Air transport

UN-No.(IATA) : 1956
Proper Shipping Name (IATA) : COMPRESSED GAS, N.O.S.
Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Hydrogen sulfide (7783-06-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on the United States SARA Section 302
Listed on United States SARA Section 313

SARA Section 302 Threshold Planning Quantity (TPQ)	500
--	-----

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

Hydrogen Sulfide (1.00% - 1.77%), Carbon Dioxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

Hydrogen sulfide (7783-06-4)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Carbon dioxide (124-38-9)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas

EU-Regulations

Hydrogen sulfide (7783-06-4)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

Hydrogen sulfide (7783-06-4)
Listed on AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

Hydrogen sulfide (7783-06-4)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List
Carbon dioxide (124-38-9)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes	: Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.
	:
Other information	: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Full text of H-phrases: see section 16:

Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Compressed gas	Gases under pressure Compressed gas
Flam. Gas 1	Flammable gases Category 1
Liquefied gas	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated

Hydrogen Sulfide (1.00% - 1.77%), Carbon Dioxide

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H330	Fatal if inhaled
H335	May cause respiratory irritation
H380	May displace oxygen and cause rapid suffocation

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.