

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture

Product name : 5 Components in Methane

Product code : SG-2006-02844

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

### 1.3. Details of the supplier of the safety data sheet

Air Liquide 2700 Post Oak Boulevard Houston, TX 77056 - USA T 1-800-819-1704 www.us.airliquide.com

# 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### **GHS-US** classification

Flam. Gas 1 H220
Compressed gas H280
Acute Tox. 3 (Inhalation:gas) H331
STOT SE 3 H335

Full text of H-phrases: see section 16

# 2.2. Label elements

# **GHS-US** labeling

Hazard pictograms (GHS-US)

Precautionary statements (GHS-US)







S02

GHS04 GHS06

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H220 - Extremely flammable gas

H280 - Contains gas under pressure; may explode if heated

H331 - Toxic if inhaled

H335 - May cause respiratory irritation

CGA-HG04 - May form explosive mixtures with air

CGA-HG11 - Symptoms may be delayed

CGA-HG16 - Extended exposure to gas reduces the ability to smell sulfides.

: P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

P261 - Avoid breathing gas

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear eye protection, face protection, protective gloves, protective clothing

P284 - Wear respiratory protection. Consult respiratory device supplier's product information

for the selection of the appropriate device.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P307+P311 - If exposed: Call a poison center/doctor

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely

P381 - Eliminate all ignition sources if safe to do so

P403 - Store in a well-ventilated place

P405 - Store locked up

P501 - Dispose of contents/container in accordance with local/regional/national/international

regulations

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)

CGA-PG05 - Use a back flow preventive device in the piping

08/20/2015 EN (English US) Page 1

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CGA-PG06 - Close valve after each use and when empty

CGA-PG10 - Use only with equipment rated for cylinder pressure

CGA-PG14 - Approach suspected leak area with caution

CGA-PG18 - When returning cylinder, install leak tight valve outlet cap or plug

CGA-PG21 - Open valve slowly

CGA-PG29 - Do not depend on odor to detect presence of gas

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

# SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Methane	(CAS No) 74-82-8	0.00001 - 85.75996	Flam. Gas 1, H220 Compressed gas, H280
Hydrogen Sulfide	(CAS No) 7783-06-4	14.24 - 50	Flam. Gas 1, H220 Liquefied gas, H280 Acute Tox. 2 (Inhalation:gas), H330 STOT SE 3, H335 Aquatic Acute 1, H400
Hydrogen	(CAS No) 1333-74-0	0.00001 - 20	Flam. Gas 1, H220 Compressed gas, H280
n-Butane	(CAS No) 106-97-8	0.00001 - 10	Flam. Gas 1, H220 Liquefied gas, H280
Propane	(CAS No) 74-98-6	0.00001 - 10	Flam. Gas 1, H220 Liquefied gas, H280
Ethane	(CAS No) 74-84-0	0.00001 - 9.99999	Flam. Gas 1, H220 Liquefied gas, H280

Full text of H-phrases: see section 16

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Apply

artificial respiration with bag or mask if breathing stopped. Get immediate medical

advice/attention.

First-aid measures after skin contact : Adverse effects not expected from this product. First-aid measures after eye contact : Adverse effects not expected from this product.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

# 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory irritation. Toxic if inhaled. Symptoms/injuries after skin contact : Adverse effects not expected from this product. Symptoms/injuries after eye contact : Adverse effects not expected from this product.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous : Not known.

administration
Chronic symptoms

: Adverse effects not expected from this product.

# 4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet to extinguish.

# 5.2. Special hazards arising from the substance or mixture

Fire hazard : This product is flammable.

08/20/2015 EN (English US) 2/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries. May form flammable/explosive vapor-air mixture.

Reactivity : None known.

5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray

or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Do not enter fire area without proper protective equipment, including respiratory

protection.

# **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation.

### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment consistent with the site emergency plan.

Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent

premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep

upwind.

### 6.1.2. For emergency responders

Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Equip cleanup crew with proper protection.

Emergency procedures : Evacuate and limit access. Ventilate area. Remove ignition sources. Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering atmospheres of unknown contaminant concentration until

proven to be safe.

### 6.2. Environmental precautions

Try to stop release if safe to do so.

# 6.3. Methods and material for containment and cleaning up

For containment : Try to stop release if safe to do so.

Methods for cleaning up : Dispose of this material and its container in accordance with local regulations.

# 6.4. Reference to other sections

See also Sections 8 and 13.

# SECTION 7: Handling and storage

# 7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder

pressure. Close valve after each use and when empty. Handle empty containers with care because residual vapors are flammable. In use, may form flammable vapor-air mixture.

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well ventilated area. Keep away from heat/spacks/open flames/het surfaces. No smeking

in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use only non-sparking tools.

: Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity

should be followed.

Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in

use. Protect cylinder from physical damage. Store in well ventilated area. Store locked up.

Incompatible products : None known

Incompatible materials : Oxidizing materials. Air.

# 7.3. Specific end use(s)

See Section 1.2.

Hygiene measures

# SECTION 8: Exposure controls/personal protection

# 8.1. Control parameters

5 Components in Methane	
ACGIH	Not applicable

08/20/2015 EN (English US) 3/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5 Components in N	Methane		
OSHA	Not applicable		
n-Butane (106-97-8	3)		
ACGIH	ACGIH STEL (ppm)	1000 ppm	
OSHA	Not applicable		
Hydrogen Sulfide (	(7783-06-4)		
ACGIH	ACGIH TWA (ppm)	1 ppm	
ACGIH	ACGIH STEL (ppm)	5 ppm	
OSHA	OSHA PEL (Ceiling) (ppm)	20 ppm	
Propane (74-98-6)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
OSHA	OSHA PEL (TWA) (mg/m³)	1800 mg/m³	
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm	
Ethane (74-84-0)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
OSHA	OSHA Not applicable		
Methane (74-82-8)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
OSHA	Not applicable		
Hydrogen (1333-74	i-0)		
ACGIH	Not applicable		
OSHA	Not applicable		

### 8.2. Exposure controls

Appropriate engineering controls : Ensure exposure is below occupational exposure limits. Provide adequate general and local

exhaust ventilation. Systems under pressure should be regularly checked for leakages. Consider work permit system e.g. for maintenance activities. Alarm detectors should be used

when toxic gases may be released.

Hand protection : Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection.

Eye protection : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.

Respiratory protection : Wear a respirator when performing non-routine tasks not limited to line breaking or sampling.

Wear a respirator during routine operations if determined to be necessary during a process-specific review. Consult respirator suppliers' product information or their representatives for the

selection of the appropriate respirator.

Thermal hazard protection : None necessary during normal and routine operations.

Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

specific methods for waste gas treatment.

Other information : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Clear, colorless gas.

Color : Colorless

Odor : sulfide-like Rotten eggs.

Odor threshold : No data available pH : No data available Melting point : No data available Freezing point : No data available

08/20/2015 EN (English US) 4/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Boiling point : No data available
Flash point : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : See Section 2.1 and 2.2
Explosion limits : No data available

Explosive properties : Without adequate ventilation formation of explosive mixtures may be possible.

Oxidizing properties : None.

Vapor pressure : No data available
Relative density : No data available
Relative vapor density at 20 °C : No data available

Molecular mass : Not applicable for gas-mixtures.

Relative gas density : Heavier than air Solubility No data available Log Pow : No data available Log Kow : No data available Auto-ignition temperature No data available Decomposition temperature : No data available Viscosity No data available No data available Viscosity, kinematic Viscosity, dynamic No data available

9.2. Other information

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level.

# SECTION 10: Stability and reactivity

## 10.1. Reactivity

None known.

# 10.2. Chemical stability

Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Can form explosive mixture with air.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Oxidizing materials. Air.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

Acute toxicity : Inhalation:gas: Toxic if inhaled.

5 Components in Methane		
ATE US (gases)	949.333 ppmV/4h	
n-Butane (106-97-8)		
LC50 inhalation rat (mg/l)	658 g/m³ (Exposure time: 4 h)	
LC50 inhalation rat (ppm)	276789.28 ppm/4h	
Hydrogen Sulfide (7783-06-4)		
LC50 inhalation rat (mg/l)	0.99 mg/l (Exposure time: 1 h)	
LC50 inhalation rat (ppm)	356 ppm/4h	
ATE US (gases)	356.000 ppmV/4h	
ATE US (vapors)	0.990 mg/l/4h	

08/20/2015 EN (English US) 5/12

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hydrogen Sulfide (7783-06-4)	
ATE US (dust, mist)	0.990 mg/l/4h
Propane (74-98-6)	
LC50 inhalation rat (mg/l)	658 mg/l/4h
LC50 inhalation rat (ppm)	282800 ppm/4h
Ethane (74-84-0)	
LC50 inhalation rat (mg/l)	658 mg/l/4h
LC50 inhalation rat (ppm)	820000 ppm/4h
ATE US (gases)	820000.000 ppmV/4h
ATE US (vapors)	658.000 mg/l/4h
ATE US (dust, mist)	658.000 mg/l/4h
Methane (74-82-8)	
LC50 inhalation rat (ppm)	820000 ppm/4h
ATE US (gases)	820000.000 ppmV/4h
Hydrogen (1333-74-0)	
LC50 inhalation rat (ppm)	820000 ppm/4h
ATE US (gases)	820000.000 ppmV/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause respiratory irritation. Toxic if inhaled.
Symptoms/injuries after skin contact	: Adverse effects not expected from this product.
Symptoms/injuries after eye contact	: Adverse effects not expected from this product.
Symptoms/injuries after ingestion	: Ingestion is not considered a potential route of exposure.
Symptoms/injuries upon intravenous administration	: Not known.

# **SECTION 12: Ecological information**

### **Toxicity** 12.1.

Chronic symptoms

Hydrogen Sulfide (7783-06-4)		
LC50 fish 1	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])	
EC50 Daphnia 1	0.022 mg/l (Exposure time: 96 h - Species: Gammarus pseudolimnaeus)	
LC50 fish 2	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	

: Adverse effects not expected from this product.

### 12.2. Persistence and degradability

n-Butane (106-97-8)	
Persistence and degradability	No data available.
Hydrogen Sulfide (7783-06-4)	
Persistence and degradability	Not applicable for inorganic gases.

08/20/2015 EN (English US) 6/12

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Propane (74-98-6)		
Persistence and degradability	The substance is biodegradable. Unlikely to persist.	
Ethane (74-84-0)		
Persistence and degradability	The substance is biodegradable. Unlikely to persist.	
Methane (74-82-8)		
Persistence and degradability	The substance is biodegradable. Unlikely to persist. No data available.	
Hydrogen (1333-74-0)		
Persistence and degradability	No ecological damage caused by this product.	

### 12.3. **Bioaccumulative potential**

n-Butane (106-97-8)	
Log Pow	2.89
Log Kow	Not applicable for gas-mixtures.
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Hydrogen Sulfide (7783-06-4)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	Not applicable for inorganic gases.
Bioaccumulative potential	No data available.
Propane (74-98-6)	
Log Pow	2.36
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Ethane (74-84-0)	
Log Pow	1.81
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Methane (74-82-8)	
Log Pow	
1 209 . 0	Not applicable for gas mixtures
Log Kow	Not applicable for gas mixtures  Not applicable for gas mixtures
<u> </u>	
Log Kow	Not applicable for gas mixtures
Log Kow Bioaccumulative potential	Not applicable for gas mixtures
Log Kow Bioaccumulative potential Hydrogen (1333-74-0)	Not applicable for gas mixtures  Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

### 12.4. **Mobility in soil**

n-Butane (106-97-8)	
Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Hydrogen Sulfide (7783-06-4)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Propane (74-98-6)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Ethane (74-84-0)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Methane (74-82-8)	
Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Hydrogen (1333-74-0)	
Ecology - soil	No ecological damage caused by this product.

# Other adverse effects

Effect on ozone layer : No known effects from this product.

08/20/2015 EN (English US) 7/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# **SECTION 13: Disposal considerations**

### Waste treatment methods

Waste treatment methods

: Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into areas where there is a risk of forming an explosive mixture with air.

Waste disposal recommendations

Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods.

# **SECTION 14: Transport information**

### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN1953 Compressed gas, toxic, flammable, n.o.s. Inhalation Hazard Zone C/D

UN-No.(DOT) : UN1953

Proper Shipping Name (DOT) : Compressed gas, toxic, flammable, n.o.s.

Inhalation Hazard Zone C/D

Hazard labels (DOT) 2.3 - Poison gas

2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx)

DOT Packaging Bulk (49 CFR 173.xxx)

DOT Symbols

: 314:315

DOT Special Provisions (49 CFR 172.102)

: G - Identifies PSN requiring a technical name

: 3 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone C (see 173.116(a) of this subchapter), and must be described as an inhalation hazard under the

provisions of this subchapter.

B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per square foot per degree Fahrenheit) temperature differential. Insulating materials must not promote corrosion to steel when wet.

DOT Packaging Exceptions (49 CFR 173.xxx)

DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : Forbidden

CFR 175.75)

**DOT Vessel Stowage Location** 

: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.

**DOT Vessel Stowage Other** : 40 - Stow "clear of living quarters"

**Additional information** 

Other information : No supplementary information available.

**ADR** 

Transport document description : UN 1953 COMPRESSED GAS, TOXIC, FLAMMABLE, N.O.S., 2.3 (2.1), (B/D)

Class (ADR) 2 - Gases Hazard identification number (Kemler No.) : 263 Classification code (ADR) : 1TF

08/20/2015 EN (English US) 8/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (ADR) : 2.3 - Toxic gases

2.1 - Flammable gases



Orange plates

263 1953

Tunnel restriction code (ADR) : B/D
Limited quantities (ADR) : 0
Excepted quantities (ADR) : E0

Transport by sea

UN-No. (IMDG) : 1953

Proper Shipping Name (IMDG) : COMPRESSED GAS, TOXIC, FLAMMABLE, N.O.S.

Class (IMDG) : 2 - Gases

Air transport

UN-No. (IATA) : 1953

Proper Shipping Name (IATA) : COMPRESSED GAS, TOXIC, FLAMMABLE, N.O.S.

Class (IATA) : 2

# **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

n Butano (406 07 9)

11-Butaile (100-97-0)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

# Hydrogen Sulfide (7783-06-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on the United States SARA Section 302

Subject to reporting requirements of United States SARA Section 313

SARA Section 302 Threshold Planning
Quantity (TPQ)

SARA Section 313 - Emission Reporting

1.0 %

# Propane (74-98-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## Ethane (74-84-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

# Methane (74-82-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

# Hydrogen (1333-74-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

# 15.2. International regulations

# **CANADA**

n-Butane (106-97-8)	
Listed on the Canadian DSL (Domestic Sustances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas

08/20/2015 EN (English US) 9/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hydrogen Sulfide (7783-06-4)	
Listed on the Canadian DSL (Domestic Sustan	ces List)
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Propane (74-98-6)	
Listed on the Canadian DSL (Domestic Sustan	ces List)
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
Ethane (74-84-0)	
Listed on the Canadian DSL (Domestic Sustan	ces List)
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
Methane (74-82-8)	
Listed on the Canadian DSL (Domestic Sustan	ces List)
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
Hydrogen (1333-74-0)	
Listed on the Canadian DSL (Domestic Sustan	ces List)
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas

# **EU-Regulations**

### n-Butane (106-97-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

# Hydrogen Sulfide (7783-06-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

# Propane (74-98-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

# Ethane (74-84-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Methane (74-82-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

# Hydrogen (1333-74-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

# Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

## **National regulations**

# n-Butane (106-97-8)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

08/20/2015 EN (English US) 10/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## Hydrogen Sulfide (7783-06-4)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

### Propane (74-98-6)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

# Ethane (74-84-0)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### Methane (74-82-8)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### Hydrogen (1333-74-0)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### 15.3. US State regulations

### n-Butane (106-97-8)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

# Hydrogen Sulfide (7783-06-4)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - Pennsylvania - RTK (Right to Know) List

# Propane (74-98-6)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

# Ethane (74-84-0)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

08/20/2015 EN (English US) 11/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# Methane (74-82-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

### Hydrogen (1333-74-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

# **SECTION 16: Other information**

Indication of changes : Revised safety data sheet in accordance with OSHA final rule on GHS implementation

promulgated March 26, 2012.

Other information : This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29

CFR, 1910.1200. Other government regulations must be reviewed for applicability to this

product.

### Full text of H-phrases:

Acute toxicity (inhalation:gas) Category 2
Acute toxicity (inhalation:gas) Category 3
Hazardous to the aquatic environment - Acute Hazard Category 1
Gases under pressure Compressed gas
Flammable gases Category 1
Gases under pressure Liquefied gas
Specific target organ toxicity (single exposure) Category 3
Extremely flammable gas
Contains gas under pressure; may explode if heated
Fatal if inhaled
Toxic if inhaled
May cause respiratory irritation
Very toxic to aquatic life

### SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

08/20/2015 EN (English US) 12/12