



# Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/18/2015

Version: 2.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene  
Product code : SG-2005-02902

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

#### 1.3. Details of the supplier of the safety data sheet

Air Liquide  
2700 Post Oak Boulevard  
Houston, TX 77056 - USA  
T 1-800-819-1704  
[www.us.airliquide.com](http://www.us.airliquide.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Gas 1	H220
Liquefied gas	H280
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Repr. 2	H361
STOT SE 3	H336
STOT RE 2	H373
Asp. Tox. 1	H304

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H220 - Extremely flammable gas  
H280 - Contains gas under pressure; may explode if heated  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H361 - Suspected of damaging fertility or the unborn child  
H373 - May cause damage to organs (kidneys, liver) through prolonged or repeated exposure  
OSHA-H01 - May displace oxygen and cause rapid suffocation  
CGA-HG04 - May form explosive mixtures with air

Precautionary statements (GHS-US)

: P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P260 - Do not breathe gas  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear eye protection, face protection, protective gloves, protective clothing  
P301+P310 - If swallowed: Immediately call a doctor

# Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P302+P352 - If on skin: Wash with plenty of water  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P331 - Do NOT induce vomiting  
P362 - Take off contaminated clothing and wash it before reuse  
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely  
P381 - Eliminate all ignition sources if safe to do so  
P403 - Store in a well-ventilated place  
P405 - Store locked up  
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations  
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)  
CGA-PG05 - Use a back flow preventive device in the piping  
CGA-PG06 - Close valve after each use and when empty  
CGA-PG10 - Use only with equipment rated for cylinder pressure  
CGA-PG14 - Approach suspected leak area with caution  
CGA-PG21 - Open valve slowly

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Toluene	(CAS No) 108-88-3	88.9002 - 99.99996	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Octane	(CAS No) 111-65-9	0.00001 - 5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	0.00001 - 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:gas), H332 Skin Irrit. 2, H315
Ethylbenzene	(CAS No) 100-41-4	0.00001 - 0.9999	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 STOT RE 2, H373 Asp. Tox. 1, H304
Benzene	(CAS No) 71-43-2	0.00001 - 0.0999	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

# Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation occurs, seek medical attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May displace oxygen and cause rapid suffocation. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.
Symptoms/injuries upon intravenous administration	: Not known.
Chronic symptoms	: Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs (kidneys, liver) through prolonged or repeated exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use water jet to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: This product is flammable.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. May form flammable/explosive vapor-air mixture.
Reactivity	: None known.

### 5.3. Advice for firefighters

Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
Protection during firefighting	: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Ensure adequate ventilation.
------------------	--------------------------------

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear protective equipment consistent with the site emergency plan.
Emergency procedures	: Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

#### 6.1.2. For emergency responders

Protective equipment	: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.
Emergency procedures	: Evacuate and limit access. Ventilate area. Remove ignition sources. Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering atmospheres of unknown contaminant concentration until proven to be safe.

### 6.2. Environmental precautions

Try to stop release if safe to do so.

### 6.3. Methods and material for containment and cleaning up

For containment	: Try to stop release if safe to do so.
Methods for cleaning up	: Dispose of this material and its container in accordance with local regulations.

# Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.4. Reference to other sections

See also Sections 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Handle empty containers with care because residual vapors are flammable. In use, may form flammable vapor-air mixture.
- Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use only non-sparking tools.
- Hygiene measures : Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area. Store locked up.
- Incompatible products : None known.
- Incompatible materials : Oxidizing materials. Air.

### 7.3. Specific end use(s)

See Section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene		
ACGIH	Not applicable	
OSHA	Not applicable	
Benzene (71-43-2)		
ACGIH	ACGIH TWA (ppm)	0.5 ppm
ACGIH	ACGIH STEL (ppm)	2.5 ppm
OSHA	OSHA PEL (TWA) (ppm)	1 ppm
OSHA	OSHA PEL (STEL) (ppm)	5 ppm (see 29 CFR 1910.1028)
OSHA	OSHA PEL (Ceiling) (ppm)	25 ppm
Toluene (108-88-3)		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
Octane (111-65-9)		
ACGIH	ACGIH TWA (ppm)	300 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	2350 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm
Ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Xylenes (o-, m-, p- isomers) (1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm

# Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Xylenes (o-, m-, p- isomers) (1330-20-7)

ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure exposure is below occupational exposure limits. Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit system e.g. for maintenance activities.
Hand protection	: Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection.
Eye protection	: Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.
Respiratory protection	: None necessary during normal and routine operations. See Sections 5 & 6.
Thermal hazard protection	: None necessary during normal and routine operations.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
Other information	: Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless liquid.
Color	: Colorless
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: See Section 2.1 and 2.2
Explosion limits	: No data available
Explosive properties	: Without adequate ventilation formation of explosive mixtures may be possible.
Oxidizing properties	: None.
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Molecular mass	: No Data Available
Relative gas density	: Heavier than air
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

### 9.2. Other information

Additional information	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
------------------------	--

# Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

None known.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Can form explosive mixture with air.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

Oxidizing materials. Air.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Benzene (71-43-2)	
LD50 oral rat	5960 mg/kg Sig Ald
LD50 dermal rabbit	8263 mg/kg Sig Ald
LC50 inhalation rat (ppm)	26460 ppm/4h AS400
ATE US (oral)	930.000 mg/kg body weight
ATE US (gases)	26460.000 ppmV/4h
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg Sig Ald
LD50 dermal rabbit	12196 mg/kg Sig Ald
LC50 inhalation rat (mg/l)	12.5 mg/l/4h
LC50 inhalation rat (ppm)	26063 ppm/4h AS400
ATE US (oral)	5580.000 mg/kg body weight
ATE US (dermal)	12196.000 mg/kg body weight
ATE US (gases)	26063.000 ppmV/4h
ATE US (vapors)	12.500 mg/l/4h
ATE US (dust, mist)	12.500 mg/l/4h
Octane (111-65-9)	
LC50 inhalation rat (mg/l)	118 g/m <sup>3</sup> (Exposure time: 4 h)
LC50 inhalation rat (ppm)	25260 ppm/4h
ATE US (gases)	25260.000 ppmV/4h
ATE US (vapors)	118.000 mg/l/4h
ATE US (dust, mist)	118.000 mg/l/4h
Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg Sig Ald & mother sheet
LD50 dermal rabbit	15354 mg/kg Sig Ald & mother sheet
LC50 inhalation rat (mg/l)	17.2 mg/l/4h
LC50 inhalation rat (ppm)	8954.02 ppm/4h AS400
ATE US (oral)	3500.000 mg/kg body weight
ATE US (dermal)	15354.000 mg/kg body weight
ATE US (gases)	8954.020 ppmV/4h
ATE US (vapors)	17.200 mg/l/4h
ATE US (dust, mist)	17.200 mg/l/4h

# Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	4300 mg/kg
LC50 inhalation rat (mg/l)	47635 mg/l/4h
LC50 inhalation rat (ppm)	4550 ppm/4h
ATE US (oral)	4300.000 mg/kg body weight
ATE US (dermal)	1100.000 mg/kg body weight
ATE US (gases)	4550.000 ppmV/4h
ATE US (vapors)	47635.000 mg/l/4h
ATE US (dust, mist)	47635.000 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Benzene (71-43-2)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 2 - Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes
In OSHA Specifically Regulated Carcinogen list	Yes

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure)	: May cause damage to organs (kidneys, liver) through prolonged or repeated exposure.
--	---

Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May displace oxygen and cause rapid suffocation. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.
Symptoms/injuries upon intravenous administration	: Not known.
Chronic symptoms	: Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs (kidneys, liver) through prolonged or repeated exposure.

## SECTION 12: Ecological information

### 12.1. Toxicity

Benzene (71-43-2)	
LC50 fish 1	10.7 - 14.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	8.76 - 15.6 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 other aquatic organisms 1	29 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	5.3 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

# Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Benzene (71-43-2)</b>	
EC50 Daphnia 2	10 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Toluene (108-88-3)</b>	
LC50 fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 other aquatic organisms 1	> 433 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 2	12.5 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])
<b>Octane (111-65-9)</b>	
EC50 Daphnia 1	0.38 mg/l (Exposure time: 48 h - Species: water flea)
<b>Ethylbenzene (100-41-4)</b>	
LC50 fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	4.6 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
EC50 other aquatic organisms 2	> 438 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

<b>Benzene (71-43-2)</b>	
BCF fish 1	3.5 - 4.4
Log Pow	1.83
<b>Toluene (108-88-3)</b>	
Log Pow	2.65
<b>Octane (111-65-9)</b>	
Log Pow	5.18
<b>Ethylbenzene (100-41-4)</b>	
BCF fish 1	15
Log Pow	3.118
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
BCF fish 1	0.6 - 15
Log Pow	2.77 - 3.15

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on ozone layer : No known effects from this product.

Effect on the global warming : No known ecological damage caused by this product.



# Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into areas where there is a risk of forming an explosive mixture with air.
- Waste disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at [www.cganet.com](http://www.cganet.com) for more guidance on suitable disposal methods.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

- Transport document description : UN3501 Chemical under pressure, flammable, n.o.s., 2.1
- UN-No.(DOT) : UN3501
- Proper Shipping Name (DOT) : Chemical under pressure, flammable, n.o.s.
- Transport hazard class(es) (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
- Hazard labels (DOT) : 2.1 - Flammable gas



- DOT Packaging Non Bulk (49 CFR 173.xxx) : 335
- DOT Packaging Bulk (49 CFR 173.xxx) : 313;315
- DOT Symbols : G - Identifies PSN requiring a technical name
- DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
- DOT Packaging Exceptions (49 CFR 173.xxx) : None
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Forbidden
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 75 kg
- DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
- DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

#### Additional information

- Other information : No supplementary information available.

#### ADR

- Transport document description : UN 3501 CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S., 2.1, (B/D)
- Class (ADR) : 2 - Gases
- Classification code (ADR) : 8F
- Hazard labels (ADR) : 2.1 - Flammable gases



- Tunnel restriction code (ADR) : B/D
- Limited quantities (ADR) : 0
- Excepted quantities (ADR) : E0

# Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Transport by sea

UN-No. (IMDG)	: 3501
Proper Shipping Name (IMDG)	: Chemical Under Pressure, Flammable, N.O.S
Class (IMDG)	: 2 - Gases

### Air transport

UN-No. (IATA)	: 3501
Proper Shipping Name (IATA)	: Chemical Under Pressure, Flammable, N.O.S
Class (IATA)	: 2.1 - Gases : Flammable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Benzene (71-43-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

#### Toluene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

#### Octane (111-65-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

#### Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

### 15.2. International regulations

#### CANADA

#### Benzene (71-43-2)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

#### Toluene (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

#### Octane (111-65-9)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

#### Ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

# Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class B Division 2 - Flammable Liquid  
Class D Division 2 Subdivision A - Very toxic material causing other toxic effects  
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

### EU-Regulations

#### Benzene (71-43-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### Toluene (108-88-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### Octane (111-65-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### Ethylbenzene (100-41-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

### National regulations

#### Benzene (71-43-2)

Listed on IARC (International Agency for Research on Cancer)  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Japanese Pollutant Release and Transfer Register Law (PRTR Law)  
Listed as carcinogen on NTP (National Toxicology Program)  
Listed on the Canadian IDL (Ingredient Disclosure List)

#### Toluene (108-88-3)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Japanese Poisonous and Deleterious Substances Control Law  
Japanese Pollutant Release and Transfer Register Law (PRTR Law)  
Listed on the Canadian IDL (Ingredient Disclosure List)

#### Octane (111-65-9)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the Canadian IDL (Ingredient Disclosure List)

# Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Ethylbenzene (100-41-4)

Listed on the AICS (Australian Inventory of Chemical Substances)  
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
 Listed on the Korean ECL (Existing Chemicals List)  
 Listed on NZIoC (New Zealand Inventory of Chemicals)  
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
 Japanese Pollutant Release and Transfer Register Law (PRTR Law)  
 Listed on the Canadian IDL (Ingredient Disclosure List)

### Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the AICS (Australian Inventory of Chemical Substances)  
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
 Listed on the Korean ECL (Existing Chemicals List)  
 Listed on NZIoC (New Zealand Inventory of Chemicals)  
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
 Japanese Poisonous and Deleterious Substances Control Law  
 Japanese Pollutant Release and Transfer Register Law (PRTR Law)

## 15.3. US State regulations

### Benzene (71-43-2)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	No	Yes	6.4 µg/day

### Toluene (108-88-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	Yes	No	

### Ethylbenzene (100-41-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	54 µg/day

### Benzene (71-43-2)

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
 U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances  
 U.S. - Pennsylvania - RTK (Right to Know) List

### Toluene (108-88-3)

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
 U.S. - Pennsylvania - RTK (Right to Know) List

### Octane (111-65-9)

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) List

# Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Ethylbenzene (100-41-4)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Xylenes (o-, m-, p- isomers) (1330-20-7)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

- Indication of changes : Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.
- Other information : This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

### Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Liquefied gas	Gases under pressure Liquefied gas
Muta. 1B	Germ cell mutagenicity Category 1B
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H340	May cause genetic defects (Inhalation)
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

# **Benzene (0.00001% - 0.0999%), Ethyl Benzene (0.00001% - 0.9999%), n-Octane (0.00001% - 5.00%), Xylene (0.00001% - 5.00%) in Toluene**

## **Safety Data Sheet**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

*This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.*