



Safety Data Sheet

Product No. 16057 PELCO® High Temperature Carbon Paste

Issue Date (01-03-12)

Review Date (12-12-14)

Section 1: Product and Company Identification

Product Name: PELCO® High Temperature Carbon Paste

Synonym: None

Company Name

Ted Pella, Inc., P.O. Box 492477, Redding, CA 96049-2477

Domestic Phone (800) 237-3526 (Mon-Thu. 6:00AM to 4:30PM PST; Fri 6:00AM to 4:00PM PST)

International Phone (01) (530) 243-2200 (Mon-Thu. 6:00AM to 4:30PM PST; Fri 6:00AM to 4:00PM PST)

Chemtrec Emergency Number 1-800-424-9300 24 hrs a day.

Section 2: Hazard Identification

GHS Pictograms:



Irritant

GHS Categories: NIF

Signal Word: Warning

Health Effects: May cause moderate irritation to eyes, skin, and digestive tract.

Physical Hazards: Spilled material is slippery. Dries to form a glassy film that can cut skin.

HMIS® Hazard Rating: Health: 1; Fire: 0; Reactivity: 0 Personal Protection: C

NFPA Hazard Rating: Health: 1; Fire: 0; Reactivity: 0

(0=least, 1=Slight, 2=Moderate, 3=High, 4=Extreme)

Results of PBT and vPvB assessment:

PBT: NIF

vPvB: NIF

Emergency overview

Appearance: Black, odorless, paste.

Immediate effects: May cause moderate irritation to eyes, skin, and digestive tract

Potential health effects

Primary Routes of entry: Ingestion, Skin and eye contact. Mist inhalation.

Signs and Symptoms of Overexposure: NIF

Eyes: May cause moderate irritation to the eyes.

Skin: May cause moderate irritation to the skin.

Ingestion: May cause irritation to mouth, esophagus, and stomach.

Inhalation: Mists may cause irritation to upper respiratory track.

Chronic Exposure: No known chronic hazards.

Chemical Listed As Carcinogen Or Potential Carcinogen: Not listed on NTP, IARC or OSHA as carcinogen.

See Toxicological Information (Section 11)

Potential environmental effects

See Ecological Information (Section 12)

Section 3: Composition / Information on Ingredients

Principle Hazardous Component(s) (chemical and common name(s)) (Cas. No)	%	OSHA PEL mg/m3	ACGIH TLV mg/m3	NTP	IARC	OSHA regulated
Aluminum Oxide (1344-28-1)	*	NE	10	No	No	No
Graphite (7782-42-5)	*	2	15	No	No	No
Sodium Silicate Solution (1312-76-1)	*	NE	NE	No	No	No

Notes:

1) This product is a liquid mixture and all powders are encapsulated.

2) Exposure values shown for guidance only. Please follow applicable regulations.

* % Proprietary

Section 4: First Aid Measures

If accidental overexposure is suspected

Eye(s) Contact: Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek immediate medical attention, preferably with an ophthalmologist.

If a physician is not immediately available, eye irrigation should be continued for an additional 15 minutes.

Skin Contact: Immediately wipe excess material off skin with a dry cloth then wash with plenty of soap and water for at least 5 minutes. Seek medical attention if irritation develops or persists. Remove contaminated clothing and shoes and clean thoroughly before re-use.

Inhalation: Remove from immediate source of exposure and assure that victim is breathing. If not breathing, administer cardio-pulmonary resuscitation (CPR). If breathing is difficult, administer oxygen if available. Seek medical attention.

Ingestion: If swallowed, do not induce vomiting. If victim is conscious and alert, give 1-2 glasses of water to drink. Do not give anything by mouth to an unconscious person.

Seek medical attention immediately. Do not leave victim unattended. To prevent aspiration of swallowed product, lay victim on side with head lower than waist. Vomiting

may occur spontaneously. If vomiting occurs and the victim is conscious, give water to further dilute the chemical.

Note to physician

Treatment: NIF

Medical Conditions generally Aggravated by Exposure: Inhalation of product may aggravate existing chronic respiratory problems such as asthma, emphysema or bronchitis. Skin contact may aggravate existing skin disease.

Section 5: Fire Fighting Measures

Flash Point: Not applicable.

Flammable Limits: This material is non-combustible.

Auto-ignition point: Not applicable.

Fire Extinguishing Media: This material is compatible with all extinguishing media.

Special Fire Fighting Procedures: For large quantities, Firefighters should wear NIOSH/MSHA approved positive pressure breathing apparatus with full face piece and full chemical resistant protective clothing. Dike area to prevent runoff and contamination of water sources. Dispose of fire control water later.

Unusual Fire and Explosion Hazards: This material is non-combustible.

Hazardous combustion products: This material is non-combustible.

DOT Class: Not regulated.

Section 6: Accidental Release Measures

Steps to be Taken in Case Material is Released or Spilled: Wear chemical goggles, body-covering protective clothing, chemical resistant gloves, and rubber boots. Use NIOSH approved respirator where mist occurs.

Mop up and neutralize liquid, then discharge to sewer in accordance with federal, state and local

regulations or permits. Flush area with water to complete cleanup. Exercise caution during neutralization as heat may be generated.

Waste Disposal Methods: Dispose of waste according to Federal, State and Local Regulations.

Section 7: Handling and Storage

Precautions to be taken in Handling and Storage: Avoid contact with eyes, skin and clothing. Avoid breathing spray mist. Keep container closed. Promptly clean residue from closures with cloth dampened with water. Promptly clean up spills.

Store in an area that is cool, dry, well ventilated. Keep containers closed. Store in clean plastic or stainless steel containers

Storage temperature: Store in an area that is cool

Storage Pressure: NA

Section 8: Exposure Controls / Personal Protection

Engineering Controls

Ventilation required: Use with adequate ventilation.

Personal Protection Equipment

Respiratory protection: This product is not considered respirable in either the liquid or cured forms. However, if the cured product is polished, ground or chipped during processing, handling or use, powders may be released as airborne respirable particles. In these instances, appropriate personal protection equipment and local ventilation controls must be employed. If exposure limits are exceeded and local ventilation is unavailable, a supplied-air respirator or a self-contained NIOSH-approved dust and mist respirator is required.

Protective gloves: Wear protective gloves.

Skin protection: Wear body-covering protective clothing and gloves.

Eye protection: Wear chemical goggles.

Additional clothing and/or equipment: Safety shower and eyewash fountain should be within direct access.

Exposure Guidelines

See Composition/Information on Ingredients (Section 3)

Section 9 Physical and Chemical Properties

Appearance and Physical State: Viscous black paste.

Odor (threshold): Odorless

Specific Gravity (H₂O=1): 1.58

Vapor Pressure (mm Hg): ND

Vapor Density (air=1): ND

Percent Volatile by volume: ND

VOC Content, g/l: 0.00

Evaporation Rate (butyl acetate=1):

Boiling Point: ND

Freezing point / melting point: ND

pH: >11.0

Solubility in Water: Soluble

Molecular Weight: NA

Section 10: Stability and Reactivity

Stability: This material is stable under all conditions of use and storage.

Conditions to Avoid: High heat. Keep the cap tight on container.

Materials to Avoid (Incompatibility): Gels and generates heat when mixed with acid.

May react with ammonium salts resulting in evolution of ammonia gas. Flammable hydrogen gas may be produced on contact with aluminum, tin, lead, and zinc.

Hazardous Decomposition Products: None.

Hazardous Polymerization: Will not occur.

Section 11: Toxicological Information

Results of component toxicity test performed: ND

Human experience: ND

This product **does not** contain any compounds listed by NTP or IARC or regulated by OSHA as a carcinogen.

Section 12: Ecological Information

Ecotoxicity: Not tested

Environmental Fate: Not tested

Ecological Information: Sinks and mixes with water. Only water will evaporate from this material.

Chemical Fate Information: ND

Section 13 Disposal Considerations

RCRA 40 CFR 261 Classification: None

Federal, State and local laws governing disposal of materials can differ. Ensure proper disposal compliance with proper authorities before disposal.

Section 14: Transportation Information

The material is not a regulated hazardous material for transportation.

US DOT Information: Proper shipping name: Not regulated.

IATA: Proper shipping name: Not regulated.

Marine Pollutant: No

Canadian TDG: Not regulated.

Section 15: Regulatory Information

United States Federal Regulations

MSDS complies with OSHA's Hazard Communication Rule 29, CFR 1910.1200.

SARA: Sections 311, 312:

Hazard Classes

Fire Hazard No

Reactivity Hazard No

Pressure Hazard No

Immediate Hazard Yes

Delayed Hazard No

SARA Title III: Sections 302, 304, 313: This product does not contain any substances reportable under these sections.

RCRA: None

TSCA: All ingredients of this material are listed on the TSCA inventory.

CERCLA: No reportable quantity has been established for this material.

State Regulations

California Proposition 65:

International Regulations

International Inventory

Status

Canada (DSL)	Yes
Europe (EINECS/ELINCS)	Yes
Australia (AICS)	Yes
Japan (MITI)	Yes
South Korea (KECL)	Yes
Canada WHMIS: ND	
Europe EINECS Numbers: ND	

Section 16: Other Information

Label Information:

European Risk and Safety Phrases: ND

European symbols needed: ND

Canadian WHMIS Symbols: ND

Abbreviations used in this document

NE= Not established

NA= Not applicable

NIF= No Information Found

ND= No Data

Disclaimer

Ted Pella, Inc. makes no warranty of any kind regarding the information furnished herein. Users should independently determine the suitability and completeness of information from all sources. While this data is presented in good faith and believed to be accurate, it should be considered only as a supplement to other information gathered by the user. It is the User's responsibility to assure the proper use and disposal of these materials as well as the safety and health of all personnel who may work with or otherwise come in contact with these materials.