

Revision Date: 05/05/2016

SAFETY DATA SHEET

1. Identification

Material name: THIN TOP SUPREME

Material: 160T 50

Recommended use and restriction on use

Recommended use: Cement, Portland, chemicals

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY 19218 REDWOOD ROAD CLEVELAND OH 44110

US

Contact person:EH&S DepartmentTelephone:216-531-9222

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 1
Skin sensitizer Category 1B
Carcinogenicity Category 1A
Specific Target Organ Toxicity - Category 3
Single Exposure

Unknown toxicity - Health

Acute toxicity, oral 96.78 %
Acute toxicity, dermal 98.1 %
Acute toxicity, inhalation, vapor 100 %
Acute toxicity, inhalation, dust or mist 99.88 %

Unknown toxicity - Environment

Acute hazards to the aquatic 98.68 % environment

Chronic hazards to the aquatic 100 %

environment

Label Elements

Hazard Symbol:



Revision Date: 05/05/2016



Signal Word: Danger

Hazard Statement: Causes skin irritation.

Causes serious eye damage. May cause an allergic skin reaction.

May cause cancer.

May cause respiratory irritation.

Precautionary Statement: Prevention:

Wash thoroughly after handling. Wear protective gloves/protective

clothing/eye protection/face protection. Avoid breathing

dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-

ventilated area.

Response: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Immediately call a POISON CENTER/doctor. Specific treatment (see this label). Wash contaminated clothing before reuse.

Storage: Store locked up. Store in well-ventilated place. Keep container tightly

closed.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

3. Composition/information on ingredients

Mixtures

Chamical Identity	CAS number	Content in percent (9/)*
Chemical Identity	CAS number	Content in percent (%)*
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	60 - 100%
Portland cement	65997-15-1	15 - 40%
Silica, fused	60676-86-0	1 - 5%
Calcium salt	7778-18-9	1 - 5%
Fumed silica	69012-64-2	1 - 5%



Revision Date: 05/05/2016

Aluminum oxide	1344-28-1	0.1 - 1%
----------------	-----------	----------

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Wash contaminated clothing

before reuse. Get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Call a physician or poison control center

immediately.

Most important symptoms/effects, acute and delayed

Symptoms: Prolonged or repeated contact with skin may cause redness, itching,

irritation and eczema/chapping. Extreme irritation of eyes and mucous membranes, including burning and tearing. Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

6. Accidental release measures



Revision Date: 05/05/2016

Personal precautions, protective equipment and emergency procedures: See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning

Collect spillage in containers, seal securely and deliver for disposal

up:

according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not get in eyes. Avoid contact with skin.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Crystalline Silica	TWA	0.025	US. ACGIH Threshold Limit Values
(Quartz)/ Silica Sand - Respirable fraction.		mg/m3	(2011)
Crystalline Silica	TWA	2.4	US. OSHA Table Z-3 (29 CFR
(Quartz)/ Silica Sand -		millions of	1910.1000) (2000)
Respirable.		particles	
		per cubic	
		foot of air	
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR
			1910.1000) (2000)
Crystalline Silica	TWA	0.3 mg/m3	US. OSHA Table Z-3 (29 CFR
(Quartz)/ Silica Sand -			1910.1000) (2000)
Total dust.			
Portland cement -	TWA	1 mg/m3	US. ACGIH Threshold Limit Values
Respirable fraction.			(2011)
Portland cement - Total	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
dust.			Contaminants (29 CFR 1910.1000) (02 2006)
Portland cement -	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air



EUCLID CHEMICAL

Version: 3.0

Revision Date: 05/05/2016

Respirable fraction.			Contaminants (29 CFR 1910.1000) (02 2006)	
Portland cement	TWA	50 millions of particles per cubic	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)	
Silica, fused	TWA	foot of air 20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)	
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)	
Calcium salt - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)	
Calcium salt - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)	
Calcium salt - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)	
Fumed silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)	
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)	
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)	
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)	
Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)	



Revision Date: 05/05/2016

Chemical name	type	Exposure Limit Values	Source	
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97 as amended) (07 2007)	
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWAEV	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)	
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)	
Portland cement - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97 as amended) (07 2007)	
Portland cement - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)	
Portland cement	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)	
Portland cement - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)	
Portland cement - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)	
Silica, fused - Respirable.	TWAEV	0.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)	
Silica, fused - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)	
Calcium salt - Inhalable	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)	
Calcium salt - Inhalable fraction.	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)	
Calcium salt - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12	



Revision Date: 05/05/2016

			2008)	
Calcium salt - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)	
Fumed silica - Total fume.	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97 as amended) (07 2007)	
Fumed silica - Respirable fume.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)	
Fumed silica - Respirable.	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)	
Fumed silica - Respirable dust and/or fume.	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)	

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required.

Observe good industrial hygiene practices. Observe occupational exposure

limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable

level.

Eye/face protection: Wear a full-face respirator, if needed. Wear safety glasses with side shields

(or goggles) and a face shield.

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Do not get in eyes. Wash contaminated clothing before reuse. Avoid contact with skin.



Revision Date: 05/05/2016

9. Physical and chemical properties

Appearance

Physical state: solid
Form: Powder
Color: Gray
Odor: Odorless

Odor threshold:

pH:

No data available.

Flash Point:

No data available.

Evaporation rate:

No data available.

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

Explosive limit - lower (%):

No data available.

No data available.

No data available.

Vapor pressure:

No data available.

No data available.

No data available.

Relative density: 2.75

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
No data available.
No data available.
Pacomposition temperature:
No data available.
Viscosity:
No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition

Thermal decomposition or combustion may liberate carbon oxides and

Products: other toxic gases or vapors.



Revision Date: 05/05/2016

11. Toxicological information

Information on likely routes of exposure

Ingestion: May be harmful if swallowed.

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: Causes skin irritation.

Eye contact: Causes serious eye damage.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 4,403.39 mg/kg

Dermal

Product: No data available.

Inhalation

Product: No data available.

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Calcium salt in vivo (Rabbit): Experimental result, Key study

Fumed silica in vivo (Rabbit): Read-across from supporting substance (structural

analogue or surrogate), Weight of Evidence study

Aluminum oxide in vivo (Rabbit): Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium salt in vivo (Rabbit, 72 hrs): Not irritating

Aluminum oxide in vivo (Rabbit, 24 hrs): Not irritating



Revision Date: 05/05/2016

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Crystalline Silica

(Quartz)/ Silica

Sand

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline Silica Known To Be Human Carcinogen.

Overall evaluation: Carcinogenic to humans.

(Quartz)/ Silica

Sand

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.



Revision Date: 05/05/2016

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Calcium salt LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 1,970 mg/l

Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Calcium salt LC 50 (Water flea (Ceriodaphnia dubia), 24 h): > 1,940 mg/l Mortality

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Aluminum oxide EC 10 (Pimephales promelas, 7 d): 2.729 mg/l Experimental result, Weight

of Evidence study

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.



Revision Date: 05/05/2016

Mobility in Soil: No data available.

Other Adverse Effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u> <u>OSHA hazard(s)</u> Formaldehyde Acute toxicity

de Acute toxicity
Skin irritation
Skin sensitization
Flammability

respiratory tract irritation Respiratory sensitization

Cancer Eye irritation



Revision Date: 05/05/2016

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u> <u>Reportable quantity</u>

Formaldehyde 100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

<u>Reportable</u>

<u>Chemical Identity</u> <u>quantity</u> <u>Threshold Planning Quantity</u>

Formaldehyde 100 lbs. 500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity Reportable quantity

Formaldehyde 100 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u> <u>Threshold Planning Quantity</u>

Formaldehyde 500lbs Crystalline Silica (Quartz)/ 500 lbs

Silica Sand

Portland cement 500 lbs
Silica, fused 500 lbs
Calcium salt 500 lbs
Fumed silica 500 lbs
Aluminum oxide 500 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Chemical Identity Reportable quantity

Formaldehyde 15000 lbs

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Crystalline Silica (Quartz)/ Silica Sand Portland cement Silica, fused Calcium salt Fumed silica



Revision Date: 05/05/2016

US. Massachusetts RTK - Substance List

Chemical Identity

Crystalline Silica (Quartz)/ Silica Sand Portland cement Silica, fused Calcium salt Formaldehyde

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Crystalline Silica (Quartz)/ Silica Sand Portland cement Silica, fused Calcium salt

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

Other Regulations:

Regulatory VOC (less water 0 g/l

and exempt solvent):

VOC Method 310: 0.00 %

Inventory Status:

Australia AICS: All components in this product are listed on or

exempt from the Inventory.

Canada DSL Inventory List: All components in this product are listed on or

exempt from the Inventory.

EINECS, ELINCS or NLP: One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List: One or more components in this product are

not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances: All components in this product are listed on or

exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): All components in this product are listed on or

exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are

not listed on or exempt from the Inventory.



Revision Date: 05/05/2016

US TSCA Inventory: All components in this product are listed on or

exempt from the Inventory.

New Zealand Inventory of Chemicals:

All components in this product are listed on or

exempt from the Inventory.

Japan ISHL Listing: One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date: 05/05/2016

Version #: 3.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.