

# SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

Date of the previous version: 2015-10-13 Revision Date: 2015-10-26 Version 2

RING DOPE-E

1. IDENTIFICATION

**Product identifier** 

**SDS #**: 083834

Product name RING DOPE-E

Other means of identification

Product Code(s) 083834

Number 0N6 Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Lubricant. Industrial applications .

**Uses advised against**Do not use for any purpose other than the one for which it is intended

Details of the supplier of the safety data sheet

Supplier Address TOTAL Specialties USA Inc

1201 Louisiana Street, Suite 1800

Houston, TX 77002 Phone: +1 800 323 3198

Contact Point Technical/ HSEQ

E-mail Address USRMLIN-info@total.com

Emergency telephone number

**Company Phone Number** +1 (908) 862-9300

Emergency telephone CHEMTREC: +1 800 424 9300 (24h)

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)



Date of the previous version: 2015-10-13 Revision Date: 2015-10-26 Version 2

\_\_\_\_\_

**Unknown Acute Toxicity**No information available

Hazards not otherwise classified (HNOC)

Not applicable

Other information

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

**Environmental properties** Should not be released into the environment.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Distillates (petroleum), hydrotreated light	64742-53-6	25-65
naphthenic		

**Additional information** 

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

## 4. FIRST AID MEASURES

### First aid measures for different exposure routes

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR

EMERGENCY MEDICAL CARE.

Eye contact Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while

rinsing.

**Skin contact** Remove contaminated clothing and shoes. Wash skin with soap and water. Wash

contaminated clothing before reuse.

High pressure jets may cause skin damage. Take victim immediately to hospital. Wash off

with soap and water.

Inhalation Inhalation of high concentrations of vapor or aerosols may cause irritation of the upper

respiratory tract.

**Ingestion** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or Poison Control Center immediately. If swallowed, do not induce vomiting -

seek medical advice.

## Most important symptoms/effects, acute and delayed

<sup>\*</sup> The exact percentage (concentration) of composition has been withheld as a trade secret



Date of the previous version: 2015-10-13 Revision Date: 2015-10-26 Version 2

\_\_\_\_\_

**Skin contact** Not classified. High pressure injection of the products under the skin may have very serious

consequences even though no symptom or injury may be apparent.

Eye contact Not classified.

**Inhalation** Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory

system.

Ingestion Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

<u>Suitable Extinguishing Media</u> Foam. Carbon dioxide (CO<sub>2</sub>). ABC powder.

**Unsuitable Extinguishing Media**Do not use a solid water stream as it may scatter and spread fire.

<u>Special Hazard</u> Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Thermal decomposition can lead to release of irritating gases and vapors; Sulfur oxides.

**Explosion Data** 

Sensitivity to Mechanical Impact Sensitivity to Static Discharge None. None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely

slippery.

**Other information** See Section 12 for additional information.

Environmental precautions

**General Information** Do not flush into surface water or sanitary sewer system. Do not allow material to

contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained. Try to prevent the material from entering drains or water

courses. See Section 12 for additional Ecological Information.



Date of the previous version: 2015-10-13 Revision Date: 2015-10-26 Version 2

\_\_\_\_\_

### Methods and materials for containment and cleaning up

**Methods for cleaning up**Keep in suitable, closed containers for disposal. Dam up. Soak up with inert absorbent

material. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according

to local / national regulations (see section 13).

### 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling When using, do not eat, drink or smoke. For personal protection see section 8. Use only in

well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes

and clothing.

Prevention of fire and explosion Take precautionary measures against static discharges. Ground/bond containers, tanks

and transfer/receiving equipment.

**Hygiene measures** Ensure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do

not use abrasives, solvents or fuels. Do not dry hands with rags that have been

contaminated with product. Do not put product contaminated rags into workwear pockets.

#### Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical

contacts. Protect from frost, heat and sunlight. Protect from moisture.

Materials to Avoid Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure limits** Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH

(TLV) TWA 5 mg/m<sup>3</sup> (highly refined).

# **Exposure controls**



Date of the previous version: 2015-10-13 Revision Date: 2015-10-26 Version 2

Engineering Measures Apply technical measures to comply with the occupational exposure limits. When working in

confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for

breathing and wear the recommended equipment.

Individual protection measures, such as personal protective equipment

**General Information** If the product is used in mixtures, it is recommended that you contact the appropriate

protective equipment suppliers. These recommendations apply to the product as supplied.

**Eye/Face Protection** If splashes are likely to occur, wear:. Safety glasses with side-shields.

**Skin and body protection** Wear suitable protective clothing. Protective shoes or boots.

Hand Protection Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the

instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which

the product is used, such as the danger of cuts, abrasion, and the contact time.

Respiratory protection None required under normal usage. If exposure limits are exceeded or irritation is

experienced, NIOSH/MSHA approved respiratory protection should be worn.

Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local

regulations.

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do

not use abrasives, solvents or fuels. Do not dry hands with rags that have been

contaminated with product. Do not put product contaminated rags into workwear pockets.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical and chemical properties

Color black
Physical State @20°C liquid

Odor Characteristic

Odor Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks</u> <u>Method</u>

pH Melting point/range Not applicable

No information available

Boiling point/boiling range No information available

Flash point >= 160 °C Cleveland Open Cup (COC)

ASTM D 92



Date of the previous version: 2015-10-13 Revision Date: 2015-10-26 Version 2

\_\_\_\_\_

>= 320 °F

< 1 g/cm3

Cleveland Open Cup (COC).

ASTM D 92.

Evaporation rate

< 1 (n-Butyl Acetate=1) @ 25 °C

Flammability Limits in Air

No information available No information available

upper -Lower -

No information available

Vapor Pressure < 0.1 hPa Vapor density > 8 Relative density < 1 @ 38 °C (Air = 1) @ 25 °C

Density Water solubility @ 25 °C Insoluble

Solubility in other solvents

Soluble in many common

organic solvents

logPow
Autoignition temperature

No information available

Decomposition temperature

No information available No information available

Viscosity, kinematic

> 48 mm2/s Not explosive

Explosive properties Oxidizing Properties

No information available

Possibility of hazardous reactions

See section 10

Other information

Freezing Point No information available

Note • Please refer to Technical Data Sheet for further information

### 10. STABILITY AND REACTIVITY

Reactivity No information available.

<u>Chemical stability</u> Stable under recommended storage conditions.

<u>Possibility of hazardous reactions</u> Hazardous polymerization does not occur. None under normal processing.

Conditions to Avoid Take precautionary measures against static discharges. Heat (temperatures above flash

point), sparks, ignition points, flames, static electricity.

Incompatible Materials Strong oxidizing agents.

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Sulfur

oxides, Hydrogen sulphide.

# 11. TOXICOLOGICAL INFORMATION

### **Acute toxicity**

**Product Information** Product does not present an acute toxicity hazard based on known or supplied information.



Date of the previous version: 2015-10-13 **Revision Date: 2015-10-26** Version 2

Information on likely routes of exposure

**Principle Routes of Exposure** Inhalation, Ingestion, Eye contact, Skin contact.

**Numerical measures of toxicity** 

7266 mg/kg ATEmix (oral) ATEmix (dermal) 3185 mg/kg

Inhalation

ATEmix (inhalation-dust/mist) 6.8 mg/l ATEmix (inhalation-vapor) 201 mg/l

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	
light naphthenic			
64742-53-6			

#### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Skin contact Not classified. High pressure injection of the products under the skin may have very serious

consequences even though no symptom or injury may be apparent.

Eye contact Not classified.

Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory Inhalation

system.

Ingestion Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Not classified as a sensitizer. Sensitization

This product is not classified carcinogenic. Carcinogenicity

Chemical Name	ACGIH	IARC	NTP	OSHA
Distillates (petroleum),	-	-		-
hydrotreated light				
naphthenic				
64742-53-6				

This product is not classified as mutagenic. Mutagenicity

Reproductive toxicity This product does not present any known or suspected reproductive hazards. Other adverse effects

Characteristic skin lesions (pimples) may develop following prolonged and repeated

exposures (contact with contaminated clothing).

Not classified. **Aspiration Hazard** 

# 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**



Date of the previous version: 2015-10-13 Revision Date: 2015-10-26 Version 2

\_\_\_\_\_

#### Acute aquatic toxicity - Product Information

No experimental data available

### Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and	Toxicity to
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6		LC50 (96h) > 5000 mg/L Oncorhynchus mykiss ()	ether aquatic invertebrates EC50 (48h) > 1000 mg/L Daphnia magna	microorganisms

## Chronic aquatic toxicity - Product Information

No experimental data available

**Chronic aquatic toxicity - Component Information** 

Effects on terrestrial organisms No experimental data available .

Persistence and degradability

General Information No information available.

Bioaccumulative potential

**Product Information** No information available.

logPow No information available

**Component Information** No information available.

<u>Mobility</u>

**Soil** Given its physical and chemical characteristics, the product has no soil mobility.

Air Loss by evaporation is limited

Water The product is insoluble and floats on water

Other adverse effects

General Information No information available

# 13. DISPOSAL CONSIDERATIONS

#### **Waste treatment**

Waste Disposal Methods Dispose of in accordance with local regulations.



Date of the previous version: 2015-10-13 Revision Date: 2015-10-26 Version 2

\_\_\_\_\_

**Contaminated packaging** Dispose of in accordance with local regulations.

# 14. TRANSPORT INFORMATION

**DOT** Not regulated

TDG Not regulated

MEX Not regulated

<u>ICAO/IATA</u> Not regulated

IMDG/IMO Not regulated

ADR/RID Not regulated

ADN Not regulated

# 15. REGULATORY INFORMATION

following inventories:

U.S.A. (TSCA)

## U.S. Federal Regulations

## **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

# SARA 311/312 Hazard Categories

Acute Health Hazard no
Chronic Health Hazard no
Fire Hazard no
Sudden Release of Pressure Hazard no
Reactive Hazard no

# **Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).



Date of the previous version: 2015-10-13 Revision Date: 2015-10-26 Version 2

\_\_\_\_\_

## Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

## **U.S. State Regulations**

### **California Proposition 65**

This product does not contain any Proposition 65 chemicals.

#### U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois
Distillates (petroleum),	X			
hydrotreated light				
naphthenic				
64742-53-6				

# **16. OTHER INFORMATION**

NFPAHealth Hazard 1Flammability 1Instability 0Physical and chemical hazards -HMISHealth Hazard 1Flammability 1Physical Hazard 0Personal protection X

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

**Revision Date:** 2015-10-26

Revision Note \*\*\* Indicates updated section

Abbreviations, acronyms



Date of the previous version: 2015-10-13 Revision Date: 2015-10-26 Version 2

Legend Section 8

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration NIOSH - National Institute for Occupational Safety and Health

TLV - Threshold Limit Values PEL - Permissible Exposure Limits

IDHL - Immediately Dangerous to Life or Health concentrations

TWA - Time Weight Average STEL - Short Term Exposure Limits

S\* - Skin notation

TSCA - Toxic Substance Control Act

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet