

Product name	DEV CKX-5704	Revision Date	TNA/EN
MSDS number	87X013	Issuing date	NOT AUTHORIZED
Revision Number	NOT AUTHORIZED.01		Oct.24.2014

1. Identification of the substance/preparation and of the company/undertaking

DEV CKX-5704

Color Code:

See Section 16 for list of Color Codes

Manufacturer, importer, supplier

Ticona Polymer, Inc.

A business of Celanese

8040 Dixie Hwy.

Florence, KY 41042

United States

www.celanese.com

Transportation emergency phone numbers:

In USA, call 800 424 9300

Outside USA, call 703 527 3887, collect calls accepted.

Product Information

1-800-833-4882

info-engineeredmaterials-am@celanese.com

Synonyms:

Acetal copolymer

Polyoxymethylene copolymer

Identified uses

Plastic processing industry.

2. Hazards identification

Emergency Overview

Powdered material may form explosive dust-air mixtures

Potential health effects

Immediate effects

Skin

Polymer particles may cause mechanical irritation. The molten product can cause serious burns.

Eyes

Resin particles, like other inert materials, are mechanically irritating to eyes

Inhalation

Overheating in processing may generate hazardous, irritating vapours. Dust irritating to respiratory tract.

Ingestion

Low toxicity by this route is expected based on the biological activity of high molecular weight polymers.

Product name	DEV CKX-5704	Revision Date	TNA/EN
MSDS number	87X013	Issuing date	NOT AUTHORIZED
Revision Number	NOT AUTHORIZED.01		Oct.24.2014

Other: Formaldehyde, which is a degradation product, is listed as a potential cancer hazard by OSHA, a known human carcinogen by The International Agency for Research on Cancer (IARC, Group 1), and is listed in the 12th Report on Carcinogens (RoC) released by The National Toxicology Program (NTP). Formaldehyde should not pose a risk if exposures are kept below the OSHA Permissible Exposure Limit.

Medical conditions which may be aggravated by exposure: No specific information available on the product. Off-gases, which may be released if overheated, may affect those with chronic diseases of the respiratory system.

3. Composition/information on ingredients

Chemical characterization 1,3,5-Trioxane, polymer with 2,2-1,4-butanediylbis(oxymethylene)bisoxirane and 1,3-dioxolane; CAS-RN: 41258-95-1

Components	CAS-No	Percent %
Formaldehyde	50-00-0	Trace level contaminant

This product may contain proprietary ingredients.

This is a polymeric material. Any hazardous constituents are wetted by the polymer system, and therefore are unlikely to present exposure under normal conditions of processing and handling.

4. First aid measures

Skin

Cool skin rapidly with cold water after contact with molten polymer. Immediate medical attention is required. Do not peel solidified product off the skin.

Eyes

Immediately flush eye(s) with plenty of water. Call a physician if irritation persists.

Inhalation

Move to fresh air in case of accidental inhalation of vapors. Get medical attention immediately if symptoms occur.

Ingestion

If swallowed, do not induce vomiting - seek medical advice.

Notes to physician

This product is essentially inert and nontoxic. However, if it is overheated or burns, gases such as carbon monoxide and formaldehyde may be released. Those exposed to off-gases may need to have their arterial blood gases and carboxyhemoglobin levels checked. If the carboxyhemoglobin levels are normal and the exposure occurred in an enclosed space, asphyxia (carbon dioxide replacing oxygen) is a possibility. Formaldehyde is a respiratory irritant gas. If patients may have inhaled high concentrations of irritating fumes they should be monitored for delayed onset pulmonary edema

5. Fire-fighting measures

Product name	DEV CKX-5704		TNA/EN
MSDS number	87X013	Revision Date	NOT AUTHORIZED
Revision Number	NOT AUTHORIZED.01	Issuing date	Oct.24.2014

5. Fire-fighting measures

Suitable extinguishing media

Water, Foam

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases

Hazardous combustion products

Carbon monoxide

Carbon dioxide (CO₂)

Formaldehyde vapours

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit.

Environmental precautions

Dike and collect water used to fight fire..

Other Information

Risk of dust explosion.

6. Accidental release measures

Personal precautions

Remove all sources of ignition. Avoid dust formation. Do not breathe dust.

Environmental precautions

No special environmental precautions required.

Methods for cleaning up

Use mechanical handling equipment.

7. Handling and storage

Advice on safe handling

Do not exceed recommended process temperatures to minimize release of decomposition products. Do not handle hot or molten material without appropriate protective equipment. Maintain good housekeeping in work areas.

Protection - fire and explosion

Do not smoke in areas where polymer dust is present. Appropriate measures should be taken to control the generation and accumulation of dust during conveying and processing operations. Risk of dust explosion

Material storage

Store in a cool dry place. Maintain dryness of resin.

Incompatible products

strong acids oxidizing agents Polyvinyl chloride

Product name DEV CKX-5704
MSDS number 87X013
Revision Number NOT AUTHORIZED.01

Revision Date TNA/EN
Issuing date NOT AUTHORIZED
Oct.24.2014

8. Exposure controls/personal protection

OSHA Exposure Limits

Components	TWA
Formaldehyde	0.75 PPM

ACGIH Exposure Limits

Components	Ceiling Limit Value:
Formaldehyde	0.3 PPM

Components	Manufacturer Workplace Exposure Limit
Formaldehyde	0.75 ppm (TWA); 2 ppm (STEL)

Mexico National Exposure Limits

Components	Mexican Carcinogen Category
Formaldehyde	A2

Components	Mexican Ceiling Exposure Limit
Formaldehyde	3 mg/m ³ 2 PPM

Exposure controls

Engineering measures

General: May not be adequate as the sole means to control employee exposure.

Local Exhaust: Recommended when appropriate to control employee exposure to dust or process vapors

General advice

Do not breathe dust. Avoid contact with skin and eyes.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment

Skin protection:

When thermal or melt processing, wear long pants, long sleeves, well insulated gloves, and face shield when there is a chance of contact.

Eyel/face protection:

safety glasses with side-shields. Safety goggles.

Comments:

Operations involving grinding and machining of parts should be reviewed to assure that particulate levels are kept below recommended standards

Product name	DEV CKX-5704	Revision Date	TNA/EN
MSDS number	87X013	Issuing date	NOT AUTHORIZED
Revision Number	NOT AUTHORIZED.01		Oct.24.2014

9. Physical and chemical properties

Appearance

Form	powder
Odor	slight , specific . (>200°F)
Method	closed cup
Ignition temperature	420°C (608°F)
Method	ASTM D 1929
Lower explosion limit	250 g/m ³
Melting Point	170 °C
Density	1.35 g/ml @ 20°C
Method	

Bulk density	approx 0.5 - 0.65 g/cm ³
Vapor pressure	not determined
Water solubility	insoluble

10. Stability and reactivity

Chemical stability

Stable under normal conditions.

Conditions to avoid

Flame. Do not allow mixing of this material with PVC, other halogen containing materials, and partially and/or fully crosslinkable thermoplastic elastomers.

Incompatible Materials

strong acids, oxidizing agents, Polyvinyl chloride.

Hazardous Combustion or Decomposition Products:

Trioxane, formaldehyde, formic acid, paraformaldehyde, Isocyanates.

Possibility of hazardous reactions

Polyvinyl chloride, Incompatible with strong acids and oxidizing agents.

11. Toxicological information

No data is available on the product itself

12. Ecological information

Ecotoxicological data are not available.

Product name	DEV CKX-5704	Revision Date	TNA/EN
MSDS number	87X013	Issuing date	NOT AUTHORIZED
Revision Number	NOT AUTHORIZED.01		Oct.24.2014

13. Disposal considerations

Disposal considerations

Recycling is encouraged. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

This product as shipped is not a RCRA hazardous waste under present EPA regulations

14. Transport information

US Department of Transportation Not regulated

TDG Not regulated

Mexico Transport Information Not regulated

ICAO/IATA Not regulated

IMDG Not regulated

15. Regulatory information

U.S. FEDERAL REGULATIONS

TSCA Inventory

This product complies with the U.S. Toxic Substances Control Act (TSCA).

SARA 313 Chemicals

Contains no substances at or above the reporting threshold under Section 313.

CANADIAN REGULATIONS

WHMIS Classification:

Not a WHMIS controlled product.

WHMIS Ingredient Disclosure List IDL:

This product does not contain substances required to be disclosed according to the Canada WHMIS Ingredient Disclosure List.

16. Other information

NFPA:	Health: 1	Flammability: 0	Instability: 0
HMIS:	Health: 1	Flammability: 0	Physical Hazard: 0

Product name	DEV CKX-5704		TNA/EN
MSDS number	87X013	Revision Date	NOT AUTHORIZED
Revision Number	NOT AUTHORIZED.01	Issuing date	Oct.24.2014

16. Other information

Color code(s)

CC45270, CC45290

Prepared By

Product Stewardship Department
Celanese

Other Information:

Observe national and local legal requirements

Except as otherwise noted, all of the trademarks referenced herein are owned by Ticona or its affiliates.

Changes against the previous version are marked by ***

This product is not intended for use in medical or dental implants.

The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. Celanese makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. User has sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.

Abbreviation and Acronym:

ADR = Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS = Chemical Abstracts Service (division of the American Chemical Society)

CLP = Classification, Labelling and Packaging

EINECS = European Inventory of Existing Commercial Chemical Substances

DNEL = Derived No Effect Level

IATA = International Air Transport Association

IBC Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk (IMO)

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

ICAO = International Civil Aviation Organization

IMDG = International Maritime Code for Dangerous Goods