

## **Safety Data Sheet**

Product No. 18394 Paraplast® X-TRA Issue Date (03-03-15) Review Date (05-15-15)

**Section 1: Product and Company Identification** 

**Product Name: Paraplast® X-TRA** 

Synonym: None **Company Name** 

Ted Pella, Inc., P.O. Box 492477, Redding, CA 96049-2477

Domestic Phone (800) 237-3526 (Mon-Thu. 6:00AM to 4:30PM PST; Fri 6:00AM to 4:00PM PST)

International Phone (01) (530) 243-2200 (Mon-Thu. 6:00AM to 4:30PM PST; Fri 6:00AM to 4:00PM PST)

Chemtrec Emergency Number 1-800-424-9300 24 hrs a day.

#### **Section 2: Hazard Identification**

GHS Pictograms: None. Not classified as dangerous/hazardous.

GHS Categories: None known when used as directed.

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS): Not classified as dangerous.

EU Classification (67-548/EEC): Not classified as dangerous.

Signal Word: NA

## **Health Effects:**

NFPA Hazard Rating: Health: 0; Fire: 1; Reactivity: 0 HMIS® Hazard Rating: Health: 0; Fire: 1; Reactivity: 0 (0=least, 1=Slight, 2=Moderate, 3=High, 4=Extreme)

Results of PBT and vPvB assessment: A chemical safety assessment has not been carried out.

PBT: ND vPvB: ND

# **Emergency overview:**

Appearance: Waxy pellets.

Immediate effects: No immediate treatment is normally required. Contact with molten product may cause thermal burns. Vapors or fumes from molten material may cause eye and respiratory tract irritation.

#### **Potential health effects**

Primary Routes of entry: Skin and eye contact, inhalation.

Signs and Symptoms of Overexposure: Upper respiratory tract irritation and nausea.

Eyes: Contact may cause slight, transient irritation. Wax fumes may cause eye irritation with redness and tearing. Contact with molten product may cause thermal burns.

Skin: Contact with molten product may cause thermal burns.

Ingestion: Small amounts are not anticipated to cause adverse effects. Large quantities may cause obstruction of the bowel.

Inhalation: Inhalation of fumes may cause irritation of the eyes, nose and upper respiratory tract. Symptoms include coughing, sneezing and sore throat.

Chronic Exposure: Contact with molten product may cause thermal burns. Vapors or fumes from molten material may cause eye and respiratory tract irritation.

Chemical Listed As Carcinogen or Potential Carcinogen: No

See Toxicological Information (Section11)

## **Potential environmental effects**

See Ecological Information (Section 12)

**Section 3: Composition / Information on Ingredients** 

D T	0.4					
Principle Hazardous Component(s) (chemical and common name(s)) (Cas. No)	%	OSHA PEL mg/m3	ACGIH TLV mg/m3	NTP Carcinogen	IARC Carcinogen	OSHA regulated Carcinogen
Paraffin (Paraffin wax) (8002-74-2) EC-No. 232-315-6	>75	NE	2 TWA 6 STEL	No	No	No
Resin (Proprietary)	<25	NE	NE	No	No	No

<sup>\*</sup> The Occupational Safety and Health Administration (OSHA) and the American Conference of Governmental Industrial Hygienists (ACGIH) have not established exposure limits for this product. However, exposure limits do exist for the primary hazardous ingredient, which is present at greater than 90%: Paraffin (8002-74-2) fumes.

## **Section 4: First Aid Measures**

### If accidental overexposure is suspected

Eye(s) Contact: Flush eyes with water, holding the eyelids apart. Get medical attention if irritation persists. If product is hot, flush eyes with water, holding the eyelids apart. Get immediate medical attention.

Skin Contact: Wash skin with soap and water after handling. If product is molten, cool skin with large amounts of water. Do not remove material bonded to the skin. Do not apply saves or ointment. Get medical attention. Launder contaminated clothing before reuse.

Inhalation: Remove victim to fresh air. Get medical attention if symptoms persist. Ingestion: If small quantities are swallowed, rinse out mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. If large amounts are swallowed or if irritation or discomfort occurs, get medical attention.

## Note to physician

Treatment: ND

Medical Conditions generally Aggravated by Exposure: ND

## **Section 5: Fire Fighting Measures**

Flash Point: 400 °F (204 °C) Method: Closed Cup

Flammable Limits: ND

Auto-ignition point: 473 °F (245 °C) (for 100% paraffin)

Fire Extinguishing Media: Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide. Use any media that is suitable for the surrounding fire.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing for firefighting if necessary. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

Unusual Fire and Explosion Hazards: Not classified as flammable but product will burn under fire conditions. Reaction with oxidizers may generate heat and cause fire. Hazardous combustion products: Carbon monoxide, carbon dioxide, wax fumes and smoke.

DOT Class: Not regulated.

### **Section 6: Accidental Release Measures**

Steps to be taken in Case Material is Released or Spilled:

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate protective equipment. Avoid contact with molten material. Avoid dust formation. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. For personal protection see section 8.

**Environmental precautions:** Prevent entry in storm sewers and waterways. Report spill as required by local and federal regulations.

Methods and materials for containment and cleaning up: At ambient temperatures, pick up material and place into a container for disposal. If molten, allow material to solidify and cool. Pick up or scrape up and place into a container for disposal.

Waste Disposal Methods: Dispose of waste according to Federal, State and Local Regulations.

### **Section 7: Handling and Storage**

Precautions to be taken in Handling and Storage:

Precautions for safe handling: Avoid contact with molten material. Avoid breathing fumes from heated material. Use with adequate ventilation. Protect containers from physical damage. Store in a cool area. Keep containers closed when not in use. Empty containers retain product residues. Do not cut, weld, braze, etc. on or near empty containers. Follow all SDS precautions in handling empty containers.

Storage temperature: 2 - 8°C

Storage Pressure: NA

# Section 8: Exposure Controls / Personal Protection Control parameters:

<b>Chemical Name</b>	US OEL	EU IOEL	UK OEL	Germany OEL		
Paraffin wax	2 mg/m3 TWA	None Est	2 mg/m3 TWA	None Est		
fumes	ACGIH TLV		6 mg/m3 STEL			
<b>Chemical Name</b>	Biological Limit Value					
Paraffin Wax	None Est					

**Exposure Controls: Recommended Monitoring Procedures:** Collection on filters with analysis by gas chromatography.

# **Engineering Controls**

Ventilation required: Use with adequate local exhaust ventilation to maintain exposure levels below the occupational exposure limits.

# **Personal Protection Equipment**

Respiratory protection: Not normally needed for normal use.

Protective gloves: None needed if handing product at ambient temperatures. Wear insulated gloves when handling hot material.

Skin protection: Clothing with long sleeves should be worn when working with molten product.

Eye protection: None needed if handing product at ambient temperatures. Wear safety glasses when handling hot material.

Additional clothing and/or equipment: Suitable washing facilities should be available.

# **Exposure Guidelines**

See Composition/Information on Ingredients (Section 3)

### **Section 9 Physical and Chemical Properties**

Appearance and Physical State: Waxy pellets. Colorless-white, translucent.

Odor (threshold): Odorless Specific Gravity (H<sub>2</sub>O=1): ND Vapor Pressure (mm Hg): NA Vapor Density (air=1): NA Percent Volatile by volume: ND

Evaporation Rate (butyl acetate=1): NA

Boiling Point: NE

Freezing point / melting point: 54 °C (122 °F)

pH: NA

Solubility in Water: Insoluble Molecular Weight: Mixture

### **Section 10: Stability and Reactivity**

Stability: Stable under recommended storage conditions.

Conditions to Avoid: Extreme heat.

Materials to Avoid (Incompatibility): Strong oxidizing agents

Hazardous Decomposition Products: Thermal breakdown of this product during fire or

very high heat conditions may evolve the following decomposition products: oxides of carbon, wax fumes, and smoke.

Hazardous Polymerization: Will not occur.

# **Section 11: Toxicological Information**

Results of component toxicity test performed:

Acute toxicity: Paraffin Wax: LD50 oral rat >5000 mg/kg

Skin corrosion/irritation: Wax: negligible skin irritant based on studies with rabbits for similar materials.

Eye damage/irritation: Wax: may cause mild, transient irritation based on studies with rabbits for similar materials.

Respiratory Irritation: No data available for mixture. High concentrations of wax fumes may be irritating to the respiratory system.

Respiratory Sensitization: No data available. None of the components are respiratory sensitizers.

Skin Sensitization: No data available for mixture. Wax: non-sensitizing in tests with laboratory animals and humans.

Germ Cell Mutagenicity: Wax: not mutagenic in in-vitro studies. None of the components are germ cell mutagens.

Carcinogenicity: No data available for mixture. Wax: Not carcinogenic in lifetime animal skin painting or oral feeding studies. None of the components of this product are listed as carcinogens by OSHA, ACGIH, IARC, NTP, or the EU Dangerous Substances Directive. Reproductive Toxicity: No data available for mixture.

Specific Target Organ Toxicity: Single Exposure: None known

Repeat Exposure: Wax: High oral doses in one rat strain (F-344) resulted in microscopic inflammatory changes (micro granulomas) in liver, spleen, and lymph nodes, some increased organ weights, inflammation of the cardiac mitral valve, and accumulation of saturated mineral hydrocarbons in certain tissues.

Human experience: ND

This product **does not** contain any compounds listed by NTP or IARC or regulated by OSHA as a carcinogen.

### **Section 12: Ecological Information**

Ecological Information:

Toxicity: No data available. Not expected to be harmful to aquatic organisms. Persistence and degradability: Wax: Expected to be inherently biodegradable. Bio accumulative Potential: Wax: Has the potential to bio accumulate, however metabolism or physical properties may reduce the bio concentration or limit bioavailability.

Mobility in Soil: Wax: Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

Chemical Fate Information: ND

#### **Section 13 Disposal Considerations**

RCRA 40 CFR 261 Classification: None

Federal, State and local laws governing disposal of materials can differ. Ensure proper disposal compliance with proper authorities before disposal.

# **Section 14: Transportation Information**

<u>US DOT Information</u>: Proper shipping name: Not regulated.

IATA: Proper shipping name: Not regulated.

Marine Pollutant: No

Canadian TDG: Not regulated.

## **Section 15: Regulatory Information**

# **United States Federal Regulations**

MSDS complies with OSHA's Hazard Communication Rule 29, CFR 1910.1200.

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

RCRA: Not listed.

TSCA: All components are listed.

CERCLA: Not listed.

## **State Regulations**

California Proposition 65: This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Massachusetts Right To Know Components: Paraffin waxes and Hydrocarbon waxes (CAS-No. 8002-74-2), Revision Date: 2007-03-01

Pennsylvania Right to Know Components: Paraffin waxes and Hydrocarbon waxes (CAS-No. 8002-74-2) Revision Date: 2007-03-01-2

New Jersey Right To Know Components: Paraffin waxes and Hydrocarbon waxes (CAS-No. 8002-74-2) Revision Date 2007-03-01 -2

# **International Regulations**

Canada WHMIS: Not a controlled product.

Europe EINECS Numbers: Paraffin (8002-74-2): EINECS#: 232-315-6.

## **Section 16: Other Information**

Label Information: ND

European Risk and Safety Phrases: ND

European symbols needed: ND

Canadian WHMIS Symbols: Not a controlled product.

## Abbreviations used in this document

NE= Not established

NA= Not applicable

NIF= No Information Found

ND= No Data

## Disclaimer

Ted Pella, Inc. makes no warranty of any kind regarding the information furnished herein. Users should independently determine the suitability and completeness of information from all sources. While this data is presented in good faith and believed to be accurate, it should be considered only as a supplement to other information gathered by the user. It is the User's responsibility to assure the proper use and disposal of these materials as well as the safety and health of all personnel who may work with or otherwise come in contact with these materials.

SDS Form 0013F1V4