

BRIWAX ORIGINAL

Page: 1

Compilation date: 20/02/2014

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BRIWAX ORIGINAL

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road Cricklewood London NW2 7TX

United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xi: R38; Xn: R48/20; Xn: R63; -: R67

Classification under CLP: Flam. Liq. 1: H224; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3:

H336

Most important adverse effects: Highly flammable. Irritating to skin. Harmful: danger of serious damage to health by

prolonged exposure through inhalation. Possible risk of harm to the unborn child.

Vapours may cause drowsiness and dizziness.

2.2. Label elements

Label elements under CLP:

Hazard statements: H224: Extremely flammable liquid and vapour.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H361d: Suspected of damaging the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard

BRIWAX ORIGINAL

Page: 2







Precautionary statements: P260: Do not breathe fumes.

P280: Wear protective gloves.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.

Rinse skin with water.

P210: Keep away from open flames. - No smoking.
P314: Get medical advice/attention if you feel unwell.

P102: Keep out of reach of children.

Label elements under CHIP:

Hazard symbols: Highly flammable.

Harmful.





Risk phrases: R11: Highly flammable.

R38: Irritating to skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through

inhalation.

R63: Possible risk of harm to the unborn child.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S36/37: Wear suitable protective clothing and gloves.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TOLUENE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
203-625-9	108-88-3	F: R11; Xi: R38; Xn: R48/20; Xn: R63; Xn: R65; -: R67	Flam. Liq. 2: H225; Repr. 2: H361d; Asp. Tox. 1: H304; STOT RE 2: H373;	81.400%
			Skin Irrit. 2: H315; STOT SE 3: H336	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least

BRIWAX ORIGINAL

Page: 3

10 minutes, holding the eyelids apart, and seek medical advice. If irritation persists seek

medical attention.

Ingestion: If accidentally swallowed, wash mouth out with water. Do not induce vomiting, keep at

rest and obtain medical attention.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. If effects occur remove to

fresh air and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: May casue stomach pain, nausea and vomiting, irritation of mouth and throat.

Inhalation: Nausea may occur. Dizziness and headache. Harmful by inhalation.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Move the exposed person to fresh air at once.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol resistant foam. Do not use water. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. In combustion emits toxic fumes of carbon dioxide / carbon

monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of

ignition. Avoid inhaling vapour. Wear appropriate protective clothing.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer into a suitable container for disposal in

accordance with the waste regulations (see section 13)

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

BRIWAX ORIGINAL

Page: 4

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Do not handle in a confined space. Use only in well ventilated areas. Where prolonged

or repeated exposure is likely Protective Clothing should be worn including impervious

gloves and eye protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep away from

direct sunlight.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

TOLUENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	191 mg/m3	384 mg/m3	_	_

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. If these are not sufficient to maintain

concentrations of particulates and/or solvent vapours below the relevant occupational

exposure limits, suitable respiratory protective equipment should be worn (see

Respiratory protection below).

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Nitrile gloves.Eye protection: Safety glasses.Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Emulsion

Solubility in water: Insoluble

Boiling point/range ℃: <=35 Flash point ℃: <21

BRIWAX ORIGINAL

Page: 5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Hot surfaces.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Acids. Bases.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

TOLUENE

IVN	RAT	LD50	1960	mg/kg
ORL	MUS	LD50	2	gm/kg
ORL	RAT	LD50	6900	mg/kg

Relevant effects for mixture:

Effect	Route	Basis	
Irritation	DRM	Hazardous: calculated	
Repeated dose toxicity	INH	Hazardous: calculated	

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

 $\textbf{Ingestion:} \ \ \text{May casue stomach pain, nausea and vomiting, irritation of mouth and throat.}$

Inhalation: Nausea may occur. Dizziness and headache. Harmful by inhalation.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

BRIWAX ORIGINAL

Page: 6

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Volatile.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Transport class: 3.2

14.4. Packing group

Packing group: 2

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

BRIWAX ORIGINAL

Page: 7

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H224: Extremely flammable liquid and vapour.

H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H361d: Suspected of damaging the unborn child.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

R11: Highly flammable.

R38: Irritating to skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

-- --- -

R63: Possible risk of harm to the unborn child.

R65: Harmful: may cause lung damage if swallowed.

R67: Vapours may cause drowsiness and dizziness.

Legend to abbreviations: PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

BRIWAX ORIGINAL

Page: 8

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.