



Solvent Blend 19306

Material Safety Data Sheet

CITGO Petroleum Corporation
1701 Golf Road, Suite 1-1101
Rolling Meadows, IL 60008-4295

MSDS No. 19306
Revision Date 8/25/2009

IMPORTANT: This MSDS is prepared in accordance with 29 CFR 1910.1200. Read this MSDS before transporting, handling, storing or disposing of this product and forward this information to employees, customers and users of this product.

Emergency Overview

Physical State Liquid.

Color Transparent, colorless.

Odor Characteristic hydrocarbon solvent odor.

DANGER:

EXTREMELY FLAMMABLE LIQUID AND VAPOR, VAPOR MAY CAUSE FLASH FIRE.

Vapor may travel considerable distance to source of ignition and flash back.

Harmful or fatal if swallowed - can enter lungs and cause damage.

Breathing high concentrations can cause irregular heartbeats which may be fatal.

May be harmful if inhaled or absorbed through the skin.

Can cause eye, skin or respiratory tract irritation.

Overexposure can cause central nervous system (CNS) depression and/or other target organ effects.

Harmful to aquatic organisms.

Hazard Rankings

	HMIS	NFPA
Health Hazard	* 2	1
Fire Hazard	3	3
Reactivity	0	0

* = Chronic Health Hazard

Protective Equipment

Minimum Recommended
See Section 8 for Details



SECTION 1. PRODUCT IDENTIFICATION

Trade Name	Solvent Blend 19306	Technical Contact	(847) 734-7699 (8am - 4pm CT M-F)
Product Number	19306	Medical Emergency	(832) 486-4700
CAS Number	Mixture.	CHEMTREC Emergency (United States Only)	(800) 424-9300
Product Family	Petroleum hydrocarbon solvent		
Synonyms	Petroleum hydrocarbon solvent; CITGO® Material Code: 19306		

SECTION 2. COMPOSITION

This product may be composed, in whole or in part, of any of the following refinery streams:

Naphtha, petroleum, hydrotreated light [CAS No.: 64742-49-0]

Naphtha, petroleum, solvent-refined light [CAS No.: 64741-84-0]

This product contains the following components:

Component Name(s)	CAS Registry No.	Concentration (%)
-------------------	------------------	-------------------

Solvent Blend 19306

Heptane, all isomers	142-82-5	15 - 40
n-Hexane	110-54-3	10 - 30
Hexane, other isomers	Mixture	10 - 30
Methylcyclopentane	96-37-7	1 - 15
Cyclohexane	110-82-7	1 - 5
Octanes, all isomers	Mixture	1 - 5
Methylcyclohexane	108-87-2	1 - 5

SECTION 3. HAZARDS IDENTIFICATION

Also see Emergency Overview and Hazard Ratings on the top of Page 1 of this MSDS.

Major Route(s) of Entry Skin contact. Eye contact. Inhalation. Ingestion.

Signs and Symptoms of Acute Exposure

Inhalation Breathing high concentrations may be harmful. Mist or vapor can irritate the throat and lungs. Breathing this material may cause central nervous system depression with symptoms including nausea, headache, dizziness, fatigue, drowsiness, or unconsciousness. Breathing high concentrations of this material, for example, in an enclosed space or by intentional abuse, can cause irregular heartbeats which can cause death.

Eye Contact This product can cause transient mild eye irritation with short-term contact with liquid sprays or mists. Symptoms include stinging, watering, redness, and swelling.

Skin Contact This material can cause skin irritation. The severity of irritation will depend on the amount of material that is applied to the skin and the speed and thoroughness that it is removed. Symptoms include redness, itching, and burning of the skin. Repeated or prolonged skin contact can produce moderate irritation (dermatitis).

Ingestion If swallowed, this material may irritate the mucous membranes of the mouth, throat, and esophagus. It can be readily absorbed by the stomach and intestinal tract. Symptoms include a burning sensation of the mouth and esophagus, nausea, vomiting, dizziness, staggered gait, drowsiness, loss of consciousness and delirium, as well as additional central nervous system (CNS) effects.

Due to its light viscosity, there is a danger of aspiration into the lungs during swallowing and subsequent vomiting. Aspiration can result in severe lung damage or death. Cardiovascular effects include shallow rapid pulse with pallor (loss of color in the face) followed by flushing (redness of the face). Also, progressive CNS depression, respiratory insufficiency and ventricular fibrillation leads to death.

Chronic Health Effects Summary Prolonged and/or repeated contact may cause skin irritation and inflammation. Symptoms include defatting, redness, blistering, lesions, and scaly dermatitis.

Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction.

Reports have associated repeated and prolonged occupational overexposure to light petroleum products with irreversible brain and nervous system damage (sometimes referred to as "Solvent or Painter's Syndrome"). Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

Repeated and prolonged overexposure to n-hexane has been associated with peripheral nerve tissue damage. Adverse effects include numbness, tingling, pain, and loss of muscle control in the extremities, disorientation, impaired vision and reflexes, decline in motor function and paralysis.

Conditions Aggravated by Exposure Disorders of the following organs or organ systems that may be aggravated by significant exposure to this material or its components include: Skin, Respiratory System, Liver, Kidneys, Peripheral Nervous System, Central Nervous System (CNS)

Target Organs May cause damage to the following organs: kidneys, lungs, liver, mucous membranes, heart, peripheral nervous system, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea

Solvent Blend 19306

Carcinogenic Potential This product is not known to contain any components at concentrations above 0.1% which are considered carcinogenic by OSHA, IARC or NTP.

OSHA Hazard Classification is indicated by an "X" in the box adjacent to the hazard title. If no "X" is present, the product does not exhibit the hazard as defined in the OSHA Hazard Communication Standard (29 CFR 1910.1200).					
OSHA Health Hazard Classification			OSHA Physical Hazard Classification		
Irritant	☒	Sensitizer	☐	Combustible	☐
Toxic	☐	Highly Toxic	☐	Flammable	☒
Corrosive	☐	Carcinogenic	☐	Compressed Gas	☐
				Explosive	☐
				Oxidizer	☐
				Organic Peroxide	☐
				Pyrophoric	☐
				Water-reactive	☐
				Unstable	☐

SECTION 4. FIRST AID MEASURES

Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid. For more specific information, refer to Exposure Controls and Personal Protection in Section 8 of this MSDS.

Inhalation	Immediately move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). If breathing is difficult, 100 percent humidified oxygen should be administered by a qualified individual. Seek medical attention immediately.
Eye Contact	Flush eyes with cool, clean, low-pressure water for at least 15 minutes. Hold eyelids apart to ensure complete irrigation of the eye and eyelid tissue. If easily accomplished, check for and remove contact lenses. If contact lenses cannot be removed, seek immediate medical attention. Do not use eye ointment. Seek medical attention.
Skin Contact	Remove contaminated shoes and clothing. Flush affected area with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. Do not use ointments. If skin surface is not damaged, clean affected area thoroughly with mild soap and water. Seek medical attention if tissue appears damaged or if pain or irritation persists.
Ingestion	Do not induce vomiting. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Never give anything by mouth to a person who is not fully conscious. Do not leave victim unattended. Seek medical attention immediately.
Notes to Physician	INHALATION: Inhalation overexposure can produce toxic effects. Monitor for respiratory distress. If cough or difficulty in breathing develops, evaluate for upper respiratory tract inflammation, bronchitis, and pneumonitis. Administer supplemental oxygen with assisted ventilation, as required.

This material (or a component) sensitizes the heart to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this material. Administration of sympathomimetic drugs should be avoided.

INGESTION: If ingested, this material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.

SECTION 5. FIRE FIGHTING MEASURES

NFPA Flammability Classification	NFPA Class-IB flammable liquid.
Flash Point	Closed cup: -23°C (-10°F). (Estimated)

Lower Flammable Limit AP 1 %

Upper Flammable Limit AP 6.7 %

Solvent Blend 19306

Autoignition Temperature	Not available.
Hazardous Combustion Products	Carbon dioxide, carbon monoxide, smoke, fumes, and/or unburned hydrocarbons.
Special Properties	Flammable Liquid! This material releases vapors at or below ambient temperatures. When mixed with air in certain proportions and exposed to an ignition source, its vapor can cause a flash fire. Use only with adequate ventilation. Vapors are heavier than air and may travel long distances along the ground to an ignition source and flash back. A vapor and air mixture can create an explosion hazard in confined spaces such as sewers. If container is not properly cooled, it can rupture in the heat of a fire.
Extinguishing Media	SMALL FIRE: Use dry chemicals, carbon dioxide, foam, or inert gas (nitrogen). Carbon dioxide and inert gas can displace oxygen. Use caution when applying carbon dioxide or inert gas in confined spaces. LARGE FIRE: Use foam, water fog, or water spray. Water may be ineffective. Water may not extinguish the fire. Water fog and spray are effective in cooling containers and adjacent structures. However, water can be used to cool the external walls of vessels to prevent excessive pressure, autoignition or explosion. DO NOT use a solid stream of water directly on the fire as the water may spread the fire to a larger area.
Protection of Fire Fighters	Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Evacuate area and fight the fire from a maximum distance or use unmanned hose holders or monitor nozzles. Cover pooling liquid with foam. Containers can build pressure if exposed to radiant heat; cool adjacent containers with flooding quantities of water until well after the fire is out. Withdraw immediately from the area if there is a rising sound from a venting safety device or discoloration of vessels, tanks, or pipelines. Be aware that burning liquid will float on water. Notify appropriate authorities of potential fire and explosion hazard if liquid enter sewers or waterways.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up. For more specific information, refer to the Emergency Overview on Page 1, Exposure Controls and Personal Protection in Section 8 and Disposal Considerations in Section 13 of this MSDS.

Flammable Liquid! Release causes an immediate fire or explosion hazard. Evacuate all non-essential personnel from immediate area and establish a "regulated zone" with site control and security. A vapor-suppressing foam may be used to reduce vapors. Eliminate all ignition sources. All equipment used when handling this material must be grounded. Stop the leak if it can be done without risk. Do not touch or walk through spilled material. Remove spillage immediately from hard, smooth walking areas. Prevent spilled material from entering waterways, sewers, basements, or confined areas. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material.

For large spills, secure the area and control access. Prevent spilled material from entering sewers, storm drains, other drainage systems, and natural waterways. Dike far ahead of a liquid spill to ensure complete collection. Water mist or spray may be used to reduce or disperse vapors; but, it may not prevent ignition in closed spaces. This material will float on water and its run-off may create an explosion or fire hazard. Verify that responders are properly HAZWOPER-trained and wearing appropriate respiratory equipment and fire-resistant protective clothing during cleanup operations. In an urban area, cleanup spill as soon as possible; in natural environments, cleanup on advice from specialists. Pick up free liquid for recycle and/or disposal if it can be accomplished safely with explosion-proof equipment. Collect any excess material with absorbent pads, sand, or other inert non-combustible absorbent materials. Place into appropriate waste containers for later disposal. Comply with all applicable local, state and federal laws and regulations.

SECTION 7. HANDLING AND STORAGE

Handling

A spill or leak can cause an immediate fire or explosion hazard. Keep containers closed and do not handle or store near heat, sparks, or any other potential ignition sources. Avoid contact with oxidizing agents. Do NOT breathe vapor. Use only with adequate ventilation and personal protection. Never siphon by mouth. Avoid contact with eyes, skin, and clothing. Prevent contact with food and tobacco products. Do NOT take internally.

When performing repairs and maintenance on contaminated equipment, keep unnecessary persons away from the area. Eliminate all potential ignition sources. Drain and purge equipment, as necessary, to remove material residues. Follow proper entry procedures, including compliance with 29 CFR 1910.146 prior to entering confined spaces such as tanks or pits. Use gloves constructed of impervious materials and protective clothing if direct contact is anticipated. Use appropriate respiratory protection when concentrations exceed any established occupational exposure level (See Section 8) Promptly remove contaminated clothing. Wash exposed skin thoroughly with soap and water after handling.

Non-equilibrium conditions may increase the fire hazard associated with this product. A static electrical charge can accumulate when this material is flowing through pipes, nozzles or filters and when it is agitated. A static spark discharge can ignite accumulated vapors particularly during dry weather conditions. Always bond receiving containers to the fill pipe before and during loading. Always confirm that receiving container is properly grounded. Bonding and grounding alone may be inadequate to eliminate fire and explosion hazards associated with electrostatic charges. Carefully review operations that may increase the risks associated with static electricity such as tank and container filling, tank cleaning, sampling, gauging, loading, filtering, mixing, agitation, etc. In addition to bonding and grounding, efforts to mitigate the hazards of an electrostatic discharge may include, but are not limited to, ventilation, inerting and/or reduction of transfer velocities. Dissipation of electrostatic charges may be improved with the use of conductivity additives when used with other mitigation efforts, including bonding and grounding. Always keep nozzle in contact with the container throughout the loading process.

Do NOT fill any portable container in or on a vehicle. Do NOT use compressed air for filling, discharging or other handling operations. Product container is NOT designed for elevated pressure. Do NOT pressurize, cut, weld, braze solder, drill, or grind on containers. Do NOT expose product containers to flames, sparks, heat or other potential ignition sources. Empty containers may contain material residues which can ignite with explosive force. Observe label precautions.

Storage

Keep container tightly closed. Store in a cool, dry, well-ventilated area. Store only in approved containers. Do not store with oxidizing agents. Do not store at elevated temperatures or in direct sunlight. Protect containers against physical damage. Head spaces in tanks and other containers may contain a mixture of air and vapor in the flammable range. Vapor may be ignited by static discharge. Storage area must meet OSHA requirements and applicable fire codes. Additional information regarding the design and control of hazards associated with the handling and storage of flammable and combustible liquids may be found in professional and industrial documents including, but not limited to, the National Fire Protection Association (NFPA) publications NFPA 30 ("Flammable and Combustible Liquid Code"), NFPA 77 ("Recommended Practice on Static Electricity") and the American Petroleum Institute (API) Recommended Practice 2003, ("Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents").

Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers or waste residues of this product.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls Provide ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits indicated below. All electrical equipment should comply with the National Electrical Code. An emergency eye wash station and safety shower should be located near the work-station.

Personal Protective Equipment Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations. The following pictograms represent the minimum requirements for personal protective equipment. For certain operations, additional PPE may be required.



Eye Protection Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. Chemical goggles should be worn during transfer operations or when there is a likelihood of misting, splashing, or spraying of this material. A suitable emergency eye wash water and safety shower should be located near the work station.

Hand Protection Avoid skin contact. Use heavy duty gloves constructed of chemical resistant materials such as Viton® or heavy nitrile rubber. Wash hands with plenty of mild soap and water before eating, drinking, smoking, use of toilet facilities or leaving work. DO NOT use gasoline, kerosene, solvents or harsh abrasives as skin cleaners.

Body Protection Avoid skin contact. Wear long-sleeved fire-retardant garments (e.g., Nomex®) while working with flammable and combustible liquids. Additional chemical-resistant protective gear may be required if splashing or spraying conditions exist. This may include an apron, boots and additional facial protection. If product comes in contact with clothing, immediately remove soaked clothing and shower. Promptly remove and discard contaminated leather goods.

Respiratory Protection Odor is not an adequate warning for potentially hazardous air concentrations. For unknown vapor or gas concentrations, use a positive-pressure, pressure-demand, supplied air respirator. Respirators should be selected and used in accordance with OSHA requirements (29 CFR 1910.134).

General Comments Warning! Use of this material in spaces without adequate ventilation may result in generation of hazardous levels of flammable vapors and/or inadequate oxygen levels for breathing. Odor is an inadequate warning for hazardous conditions.

Occupational Exposure Guidelines

Substance	Applicable Workplace Exposure Levels
Heptane, all isomers	ACGIH (United States). TWA: 400 ppm 8 hour(s). STEL: 500 ppm 15 minute(s). OSHA (United States). TWA: 500 ppm 8 hour(s).
n-Hexane	ACGIH (United States). Skin TWA: 50 ppm 8 hour(s). OSHA (United States). TWA: 500 ppm 8 hour(s).
Hexane, other isomers	ACGIH (United States). TWA: 500 ppm 8 hour(s). STEL: 1000 ppm 15 minute(s). OSHA (United States). TWA: 300 ppm 8 hour(s).
Cyclohexane	ACGIH (United States). TWA: 100 ppm 8 hour(s). OSHA (United States). TWA: 300 ppm 8 hour(s).

Solvent Blend 19306

Octanes, all isomers

ACGIH (United States).
TWA: 300 ppm 8 hour(s).
OSHA (United States).
TWA: 500 ppm 8 hour(s).
ACGIH (United States).
TWA: 400 ppm 8 hour(s).
OSHA (United States).
TWA: 500 ppm 8 hour(s).

Methylcyclohexane

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES (TYPICAL)

Physical State	Liquid.	Color	Transparent, colorless.	Odor	Characteristic hydrocarbon solvent odor.
Specific Gravity	0.69 (Water = 1)	pH	Not applicable	Vapor Density	>1 (Air = 1)
Boiling Range	71 to 98°C (160 to 208°F)			Melting/Freezing Point	Not available.
Vapor Pressure	12 kPa (90 mm Hg) (at 20°C)			Volatility	690 g/l VOC (w/v)
Solubility in Water	Very slightly soluble in cold water. (<0.1 % w/w)			Viscosity (cSt @ 40°C)	Not available.
Flash Point	Closed cup: -23°C (-10°F). (Estimated)				
Additional Properties	Conductivity = <5 picosiemens/meter (unadditized)				

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability	Stable.	Hazardous Polymerization	Not expected to occur.
Conditions to Avoid	Keep away from all ignition sources and strong oxidizing conditions.		
Materials Incompatibility	Strong acids, alkalies, and oxidizers such as liquid chlorine and oxygen.		
Hazardous Decomposition Products	No additional hazardous decomposition products were identified other than the combustion products identified in Section 5 of this MSDS.		

SECTION 11. TOXICOLOGICAL INFORMATION

For other health-related information, refer to the Emergency Overview on Page 1 and the Hazards Identification in Section 3 of this MSDS.

Toxicity Data	Heptane, all isomers n-Heptane was not mutagenic in the Salmonella/microsome (Ames) assay and is not considered to be carcinogenic. n-Hexane This material contains n-hexane. Long-term or repeated exposure to n-hexane can cause permanent peripheral nerve damage. Initial symptoms are numbness of the fingers and toes. Also, motor weakness can occur in the digits, but may also involve muscles of the arms, thighs and forearms. The onset of these symptoms may be delayed for several months to a year after the beginning of exposure. Co-exposure to methylethyl ketone or methyl isobutyl ketone increases the neurotoxic properties of n-hexane. In laboratory studies, prolonged exposure to elevated concentrations of n-hexane was associated with decreased sperm count and degenerative changes in the testicles of rats.
----------------------	--

Solvent Blend 19306

Cyclohexane

ORAL (LD50): Acute: 12705 mg/kg [Rat]. 813 mg/kg [Mouse].

Cyclohexane can cause eye, skin and mucous membrane irritation, CNS depressant and narcosis at elevated concentrations. In experimental animals exposed to lethal concentrations by inhalation or oral route, generalized vascular damage and degenerative changes in the heart, lungs, liver, kidneys and brain were identified.

Cyclohexane has been the focus of substantial testing in laboratory animals. Cyclohexane was not found to be genotoxic in several tests including unscheduled DNA synthesis, bacterial and mammalian cell mutation assays, and in vivo chromosomal aberration. An increase in chromosomal aberrations in bone marrow cells of rats exposed to cyclohexane was reported in the 1980's. However, a careful re-evaluation of slides from this study by the laboratory which conducted the study indicates these findings were in error, and that no significant chromosomal effects were observed in animals exposed to cyclohexane. Findings indicate long-term exposure to cyclohexane does not promote dermal tumorigenesis.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity	Ecotoxicity data are not available for this product. Aquatic toxicity values are expected to be in the range of 1 - 10 mg/l based upon data from components and similar products. This mixture contains components that are potentially toxic to freshwater and saltwater ecosystems.
Environmental Fate	This product will normally float on water. Components will evaporate rapidly. This material may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment. The octanol-water partition coefficient (log Kow) for this product is expected to be in the range of 2.1 to 5.

SECTION 13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

Maximize material recovery for reuse or recycling. Recovered non-usable material may be regulated by US EPA as a hazardous waste due to its ignitibility (D001) and/or its toxic (D018) characteristics. Conditions of use may cause this material to become a "hazardous waste", as defined by federal or state regulations. It is the responsibility of the user to determine if the material is a RCRA "hazardous waste" at the time of disposal. Transportation, treatment, storage and disposal of waste material must be conducted in accordance with RCRA regulations (see 40 CFR 260 through 40 CFR 271). State and/or local regulations may be more restrictive. Contact your regional US EPA office for guidance concerning case specific disposal issues.

SECTION 14. TRANSPORT INFORMATION

The shipping description below may not represent requirements for all modes of transportation, shipping methods or locations outside of the United States.

US DOT Status	A U.S. Department of Transportation regulated material.		
Proper Shipping Name	UN1268, Petroleum Distillates, n.o.s. (Naphtha Solvent), 3, PG II		
Hazard Class	3	Packing Group	II
		UN/NA Number	UN1268
Reportable Quantity	A Reportable Quantity (RQ) has not been established for this material.		

Solvent Blend 19306

Placard(s)



Emergency Response
Guide No.

128

MARPOL III Status

Not a DOT "Marine
Pollutant" per 49 CFR
171.8.

SECTION 15. REGULATORY INFORMATION

TSCA Inventory	This product and/or its components are listed on the Toxic Substances Control Act (TSCA) inventory.
SARA 302/304 Emergency Planning and Notification	The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to Subparts 302 and 304 to submit emergency planning and notification information based on Threshold Planning Quantities (TPQs) and Reportable Quantities (RQs) for "Extremely Hazardous Substances" listed in 40 CFR 302.4 and 40 CFR 355. No components were identified.
SARA 311/312 Hazard Identification	The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to this subpart to submit aggregate information on chemicals by "Hazard Category" as defined in 40 CFR 370.2. This material would be classified under the following hazard categories: Fire, Acute (Immediate) Health Hazard, Chronic (Delayed) Health Hazard
SARA 313 Toxic Chemical Notification and Release Reporting	This product contains the following components in concentrations above <i>de minimis</i> levels that are listed as toxic chemicals in 40 CFR Part 372 pursuant to the requirements of Section 313 of SARA: n-Hexane [CAS No.: 110-54-3] Concentration: 10 - 30% Cyclohexane [CAS No.: 110-82-7] Concentration: <5%
CERCLA	The Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) requires notification of the National Response Center concerning release of quantities of "hazardous substances" equal to or greater than the reportable quantities (RQ's) listed in 40 CFR 302.4. As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically designated in 40 CFR 302.4. Chemical substances present in this product or refinery stream that may be subject to this statute are: n-Hexane [CAS No.: 110-54-3] RQ = 5000 lbs. (2268 kg) Concentration: 10 - 30% Cyclohexane [CAS No.: 110-82-7] RQ = 1000 lbs. (453.6 kg) Concentration: <5% Benzene [CAS No.: 71-43-2] RQ = 10 lbs. (4.536 kg) Concentration: <0.02%
Clean Water Act (CWA)	This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.
California Proposition 65	This material may contain the following components which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5): Benzene: <0.06% Toluene: <0.02% Ethylbenzene: <0.01%
New Jersey Right-to-Know Label	For New Jersey R-T-K labeling requirements, refer to components listed in Section 2.

Solvent Blend 19306

Additional Remarks

Federal Hazardous Substances Act, related statutes, and Consumer Product Safety Commission regulations, as defined by 16 CFR 1500.14(b)(3) and 1500.83(a)(13): This product contains "Petroleum Distillates" which may require special labeling if distributed in a manner intended or packaged in a form suitable for use in the household or by children. Precautionary label dialogue should display the following: **DANGER: Contains Petroleum Distillates! Harmful or fatal if swallowed! Call Physician Immediately. KEEP OUT OF REACH OF CHILDREN!**

SECTION 16. OTHER INFORMATION

Refer to the top of Page 1 for the HMIS and NFPA Hazard Ratings for this product.

REVISION INFORMATION

Version Number 2.1
Revision Date 8/25/2009

ABBREVIATIONS

AP: Approximately	EQ: Equal	>: Greater Than	<: Less Than
NA: Not Applicable	ND: No Data	NE: Not Established	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

IARC: International Agency for Research on Cancer

NIOSH: National Institute of Occupational Safety and Health

NPCA: National Paint and Coating Manufacturers Association

EPA: US Environmental Protection Agency

HMIS: Hazardous Materials Information System

OSHA: Occupational Safety and Health Administration

NTP: National Toxicology Program

NFPA: National Fire Protection Association

DISCLAIMER OF LIABILITY

THE INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS MSDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS MSDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

***** END OF MSDS *****