

Safety Data Sheet



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: 194-85741 ACRASILANE

Recommended Use: Water repellent for cementitious substrates. Applied by brush, spray or flood coating.

Supplier: Dulux New Zealand, a division of DuluxGroup (New Zealand) Pty Ltd
ABN 55 133 404 118
Co. 2355191

Street Address: 150 Hutt Park Road
Lower Hutt,
New Zealand

Telephone Number: +64 4 576 6400

Facsimile: +64 4 576 6496

Emergency Telephone: 0 800 734 607 (ALL HOURS)

2. HAZARDS IDENTIFICATION

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Based on available information, not classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Water	7732-18-5	>60%	-
Alkyltrialkoxo silane	-	1-<10%	-

4. FIRST AID MEASURES

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion:

Rinse mouth with water. If swallowed, give a glass of water to drink. If vomiting occurs give further water. Seek medical assistance.

Medical attention and special treatment:

Treat symptomatically.



5. FIRE FIGHTING MEASURES

Hazards from combustion products:

Not combustible, however following evaporation of the water component of the material, the residual material can burn if ignited. On burning will emit toxic fumes.

Precautions for fire fighters and special protective equipment:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures:

If contamination of sewers or waterways has occurred advise local emergency services.

Methods and materials for containment and clean up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid skin and eye contact and breathing in vapour, mists and aerosols.

Conditions for safe storage: Store in cool place and out of direct sunlight. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits: No value assigned for this specific material by the New Zealand Occupational Safety and Health Service (OSH). However, Workplace Exposure Standard(s) for hydrolysis product:

Ethyl alcohol: WES-TWA 1,000 ppm, 1,880 mg/m³

As published by the New Zealand Occupational Safety and Health Service (OSH).

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering controls:

Provide adequate ventilation. If using indoors, keep windows and doors open during use. Keep containers closed when not in use.

Product Name: 194-85741 ACRASILANE
Substance No: 000014568001

Issued: 10/04/2012
Version: 4

Safety Data Sheet



Personal Protective Equipment:

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Personal Protection: B - OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.



Wear overalls, safety glasses and impervious gloves. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. If risk of inhalation exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Colour:	Milky white
Odour:	Alcohol
Solubility:	Miscible with water.
Specific Gravity:	0.994 @20°C
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	Not available
Flash Point (°C):	Not applicable
Flammability Limits (%):	Not applicable
Autoignition Temperature (°C):	Not applicable
% Volatile by Volume:	Not available
Solubility in water (g/L):	Complete
Melting Point/Range (°C):	Not applicable
Boiling Point/Range (°C):	100 (water)
Decomposition Point (°C):	Not available
pH:	7-7.5
Viscosity:	Not available
Evaporation Rate:	Not available

10. STABILITY AND REACTIVITY

Chemical stability:	Stable under normal conditions of use.
Conditions to avoid:	Avoid exposure to extremes of temperature. Avoid exposure to heat, sources of ignition, and open flame.
Incompatible materials:	Incompatible with oxidising agents.
Hazardous decomposition products:	Formaldehyde. Oxides of carbon. Silicon dioxide.

Safety Data Sheet



Hazardous reactions: Hydrolyses slowly in water liberating ethanol.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: No adverse effects expected, however, large amounts may cause nausea and vomiting.

Eye contact: May be an eye irritant.

Skin contact: Contact with skin may result in irritation.

Inhalation: Breathing in mists or aerosols may produce respiratory irritation.

Long Term Effects:

No information available for the product.

Toxicological Data: No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for disposal at approved land waste site.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

Based on available information, not classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

16. OTHER INFORMATION



16. OTHER INFORMATION

Reason(s) for Issue:

5 Yearly Revised Primary SDS

This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.