

Material Name: Specialty Fiber Glass Insulation

Material Safety Data Sheet ID: 1293

Section 1 - Chemical Product and Company Identification

Product Name Fiber Glass Insulation CAS# Mixture/None Assigned Generic Name Fiber Glass Wool

Formula Not available Chemical Name: Mixture

Hazard Label FG-02-FA or FGW-01 or L1041

Manufacturer Information

Johns Manville

Performance Materials Division

P.O. Box 5108

Denver, CO 80127 USA

Telephone: 303-978-2000 8:00AM-5:00PM M-F

Internet Address: http://www.jm.com Emergency: 800-424-9300 (Chemtrec, In English)

Trade Names:

Whispertone Wallboard LE

Whispertone Wallboard (Plain) LE Whispertone Wallboard (FSK) LE

Section 2 - Composition / Information on Ingredients

CAS#	Component	Percent
65997-17-3	Fiber Glass Wool	50-99
NA	FSK	0-40*
NA	Continuous Filament Glass fiber (CAS # 65997-17-3)	0-40*
25104-55-6	Urea extended phenol-formaldehyde resin (cured)	10-25
9011-05-6	Urea Formaldehyde Binder, Cured	0-10*

Section 3 - Hazards Identification

Emergency Overview

APPEARANCE AND ODOR: Amber board. May have off-white facer. No significant odor.

Inhalation of excessive amounts of dust from the product may cause temporary upper respiratory irritation and/or congestion-remove individual to fresh air.

Potential Health Effects

Summary

Breathing dust from this product may cause a scratchy throat, congestion, and slight coughing. Getting dust or fibers on the skin, or in the eyes may cause itching, rash, or redness. Additional health and safety information is provided in Section 11 of this material safety data sheet.

Inhalation

Irritation of the upper respiratory tract (scratchy throat), coughing, and congestion may occur in extreme exposures.

Skin

Temporary irritation (itching) or redness may occur.

Ingestion

This product is not intended to be ingested (eaten). If ingested, it may cause temporary irritation to the gastrointestinal (digestive) tract.

Eyes

Temporary irritation (itching) or redness may occur.

Page 1 of 6 Issue Date: 05/06/2014 Revision: 1.00

Material Name: Specialty Fiber Glass Insulation **Material Safety Data** Sheet ID: 1293

Ears

Temporary irritation (itching) or redness may occur.

Primary Routes of Entry (Exposure)

Inhalation (breathing dust, fibers, or vapors), skin, and eye contact.

Target Organs

Nose (nasal passages), throat, lungs, skin, eyes.

Medical Conditions Aggravated by Exposure

Pre-existing chronic respiratory, skin, or eye diseases or conditions.

Section 4 - First Aid Measures

First Aid: Inhalation

Remove to fresh air. Drink water to clear throat, and blow nose to remove dust.

First Aid: Skin

Wash gently with soap and water to remove dust. Wash hands before eating or using the restroom.

First Aid: Ingestion

Product is not intended to be ingested or eaten. If this product is ingested, irritation of the gastrointestinal (GI) tract may occur, and should be treated symptomatically. Rinse mouth with water to remove fibers, and drink plenty of water to help reduce the irritation. No chronic effects are expected following ingestion.

First Aid: Eves

Do not rub or scratch your eyes. Dust particles may cause the eye to be scratched. Flush eyes with large amounts of water for 5-15 minutes. If irritation persists, contact a medical professional.

First Aid: Ears

Wash exposed skin with soap and water. If irritation develops in the inner ear, seek medical attention.

First Aid: Notes to Physician

This product is a mechanical irritant, and is not expected to produce any chronic health effects from acute exposures. Treatment should be directed toward removing the source of irritation with symptomatic treatment as necessary.

Section 5 - Fire Fighting Measures

Flash Point: Not applicable Method Used: Not applicable

Lower Flammable Limit (LFL): Not applicable Upper Flammable Limit (UFL): Not applicable Flammability Classification: Not determined

Auto Ignition: Not determined Rate of Burning: Not determined

General Fire Hazards

There is no potential for spontaneous fire or explosion.

Extinguishing Media

Carbon dioxide (CO₂), water, water fog, dry chemical.

Fire Fighting Equipment/Instructions

No special procedures are expected to be necessary for this product. Normal fire fighting procedures should be followed to avoid inhalation of smoke and gases.

Section 6 - Accidental Release Measures

Containment Procedures

Pick up large pieces. Vacuum dusts. If sweeping is necessary, use a dust suppressant such as water. Do not dry sweep dust accumulation or use compressed air for clean-up. These procedures will help to minimize potential exposures.

Clean-Up Procedures

Avoid the generation of dusts during clean-up.

Section 7 - Handling and Storage

Handling Procedures

Use protective equipment as described in Section 8 of this material safety data sheet when handling uncontained material.

Storage Procedures

Warehouse storage should be in accordance with package directions, if any. Material should be kept dry, and protected from moisture.

Material Name: Specialty Fiber Glass Insulation

Material Safety Data

Sheet ID: 1293

Section 8 - Exposure Controls / Personal Protection

Exposure Guidelines

A: General Product Information

Glass wool fiber, OSHA voluntary Health and Safety Partnership Program (HSPP): 1 f/cc TWA for fibers longer than 5 μ m with a diameter less than 3 μ m.

B: Component Exposure Limits

Fiber Glass Wool (65997-17-3)

ACGIH: 1 fiber/cm3 TWA (respirable fibers: length > 5 µm, aspect ratio equal to or greater than 3:1, as

determined by the membrane filter method at 400-450X magnification (4-mm objective), using

phase-contrast illumination.)

Continuous Filament Glass fiber (CAS # 65997-17-3)

ACGIH: 1 fiber/cm3 TWA (respirable fibers: length > 5 μ m, aspect ratio equal to or greater than 3:1, as

determined by the membrane filter method at 400-450X magnification (4-mm objective), using

phase-contrast illumination.); 5 mg/m3 TWA (inhalable fraction)

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Safety glasses with sideshields are recommended to keep dust out of the eyes.

Personal Protective Equipment: Ears

Use ear protection (earplugs, hood, or earmuffs) to prevent airborne dust or fibers from entering the ear, if necessary.

Personal Protective Equipment: Skin

Leather or cotton gloves should be worn to prevent skin contact and irritation. Barrier creams may also be used to reduce skin contact and irritation caused by fiber glass.

Personal Protective Equipment: Respiratory

A NIOSH-approved respirator should be used if ventilation is unavailable, or is inadequate for keeping levels below the applicable exposure limits referenced in Section 8 of this SDS.

Ventilation

In fixed manufacturing settings, local exhaust ventilation should be provided at areas of cutting to remove airborne dust and fibers. General dilution ventilation should be provided as necessary to keep airborne dust and fibers below the applicable exposure limits and guidelines. The need for ventilation systems should be evaluated by a professional industrial hygienist, while the design of specific ventilation systems should be conducted by a professional engineer.

Personal Protective Equipment: General

Wear a cap, a loose-fitting, long-sleeved shirt and long pants to protect skin from irritation. Exposed skin areas should be washed with soap and warm water after handling or working with fiber glass. Clothing should be washed separately from other clothes, and the washer should be rinsed thoroughly (run empty for a complete wash cycle). This will reduce the chances of fiber glass being transferred to other clothing.

Section 9 - Physical & Chemical Properties

Appearance: Amber fiber glass core or off- Odor: No significant odor

white facing with amber fiber

glass core.

Physical State: Solid Not applicable pH: Vapor Density: Vapor Pressure: Not applicable Not applicable **Boiling Point:** Not applicable **Melting Point:** >871°C/1600°F Specific Gravity: Solubility (H₂O): Nil Variable Freezing Point: **Evaporation Rate:** Not applicable Not applicable

Percent Volatile: 0 VOC: Not applicable

Section 10 - Chemical Stability & Reactivity Information

Chemical Stability

This is a stable material. This product is not reactive.

Hazardous Decomposition

Although fiber glass itself is not combustible, the following decomposition products may be released during burning of the insulation binder: carbon monoxide, carbon dioxide, carbon particles, and small hydrocarbons.

Page 2 of 6 | January Detay 05/06/2014 | Payiniany 1 00

Material Name: Specialty Fiber Glass Insulation

Material Safety Data Sheet ID: 1293

Hazardous Polymerization

Will not occur.

Section 11 - Toxicological Information

Acute Toxicity

A: General Product Information

Dust from this product is a mechanical irritant, which means that it may cause temporary irritation or scratchiness of the throat, and/or itching of the eyes and skin.

B: Component Analysis - LD50/LC50

Urea extended phenol-formaldehyde resin (cured) (25104-55-6)

Oral LD50 Rat: 7 g/kg

Urea Formaldehyde Binder, Cured (9011-05-6)

Inhalation LC50 Rat: >167 mg/m3/4H; Oral LD50 Rat: 8394 mg/kg

Carcinogenicity

A: General Product Information

The Occupational Safety and Health Administration (OSHA), National Toxicology Program (NTP), International Agency for Research on Cancer (IARC), and American Conference of Governmental Industrial Hygienists (ACGIH) have not classified this product as a carcinogen.

B: Component Carcinogenicity

Fiber Glass Wool (65997-17-3)

ACGIH: A3 - Confirmed animal carcinogen with unknown relevance to humans

NTP: Reasonably Anticipated To Be A Carcinogen (respirable size)

IARC: Group 2B - Possibly Carcinogenic to Humans (IARC Monograph 43, 1988)

Continuous Filament Glass fiber (CAS # 65997-17-3)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

IARC: Group 3 - Not Classifiable (IARC Monograph 43, 1988; Monograph 81, 2002)

Chronic Toxicity

In October 2001, IARC classified fiber glass wool as Group 3, "not classifiable as to its carcinogenicity to humans." The 2001 decision was based on current human and animal research that shows no association between inhalation exposure to dust from fiber glass wool and the development of respiratory disease

In 2011, the National Toxicology Program (NTP, a component of the United States Department of Health and Human Services) issued its 12th Report on Carcinogens (Report). The Report makes clear that any glass fibers that have been successfully assessed in an animal study and shown no cancer hazard are NOT among those "certain" fibers and NOT listed in the Report.

The glass fibers comprising the products on this MSDS have either been successfully assessed by appropriate animal protocols and / or have modeled Kdis values such that they are considered non-durable and the current human and animal research that shows no association between inhalation exposure to dust from fiber glass wool and the development of respiratory disease is applicable to these fibers

Continuous Filament Glass Fiber: No chronic health effects are known to be associated with exposure to continuous filament fiber glass. Long-term epidemiologic studies do not show any increases in respiratory cancer or other disease among employees who manufacture this product. In 1987, the International Agency for Research on Cancer (IARC) classified continuous filament fiber glass as a Group 3 substance, "not classifiable as to its carcinogenicity to humans." In 2001, IARC re-affirmed this designation. Because of the large diameter of continuous filament fibers, these fibers are not considered respirable.

Section 12 - Ecological Information

Ecotoxicity

A: General Product Information

No data available for this product.

Page 4 of 6 Issue Date: 05/06/2014 Revision: 1.00 Material Name: Specialty Fiber Glass Insulation

Material Safety Data
Sheet ID: 1293

Section 13 - Disposal Considerations

US EPA Waste Number & Descriptions

A: General Product Information

This product, as supplied, is not regulated as a hazardous waste by the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. Comply with state and local regulations for disposal. If you are unsure of the regulations, contact your local Public Health Department, or the local office of the EPA.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Section 14 - Transportation Information

Shipping Name: This product is not classified as a hazardous material for transport.

Section 15 - Regulatory Information

US Federal Regulations

A: General Product Information

SARA 311/312: This product is not classified as hazardous under SARA 311/312. Immediate (acute) health hazard. Delayed (chronic) health hazard.

B: Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

State Regulations

A: General Product Information

Other state regulations may apply. Check individual state requirements.

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS#	MA	NJ	PA
Fiber Glass Wool (¹related to Mineral wool fiber)	65997-17-3	Yes1	No	Yes ²
(²related to Glass wool fiber)				

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains a chemical known to the state of California to cause cancer.

A: TSCA Status

This product and its components are listed on the TSCA 8(b) inventory.

None of the components listed in this product are listed on the TSCA Export Notification 12(b) list.

B: Component Analysis - Inventory

Component	CAS#	TSCA	DSL	EINECS
Fiber Glass Wool	65997-17-3	Yes	Yes	Yes
Urea extended phenol-formaldehyde resin (cured)	25104-55-6	Yes	Yes	No
Urea Formaldehyde Binder, Cured	9011-05-6	Yes	Yes	No

Component Analysis - WHMIS IDL

No components are listed in the WHMIS IDL.

Section 16 - Other Information

Other Information

Prepared for: Johns Manville Performance Materials P. O. Box 5108

5.40

Material Name: Specialty Fiber Glass Insulation

Material Safety Data Sheet ID: 1293

Denver, CO USA 80217-5108

Prepared by: Johns Manville Technical Center P.O. Box 625005 Littleton, CO USA 80162-5005

The information herein is presented in good faith and believed to be accurate as of the effective date given. However, no warranty, expressed or implied, is given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

 Date
 MSDS #
 Reason

 05/06/14
 1293-1.00
 New MSDS.

This is the end of MSDS # 1293
