

Prepared to OSHA, ACC, ANSI, WHMIS, NOHSC & 2001/58 EC Standards

MATERIAL SAFETY DATA SHEET

MSDS Revision: 1.0

Page 1 of 7

MSDS-E-DFW-V710

MSDS Revision Date: 09/01/2007

1. PRODUCT IDENTIFICATION **CHEMICAL RESPONSE CARD:** 21 1.1 Product Name: DeoxIT® FLUX WASH, DFW-V710, 10 oz. **RESPONSE** 1.2 Chemical Name: **TEAM PPE:** See ingredients listed in section 3 1.3 Synonyms: Flux Wash WHMIS: 1.4 Trade Names: NA 1.5 Product Use: Aerosol Electronics Flux Cleaner **HEALTH:** 1 1.6 Manufacturer's Name: CAIG Laboratories, Inc. **FLAMMABILITY:** 3 1.7 Manufacturer's 12200 Thatcher Court, Poway, CA 92064-6876 **REACTIVITY:** 0 1.8 Business Phone: PERSONAL PROTECTION: +1 (800) 224-4123 В 1.9 Emergency Phone: CHEMTREC +1 (703) 527-3887 / +1 (800) 424-9300 Other Product Names: 1 10 2. HAZARD IDENTIFICATION 21 Hazard Identification: This product is classified as a hazardous substance and as a dangerous good according to the classification criteria of NOHSC and ADG Code (Australia). Warning! Extremely flammable. Contents under pressure. Do not puncture or incinerate. Keep away from heat, sparks, and flame. Use only with adequate ventilation. Keep containers closed when not in use. Gross inhalation over exposure may cause central nervous system depression. 2.2 Routes of Entry: Inhalation: YES Absorption: YES Ingestion: YES 2.3 Effects of Exposure: Can cause irritation, tearing, and blurred vision. EYES: SKIN: Can cause minor irritation and burns. INGESTION: Can cause damage to throat and esophagus. Can cause nausea, vomiting and diarrhea. INHALATION: Can cause nasal irritation, dizziness, nausea and headache. 24 Symptoms of Overexposure: EYES: Mild irritation, redness, and watering. SKIN: Contact dermatitis, characterized by localized red or puffy dry skin and itching. INGESTION: May cause gastro intestinal irritation, nausea, vomiting, and diarrhea. INHALATION: Upper respiratory irritation, coughing, sneezing, staggering gait, giddiness, drowsiness, slurred speech, nausea, and possible nervous system depression. Gross overexposure by purposely inhaling fumes may cause central nervous system depression or death. 2.5 Acute Health Effects: EYES: Mild to moderate irritation to eyes. SKIN: Mild irritation and dermatitis (rash). INGESTION: May cause gastrointestinal irritation. INHALATION: May irritate mucous membranes and upper respiratory system irritation and discomfort. Prolonged overexposure may cause central nervous system depression or death. Chronic Health Effects: 2.6 None reported by the manufacturer. 2.7 Target Organs: Eyes, Skin, Lungs

NA = Not Available; ND = Not Determined; NE = Not Established; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used NOTE: all WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2004 format.



Page 2 of 7

MSDS-E-DFW-V710

Prepared to OSHA, ACC, ANSI, WHMIS, NOHSC & 2001/58 EC Standards | MSDS Revision: 1.0 MSDS Revision Date: 09/01/2007

		<u> </u>		N & INGR	LDILIN	1 1141 0			AITC IN	A ID / / 3	`
						ACGIL	l - ppm		NIIS IN /	AIR (mg/m³	OTHER
	CHEMICAL NAM	E(S) CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	PEL	STEL	IDLH	O III EK
· · · · · · · · · · · · · · · · · · ·		MI7700000	205-563-8	≤ 60.0	400	500	500	2000	750		
ACET	ONE	64-64-1	AL3150000	200-662-2	≤ 25.0	500	750	1000	2400	2500	
ETHYI	LALCOHOL	64-17-5	KQ6300000	200-578-6	≤ 25.0	1000	1900	1000	1900	3300	
METH	IYL ALCOHOL	67-56-1	PC1400000	200-659-6	≤ 5.0	200	250	200	260	6000	
CAR	BON DIOXIDE	124-38-9	FF6400000	204-696-9	≤ 4.0	5000	30000	5000	1500	9000	ASPHYXIANT IRRITANT
				4. FIRST	ΔID						
4.1	First Aid:			7. IIII	AID						
	EYES: As a precaution remove contact lenses if worn and the strength of the s					,	0 ,				
	SKIN:	Remove contamina attention. Do not we	0							s, seek pro	mpt medical
INGESTION: Do not induce vomiting! Call a physician or poison control center for assistance and in medial attention. If vomiting occurs spontaneously, keep victim's head lowered (for aspiration.											
	INHALATION:	Remove victim to fre		0					, 0	_	

None reported by the manufacturer. **FLAMMABILITY** 3

	REAC	IIVIIY		U
	PROTI	CTIVE E	QUIPMENT	В
	EYES	SKIN	LUNGS	
5. FIREFIGHTING MEASURES				

5.1	Flashpoint & Method:				
	30 °F, Estimated				
5.2	Autoignition Temperature:				
	ND				
5.3	Flammability Limits:	Lower Explosive Limit (LEL):	NA	Upper Explosive Limit (UEL):	NA

5.4 Fire & Explosion Hazards: Warning! Contents under pressure! Highly flammable liquid. NFPA Level 3 Aerosol. Closed containers may explode when exposed to extreme heat.

5.5 Extinguishing Methods:

> Large fire - Alcohol foam or water fog. Small fire - Dry chemical or carbon dioxide. Use water to cool fire exposed containers. Do not use water in straight streams. Water spray may be ineffective. If water is used, fog nozzles are preferable.

Firefighting Procedures:

Wear NIOSH/MSHA approved self-contained breathing apparatus and protective clothing. Use a water spray to cool containers involved in fire. Do not use direct water stream. Container storage areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Keep containers cool until well after the fire is out to prevent rupture. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Avoid breathing vapor or fumes.





Page 3 of 7

MSDS-E-DFW-V710

Prepared to OSHA, ACC, ANSI, WHMIS, NOHSC & 2001/58 EC Standards

MSDS Revision: 1.0

MSDS Revision Date: 09/01/2007

6. ACCIDENTAL RELEASE MEASURES

6.1 Spills

Ventilate if in enclosed area. Eliminate all ignition sources.

<u>Small Spills:</u> Wipe, scrape or soak up in an inert material like vermiculite, floor absorbent, or other absorbent material and transfer to isolated well ventilated area. Leaking containers should be removed to an isolated well ventilated area and transferred to other suitable container. Do not puncture or incinerate container, contents under pressure.

<u>Large Spills:</u> Contain by diking with a non-combustible absorbent inorganic material. Prevent runoff from entering sewers, storm drains, surface water and soil. Transfer to a DOT approved container.

Must be in accordance with federal, state and local laws and regulations.

7. HANDLING & STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Wash hands thoroughly after using this product and before eating, drinking, or smoking. Remove soiled clothing to prevent prolonged skin contact

7.2 Storage & Handling:

Use and store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Contents under pressure. Do not store at temperatures above 120 °F. Exposure to high temperatures may cause bursting. Do not store in unmarked containers or storage devices. Container is not designed to contain pressure.

7.3 Special Precautions:

Empty containers may contain product residues. Do not use pressure to empty container, or it may rupture with explosive force. Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1 Ventilation & Engineering Controls:

Use with adequate ventilation (e.g., open doors and windows, local exhaust ventilation). Local exhaust may be necessary to maintain exposures to within applicable limits. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station). Do not puncture containers.

8.2 Respiratory Protection:

None required, when used with adequate ventilation. Local exhaust ventilation or other engineering controls may be required to control airborne levels below the recommended exposure limits. A respiratory protection program that meets ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirators use. Avoid breathing mist and vapors.

8.3 Eye Protection:

Safety glasses with side shields or goggles should be used with this product. If splashing is anticipated, splash goggles and a face-shield are recommended. Do not wear contact lenses.

8.4 Hand Protection:

Where contact is likely, impervious gloves are recommended. Do not wear rings, watches, or jewelry that could entrap the material against the skin.

8.5 Body Protection

None required under normal use. Avoid prolonged contact with skin and wear long sleeves. A safety shower may be needed for emergency situations.

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Density:	NA NA
9.2	Boiling Point:	NA
9.3	Melting Point:	ND
9.4	Evaporation Rate:	NA
9.5	Vapor Pressure:	NA
9.6	Molecular Weight:	NA
9.7	Appearance & Color:	Colorless liquid in aerosol
9.8	Odor Threshold:	Mild alcohol
9.9	Solubility:	NA
9.10	Ph	ND
9.11	Viscosity:	NA
9.12	Other Information: VOC Content	563 g/L



Page 4 of 7

MSDS-E-DFW-V710

repo	ared to OSHA, ACC, ANSI	, WHMIS, NOHSC & 2001/58 EC Standards	MSDS Revision: 1.0	MSDS Revision Date: 09/01/2007
		10. STABILITY &	REACTIVITY	
0.1	Stability:			
	Stable			
0.2	Hazardous Decomposition Pro			
	Carbon dioxide, carbo	n monoxide.		
0.3	Hazardous Polymerization:			
	Will not occur.			
0.4	Conditions to Avoid:			
	heavily trafficked area	oen flames, sparks, high heat (>120 °F) or o s.	ther heat sources, and pr	oximity to incompatible substances an
0.5	Incompatible Substances:			
	Oxidizing agents; conc	entrated Oxygen. Materials to avoid – zinc	, copper, tin and alkali me	etals (sodium, potassium, lithium, etc.).
		11. TOXICOLOGICA	I INFORMATION	
	Tandada Datan	TI. TOXICOLOGICA	LINIORMATION	
1.1	Toxicity Data:	and tested on animals to obtain tovicaled	ical data. There are tovi	cology data for the components of th
		een tested on animals to obtain toxicolog and in the scientific literature. This data has		
			noi been piesemed in inis	document.
1.0		-17-5) IARC: Group 3 carcinogen		
.2	Acute Toxicity:			
1.2	See section 2.5 Chronic Toxicity:			
.3	·			
	See section 2.6			
.4	Suspected Carcinogen:			
_		spected carcinogen in humans.		
1.5	Reproductive Toxicity:			
		orted to produce reproductive toxicity in hur		
	Mutagenicity:	This product is not reported to prod		
	Embryotoxicity:	This product is not reported to prod		
	Teratogenicity:	This product is not reported to prod This product is not reported to prod		
1.6	Reproductive Toxicity: Irritancy of Product:	This product is not reported to prod	oce reproductive effects	in nomans.
0.1	See Section 2.3			
1.7				
1./	Biological Exposure Indices: NE			
1.0	Physician Recommendations:			
1.8	Treat symptomatically.			
	Treat symptomatically.			
		12. ECOLOGICAL I	NFORMATION	
2.1	Environmental Stability:			
	This product will slowly	volatilize from soil. Components of this pro-	duct will slowly decompos	se into organic compounds.
2.2	Effects on Plants & Animals:			
	There is no specific do	ta available for this product.		
2.3	Effects on Aquatic Life:			
		e kept out of sewage and drainage systems armful or fatal to overexposed aquatic life.	s and all bodies of water.	Releases of large volumes of this produ
		13. DISPOSAL CON	NSIDERATIONS	
3.1	Waste Disposal:	13. DISI OSAL COL	131DEKAHON3	
		nce with federal, state or local regulations.	D001 Ignitable.	
			-	·
3.2	Special Considerations:			



Page 5 of 7

MSDS-E-DFW-V710

Prepared to OSHA, ACC, ANSI, WHMIS, NOHSC & 2001/58 EC Standards MSDS Revision: 1.0 MSDS Revision Date: 09/01/2007

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):
	CONSUMER COMMODITY, ORM-D
14.2	IATA (AIR):
	ID8000, CONSUMER COMMODITY, 9 (Packing Instructions 910)
14.3	IMDG (OCN):
	UN1950, AEROSOLS, 2.1, LTD QTY
14.4	TDGR (Canadian GND):
	MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE"
14.5	ADR/RID (EU):
	UN1950, AEROSOLS, 2, LTD QTY
14.6	MEXICO (SCT):
	UN1950, AEROSOLES, 2, CANTIDAD LIMITADA



15. REGULATORY INFORMATION

15.1 SARA Reporting Requirements:

This product contains substances that are subject to SARA reporting requirements:

N-Heptane (CAS# 142-82-5); Immediate, delayed, fire.

Acetone (CAS# 64-17-5); Immediate, fire.

Ethanol (CAS# 64-17-5); Acute, chronic, flammable.

Methyl alcohol (CAS# 67-56-1); Acute, flammable.

15.2 SARA Threshold Planning Quantity:

None of the chemicals in this product have a TPQ.

15.3 TSCA Inventory Status:

All chemical substances of this product are listed on the TSCA inventory or are otherwise exempt from inventory status.

15.4 CERCLA Reportable Quantity (RQ):

Acetone: 5000 lb final RQ; 2270 kg final RQ

Methyl Alcohol: 5000 pounds final RQ; 2270 kg final RQ

Ethyl Alcohol: 5000 pounds final RQ; 2270 kg final RQ

15.5 Other Federal Requirements:

Clean Air Act:

This material contains Methyl alcohol listed as a hazardous air pollutant (HAP). None of the chemicals in this product are listed as Hazardous Substances under the CAA. This material does not contain any Class 1 Ozone depletors. This material does not contain any Class 2 Ozone depletors.

Clean Water Act:

None of the chemicals in this product are listed as Hazardous Substances under the CWA. None of the chemicals in this product are listed as Priority Pollutants under the CWA. None of the chemicals in this product are listed as Toxic Pollutants under the CWA.

None of the chemicals in this product are considered highly hazardous by OSHA.

15.6 Other Canadian Regulations

This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List.





Page 6 of 7

MSDS-E-DFW-V710

Prepared to OSHA, ACC, ANSI, WHMIS, NOHSC & 2001/58 EC Standards

MSDS Revision: 1.0

MSDS Revision Date: 09/01/2007

15. REGULATORY INFORMATION- continued

15.7 State Regulatory Information:

> N-Heptane (CAS# 142-82-5), can be found on the following state right to know lists: California, New Jersey, Pennsylvania, Minnesota, and Massachusetts.

Acetone (CAS# 67-64-1), can be found on the following state right to know lists: California, New Jersey, Pennsylvania, Minnesota, and Massachusetts.

Ethanol (CAS# 67-56-1), can be found on the following state right to know lists: California, New Jersey, Florida, Pennsylvania, Minnesota, and Massachusetts.

Methyl Alcohol (CAS# 67-56-1), can be found on the following state right to know lists: California, New Jersey, Florida, Pennsylvania, Minnesota, and Massachusetts.

California Prop 65

This product contains Ethyl Alcohol, a chemical known to the state of California to cause birth defects or other reproductive harm.

WGK (Water Danger/Protection)

Ethanol (CAS# 64-17-5): 0

Methyl Alcohol (CAS# 67-56-1): 1

15.8 67/548/EEC (European Union) Requirements:

The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC.

(F) Flammable (Xi) Irritant

R: 11 Highly flammable.

S: 2 Keep out of reach of children

S: 3/7 Keep container closed and dry in a well ventilated space

S: 16 Keep away from sources of ignition - No smoking.

\$ 36/37 Wear suitable protective clothing and gloves.

S: 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S: 7 Keep containers tightly closed.





16. OTHER INFORMATION

16.1	Other Information:
	NA NA
16.2	Terms & Definitions:
	See last page of this MSDS.
16.3	Disclaimer:
	This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAIG Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.
16.4	Prepared for: CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 +1 (800) CAIG-123 (244-4123) phone +1 (858) 486-8398 fax

16.5 Prepared by:

> ShipMate, Inc. 18436 Hawthorne Blvd., Suite 201 Torrance, CA 90504 +1 (310) 370-3600 phone

+1 (310) 370-5700 fax

http://www.caig.com/

http://www.shipmate.com/







Page 7 of 7

MSDS-E-DFW-V710

Prepared to OSHA, ACC, ANSI, WHMIS, NOHSC & 2001/58 EC Standards MSDS Revision: 1.0

MSDS Revision Date: 09/01/2007

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH American Conference on Governmental Industrial Hygieni	
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person					
	whose heart has stopped receives manual chest					
	compressions and breathing to circulate blood and provide					
	oxygen to the body.					

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:


0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

A	S			
В	S			
С	S	The second	*	
		-00	- 11	
D			~	
D E	⊕			





OTHER STANDARD ABBREVIATIONS:

NA	Not Available					
NR	No Results					
NE	Not Established					
ND	Not Determined					
ML	Maximum Limit					
SCBA	Self-Contained Breathing Apparatus					


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				

HAZARD RATINGS:

0	Minimal Hazard		
1	Slight Hazard		
2	Moderate Hazard		
3	Severe Hazard		
4	Extreme Hazard		
ACD	Acidic		
ALK	Alkaline		
COR	Corrosive		
w —	Use No Water		
OX	Oxidizer		



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s					
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal					
ppm	Concentration expressed in parts of material per million parts					
TD _{Io}	Lowest dose to cause a symptom					
TCLo	Lowest concentration to cause a symptom					
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or					
TC, TCo, LCio, & LCo	toxic effects					
IARC	International Agency for Research on Cancer					
NTP	National Toxicology Program					
RTECS	Registry of Toxic Effects of Chemical Substances					
BCF	Bioconcentration Factor					
TLm	m Median threshold limit					
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution					

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System			
DOT	U.S. Department of Transportation			
TC	Transport Canada			
EPA	U.S. Environmental Protection Agency			
DSL	Canadian Domestic Substance List			
NDSL	Canadian Non-Domestic Substance List			
PSL	Canadian Priority Substances List			
TSCA	U.S. Toxic Substance Control Act			
EU	European Union (European Union Directive 67/548/EEC)			

EC INFORMATION:

Tall I						×	X
С	E	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful