

Page 1 of 6

Prep	Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 12/10/2007							
1.	1. PRODUCT IDENTIFICATION					. RESPONSE CAR	D: 04	
1.1	Product Name:	DeoxIT® SHIELD, S5L-A, 5% Liquid			RESPONSE			
1.2	Chemical Name:	See ingredients listed in section 3	•		TEAM PPE:			
1.3	Synonyms:	DeoxIT® SHIELD, S5L-A, 5% Liquid						
1.4	Trade Names:	DeoxIT® SHIELD, S5L-A, 5% Liquid			WHMIS:			
1.5	Product Use:	Protect and lubricate electrical co	ontacts & conn	ectors	HEALTH:		1	
1.6	Manufacturer's Name:	CAIG Laboratories, Inc.			FLAMMABIL	ITY:	2	
1.7	Manufacturer's Address:	12200 Thatcher Court, Poway, CA	92064-6876		REACTIVITY:		0	
1.8	Business Phone:	+1 (800)-224-4123			PERSONAL F	PROTECTION:	B	
1.9	Emergency Phone:	CHEMTREC: +1 (703) 527-388	87 / +1 (800)) 424-3887			1 -	
1.10	Other Product Names:							
		2. HAZA	RD IDENTII	ICATION				
2.1		. Colorless, volatile liquid with ether DANGEROUS GOODS according to the						
2.2	Routes of Entry:							
2.3	Effects of Exposure: EYES: Mild irritation. SKIN: Prolonged or repeated contact may cause contact dermatitis (localized redness or rash). INGESTION: Gastrointestinal irritation, intestinal discomfort, nausea. INHALATION: Irritating to the upper respiratory tract.							
2.4	Symptoms of Overexposure:							
		Contact dermatitis, characterized by localized red or puffy dry skin and itching. Nausea, intestinal discomfort.						
3.5	Acute Health Effects:							
		Mild irritation. Redness, irritation at site of exposure.						
		Gastrointestinal irritation, intestinal disc	comfort. nause	a.				
		Irritating to the upper respiratory tract.						
2.6	Chronic Health Effects: None reported by	the manufacturer.						
2.7	Target Organs: Eyes and skin.							



Page 2 of 6

Prop	Propagad to OSHA ACC ANSI NOUSC WIHAIS & 2001/58 EC Standards AMSDS Bovision: 2.0 AMSDS Bovision Date: 12/10/2007										
пер	Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 12/10/2007										
	3. COMPOSITION & INGREDIENT INFORMATION										
	EXPOSURE LIMITS IN AIR (mg/m ³)										
						AC	GIH	JOKE LINK	OSHA	iiig/iii j	OTHER
						TLV	STEL	PEL	STEL	IDLH	OTTER
	CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	ppm	ppm	ppm	ppm	ppm	
PETRC	DLEUM NAPHTHA	64742-88-7	XS5250000	265-191-7	≤ 75	100	NE	100	NE	NE	
1,1,1,3,3-PENTAFLUOROPROPANE		E 460-73-1	UNK	419-170-6	≤ 20	300	NE	300	NE	NE	
Deox	IT® SHIELD S100L	TRADE SECRET	NA	NA	≤ 5	NE	NE	NE	NE	NE	
NA =	Not Available; ND = Not [Determined; NE	= Not Establis	hed; C = Ceilir	ng Limit;	See Sectio	on 16 for A	dditional	Definition	s of Term	s Used
	E: all WHMIS required infor				-						
			4. FI	RST AID N	IEASU	RES					
4.1	First Aid:										
		eyes thoroughl						tes, hold	ing eyelid	l(s) open	to ensure
		ete flushing. If	-								. 1
		e contaminate al attention. De	-				-		-	ersists, se	ek prompt
		enty of water.			-			propen,	ciculicu.		
	•	ve victim to fre	-		• •		ster suppl	emental	oxygen a	nd seek	immediate
	medic	al attention. If	breathing stop	os, perform arti	ficial res	spiration.					
4.2											
	None reported by the mo	inufacturer.									
FLAMMABILITY					2						
					REA	CTIVIT	Y		0		
							PRO	TECTI	/E EQU	IPMEN	T
							EYES	SKI			
			5. FIRE	FIGHTING	MEA	SURES					
5.1	Flashpoint & Method:										
	48.8 °C - 54.4 °C (120 °F -	130 °F).									
5.2	Autoignition Temperature:										
5.2	NA Florence claith a Lineitea							- · ·			
5.3	Flammability Limits: Fire & Explosion Hazards:		Lower Explo	osive Limit (LEL)	:	NA	Upper	Explosive	e Limit (UEI	_):	NA
5.4	Carbon dioxide, carbon	monoxide. hvd	rocarbons.								
5.5	Extinguishing Methods:										1
	CO ₂ , Alcohol foam, Dry C	hemical, Wate	r Fog							<u> </u>	
5.6	Firefighting Procedures:										0
	Wear NIOSH/MSHA appr spray to cool container										<u> </u>
	exposed to direct flame									X	Y
	weakening of container	structure. Keep	o containers c	ool until well o	after the	fire is out	to preven	t rupture.		V	
	Prevent runoff from fire	control or dilut	on from ente	ring sewers, d	rains, dı	rinking wa	iter supply	y, or any		-	
	natural waterway.								1		



Page 3 of 6

ep	ared to OSHA, AC	C, ANSI, NOHSC, WHMIS & 2001/58 EC	: Standards	MSDS Revision: 2.0	MSDS Revision [Date: 12/10/2007		
		6. ACCIDE	NTAL REL	EASE MEASURES				
.1	protective equipr commercial abso ahead of the spi	and deny entry to all unprotected inc nent. Area may become slippery. A rbent material. Place into leak-prod I to prevent runoff into sewers, drain reporting requirements.	bsorb produc of, U.S. DOT-c	ct onto porous material, s approved containers. If	uch as sand, clay, di necessary, cover all	atomaceous earth or drains and dike well		
		7 HANDUNG	& STORA		N			
.1	Work & Hygiene Practices: Wash hands thoroughly after using this product and before eating, drinking, or smoking. Remove soiled clothing to prevent prolonged skin contact.							
7.2	Storage & Handling: Store at temperatures between 59 °F and 95 °F (15 °C and 35 °C) in a dry, well-ventilated location. Keep away from heat, sparks, open flame, and other sources of ignition. Normal shelf-life: 2-3 years.							
7.3	Special Precautions: Empty containers	can contain flammable vapors. Do i	not cut, drill,	grind, weld or perform sin	nilar operations on or	near containers.		
		8. EXPOSURE CON	TROIS &	PERSONAL PROTE				
3.1	Ventilation & Engineering Controls:							
	Use with adequate ventilation (e.g., open doors and windows, local exhaust ventilation). Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).							
3.2	Respiratory Protection: None required, when used with adequate ventilation.							
3.3	Eye Protection: Wear safety glass	es with side shields (ANSI Z87) under	normal use c	onditions.				
3.4	Hand Protection: None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. In such cases, wear rubber or impervious plastic gloves.							
3.5	Body Protection:	to provent alia contrat						
	use as necessary	to prevent skin contact.						
			& CHEM	NICAL PROPERTIES				
.1	Density:	0.75	a onen					
.2	Boiling Point:	171.1 °C – 204 °C @ 76	0 mmHa					
.3	Melting Point:	NA	<u>-</u>					
.4	Evaporation Rate:	NA						
.5	Vapor Pressure:	35 psig @ 20 °C, 50 psi	g @ 50 °C					
.6	Molecular Weight:	NA	-					
.7	Appearance & Color:	Light blue liquid						
.8	Odor Threshold:	Ethereal/hydrocarbor	odor					
9.9	Solubility:	Not soluble in water						
9.10	рН	ND						
7.11	Viscosity:	10.0 cps						



Page 4 of 6 MSDS-E-S5L-A

		10. STABILITY & REACTIVITY					
0.1	Stability:	Stable under normal conditions of use (see section 7).					
0.2	Hazardous Decomposition Products:	Change in color signifies exposure to ultraviolet light or exceeding shelf life. Will not degrade t unstable products. Discard solution.					
0.3	Hazardous Polymerization:	Will not occur.					
0.4	Conditions to Avoid:	Use or storage near open flames, sparks, high heat (>100 °F) or other heat sources, and proximity t incompatible substances and heavily trafficked areas.					
0.5	Incompatible Substances:	Strong oxidizers.					
		11. TOXICOLOGICAL INFORMATION					
1.1	Toxicity Data:						
	Tokely bald.	This product has not been tested on animals to obtain toxicological data. There are toxicology dat for the components of this product, which are found in the scientific literature. These data have no been presented in this document.					
1.2	Acute Toxicity:	See section 3.5					
1.3	Chronic Toxicity:	See section 3.6					
1.4	Suspected Carcinogen:	NE					
1.5	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.					
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.					
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.					
	Teratogenicity:	This product is not reported to produce teratogenic effects in humans.					
	Reproductive Toxicity:	This product is not reported to produce reproductive effects in humans.					
1.6	Irritancy of Product:	See Section 3.3					
1.7	Biological Exposure Indices:	NE					
1.8	Physician Recommendations:	Treat symptomatically.					
		12. ECOLOGICAL INFORMATION					
2.1	Environmental Stability:	This product will slowly volatile from soil. Components of this product will slowly decompose int					
2		organic compounds.					
2.2	Effects on Plants & Animals:	There is no specific data available for this product.					
2.3	Effects on Aquatic Life:	Releases of large volumes of this product are expected to be harmful or fatal to overexpose aquatic life.					
		13. DISPOSAL CONSIDERATIONS					
3.1	Waste Disposal: Dispose of in accordance with	h federal, state or local regulations.					
3.2	Special Considerations: EPA Waste Code: D001 (charc	ucteristic – ignitability)					
		14. TRANSPORTATION INFORMATION					
		ing name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may b					
equire	ed by 49 CFR, IATA/ICAO, IMDG and the (49 CFR (GND): NOT PEGULATED PER 49 CFP 17						
4.1	NOT REGULATED PER 49 CFR 173.150(f) IATA (AIR):						
4.1	ivery () utc).	CONSUMER COMMODITY, 9, ID8000 (≤ 500 ml) UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III (> 500 ml)					
	CONSUMER COMMODITY, 9, II						
	CONSUMER COMMODITY, 9, II UN1268, PETROLEUM DISTILLATI IMDG (OCN): UN1268, PETROLEUM DISTILLATI	ES, N.O.S., 3, III (> 500 ml) ES, N.O.S., 3, III, LTD QTY (≤ 5.0 L)					
4.2	CONSUMER COMMODITY, 9, II UN1268, PETROLEUM DISTILLATI IMDG (OCN): UN1268, PETROLEUM DISTILLATI UN1268, PETROLEUM DISTILLATI TDGR (Canadian GND):	ES, N.O.S., 3, III (> 500 ml) ES, N.O.S., 3, III, LTD QTY (≤ 5.0 L)					
4.2	CONSUMER COMMODITY, 9, II UN1268, PETROLEUM DISTILLATI IMDG (OCN): UN1268, PETROLEUM DISTILLATI UN1268, PETROLEUM DISTILLATI TDGR (Canadian GND):	ES, N.O.S., 3, III (> 500 ml) ES, N.O.S., 3, III, LTD QTY (≤ 5.0 L) ES, N.O.S., 3, III (> 5.0 L) ANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 5.0 L)					



Page 5 of 6

Prep	ared to OSHA, ACC, ANSI, NOHSC, WHMIS	& 2001/58 EC Standards	MSDS Revision: 2.0	MSDS Revision Date: 12/10/2007
		15. REGULATORY I	NFORMATION	
15.1	SARA Reporting Requirements:			
	NA			
15.2	SARA Threshold Planning Quantity:			
15.3	TSCA Inventory Status:			
	All chemical substances of this product of	are listed on the TSCA inver	ntory or are otherwise exem	pt from inventory status.
15.4	CERCLA Reportable Quantity (RQ):			
15.5	Other Federal Requirements:			
15.6	Other Canadian Regulations This product has been classified accordi (CPR) and the MSDS contains all of the in are listed on the DSL/NDSL. None of Substances List.	formation required by the	CPR. The components of thi	is product (
15.7	State Regulatory Information: The primary component of this produ Massachusetts Right to Know List of Che List 34 323 Appendix A; Wisconsin Haz Substances List.	micals; New Jersey Right t	o Know List 8:59 Appendix	A; Pennsylvania Hazardous Substances
15.8	67/548/EEC (European Union) Requirements: The primary component of this product is <u>Petroleum Naphtha</u> : Flammable, Harmi damage if swallowed. S: 2-23-24-62 – K spray. Avoid contact with skin. If swallow and show this MSDS or the container labor	iul (F, Xn). R: 10-65 – Fla eep away from children. I ved, do not induce vomitin	mmable. Harmful: may co Do not breathe gas, fumes,	, vapor or
		16. OTHER INFO	ORMATION	
16.1	Other Information:			
	ΝΑ			
16.2	Terms & Definitions:			
	See page 7 of this MSDS.			
16.3	Disclaimer: This Material Safety Data Sheet is offer government regulations must be review knowledge, the information contained h are not guaranteed and no warranties relates only to the specific product(s). considered. Data may be changed from	red for applicability to this erein is reliable and accur of any type, either expre If this product(s) is con	s product. To the best of s ate as of this date; howeve ssed or implied, are provid nbined with other materia	ShipMate's & CAIG Laboratories, Inc.'s r, accuracy, suitability or completeness ed. The information contained herein
16.4	Prepared for: CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 +1 (800) CAIG-123 (244-4123) phone +1 (858) 486-8398 fax http://www.caig.com/	CAIG LABORATORIES, INC.		
16.5	Prepared by: ShipMate, Inc. 18436 Hawthorne Blvd., Suite 201 Torrance, CA 90504 310-370-3600 phone 310-370-5700 fax http://www.shipmate.com/	ShipMate Dangerous Goods Training & Consulting		



Page 6 of 6

MSDS-E-S5L-A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 12/10/2007

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

EXPOSURE	LIMITS	IN AIR:	
EXT OCONE			

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person
	whose heart has stopped receives manual chest
	compressions and breathing to circulate blood and provide
	oxygen to the body.

HEALTH

FLAMMABILITY

56

Ť


REACTIVITY PERSONAL PROTECTION

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard			
1	1 Slight Hazard			
2	Moderate Hazard			
3	3 Severe Hazard			
4	Extreme Hazard			

PERSONAL PROTECTION RATINGS:



equipment is required for high concentrations or for large volume spills or releases of product.


OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

Minimal Hazard
Slight Hazard
Moderate Hazard
Severe Hazard
Extreme Hazard
Acidic
Alkaline
Corrosive
Use No Water
Oxidizer



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the					
	exposed animals s					
1.0						
LC ₅₀	Lethal concentration (gases) which kills 50% of the					
	exposed animal					
ppm	Concentration expressed in parts of material per					
P P P P P P P P P P P P P P P P P P P	million parts					
TD _{io}	Lowest dose to cause a symptom					
TCLo	Lowest concentration to cause a symptom					
TDIo, LDIo, & LDo Or	Lowest dose (or concentration) to cause lethal or					
TC, TC _o , LC _{lo} , & LC _o	toxic effects					
IARC	International Agency for Research on Cancer					
NTP	National Toxicology Program					
RTECS	Registry of Toxic Effects of Chemical Substances					
BCF	Bioconcentration Factor					
TLm	Median threshold limit					
log Kow or log Koc	Coefficient of Oil/Water Distribution					

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	U.S. Department of Transportation				
TC	Transport Canada				
EPA	U.S. Environmental Protection Agency				
DSL	Canadian Domestic Substance List				
NDSL	Canadian Non-Domestic Substance List				
PSL	Canadian Priority Substances List				
TSCA	U.S. Toxic Substance Control Act				
EU	European Union (European Union Directive 67/548/EEC)				

EC INFORMATION:

V		×	¥		*	×	×
С	E	F	Ν	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful