

MATERIAL SAFETY DATA SHEET



Date Issued: 12/03/2004
MSDS No: 10022V
Date-Revised: 01/05/2010
Revision No: 5

Strawberry Wet Wax®

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Strawberry Wet Wax®
PRODUCT DESCRIPTION: Automotive reconditioning product
PRODUCT CODE: 22
PRODUCT FORMULATION NAME: Strawberry Wet Wax®
GENERIC NAME: Polish

MANUFACTURER

Auto Wax - An ITW Company
Auto Magic®
1275 Round Table Drive
Dallas, TX 75247
Product Stewardship: 1-800-826-0828
Transportation: 1-800-826-0828
Service Number: 1-214-631-4000
Auto Wax - An ITW Company
Auto Magic®

24 HR. EMERGENCY TELEPHONE NUMBERS

1-800-826-0828

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Harmful if swallowed.

POTENTIAL HEALTH EFFECTS

EYES: Moderately irritating to the eyes.

SKIN: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INGESTION: Harmful if swallowed.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Eye contact may cause redness, tearing and a burning sensation.

SKIN: Repeated or prolonged skin contact may cause redness and irritation.

INGESTION: Ingestion may cause nausea and irritation.

ACUTE TOXICITY: May cause headaches and dizziness.

MEDICAL CONDITIONS AGGRAVATED: dermatitis may be aggravated by excessive exposure to skin.

ROUTES OF ENTRY: include skin contact, eye contact and ingestion

TARGET ORGAN STATEMENT: not established

CANCER STATEMENT: not established

HEALTH HAZARDS: Moderately irritating to the eyes.

PHYSICAL HAZARDS: combustible liquid

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS	EINECS	Classification
Distillates (petroleum) hydrotreated light	5 - 10	64742-47-8	265-149-8	Xn; R65
Odorless Mineral Spirits	5 - 10	64742-48-9	265-150-3	Xn; R10-65-66-67
Naphtha	1 - 5	8032-32-4	232-453-7	F, Xn; R11-65-66-67

(Full text of R-Phrases can be found under heading 16)

4. FIRST AID MEASURES

EYES: Flush eye with water for 15 minutes. Seek medical attention if irritation persists.

SKIN: Wash with soap and water.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

INHALATION: Move to fresh air

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: ~ 41°C (106°F) TCC

AUTOIGNITION TEMPERATURE: not established

GENERAL HAZARD: Combustible liquid. Keep away from heat and open flame.

EXTINGUISHING MEDIA: use foam, dry chemical or carbon dioxide extinguisher

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide and Carbon Dioxide

EXPLOSION HAZARDS: not established

FIRE FIGHTING PROCEDURES: not established

SENSITIVE TO STATIC DISCHARGE: not established

SENSITIVITY TO IMPACT: not established

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Contain and collect with absorbent

LARGE SPILL: LARGE SPILLS: Shut off leak if safe to do so. Contain material to avoid run off and collect spill with absorbent. Proper disposal of absorbent is required after use.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep out of reach of Children.

STORAGE TEMPERATURE: 4°C (40°F) Minimum to 35°C (95°F) Maximum

SHELF LIFE: one year

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Distillates (petroleum) hydrotreated light	TWA					300 ppm	2300 mg/m ³
Odorless Mineral Spirits	TWA					300 ppm	1900 mg/m ³
Naphtha	TWA	300 ppm		300 ppm			
	STEL			400 ppm			

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields or goggles.

SKIN: Use Nitrile/ Vinyl gloves

RESPIRATORY: NIOSH respirator -(organic vapor) in absence of proper environmental control.

PROTECTIVE CLOTHING: Clean, body-covering clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point (°C)	Boiling Point (°C)	Specific Gravity
Distillates (petroleum) hydrotreated light	81	218	0.79
Odorless Mineral Spirits	49	178	0.76

PHYSICAL STATE: Liquid

ODOR: Strawberry odor

APPEARANCE: Pink Liquid

pH: Not applicable

FREEZING POINT: ~ (32°F)

FLASHPOINT AND METHOD: ~ 41°C (106°F) TCC

SOLUBILITY IN WATER: Insoluble

SPECIFIC GRAVITY: ~ 0.900 to 1 gm/ml

(VOC): < 15.000 % by weight

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Distillates (petroleum) hydrotreated light	> 5 g/Kg-rat	> 3.16 g/kg - rabbit	
Naphtha			~ 3400 ppm/4H- rat

CARCINOGENICITY

IARC: Listed by IARC- NO

NTP: Listed by NTP- NO

OSHA: Listed by OSHA- NO

SENSITIZATION: not available

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: not available

ECOTOXICOLOGICAL INFORMATION: not available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose in accordance with local, state, and federal laws.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

OTHER SHIPPING INFORMATION: Refer to bill of lading or container label for DOT or other transportation hazard classification, if any.

15. REGULATORY INFORMATION

UNITED STATES

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: All Ingredients are on the TSCA Inventory or are not required to be listed on the TSCA Inventory

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION


Toxic



Combustible Liquid

16. OTHER INFORMATION**RELEVANT R-PHRASES:**R65- Harmful: may cause lung damage if swallowed.**PREPARED BY:** Mark Dean**REVISION SUMMARY:** Revision #: 5. This MSDS replaces the September 12, 2008 MSDS.**HMIS RATING**

HEALTH:	-	1
FLAMMABILITY:		2
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA CODES

MANUFACTURER DISCLAIMER: The information in this MSDS was obtained from current and reputable sources. However, the data is provided without any warranty, express or implied, regarding its correctness or accuracy. It is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense resulting from improper use of this product.